

THE 2024 COLLECTION

P R O

F E S

S I O

N A L

ARKOSLIGHT

ARKOSLIGHT
THE 2024 PROFESSIONAL COLLECTION



40

ARKOSLIGHT
40TH ANNIVERSARY

Arkoslight cumple cuarenta años, una historia prendida por una pasión que nos hace más capaces y soñadores con el tiempo. En 1984, José Luís Latrás inicia esta labor de resplandeciente eco en el presente basada en el diseño y la fabricación de luminarias de alta calidad. Consagrados al talento de arquitectos y creadores, nuestros productos velan por la armonía y el bienestar en la arquitectura que habitamos. Y la luz, su hermoso lenguaje bien tratado, siempre es la respuesta. LIGHT&LIFE


Arkoslight celebrates its fortieth anniversary, a story ignited by a passion that makes us more capable and dreamers with time. In 1984, José Luís Latrás began this work of resplendent echo in the present based on the design and manufacture of high-quality luminaires. Dedicated to the talent of architects and creators, our products ensure harmony and well-being in the architecture we inhabit. And light, its beautiful and well-treated language, is always the answer. LIGHT&LIFE

Arkoslight fête son quarantième anniversaire, une histoire enflammée par une passion qui nous rend plus capables et plus rêveurs avec le temps. C'est en 1984 que José Luís Latrás a commencé cette démarche basée sur la conception et la fabrication de luminaires de haute qualité, et qui trouve un écho resplendissant dans le présent. Dédiés au talent des architectes et des créateurs, nos produits assurent l'harmonie et le bien-être de l'architecture que nous habitons. Et la lumière, grâce à son langage beau et bien traité, est toujours une valeur ajoutée. LIGHT&LIFE


Arkoslight compie quarant'anni, una storia accesa da una passione che ci rende più capaci e sognatori col passare del tempo. Nel 1984, José Luís Latrás inizia questa attività di eco splendente nel presente basata sul design e sulla produzione di illuminazione di alta qualità. Dedicati al talento di architetti e creatori, i nostri prodotti vegliano sull'armonia e sul benessere nell'architettura che abitiamo. E la luce, il suo bel linguaggio ben trattato, è sempre la risposta. LIGHT&LIFE

Arkoslight feiert sein vierzigjähriges Bestehen, eine Geschichte, entfacht von einer Leidenschaft, die uns im Laufe der Zeit fähiger und träumerischer macht. Im Jahr 1984 startete José Luís Latrás dieses Werk, welches in der Gegenwart ein strahlendes Echo erhält, basierend auf dem Design und der Herstellung hochwertiger Leuchten. Unsere Produkte sind dem Talent von Architekten und Kreativen gewidmet und sorgen für Harmonie und Wohlbefinden in der Architektur, die wir bewohnen. Und das Licht, seine wunderschöne wohlbehandelte Sprache, ist immer die Antwort. LIGHT&LIFE


CEILING
RECESSED




BLACK FOSTER_10 SHOT LIGHT_22 LENS LIGHT_34 BUDDY_36 SWAP_40 POINTER_51




LEX_52 DUOMO_58 PUCK RECESSED_59 ALASKA TRIMLESS_60 OLYMPIA_62 DEEP_63 DROP_64



STRAM_66 FOX_68 MIX_69 MADISON_70 QUAD_71 ESSENTIALS_72 POP UP_76



HIDDEN_77 TWIST_78 ORBITAL_80 WELLIT_86 HUBBLE_89 MAGNETIC COCO_90 MAGNETIC FLIP_91




MAGNETIC FIT_92 MAGNETIC IO MICRO_93 MAGNETIC PLUS MICRO_94 MAGNETIC TOP MICRO_94 MAGNETIC SIX XS_95 FLIP RECESSED_96 SIX RECESSED_97



FIT RECESSED_100 PLUS RECESSED_101 BLACK FOSTER SURFACE_104 SHOT LIGHT SURFACE_110 SCOPE SURFACE_113 TOP_114




PUCK_116 STRAM SURFACE_117 ORBITAL SURFACE_118 VOLA_120 SKY_120 DRUM_121 FIFTY+ SURFACE_122



FLIP SURFACE_123 FIT SURFACE_124 IO SURFACE_126 ZEN TUBE SURFACE_127 ALASKA_130 LOOP_132



BLACK FOSTER SUSPENSION_133 ART_134 STICK_142 HOLLY_143 SPIN_144 DUNE_146 PIPE_148




SCOPE_149 SALT_150 VOLA SUSPENSION_152 DRUM SUSPENSION_153 LINE SUSPENSION_154 SLIMGOT_157 FIFTY+ SUSPENSION_158

WALL, FLOOR
& PORTABLE




STANDUP_162 UP_163 YORU_164 LIP_165 AURAE_165 REC_166



DREAM_169 RHINO_170 WALLY_171 TRACK LIGHTS MINIMAL TRACK BLACK FOSTER MICRO 24V_180 ALASKA 24V_181



TOP MICRO 24V_181 PLUS MICRO 24V_182 SIX XS 24V_182 LINE MICRO 24V_183 IO MICRO 24V_183 FIT 24V_184 STICK 22 24V_185




TRACK 48V SIX 48V_194 FIT 48V_197 PLUS 48V_201 IO 48V_202 ZEN TUBE 48V_203 COCO 48V_204



FLIP 48V_206 BLACK FOSTER 48V_207 LINE 48V_209 TOP 48V_210 WIZ 48V_212 SPIN 48V_213 STICK 48V_214



HOLLY 48V_215 TRACK 1L IO_220 PLUS MINI L_221 FIT 651L_221 WIZ 48V_212 SPIN 48V_213 STICK 48V_214



FIT_228 PLUS_229 ZEN TUBE_230 THOR_231 CUSTOM SYSTEMS FANCY SHAPE TOP FANCY SHAPE_236



STICK FANCY SHAPE_237 ALASKA FANCY SHAPE_238 SPIN FANCY SHAPE_240 HOLLY FANCY SHAPE_241 OTHER CUSTOM SYSTEMS BLACK FOSTER CUSTOM_242 BRIGHT LINE_258



FIFTY+ CUSTOM_261 OUTDOOR SKIP_266 YORU SPIKE_267 STEP_268 DARK_270 ACCESSORIES



LARK-111_274 LARK_275 TRIMLESS TOOL_276 WIRE TRIMLESS_278 ACCESSORIES

LIGHT &
EXPLORE




03



09



12




15




04




06




10




13




16



01



07



13



17



02




05



08



11



14

01_BLACK FOSTER S P.20 · 02_BLACK FOSTER
TILT P.15 · 03_SHOT LIGHT S SEMI RECESSED P.28
· 04_SHOT LIGHT S FLEX P.29 · 05_BUDDY P.36
· 06_MAGNETIC FLIP P.91 · 07_MAGNETIC COCO
P.90 · 08_FLIP RECESSED P.96 · 09_SHOT LIGHT S
SURFACE P.110/112 · 10_BLACK FOSTER SURFACE
REMOTE P.108 · 11_DUNE P.146 · 12_PIPE P.148 ·
13_STANDUP P.162 · 14_COCO 48V P.204 · 15_FLIP
48V P.206 · 16_BLACK FOSTER 48V TILT P.207 ·
17_SKIP P.266

BLACK FOSTER_10
SHOT LIGHT_22
LENS LIGHT_34
BUDDY_36
SWAP_40
POINTER_51
LEX_52
DUOMO_58
PUCK RECESSED_59
ALASKA TRIMLESS_60
OLYMPIA_62
DEEP_63
DROP_64
STRAM_66
FOX_68
MIX_69
MADISON_70
QUAD_71
ESSENTIALS_72
POP UP_76
HIDDEN_77
TWIST_78
ORBITAL_80
WELLIT_86
HUBBLE_89
MAGNETIC SYSTEM_90
FLIP RECESSED_96
SIX RECESSED_97
FIT RECESSED_100
PLUS RECESSED_101

CEILING RECESSED

BLACK FOSTER



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------------------------------------|-------------------|------|-------|-------|--------|-----|
| BLACK FOSTER MICRO Recessed 3 | A414-10- 0-0- N | 4,2W | 2700K | 500mA | 465 lm | 87% |
| | A414-10- 0-1- N | 4,2W | 3000K | 500mA | 480 lm | 87% |
| | A414-10- 0-2- N | 4,2W | 4000K | 500mA | 510 lm | 87% |



220 V~ | IP20 | CRI>90 | L90B10 >60.000h | MacAdam Step 3 | OPTIONS* | INCL | 24 X 60 | UGR <19 | 37°



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------------------------------------|-------------------|----|-------|-------|--------|-----|
| BLACK FOSTER MICRO Recessed 5 | A414-20- 0-0- N | 7W | 2700K | 500mA | 775 lm | 87% |
| | A414-20- 0-1- N | 7W | 3000K | 500mA | 800 lm | 87% |
| | A414-20- 0-2- N | 7W | 4000K | 500mA | 850 lm | 87% |


220 V~ | IP20 | CRI>90 | L90B10 >60.000h | MacAdam Step 3 | OPTIONS* | INCL | 24 X 96 | UGR <19 | 37°



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--|-------------------|------|-------|-------|--------|-----|
| BLACK FOSTER MICRO Recessed 2x2 | A414-30- 0-0- N | 5,6W | 2700K | 500mA | 620 lm | 87% |
| | A414-30- 0-1- N | 5,6W | 3000K | 500mA | 640 lm | 87% |
| | A414-30- 0-2- N | 5,6W | 4000K | 500mA | 680 lm | 87% |

220 V~ | IP20 | CRI>90 | L90B10 >60.000h | MacAdam Step 3 | OPTIONS* | INCL | 42 X 42 | UGR <19 | 37°




MORE INFO >>


| | | P | CCT | I | Flux | LOR |
|--|-------------------|-------|-------|-------|---------|-----|
| BLACK FOSTER MICRO Recessed 3x3 | A414-40- 0-0- N | 12,6W | 2700K | 500mA | 1395 lm | 87% |
| | A414-40- 0-1- N | 12,6W | 3000K | 500mA | 1440 lm | 87% |
| | A414-40- 0-2- N | 12,6W | 4000K | 500mA | 1530 lm | 87% |

220 V~ | IP20 | CRI>90 | L90B10 >60.000h | MacAdam Step 3 | OPTIONS* | INCL | 60 X 60 | UGR <19 | 37°

- Ⓜ OPTIONS*
- | | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM PUSH |
- DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



BLACK FOSTER



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------|-----------------------------------|------|-------|------|-------|--------|-----|
| BLACK FOSTER Recessed 1 | A319-10- ① -0- N W WN NMG | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| | A319-10- ① -1- N W WN NMG | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |
| | A319-10- ① -2- N W WN NMG | 2,1W | 4000K | 38° | 700mA | 250 lm | 92% |
| | A319-11- ① -0- N WN NMG | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| | A319-11- ① -1- N WN NMG | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| | A319-11- ① -2- N WN NMG | 2,1W | 4000K | 19° | 700mA | 250 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------|-----------------------------------|------|-------|------|-------|--------|-----|
| BLACK FOSTER Recessed 2 | A319-20- ① -0- N W WN NMG | 4,2W | 2700K | 38° | 700mA | 380 lm | 92% |
| | A319-20- ① -1- N W WN NMG | 4,2W | 3000K | 38° | 700mA | 420 lm | 92% |
| | A319-20- ① -2- N W WN NMG | 4,2W | 4000K | 38° | 700mA | 500 lm | 92% |
| | A319-21- ① -0- N WN NMG | 4,2W | 2700K | 19° | 700mA | 380 lm | 90% |
| | A319-21- ① -1- N WN NMG | 4,2W | 3000K | 19° | 700mA | 420 lm | 90% |
| | A319-21- ① -2- N WN NMG | 4,2W | 4000K | 19° | 700mA | 500 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------|-----------------------------------|------|-------|------|-------|--------|-----|
| BLACK FOSTER Recessed 3 | A319-30- ① -0- N W WN NMG | 6,3W | 2700K | 38° | 700mA | 570 lm | 92% |
| | A319-30- ① -1- N W WN NMG | 6,3W | 3000K | 38° | 700mA | 630 lm | 92% |
| | A319-30- ① -2- N W WN NMG | 6,3W | 4000K | 38° | 700mA | 750 lm | 92% |
| | A319-31- ① -0- N WN NMG | 6,3W | 2700K | 19° | 700mA | 570 lm | 90% |
| | A319-31- ① -1- N WN NMG | 6,3W | 3000K | 19° | 700mA | 630 lm | 90% |
| | A319-31- ① -2- N WN NMG | 6,3W | 4000K | 19° | 700mA | 750 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING | Body | Lampshade |
|-----------|------|-----------|
| N | N ■ | N ■ |
| W | W □ | W □ |
| WN | W □ | N ■ |
| NMG | N ■ | MG ■ |

COLOUR | N ■ | W □ | WN □ | NMG ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, WN & NMG COLOURS

Ⓜ & Ⓜ » 288



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------|-----------------------------------|-------|-------|------|-------|---------|-----|
| BLACK FOSTER Recessed 5 | A319-40- ① -0- N W WN NMG | 10,5W | 2700K | 38° | 700mA | 950 lm | 92% |
| | A319-40- ① -1- N W WN NMG | 10,5W | 3000K | 38° | 700mA | 1050 lm | 92% |
| | A319-40- ① -2- N W WN NMG | 10,5W | 4000K | 38° | 700mA | 1250 lm | 92% |
| | A319-41- ① -0- N WN NMG | 10,5W | 2700K | 19° | 700mA | 950 lm | 90% |
| | A319-41- ① -1- N WN NMG | 10,5W | 3000K | 19° | 700mA | 1050 lm | 90% |
| | A319-41- ① -2- N WN NMG | 10,5W | 4000K | 19° | 700mA | 1250 lm | 90% |


220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|------------------------------|-----------------------------|------|-------|------|-------|---------|-----|
| BLACK FOSTER Recessed 2x2 | A319-50- ① -0- N W WN | 8,4W | 2700K | 38° | 700mA | 760 lm | 92% |
| | A319-50- ① -1- N W WN | 8,4W | 3000K | 38° | 700mA | 840 lm | 92% |
| | A319-50- ① -2- N W WN | 8,4W | 4000K | 38° | 700mA | 1000 lm | 92% |
| | A319-51- ① -0- N WN | 8,4W | 2700K | 19° | 700mA | 760 lm | 90% |
| | A319-51- ① -1- N WN | 8,4W | 3000K | 19° | 700mA | 840 lm | 90% |
| | A319-51- ① -2- N WN | 8,4W | 4000K | 19° | 700mA | 1000 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h




COLOUR | N ■ | W □ | WN □ | NMG ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, WN & NMG COLOURS

Ⓜ & Ⓜ » 288



BLACK FOSTER



MORE INFO >>



MORE INFO >>



MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|------------------------------------|----------------------|------|-------|-------|--------|-----|
| BLACK FOSTER Asymmetric Recessed 2 | A374-20- 0- N WN | 4,2W | 2700K | 700mA | 380 lm | 90% |
| | A374-20- 1- N WN | 4,2W | 3000K | 700mA | 420 lm | 90% |
| | A374-20- 2- N WN | 4,2W | 4000K | 700mA | 500 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



| | P | CCT | I | Flux | LOR | |
|------------------------------------|----------------------|------|-------|-------|--------|-----|
| BLACK FOSTER Asymmetric Recessed 3 | A374-30- 0- N WN | 6,3W | 2700K | 700mA | 570 lm | 90% |
| | A374-30- 1- N WN | 6,3W | 3000K | 700mA | 630 lm | 90% |
| | A374-30- 2- N WN | 6,3W | 4000K | 700mA | 750 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



| | P | CCT | I | Flux | LOR | |
|------------------------------------|----------------------|-------|-------|-------|---------|-----|
| BLACK FOSTER Asymmetric Recessed 5 | A374-40- 0- N WN | 10,5W | 2700K | 700mA | 950 lm | 90% |
| | A374-40- 1- N WN | 10,5W | 3000K | 700mA | 1050 lm | 90% |
| | A374-40- 2- N WN | 10,5W | 4000K | 700mA | 1250 lm | 90% |


220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



| *OPTIONS | | |
|----------|----------|--|
| 1 | No DIM | |
| 2 | DIM Push | |
| 4 | DIM DALI | |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING | Body | Lampshade |
|-----------|------|-----------|
| N | N ■ | N ■ |
| WN | W □ | N ■ |



COLOUR | N ■ | WN □ | MATERIAL | AL | ABS+PC

RAL ⓘ » 312

Ⓜ & Ⓜ » 288



MORE INFO >>



| | P | CCT | Beam | I | Flux | LOR | |
|---------------------|------------------------------|-------|-------|-----|-------|---------|-----|
| BLACK FOSTER Tilt 5 | A479-40- 0- NT WT NTMG | 10,5W | 2700K | 38° | 700mA | 950 lm | 92% |
| | A479-40- 1- NT WT NTMG | 10,5W | 3000K | 38° | 700mA | 1050 lm | 92% |
| | A479-40- 2- NT WT NTMG | 10,5W | 4000K | 38° | 700mA | 1250 lm | 92% |
| | A479-41- 0- NT WT NTMG | 10,5W | 2700K | 19° | 700mA | 950 lm | 90% |
| | A479-41- 1- NT WT NTMG | 10,5W | 3000K | 19° | 700mA | 1050 lm | 90% |
| | A479-41- 2- NT WT NTMG | 10,5W | 4000K | 19° | 700mA | 1250 lm | 90% |


220 V~ | IP20 | CRI>90 | L90B10 > 102.000h



| *OPTIONS | |
|----------|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING | Body | Tilt Profile | Lampshade |
|-----------|------|--------------|-----------|
| NT | NT ■ | NT ■ | N ■ |
| WT | WT □ | WT □ | N ■ |
| NTMG | NT ■ | NT ■ | MG ■ |




COLOUR | NT ■ | WT □ | NTMG ■ | MATERIAL | AL | ABS+PC

RAL ⓘ » 312

Ⓜ & Ⓜ » 288

BLACK FOSTER




MORE INFO >>

| | | P | CCT | I | Flux |
|----------------------------|-----------------------------|------|-------|-------|--------|
| BLACK FOSTER Trimless 1 | A318-1- ○ - Ⓞ -0- N NMG | 2,1W | 2700K | 700mA | 190 lm |
| | A318-1- ○ - Ⓞ -1- N NMG | 2,1W | 3000K | 700mA | 210 lm |
| | A318-1- ○ - Ⓞ -2- N NMG | 2,1W | 4000K | 700mA | 250 lm |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 50 | UGR <19 | 38° / 19°



MORE INFO >>

| | | P | CCT | I | Flux |
|----------------------------|-----------------------------|------|-------|-------|--------|
| BLACK FOSTER Trimless 2 | A318-2- ○ - Ⓞ -0- N NMG | 4,2W | 2700K | 700mA | 380 lm |
| | A318-2- ○ - Ⓞ -1- N NMG | 4,2W | 3000K | 700mA | 420 lm |
| | A318-2- ○ - Ⓞ -2- N NMG | 4,2W | 4000K | 700mA | 500 lm |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 93 | UGR <19 | 38° / 19°



MORE INFO >>

| | | P | CCT | I | Flux |
|----------------------------|-----------------------------|------|-------|-------|--------|
| BLACK FOSTER Trimless 3 | A318-3- ○ - Ⓞ -0- N NMG | 6,3W | 2700K | 700mA | 570 lm |
| | A318-3- ○ - Ⓞ -1- N NMG | 6,3W | 3000K | 700mA | 630 lm |
| | A318-3- ○ - Ⓞ -2- N NMG | 6,3W | 4000K | 700mA | 750 lm |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 136 | UGR <19 | 38° / 19°



MORE INFO >>

| | | P | CCT | I | Flux |
|----------------------------|-----------------------------|-------|-------|-------|---------|
| BLACK FOSTER Trimless 5 | A318-4- ○ - Ⓞ -0- N NMG | 10,5W | 2700K | 700mA | 950 lm |
| | A318-4- ○ - Ⓞ -1- N NMG | 10,5W | 3000K | 700mA | 1050 lm |
| | A318-4- ○ - Ⓞ -2- N NMG | 10,5W | 4000K | 700mA | 1250 lm |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 222 | UGR <19 | 38° / 19°



COLOUR | N ■ | NMG ■■ | MATERIAL | AL | ABS+PC |

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm.

RAL ⓘ » 312

Ⓞ & ⓘ » 288




MORE INFO >>

| | | P | CCT | I | Flux |
|-----------------------------|-----------------------------|-----|-------|-------|---------|
| BLACK FOSTER Trimless 10 | A318-5- ○ - Ⓞ -0- N NMG | 21W | 2700K | 700mA | 1900 lm |
| | A318-5- ○ - Ⓞ -1- N NMG | 21W | 3000K | 700mA | 2100 lm |
| | A318-5- ○ - Ⓞ -2- N NMG | 21W | 4000K | 700mA | 2500 lm |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h

MacAdam Step 3 | OPTIONS* | INCL | 50 X 437 | UGR <19 | 38° / 19°



MORE INFO >>

| | | P | CCT | I | Flux |
|-----------------------------|-----------------------------|-------|-------|-------|---------|
| BLACK FOSTER Trimless 15 | A318-6- ○ - Ⓞ -0- N NMG | 31,5W | 2700K | 700mA | 2850 lm |
| | A318-6- ○ - Ⓞ -1- N NMG | 31,5W | 3000K | 700mA | 3150 lm |
| | A318-6- ○ - Ⓞ -2- N NMG | 31,5W | 4000K | 700mA | 3750 lm |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h


MacAdam Step 3 | OPTIONS* | INCL | 50 X 652 | UGR <19 | 38° / 19°

| ○ | BEAM | LOR | FINISHING | Body | Lampshade |
|---|------|-----|-----------|------|-----------|
| 0 | 38° | 92% | N | N ■ | N ■ |
| 1 | 19° | 90% | NMG | N ■ | MG ■ |

Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | N ■ | NMG ■■ | MATERIAL | AL | ABS+PC |


PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm.

RAL ⓘ » 312

Ⓞ & ⓘ » 288



BLACK FOSTER



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------------------------------|--------------------|------|-------|-------|--------|-----|
| BLACK FOSTER Asymmetric Trimless 2 | A373-20- ① -0- N | 4,2W | 2700K | 700mA | 380 lm | 90% |
| | A373-20- ① -1- N | 4,2W | 3000K | 700mA | 420 lm | 90% |
| | A373-20- ① -2- N | 4,2W | 4000K | 700mA | 500 lm | 90% |

220 V~ | 240 | IP20 | CRI>90 | L90B10 >102.000h



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------------------------------|--------------------|------|-------|-------|--------|-----|
| BLACK FOSTER Asymmetric Trimless 3 | A373-30- ① -0- N | 6,3W | 2700K | 700mA | 570 lm | 90% |
| | A373-30- ① -1- N | 6,3W | 3000K | 700mA | 630 lm | 90% |
| | A373-30- ① -2- N | 6,3W | 4000K | 700mA | 750 lm | 90% |

220 V~ | 240 | IP20 | CRI>90 | L90B10 >102.000h



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------------------------------|--------------------|-------|-------|-------|---------|-----|
| BLACK FOSTER Asymmetric Trimless 5 | A373-40- ① -0- N | 10,5W | 2700K | 700mA | 950 lm | 90% |
| | A373-40- ① -1- N | 10,5W | 3000K | 700mA | 1050 lm | 90% |
| | A373-40- ① -2- N | 10,5W | 4000K | 700mA | 1250 lm | 90% |

220 V~ | 240 | IP20 | CRI>90 | L90B10 >102.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

COLOUR | N ■ | MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm.


Ⓢ & ⓘ » 288



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------------------------------|--------------------|-----|-------|-------|---------|-----|
| BLACK FOSTER Asymmetric Trimless 10 | A373-50- ① -0- N | 21W | 2700K | 700mA | 1900 lm | 90% |
| | A373-50- ① -1- N | 21W | 3000K | 700mA | 2100 lm | 90% |
| | A373-50- ① -2- N | 21W | 4000K | 700mA | 2500 lm | 90% |


220 V~ | 240 | IP20 | CRI>90 | L90B10 >102.000h



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------------------------------|--------------------|-------|-------|-------|---------|-----|
| BLACK FOSTER Asymmetric Trimless 15 | A373-60- ① -0- N | 31,5W | 2700K | 700mA | 2850 lm | 90% |
| | A373-60- ① -1- N | 31,5W | 3000K | 700mA | 3150 lm | 90% |
| | A373-60- ① -2- N | 31,5W | 4000K | 700mA | 3750 lm | 90% |

220 V~ | 240 | IP20 | CRI>90 | L90B10 >102.000h



COLOUR | N ■ | MATERIAL | AL | ABS+PC |

RAL ⓘ » 312


PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm.

Ⓢ & ⓘ » 288

BLACK FOSTER




CEILING RECESSED



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------------|-----------------------------|----|-------|------|-------|--------|-----|
| BLACK FOSTER S Recessed 1 | A484-1- 00-00- N WN | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A484-1- 00-01- N WN | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A484-1- 00-02- N WN | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A484-1- 00-10- N W WN | 6W | 2700K | 40° | 500mA | 640 lm | 89% |
| | A484-1- 00-11- N W WN | 6W | 3000K | 40° | 500mA | 670 lm | 89% |
| | A484-1- 00-12- N W WN | 6W | 4000K | 40° | 500mA | 720 lm | 89% |

220 V~ | IP20 | CRI>90 | L80B10 > 60.000h



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------------|-----------------------------|-----|-------|------|-------|---------|-----|
| BLACK FOSTER S Recessed 2 | A484-2- 00-00- N WN | 12W | 2700K | 18° | 500mA | 1280 lm | 89% |
| | A484-2- 00-01- N WN | 12W | 3000K | 18° | 500mA | 1340 lm | 89% |
| | A484-2- 00-02- N WN | 12W | 4000K | 18° | 500mA | 1440 lm | 89% |
| | A484-2- 00-10- N W WN | 12W | 2700K | 40° | 500mA | 1280 lm | 89% |
| | A484-2- 00-11- N W WN | 12W | 3000K | 40° | 500mA | 1340 lm | 89% |
| | A484-2- 00-12- N W WN | 12W | 4000K | 40° | 500mA | 1440 lm | 89% |


220 V~ | IP20 | CRI>90 | L80B10 > 60.000h



| ⊕ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING | Body | Lampshade |
|-----------|------|-----------|
| N | N ■ | N ■ |
| W | W □ | W □ |
| WN | W □ | N ■ |




COLOUR | N ■ | W □ | WN ■

MATERIAL | AL | ABS+PC

RAL ⓘ » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N & WN COLOURS


Ⓜ & Ⓜ » 288



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------------|--------------------|----|-------|------|-------|--------|-----|
| BLACK FOSTER S Trimless 1 | A485-1- 00-00- N | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A485-1- 00-01- N | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A485-1- 00-02- N | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A485-1- 00-10- N | 6W | 2700K | 40° | 500mA | 640 lm | 89% |
| | A485-1- 00-11- N | 6W | 3000K | 40° | 500mA | 670 lm | 89% |
| | A485-1- 00-12- N | 6W | 4000K | 40° | 500mA | 720 lm | 89% |


220 V~ | IP20 | CRI>90 | L80B10 > 60.000h



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------------|--------------------|-----|-------|------|-------|---------|-----|
| BLACK FOSTER S Trimless 2 | A485-2- 00-00- N | 12W | 2700K | 18° | 500mA | 1280 lm | 89% |
| | A485-2- 00-01- N | 12W | 3000K | 18° | 500mA | 1340 lm | 89% |
| | A485-2- 00-02- N | 12W | 4000K | 18° | 500mA | 1440 lm | 89% |
| | A485-2- 00-10- N | 12W | 2700K | 40° | 500mA | 1280 lm | 89% |
| | A485-2- 00-11- N | 12W | 3000K | 40° | 500mA | 1340 lm | 89% |
| | A485-2- 00-12- N | 12W | 4000K | 40° | 500mA | 1440 lm | 89% |

220 V~ | IP20 | CRI>90 | L80B10 > 60.000h



MORE INFO >>


| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------------|--------------------|-----|-------|------|-------|---------|-----|
| BLACK FOSTER S Trimless 4 | A485-4- 00-00- N | 24W | 2700K | 18° | 500mA | 2560 lm | 89% |
| | A485-4- 00-01- N | 24W | 3000K | 18° | 500mA | 2680 lm | 89% |
| | A485-4- 00-02- N | 24W | 4000K | 18° | 500mA | 2880 lm | 89% |
| | A485-4- 00-10- N | 24W | 2700K | 40° | 500mA | 2560 lm | 89% |
| | A485-4- 00-11- N | 24W | 3000K | 40° | 500mA | 2680 lm | 89% |
| | A485-4- 00-12- N | 24W | 4000K | 40° | 500mA | 2880 lm | 89% |

220 V~ | IP20 | CRI>90 | L80B10 > 60.000h



| ⊕ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | N ■

MATERIAL | AL | ABS+PC


RAL ⓘ » 312

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm.

Ⓜ & Ⓜ » 288




SHOT LIGHT




MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|------------|-----------------------------|------|-------|------|-------|--------|-----|
| SHOT LIGHT | A268-01-10- N NMG WMG | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| | A268-01-11- N NMG WMG | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| | A268-01-12- N NMG WMG | 2,1W | 4000K | 19° | 700mA | 250 lm | 90% |
| | A268-01-20- N NMG WMG | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| | A268-01-21- N NMG WMG | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |
| | A268-01-22- N NMG WMG | 2,1W | 4000K | 38° | 700mA | 250 lm | 92% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h





Extended Family
Shot Light Surface_P.110



MORE INFO >>



| | | P | CCT | Beam | I | Flux | LOR |
|------------|---------------------------------|------|-------|------|-------|--------|-----|
| SHOT LIGHT | A268-02-20- N W NMG WMG | 2,1W | 2700K | 38° | 700mA | 190 lm | 86% |
| IP65 | A268-02-21- N W NMG WMG | 2,1W | 3000K | 38° | 700mA | 210 lm | 86% |
| | A268-02-22- N W NMG WMG | 2,1W | 4000K | 38° | 700mA | 250 lm | 86% |

220 V~ | IP65 | CRI>90 | L90B10 >102.000h




EASY INSTALLATION

DRIVER FITS INTO CUT-OUT DIAMETER



EASY INSTALLATION

DRIVER FITS INTO CUT-OUT DIAMETER



COLOUR | N ■ | NMG ■■ | WMG □□

MATERIAL | AL | ABS+PC

RAL ⓘ » 312

* DIM OPTIONS PLEASE CONSULT

Ⓜ & Ⓜ » 288



COLOUR | N ■ | W □ | NMG ■■ | WMG □□


MATERIAL | AL | ABS+PC

RAL ⓘ » 312

* DIM OPTIONS PLEASE CONSULT | "THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, NMG & WMG COLOURS

Ⓜ & Ⓜ » 288


SHOT LIGHT



MORE INFO >>


| | | P | CCT | Beam | I | Flux | LOR |
|------------------------|---------------------------|------|-------|------|-------|--------|-----|
| SHOT LIGHT Trimless | A269-01-10- N NMG | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| | A269-01-11- N NMG | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| | A269-01-12- N NMG | 2,1W | 4000K | 19° | 700mA | 250 lm | 90% |
| | A269-01-20- N W NMG | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| | A269-01-21- N W NMG | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |
| | A269-01-22- N W NMG | 2,1W | 4000K | 38° | 700mA | 250 lm | 92% |

220
240 V~ | IP20 | CRI>90 | L90B10
>102.000h



EASY INSTALLATION

DRIVER FITS INTO
CUT-OUT DIAMETER



COLOUR | N ■ | W □ | NMG ■ ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

* DIM OPTIONS PLEASE CONSULT | "THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N & NMG COLOURS

Ⓜ & Ⓜ » 288



ACCESSORIES**

MANDATORY FOR TRIMLESS INSTALLATION


SHOT LIGHT Trimless Accessory

A269-00-00




SHOT LIGHT Trimless Accessory 2

A269-00-01




SHOT LIGHT Trimless Accessory 3

A269-00-02



SHOT LIGHT Trimless Accessory 2x2


A269-00-03




CUSTOM LAYOUT EXAMPLES

FOR EQUIDISTANT COMPOSITIONS

Trimless Accessory 2 + Trimless Accessory 2 / Trimless Accessory 3




Trimless Accessory 3 + Trimless Accessory 2 / Trimless Accessory 3



Trimless Accessory 2x2 + Trimless Accessory 2x2

THE "TA2X2" FRAME IS ONLY COMPATIBLE WITH FURTHER "TA2X2" FRAMES



OPTIONAL ACCESSORY

TRIMLESS TOOL D43 X D70MM

A478-00-02



SHOT LIGHT



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|--------------|-----------------------------|----|-------|------|-------|--------|-----|
| SHOT LIGHT S | A462-0- 00- N NMG WMG | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A462-0- 01- N NMG WMG | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A462-0- 02- N NMG WMG | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A462-0- 10- N NMG WMG | 6W | 2700K | 40° | 500mA | 640 lm | 89% |
| | A462-0- 11- N NMG WMG | 6W | 3000K | 40° | 500mA | 670 lm | 89% |
| | A462-0- 12- N NMG WMG | 6W | 4000K | 40° | 500mA | 720 lm | 89% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



| | | P | CCT | Beam | I | Flux | LOR |
|----------------------|---------------------------------|----|-------|------|-------|--------|-----|
| SHOT LIGHT S IP65 | A462-1- 10- N W NMG WMG | 6W | 2700K | 40° | 500mA | 640 lm | 84% |
| | A462-1- 11- N W NMG WMG | 6W | 3000K | 40° | 500mA | 670 lm | 84% |
| | A462-1- 12- N W NMG WMG | 6W | 4000K | 40° | 500mA | 720 lm | 84% |


220 V~ | IP65 | CRI>90 | L80B10 >60.000h



*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT



COLOUR | N ■ | W □ | NMG ■■ | WMG □■

MATERIAL | AL | ABS+PC

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, NMG & WMG COLOURS

Ⓢ & Ⓢ » 288



CEILING RECESSED



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|--------------------------|---------------------------|----|-------|------|-------|--------|-----|
| SHOT LIGHT S Trimless | A463-0- 00- N NMG | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A463-0- 01- N NMG | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A463-0- 02- N NMG | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A463-0- 10- N W NMG | 6W | 2700K | 40° | 500mA | 640 lm | 89% |
| | A463-0- 11- N W NMG | 6W | 3000K | 40° | 500mA | 670 lm | 89% |
| | A463-0- 12- N W NMG | 6W | 4000K | 40° | 500mA | 720 lm | 89% |


220 V~ | IP20 | CRI>90 | L80B10 >60.000h



*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT



COLOUR | N ■ | W □ | NMG ■■

MATERIAL | AL | ABS+PC

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N & NMG COLOURS


Ⓢ & Ⓢ » 288



ACCESSORY


SHOT LIGHT S Trimless Accessory** A463-00-00

** MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORY

TRIMLESS TOOL D59 X D100mm A478-00-03



SHOT LIGHT



MORE INFO >>

| | P | CCT | Beam | I | Flux | LOR |
|-------------------------------|--|-----|-------|-----|-------|------------|
| SHOT LIGHT S Semi Recessed | A495-0- 00- WT NT BG CR NTMG | 6W | 2700K | 18° | 500mA | 640 lm 89% |
| | A495-0- 01- WT NT BG CR NTMG | 6W | 3000K | 18° | 500mA | 670 lm 89% |
| | A495-0- 02- WT NT BG CR NTMG | 6W | 4000K | 18° | 500mA | 720 lm 89% |
| | A495-0- 10- WT NT BG CR NTMG WTW | 6W | 2700K | 40° | 500mA | 640 lm 89% |
| | A495-0- 11- WT NT BG CR NTMG WTW | 6W | 3000K | 40° | 500mA | 670 lm 89% |
| | A495-0- 12- WT NT BG CR NTMG WTW | 6W | 4000K | 40° | 500mA | 720 lm 89% |

220
240 V~ | IP20 | CRI>90 | L80B10
>60.000h




*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT

| FINISHING | Body | Lampshade |
|-----------|---|-----------|
| WT | WT <input type="checkbox"/> N <input checked="" type="checkbox"/> | |
| NT | NT <input checked="" type="checkbox"/> N <input checked="" type="checkbox"/> | |
| BG | BG <input checked="" type="checkbox"/> N <input checked="" type="checkbox"/> | |
| CR | CR <input checked="" type="checkbox"/> N <input checked="" type="checkbox"/> | |
| NTMG | NT <input checked="" type="checkbox"/> MG <input checked="" type="checkbox"/> | |
| WTW | WT <input type="checkbox"/> W <input type="checkbox"/> | |



MIN. 60 (NO DIM)
MIN. 90 (DIM DALI/PUSH)



WTW



WT



NT



NTMG



CR



BG

COLOUR | WT | NT | BG | CR | NTMG | WTW | MATERIAL | AL | ABS+PC | RAL >> 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR WT, NT, BG, CR & NTMG COLOURS

& >> 288



MORE INFO >>

| | P | CCT | Beam | I | Flux | LOR |
|----------------------|------------------------------|-----|-------|-----|-------|------------|
| SHOT LIGHT S Flex | A477-0- 00- WT NT NTMG | 6W | 2700K | 18° | 500mA | 640 lm 89% |
| | A477-0- 01- WT NT NTMG | 6W | 3000K | 18° | 500mA | 670 lm 89% |
| | A477-0- 02- WT NT NTMG | 6W | 4000K | 18° | 500mA | 720 lm 89% |
| | A477-0- 10- WT NT NTMG | 6W | 2700K | 40° | 500mA | 640 lm 84% |
| | A477-0- 11- WT NT NTMG | 6W | 3000K | 40° | 500mA | 670 lm 84% |
| | A477-0- 12- WT NT NTMG | 6W | 4000K | 40° | 500mA | 720 lm 84% |

220
240 V~ | IP20 | CRI>90 | L80B10
>60.000h



*OPTIONS





| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT

| FINISHING** | Body | Lampshade |
|-------------|---|-----------|
| WT | WT <input type="checkbox"/> N <input checked="" type="checkbox"/> | |
| NT | NT <input checked="" type="checkbox"/> N <input checked="" type="checkbox"/> | |
| NTMG | NT <input checked="" type="checkbox"/> MG <input checked="" type="checkbox"/> | |

OPTIONAL ACCESSORY

TRIMLESS TOOL D79 X D86mm A478-00-04



RECESSED VERSION
(COVER INCLUDED)

COLOUR | WT | NT | NTMG | MATERIAL | AL | ABS+PC | RAL >> 312

** OTHER FINISHING COMBINATION PLEASE CONSULT

& >> 288

SHOT LIGHT



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|----------------|---------------------------------|-------|-------|-------|---------|-----|
| SHOT LIGHT M 1 | A297-01-10- N W NMG WMG | 5W | 2700K | 150mA | 675 lm | 86% |
| | A297-01-11- N W NMG WMG | 5W | 3000K | 150mA | 700 lm | 86% |
| | A297-01-12- N W NMG WMG | 5W | 4000K | 150mA | 710 lm | 86% |
| SHOT LIGHT M 2 | A297-02-10- N W NMG WMG | 6,5W | 2700K | 200mA | 910 lm | 86% |
| | A297-02-11- N W NMG WMG | 6,5W | 3000K | 200mA | 940 lm | 86% |
| | A297-02-12- N W NMG WMG | 6,5W | 4000K | 200mA | 960 lm | 86% |
| | A297-02-30- N W NMG WMG | 6,5W | 2700K | 200mA | 910 lm | 86% |
| | A297-02-31- N W NMG WMG | 6,5W | 3000K | 200mA | 940 lm | 86% |
| | A297-02-32- N W NMG WMG | 6,5W | 4000K | 200mA | 960 lm | 86% |
| SHOT LIGHT M 3 | A297-03-10- N W NMG WMG | 10,3W | 2700K | 300mA | 1230 lm | 86% |
| | A297-03-11- N W NMG WMG | 10,3W | 3000K | 300mA | 1280 lm | 86% |
| | A297-03-12- N W NMG WMG | 10,3W | 4000K | 300mA | 1300 lm | 86% |
| | A297-03-30- N W NMG WMG | 10,3W | 2700K | 300mA | 1230 lm | 86% |
| | A297-03-31- N W NMG WMG | 10,3W | 3000K | 300mA | 1280 lm | 86% |
| | A297-03-32- N W NMG WMG | 10,3W | 4000K | 300mA | 1300 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|---------------------|---------------------|-------|-------|-------|---------|-----|
| SHOT LIGHT M IP65 1 | A297-21-10- N W | 5W | 2700K | 150mA | 675 lm | 78% |
| | A297-21-11- N W | 5W | 3000K | 150mA | 700 lm | 78% |
| | A297-21-12- N W | 5W | 4000K | 150mA | 710 lm | 78% |
| SHOT LIGHT M IP65 2 | A297-22-10- N W | 6,5W | 2700K | 200mA | 910 lm | 78% |
| | A297-22-11- N W | 6,5W | 3000K | 200mA | 940 lm | 78% |
| | A297-22-12- N W | 6,5W | 4000K | 200mA | 960 lm | 78% |
| | A297-22-30- N W | 6,5W | 2700K | 200mA | 910 lm | 78% |
| | A297-22-31- N W | 6,5W | 3000K | 200mA | 940 lm | 78% |
| | A297-22-32- N W | 6,5W | 4000K | 200mA | 960 lm | 78% |
| SHOT LIGHT M IP65 3 | A297-23-10- N W | 10,3W | 2700K | 300mA | 1230 lm | 78% |
| | A297-23-11- N W | 10,3W | 3000K | 300mA | 1280 lm | 78% |
| | A297-23-12- N W | 10,3W | 4000K | 300mA | 1300 lm | 78% |
| | A297-23-30- N W | 10,3W | 2700K | 300mA | 1230 lm | 78% |
| | A297-23-31- N W | 10,3W | 3000K | 300mA | 1280 lm | 78% |
| | A297-23-32- N W | 10,3W | 4000K | 300mA | 1300 lm | 78% |

220 V~ | IP65 | CRI>90 | L90B10 >55.000h


* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



OPTIONAL ACCESSORY

SHOT LIGHT M High Chromatic LED ⓘ >> 281

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | N ■ | W □ | NMG ■ | WMG □


MATERIAL | AL | ABS+PC

RAL ⓘ >> 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N, NMG & WMG COLOURS

Ⓢ & ⓘ >> 288




MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------------------|---------------------------|-------|-------|-------|---------|-----|
| SHOT LIGHT M 1 Trimless | A298-01-10- N W NMG | 5W | 2700K | 150mA | 675 lm | 86% |
| | A298-01-11- N W NMG | 5W | 3000K | 150mA | 700 lm | 86% |
| | A298-01-12- N W NMG | 5W | 4000K | 150mA | 710 lm | 86% |
| SHOT LIGHT M 2 Trimless | A298-02-10- N W NMG | 6,5W | 2700K | 200mA | 910 lm | 86% |
| | A298-02-11- N W NMG | 6,5W | 3000K | 200mA | 940 lm | 86% |
| | A298-02-12- N W NMG | 6,5W | 4000K | 200mA | 960 lm | 86% |
| | A298-02-30- N W NMG | 6,5W | 2700K | 200mA | 910 lm | 86% |
| | A298-02-31- N W NMG | 6,5W | 3000K | 200mA | 940 lm | 86% |
| | A298-02-32- N W NMG | 6,5W | 4000K | 200mA | 960 lm | 86% |
| SHOT LIGHT M 3 Trimless | A298-03-10- N W NMG | 10,3W | 2700K | 300mA | 1230 lm | 86% |
| | A298-03-11- N W NMG | 10,3W | 3000K | 300mA | 1280 lm | 86% |
| | A298-03-12- N W NMG | 10,3W | 4000K | 300mA | 1300 lm | 86% |
| | A298-03-30- N W NMG | 10,3W | 2700K | 300mA | 1230 lm | 86% |
| | A298-03-31- N W NMG | 10,3W | 3000K | 300mA | 1280 lm | 86% |
| | A298-03-32- N W NMG | 10,3W | 4000K | 300mA | 1300 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h


* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



ACCESSORY

SHOT LIGHT M Trimless Accessory** A298-00-00

** MANDATORY FOR INSTALLATION





OPTIONAL ACCESSORIES

SHOT LIGHT M High Chromatic LED ⓘ >> 281

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D79 X D120mm A478-00-05



COLOUR | N ■ | W □ | NMG ■

MATERIAL | AL | ABS+PC

RAL ⓘ >> 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N & NMG COLOURS



Ⓢ & ⓘ >> 288




SHOT LIGHT



MORE INFO >>



MORE INFO >>



| | | P | CCT | I | Flux | LOR |
|------------------------------|----------------------------------|-------|-------|-------|---------|-----|
| SHOT LIGHT M 1 Asymmetric | A297-11-10- N W | 5W | 2700K | 150mA | 675 lm | 83% |
| | A297-11-11- N W | 5W | 3000K | 150mA | 700 lm | 83% |
| | A297-11-12- N W | 5W | 4000K | 150mA | 710 lm | 83% |
| SHOT LIGHT M 2 Asymmetric | A297-12-10- N W | 6,5W | 2700K | 200mA | 910 lm | 83% |
| | A297-12-11- N W | 6,5W | 3000K | 200mA | 940 lm | 83% |
| | A297-12-12- N W | 6,5W | 4000K | 200mA | 960 lm | 83% |
| | A297-12-30- N W | 6,5W | 2700K | 200mA | 910 lm | 83% |
| | A297-12-31- N W | 6,5W | 3000K | 200mA | 940 lm | 83% |
| | DALI PUSH* A297-12-32- N W | 6,5W | 4000K | 200mA | 960 lm | 83% |
| SHOT LIGHT M 3 Asymmetric | A297-13-10- N W | 10,3W | 2700K | 300mA | 1230 lm | 83% |
| | A297-13-11- N W | 10,3W | 3000K | 300mA | 1280 lm | 83% |
| | A297-13-12- N W | 10,3W | 4000K | 300mA | 1300 lm | 83% |
| | A297-13-30- N W | 10,3W | 2700K | 300mA | 1230 lm | 83% |
| | A297-13-31- N W | 10,3W | 3000K | 300mA | 1280 lm | 83% |
| | DALI PUSH* A297-13-32- N W | 10,3W | 4000K | 300mA | 1300 lm | 83% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|--|----------------------------------|-------|-------|-------|---------|-----|
| SHOT LIGHT M 1 Asymmetric Trimless | A298-11-10- N W | 5W | 2700K | 150mA | 675 lm | 83% |
| | A298-11-11- N W | 5W | 3000K | 150mA | 700 lm | 83% |
| | A298-11-12- N W | 5W | 4000K | 150mA | 710 lm | 83% |
| SHOT LIGHT M 2 Asymmetric Trimless | A298-12-10- N W | 6,5W | 2700K | 200mA | 910 lm | 83% |
| | A298-12-11- N W | 6,5W | 3000K | 200mA | 940 lm | 83% |
| | A298-12-12- N W | 6,5W | 4000K | 200mA | 960 lm | 83% |
| | A298-12-30- N W | 6,5W | 2700K | 200mA | 910 lm | 83% |
| | A298-12-31- N W | 6,5W | 3000K | 200mA | 940 lm | 83% |
| | DALI PUSH* A298-12-32- N W | 6,5W | 4000K | 200mA | 960 lm | 83% |
| SHOT LIGHT M 3 Asymmetric Trimless | A298-13-10- N W | 10,3W | 2700K | 300mA | 1230 lm | 83% |
| | A298-13-11- N W | 10,3W | 3000K | 300mA | 1280 lm | 83% |
| | A298-13-12- N W | 10,3W | 4000K | 300mA | 1300 lm | 83% |
| | A298-13-30- N W | 10,3W | 2700K | 300mA | 1230 lm | 83% |
| | A298-13-31- N W | 10,3W | 3000K | 300mA | 1280 lm | 83% |
| | DALI PUSH* A298-13-32- N W | 10,3W | 4000K | 300mA | 1300 lm | 83% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h


* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



ACCESSORY

SHOT LIGHT M Asymmetric Trimless Accessory** A298-10-00

** MANDATORY FOR INSTALLATION




OPTIONAL ACCESSORIES

SHOT LIGHT M High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D79 X D120mm A478-00-05



COLOUR | N ■ | W □ |

MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N COLOUR



Ⓢ & ⓘ » 288



MORE INFO >>

BEAM OPTIONS

| | |
|---|-----|
| 1 | 18° |
| 2 | 49° |



| | | P | CCT | I | Flux | LOR |
|--------------------------|---------------------------|-------|-------|-------|---------|-----|
| SHOT LIGHT Big 1 | A448-11- 00 -0- N | 11,8W | 2700K | 350mA | 1490 lm | 89% |
| | A448-11- 00 -1- N | 11,8W | 3000K | 350mA | 1600 lm | 89% |
| | A448-11- 00 -2- N | 11,8W | 4000K | 350mA | 1720 lm | 89% |
| SHOT LIGHT Big 2 | A448-21- 00 -0- N | 17,5W | 2700K | 500mA | 2010 lm | 89% |
| | A448-21- 00 -1- N | 17,5W | 3000K | 500mA | 2160 lm | 89% |
| | A448-21- 00 -2- N | 17,5W | 4000K | 500mA | 2320 lm | 89% |
| SHOT LIGHT Big 3 | A448-31- 00 -0- N | 25,3W | 2700K | 700mA | 2600 lm | 89% |
| | A448-31- 00 -1- N | 25,3W | 3000K | 700mA | 2780 lm | 89% |
| | A448-31- 00 -2- N | 25,3W | 4000K | 700mA | 3000 lm | 89% |
| | A448-32- 00 -0- N | 25,3W | 2700K | 700mA | 2600 lm | 89% |
| | A448-32- 00 -1- N | 25,3W | 3000K | 700mA | 2780 lm | 89% |
| | DALI* A448-32- 00 -2- N | 25,3W | 4000K | 700mA | 3000 lm | 89% |
| SHOT LIGHT Big IP65 1 | A449-11-20- N W | 11,8W | 2700K | 350mA | 1490 lm | 86% |
| | A449-11-21- N W | 11,8W | 3000K | 350mA | 1600 lm | 86% |
| | A449-11-22- N W | 11,8W | 4000K | 350mA | 1720 lm | 86% |
| SHOT LIGHT Big IP65 2 | A449-21-20- N W | 17,5W | 2700K | 500mA | 2010 lm | 86% |
| | A449-21-21- N W | 17,5W | 3000K | 500mA | 2160 lm | 86% |
| | A449-21-22- N W | 17,5W | 4000K | 500mA | 2320 lm | 86% |
| SHOT LIGHT Big IP65 3 | A449-31-20- N W | 25,3W | 2700K | 700mA | 2600 lm | 86% |
| | A449-31-21- N W | 25,3W | 3000K | 700mA | 2780 lm | 86% |
| | A449-31-22- N W | 25,3W | 4000K | 700mA | 3000 lm | 86% |
| | A449-32-20- N W | 25,3W | 2700K | 700mA | 2600 lm | 86% |
| | DALI* A449-32-21- N W | 25,3W | 3000K | 700mA | 2780 lm | 86% |
| | A449-32-22- N W | 25,3W | 4000K | 700mA | 3000 lm | 86% |
| SHOT LIGHT Big IP65 3 | A449-33-20- N W | 25,3W | 2700K | 700mA | 2600 lm | 86% |
| | A449-33-21- N W | 25,3W | 3000K | 700mA | 2780 lm | 86% |
| | PUSH* A449-33-22- N W | 25,3W | 4000K | 700mA | 3000 lm | 86% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|--------------------------|---------------------------|-------|-------|-------|---------|-----|
| SHOT LIGHT Big IP65 1 | A449-11-20- N W | 11,8W | 2700K | 350mA | 1490 lm | 86% |
| | A449-11-21- N W | 11,8W | 3000K | 350mA | 1600 lm | 86% |
| | A449-11-22- N W | 11,8W | 4000K | 350mA | 1720 lm | 86% |
| SHOT LIGHT Big IP65 2 | A449-21-20- N W | 17,5W | 2700K | 500mA | 2010 lm | 86% |
| | A449-21-21- N W | 17,5W | 3000K | 500mA | 2160 lm | 86% |
| | A449-21-22- N W | 17,5W | 4000K | 500mA | 2320 lm | 86% |
| SHOT LIGHT Big IP65 3 | A449-31-20- N W | 25,3W | 2700K | 700mA | 2600 lm | 86% |
| | A449-31-21- N W | 25,3W | 3000K | 700mA | 2780 lm | 86% |
| | A449-31-22- N W | 25,3W | 4000K | 700mA | 3000 lm | 86% |
| | A449-32-20- N W | 25,3W | 2700K | 700mA | 2600 lm | 86% |
| | DALI* A449-32-21- N W | 25,3W | 3000K | 700mA | 2780 lm | 86% |
| | A449-32-22- N W | 25,3W | 4000K | 700mA | 3000 lm | 86% |
| SHOT LIGHT Big IP65 3 | A449-33-20- N W | 25,3W | 2700K | 700mA | 2600 lm | 86% |
| | A449-33-21- N W | 25,3W | 3000K | 700mA | 2780 lm | 86% |
| | PUSH* A449-33-22- N W | 25,3W | 4000K | 700mA | 3000 lm | 86% |

220 V~ | IP65 | CRI>90 | L80B10 >60.000h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | N ■ | W □ |


MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR N COLOUR

Ⓢ & ⓘ » 288

LENS LIGHT



MORE INFO >>


| | | P | CCT | I | Flux | LOR |
|------------|------------------------|------|-------|-------|--------|-----|
| LENS LIGHT | A469-0- ① -00- N W | 5,7W | 2700K | 500mA | 510 lm | 82% |
| | A469-0- ① -01- N W | 5,7W | 3000K | 500mA | 540 lm | 82% |
| | A469-0- ① -02- N W | 5,7W | 4000K | 500mA | 580 lm | 82% |

220 V~ | 240 V~ | IP20 | CRI>90 | L90B10 >108.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT




COLOUR | N ■ | W □ |

MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓜ & Ⓜ » 288



MORE INFO >>


| | | P | CCT | I | Flux | LOR |
|------------|------------------------|------|-------|-------|--------|-----|
| LENS LIGHT | A470-0- ① -00- N W | 5,7W | 2700K | 500mA | 510 lm | 82% |
| Trimless | A470-0- ① -01- N W | 5,7W | 3000K | 500mA | 540 lm | 82% |
| | A470-0- ① -02- N W | 5,7W | 4000K | 500mA | 580 lm | 82% |

220 V~ | 240 V~ | IP20 | CRI>90 | L90B10 >108.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | N ■ | W □ |

MATERIAL | AL | ABS+PC |

RAL ⓘ » 312



COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓜ & Ⓜ » 288

ACCESSORY


LENS LIGHT Trimless Accessory** A470-00-00

** MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORY

TRIMLESS TOOL D43 X D70mm A478-00-02




BUDDY



MORE INFO >>

| | BEAM | LOR |
|---|------|-----|
| 1 | 29° | 82% |
| 2 | 43° | 83% |
| 3 | 54° | 80% |



OPTIONAL ACCESSORY

BUDDY

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



| BUDDY | A507-00-0-0- W N WG NG WN | CCT |
|-------|-------------------------------------|-------|
| | A507-00-0-1- W N WG NG WN | 2700K |
| | A507-00-0-2- W N WG NG WN | 3000K |
| | A507-00-0-2- W N WG NG WN | 4000K |

220 V~ | IP54 | CRI>90 | L80B10 >66.000h | MacAdam Step 2 | EXCL | Ø79 | 29° / 43° / 54°

| BUDDY Super Spot | A507-00-00- W N WG NG WN | CCT | Beam | LOR |
|------------------|------------------------------------|-------|------|-----|
| | A507-00-01- W N WG NG WN | 2700K | 12° | 62% |
| | A507-00-01- W N WG NG WN | 3000K | 12° | 62% |
| | A507-00-02- W N WG NG WN | 4000K | 12° | 62% |

220 V~ | IP54 | CRI>90 | L80B10 >55.000h | MacAdam Step 2 | EXCL | Ø79 | 12°

| BUDDY Tunable White | A507-01-18- W N WG NG WN | CCT | Beam | LOR |
|---------------------|------------------------------------|------------|------|-----|
| | A507-01-28- W N WG NG WN | 2700-5000K | 28° | 85% |
| | A507-01-28- W N WG NG WN | 2700-5000K | 43° | 86% |
| | A507-01-38- W N WG NG WN | 2700-5000K | 55° | 81% |

220 V~ | IP54 | CRI>90 | L80B10 >55.000h | MacAdam Step 3 | EXCL | Ø79 | 28° / 43° / 55°

| BUDDY DIM to warm | A507-02-39- W N WG NG WN | CCT | Beam | LOR |
|-------------------|------------------------------------|------------|------|-----|
| | A507-02-39- W N WG NG WN | 1800-3000K | 54° | 75% |

220 V~ | IP54 | CRI>90 | L80B10 >55.000h | MacAdam Step 3 | EXCL | Ø79 | 54°

| *DRIVER OPTIONS | P | I | CCT | Flux | | |
|---------------------|--------|------------|-----------|------------|------------|---------|
| BUDDY 1 | NO DIM | 0434-01-85 | 4W | 125mA | 2700K | 760 lm |
| | | | 3000K | 790 lm | | |
| | | | 4000K | 800 lm | | |
| BUDDY 2 | NO DIM | 0434-01-86 | 6,6W | 200mA | 2700K | 1150 lm |
| | | | DALI | 0434-01-89 | 3000K | 1200 lm |
| | | | CASAMBI | 0434-01-91 | 4000K | 1220 lm |
| | | | PHASE CUT | 0434-01-92 | | |
| BUDDY Super Spot | NO DIM | 0434-01-87 | 6W | 500mA | 2700K | 750 lm |
| | | | DALI | 0434-01-88 | 3000K | 790 lm |
| BUDDY Tunable White | DALI | 0434-01-90 | 6,7W | 400mA | 2700-5000K | 815 lm |
| | | | | | | |
| BUDDY DIM to warm | DALI | 0434-01-94 | 6W | 350mA | 1800-3000K | 650 lm |
| | | | PHASE CUT | 0434-01-95 | | |

220 V~ | 48V PLEASE CONSULT | 282


COLOUR | W □ | N ■ | WG ■ | NG ■ | WN ■ | MATERIAL | AL | PC/PMMA | RAL | 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS | OTHER CCT OPTIONS PLEASE CONSULT | 288



MORE INFO >>

| | BEAM | LOR |
|---|------|-----|
| 1 | 29° | 82% |
| 2 | 43° | 83% |
| 3 | 54° | 80% |




ACCESSORY

BUDDY Trimless Accessory**

A507-10-90

MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORIES



BUDDY Trimless

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D79 X D120mm

A478-00-05



| BUDDY Trimless | A507-10-0-0- W N G | CCT |
|----------------|--------------------------|-------|
| | A507-10-0-1- W N G | 2700K |
| | A507-10-0-2- W N G | 3000K |
| | A507-10-0-2- W N G | 4000K |

220 V~ | IP20 | CRI>90 | L80B10 >66.000h | MacAdam Step 2 | EXCL | EXCL** | Ø79 | 29° / 43° / 54°

| BUDDY Trimless Super Spot | A507-10-00- W N G | CCT | Beam | LOR |
|---------------------------|-------------------------|-------|------|-----|
| | A507-10-01- W N G | 2700K | 12° | 62% |
| | A507-10-01- W N G | 3000K | 12° | 62% |
| | A507-10-02- W N G | 4000K | 12° | 62% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h | MacAdam Step 2 | EXCL | EXCL** | Ø79 | 12°

| BUDDY Trimless Tunable White | A507-11-18- W N G | CCT | Beam | LOR |
|------------------------------|-------------------------|------------|------|-----|
| | A507-11-28- W N G | 2700-5000K | 28° | 85% |
| | A507-11-28- W N G | 2700-5000K | 43° | 86% |
| | A507-11-38- W N G | 2700-5000K | 55° | 81% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h | MacAdam Step 3 | EXCL | EXCL** | Ø79 | 28° / 43° / 55°

| BUDDY Trimless DIM to warm | A507-12-39- W N G | CCT | Beam | LOR |
|----------------------------|-------------------------|------------|------|-----|
| | A507-12-39- W N G | 1800-3000K | 54° | 75% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h | MacAdam Step 3 | EXCL | EXCL** | Ø79 | 54°

| *DRIVER OPTIONS | P | I | CCT | Flux | | |
|------------------------------|--------|------------|-----------|------------|------------|---------|
| BUDDY Trimless 1 | NO DIM | 0434-01-85 | 4W | 125mA | 2700K | 760 lm |
| | | | 3000K | 790 lm | | |
| | | | 4000K | 800 lm | | |
| BUDDY Trimless 2 | NO DIM | 0434-01-86 | 6,6W | 200mA | 2700K | 1150 lm |
| | | | DALI | 0434-01-89 | 3000K | 1200 lm |
| | | | CASAMBI | 0434-01-91 | 4000K | 1220 lm |
| | | | PHASE CUT | 0434-01-92 | | |
| BUDDY Trimless Super Spot | NO DIM | 0434-01-87 | 6W | 500mA | 2700K | 750 lm |
| | | | DALI | 0434-01-88 | 3000K | 790 lm |
| BUDDY Trimless Tunable White | DALI | 0434-01-90 | 6,7W | 400mA | 2700-5000K | 815 lm |
| | | | | | | |
| BUDDY Trimless DIM to warm | DALI | 0434-01-94 | 6W | 350mA | 1800-3000K | 650 lm |
| | | | PHASE CUT | 0434-01-95 | | |

220 V~ | 48V PLEASE CONSULT | 282

COLOUR | W □ | N ■ | G ■ | MATERIAL | AL | PC/PMMA | RAL | 312


COLOURS MAY AFFECT THE LIGHTING PARAMETERS | OTHER CCT OPTIONS PLEASE CONSULT | 288

BUDDY



MORE INFO >>

| | BEAM | LOR |
|---|------|-----|
| 1 | 29° | 82% |
| 2 | 43° | 83% |
| 3 | 54° | 80% |



OPTIONAL ACCESSORY

BUDDY Tilt
High Chromatic LED ⓘ » 281
 NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



| | | CCT | |
|------------|-------------------------------------|-------|--|
| BUDDY Tilt | A508-00-0-0- W N WG NG WN | 2700K | |
| | A508-00-0-1- W N WG NG WN | 3000K | |
| | A508-00-0-2- W N WG NG WN | 4000K | |

220 V~ | IP54 | CRI>90 | L80B10 >66.000h
 MacAdam Step 2 EXCL 355° 25° Ø79 29° / 43° / 54°

| | | CCT | Beam | LOR |
|-----------------------|------------------------------------|-------|------|-----|
| BUDDY Tilt Super Spot | A508-00-00- W N WG NG WN | 2700K | 12° | 62% |
| | A508-00-01- W N WG NG WN | 3000K | 12° | 62% |
| | A508-00-02- W N WG NG WN | 4000K | 12° | 62% |

220 V~ | IP54 | CRI>90 | L80B10 >55.000h
 MacAdam Step 2 EXCL 355° 25° Ø79 12°

| | | CCT | Beam | LOR |
|--------------------------|------------------------------------|------------|------|-----|
| BUDDY Tilt Tunable White | A508-01-18- W N WG NG WN | 2700-5000K | 28° | 85% |
| | A508-01-28- W N WG NG WN | 2700-5000K | 43° | 86% |
| | A508-01-38- W N WG NG WN | 2700-5000K | 55° | 81% |

220 V~ | IP54 | CRI>90 | L80B10 >55.000h
 MacAdam Step 3 EXCL 355° 25° Ø79 28° / 43° / 55°

| | | CCT | Beam | LOR |
|------------------------|------------------------------------|------------|------|-----|
| BUDDY Tilt DIM to warm | A508-02-39- W N WG NG WN | 1800-3000K | 54° | 75% |

220 V~ | IP54 | CRI>90 | L80B10 >55.000h
 MacAdam Step 3 EXCL 355° 25° Ø79 54°

| *DRIVER OPTIONS | | P | I | CCT | Flux |
|--------------------------|-----------|------|-------|------------|---------|
| BUDDY Tilt 1 | NO DIM | 4W | 125mA | 2700K | 760 lm |
| | DALI | | | 3000K | 790 lm |
| | CASAMBI | | | 4000K | 800 lm |
| BUDDY Tilt 2 | NO DIM | 6,6W | 200mA | 2700K | 1150 lm |
| | DALI | | | 3000K | 1200 lm |
| | CASAMBI | | | 4000K | 1220 lm |
| BUDDY Tilt Super Spot | NO DIM | 6W | 500mA | 2700K | 750 lm |
| | DALI | | | 3000K | 790 lm |
| | PHASE CUT | | | 4000K | 845 lm |
| BUDDY Tilt Tunable White | DALI | 6,7W | 400mA | 2700-5000K | 815 lm |
| BUDDY Tilt DIM to warm | DALI | 6W | 350mA | 1800-3000K | 650 lm |
| | PHASE CUT | | | 4000K | 845 lm |
| | PHASE CUT | | | 4000K | 845 lm |

220 V~ | 48V PLEASE CONSULT ⓘ » 282


COLOUR | W □ | N ■ | WG ■ | NG ■ | WN ■ | MATERIAL | AL | PC/PMMA | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS ⓘ & » 288
 OTHER CCT OPTIONS PLEASE CONSULT



MORE INFO >>


| | BEAM | LOR |
|---|------|-----|
| 1 | 29° | 82% |
| 2 | 43° | 83% |
| 3 | 54° | 80% |



ACCESSORY

BUDDY Tilt Trimless Accessory**
A508-10-90

MANDATORY FOR INSTALLATION





OPTIONAL ACCESSORIES

BUDDY Tilt Trimless
High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D79 X D120mm
A478-00-05



| | | CCT | |
|---------------------|--------------------------|-------|--|
| BUDDY Tilt Trimless | A508-10-0-0- W N G | 2700K | |
| | A508-10-0-1- W N G | 3000K | |
| | A508-10-0-2- W N G | 4000K | |

220 V~ | IP20 | CRI>90 | L80B10 >66.000h
 MacAdam Step 2 EXCL EXCL** 25° Ø79 29° / 43° / 54°

| | | CCT | Beam | LOR |
|--------------------------------|-------------------------|-------|------|-----|
| BUDDY Tilt Trimless Super Spot | A508-10-00- W N G | 2700K | 12° | 62% |
| | A508-10-01- W N G | 3000K | 12° | 62% |
| | A508-10-02- W N G | 4000K | 12° | 62% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h
 MacAdam Step 2 EXCL EXCL** 25° Ø79 12°

| | | CCT | Beam | LOR |
|-----------------------------------|-------------------------|------------|------|-----|
| BUDDY Tilt Trimless Tunable White | A508-11-18- W N G | 2700-5000K | 28° | 85% |
| | A508-11-28- W N G | 2700-5000K | 43° | 86% |
| | A508-11-38- W N G | 2700-5000K | 55° | 81% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h
 MacAdam Step 3 EXCL EXCL** 25° Ø79 28° / 43° / 55°

| | | CCT | Beam | LOR |
|---------------------------------|-------------------------|------------|------|-----|
| BUDDY Tilt Trimless DIM to warm | A508-12-39- W N G | 1800-3000K | 54° | 75% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h
 MacAdam Step 3 EXCL EXCL** 25° Ø79 54°

| *DRIVER OPTIONS | | P | I | CCT | Flux |
|-----------------------------------|-----------|------|-------|------------|---------|
| BUDDY Tilt Trimless 1 | NO DIM | 4W | 125mA | 2700K | 760 lm |
| | DALI | | | 3000K | 790 lm |
| | CASAMBI | | | 4000K | 800 lm |
| BUDDY Tilt Trimless 2 | NO DIM | 6,6W | 200mA | 2700K | 1150 lm |
| | DALI | | | 3000K | 1200 lm |
| | CASAMBI | | | 4000K | 1220 lm |
| BUDDY Tilt Trimless Super Spot | NO DIM | 6W | 500mA | 2700K | 750 lm |
| | DALI | | | 3000K | 790 lm |
| | PHASE CUT | | | 4000K | 845 lm |
| BUDDY Tilt Trimless Tunable White | DALI | 6,7W | 400mA | 2700-5000K | 815 lm |
| BUDDY Tilt Trimless DIM to warm | DALI | 6W | 350mA | 1800-3000K | 650 lm |
| | PHASE CUT | | | 4000K | 845 lm |
| | PHASE CUT | | | 4000K | 845 lm |

220 V~ | 48V PLEASE CONSULT ⓘ » 282

COLOUR | W □ | N ■ | G ■ | MATERIAL | AL | PC/PMMA | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS ⓘ & » 288
 OTHER CCT OPTIONS PLEASE CONSULT



MORE INFO >>

| | | P | CCT | I | Flux | LOR | |
|-------------------------------|--|--|-------|-------|--------|--------|-----|
| SWAP S CRI>90 | A212-11-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 86% | |
| | A212-11-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 86% | |
| | A212-11-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 86% | |
| | A212-12-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% | |
| | A212-12-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% | |
| | A212-12-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% | |
| | A212-12-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% | |
| | A212-12-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% | |
| | PHASE CUT** | A212-12-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | | A212-12-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | | A212-12-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | DALI I PUSH** | A212-12-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| SWAP S Super CRI CRI>97 | A312-12-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% | |
| | A312-12-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% | |
| | A312-12-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% | |
| | A312-12-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% | |
| | A312-12-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% | |
| | PHASE CUT** | A312-12-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | | A312-12-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | | A312-12-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | DALI I PUSH** | A312-12-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |

220 V~ | IP20 | IP65* | L90B10 >55.000h


MacAdam Step 2 FAST I CONNEX INCL INCL I ACC. Ø62 UGR <19 33°

| | | P | CCT | I | Flux | LOR |
|---------------------------------|--|----|------------|-------|--------|-----|
| SWAP S DIM to warm CRI>90 | A212-13-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | A212-13-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h

MacAdam Step 3 FAST I CONNEX INCL INCL I ACC. Ø62 UGR <19 33°

OPTIONAL ACCESSORY



*SWAP IP65
AFFECTS THE LIGHTING PARAMETERS

| WHITE - DIRECT REFERENCE | LOR |
|--------------------------|-----|
| W65 □ | 81% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS
REFERENCE + A212-10-65- | W | N | IP65 ACCESSORY S
PRE-ASSEMBLED. NOT SOLD SEPARATELY

36°

↑↑↑ *IP65

COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ » 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓢ & Ⓜ » 288



MORE INFO >>

| | | P | CCT | I | Flux | LOR | |
|-------------------------------|--|--|-------|-------|--------|--------|-----|
| SWAP M CRI>90 | A212-21-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 86% | |
| | A212-21-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 86% | |
| | A212-21-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 86% | |
| | A212-22-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% | |
| | A212-22-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% | |
| | A212-22-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% | |
| | A212-22-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% | |
| | A212-22-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% | |
| | PHASE CUT** | A212-22-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | | A212-22-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | | A212-22-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | DALI I PUSH** | A212-22-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| SWAP M Super CRI CRI>97 | A312-22-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% | |
| | A312-22-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% | |
| | A312-22-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% | |
| | A312-22-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% | |
| | A312-22-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% | |
| | PHASE CUT** | A312-22-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | | A312-22-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | | A312-22-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | DALI I PUSH** | A312-22-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |

220 V~ | IP20 | IP65* | L90B10 >55.000h


MacAdam Step 2 FAST I CONNEX INCL INCL I ACC. Ø75 UGR <19 42°

| | | P | CCT | I | Flux | LOR |
|---------------------------------|--|----|------------|-------|--------|-----|
| SWAP M DIM to warm CRI>90 | A212-23-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | A212-23-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h

MacAdam Step 3 FAST I CONNEX INCL INCL I ACC. Ø75 UGR <19 42°

OPTIONAL ACCESSORIES



*SWAP IP65
AFFECTS THE LIGHTING PARAMETERS

| WHITE - DIRECT REFERENCE | LOR |
|--------------------------|-----|
| W65 □ | 81% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS
REFERENCE + A212-20-65- | W | N | IP65 ACCESSORY M
PRE-ASSEMBLED. NOT SOLD SEPARATELY

46°

↑↑↑ *IP65


COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ » 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓢ & Ⓜ » 288



FLAT SPRING ACCESSORY
A212-00-00
ACCESSORY FOR CONCRETE CEILINGS. NOT PRE-ASSEMBLED. SELF-INSTALLATION KIT TOGETHER WITH THE PRODUCT.





MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|-------------------------------|--|-----|-------|-------|--------|-----|
| SWAP L CRI>90 | A212-31-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 86% |
| | A212-31-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 86% |
| | A212-31-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 86% |
| | A212-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A212-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | A212-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A212-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A212-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | PHASE CUT** A212-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A212-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A212-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | DALI I PUSH** A212-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| SWAP L Super CRI CRI>97 | A312-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A312-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | A312-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A312-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A312-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | PHASE CUT** A312-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A312-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A312-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | DALI I PUSH** A312-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |

220 V~ | IP20 | IP65* | L80B10 >55.000h


MacAdam Step 2 FAST I CONNEC INCL INCL | ACC. Ø85 UGR <19 40°

| | P | CCT | I | Flux | LOR | |
|---------------------------------|--|-----|------------|-------|--------|-----|
| SWAP L DIM to warm CRI>90 | A212-33-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | DALI I PUSH** A212-33-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h

MacAdam Step 3 FAST I CONNEC INCL INCL | ACC. Ø85 UGR <19 40°

OPTIONAL ACCESSORIES



***SWAP IP65**
AFFECTS THE LIGHTING PARAMETERS

| | |
|--------------------------|-----|
| WHITE - DIRECT REFERENCE | LOR |
| W65 □ | 81% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS
REFERENCE + A212-30-65- | W | N | IP65 ACCESSORY L
PRE-ASSEMBLED. NOT SOLD SEPARATELY

FLAT SPRING ACCESSORY
A212-00-00
ACCESSORY FOR CONCRETE CEILINGS. NOT PRE-ASSEMBLED. SELF-INSTALLATION KIT TOGETHER WITH THE PRODUCT.

↑↑↑ *IP65



COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ » 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS ⓘ & ⓘ » 288



MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|--------------------------------|--|-----|-------|-------|--------|-----|
| SWAP XL CRI>90 | A212-41-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 86% |
| | A212-41-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 86% |
| | A212-41-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 86% |
| | A212-42-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A212-42-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | A212-42-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A212-42-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A212-42-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | PHASE CUT** A212-42-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A212-42-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A212-42-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | DALI I PUSH** A212-42-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| SWAP XL Super CRI CRI>97 | A312-42-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A312-42-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | A312-42-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A312-42-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A312-42-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | PHASE CUT** A312-42-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A312-42-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A312-42-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | DALI I PUSH** A312-42-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |

220 V~ | IP20 | IP65* | L80B10 >55.000h


MacAdam Step 2 FAST I CONNEC INCL INCL | ACC. Ø101 UGR <19 43°

| | P | CCT | I | Flux | LOR | |
|----------------------------------|--|-----|------------|-------|--------|-----|
| SWAP XL DIM to warm CRI>90 | A212-43-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | DALI I PUSH** A212-43-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h

MacAdam Step 3 FAST I CONNEC INCL INCL | ACC. Ø101 UGR <19 43°

OPTIONAL ACCESSORIES



***SWAP IP65**
AFFECTS THE LIGHTING PARAMETERS

| | |
|--------------------------|-----|
| WHITE - DIRECT REFERENCE | LOR |
| W65 □ | 81% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS
REFERENCE + A212-40-65- | W | N | IP65 ACCESSORY XL
PRE-ASSEMBLED. NOT SOLD SEPARATELY

FLAT SPRING ACCESSORY
A212-00-00
ACCESSORY FOR CONCRETE CEILINGS. NOT PRE-ASSEMBLED. SELF-INSTALLATION KIT TOGETHER WITH THE PRODUCT.

↑↑↑ *IP65



COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ » 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS ⓘ & ⓘ » 288



MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|--|--|-----|-------|-------|--------|-----|
| SWAP M Asymmetric CRI>90 | A216-21-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 86% |
| | A216-21-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 86% |
| | A216-21-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 86% |
| | A216-22-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A216-22-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | A216-22-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A216-22-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | PHASE CUT** A216-22-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | A216-22-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A216-22-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A216-22-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | DALI PUSH** A216-22-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| SWAP M Asymmetric Super CRI CRI>97 | A316-22-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A316-22-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | A316-22-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A316-22-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | PHASE CUT** A316-22-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | A316-22-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A316-22-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A316-22-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | DALI PUSH** A316-22-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |

220 V~ | IP20 | IP65* | L80B10 >55.000h




| | P | CCT | I | Flux | LOR | |
|--|--|-----|------------|-------|--------|-----|
| SWAP M Asymmetric DIM to warm CRI>90 | PHASE CUT** A216-23-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | DALI PUSH** A216-23-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h



OPTIONAL ACCESSORY

Swap M
Asymmetric



*SWAP IP65


AFFECTS THE LIGHTING PARAMETERS

| WHITE - DIRECT REFERENCE | LOR |
|--------------------------|-----|
| W65 □ | 81% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS

REFERENCE + A212-20-65- | W | N | IP65 ACCESSORY M

PRE-ASSEMBLED. NOT SOLD SEPARATELY



COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ » 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓢ & Ⓢ » 288



MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|--|--|-----|-------|-------|--------|-----|
| SWAP L Asymmetric CRI>90 | A216-31-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 86% |
| | A216-31-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 86% |
| | A216-31-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 86% |
| | A216-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A216-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | A216-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A216-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | PHASE CUT** A216-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | A216-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A216-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A216-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | DALI PUSH** A216-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| SWAP L Asymmetric Super CRI CRI>97 | A316-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A316-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | A316-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A316-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | PHASE CUT** A316-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | A316-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A316-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A316-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | DALI PUSH** A316-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |

220 V~ | IP20 | IP65* | L80B10 >55.000h




| | P | CCT | I | Flux | LOR | |
|--|--|-----|------------|-------|--------|-----|
| SWAP L Asymmetric DIM to warm CRI>90 | PHASE CUT** A216-33-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | DALI PUSH** A216-33-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h



OPTIONAL ACCESSORY

Swap L
Asymmetric



*SWAP IP65


AFFECTS THE LIGHTING PARAMETERS

| WHITE - DIRECT REFERENCE | LOR |
|--------------------------|-----|
| W65 □ | 81% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS

REFERENCE + A212-30-65- | W | N | IP65 ACCESSORY L

PRE-ASSEMBLED. NOT SOLD SEPARATELY



COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ » 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓢ & Ⓢ » 288





MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|---|--|-----|-------|-------|--------|-----|
| SWAP Square CRI>90 | A254-31-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 90% |
| | A254-31-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 90% |
| | A254-31-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 90% |
| | A254-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 90% |
| | A254-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 90% |
| | A254-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 90% |
| | A254-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 90% |
| | A254-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 90% |
| | PHASE CUT** A254-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 90% |
| | A254-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 90% |
| | A254-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 90% |
| | DALI I PUSH** A254-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 90% |
| SWAP Square Super CRI CRI>97 | A354-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 90% |
| | A354-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 90% |
| | A354-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 90% |
| | A354-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 90% |
| | A354-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 90% |
| | PHASE CUT** A354-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 90% |
| | A354-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 90% |
| | A354-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 90% |
| | DALI I PUSH** A354-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 90% |

220 V~ | IP20 | IP65* | L90B10 >55.000h

MacAdam Step 2 FAST | CONNEC INCL INCL | ACC. 85 X 85 UGR <19 44°

| | P | CCT | I | Flux | LOR | |
|---|--|-----|------------|-------|--------|-----|
| SWAP Square DIM to warm CRI>90 | A254-33-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | DALI I PUSH** A254-33-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h

MacAdam Step 3 FAST | CONNEC INCL INCL | ACC. 85 X 85 UGR <19 44°

OPTIONAL ACCESSORY

*SWAP IP65



AFFECTS THE LIGHTING PARAMETERS

| WHITE - DIRECT REFERENCE | LOR |
|--------------------------|-----|
| W65 □ | 85% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS

REFERENCE + A254-30-65- | W | N | IP65 ACCESSORY Square

PRE-ASSEMBLED. NOT SOLD SEPARATELY



COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ >> 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓢ & Ⓜ >> 288



MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|---|--|-----|-------|-------|--------|-----|
| SWAP Square Asymmetric CRI>90 | A255-31-10- W R G Z WN N W65 | 5W | 2700K | 150mA | 675 lm | 86% |
| | A255-31-11- W R G Z WN N W65 | 5W | 3000K | 150mA | 700 lm | 86% |
| | A255-31-12- W R G Z WN N W65 | 5W | 4000K | 150mA | 710 lm | 86% |
| | A255-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A255-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | A255-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A255-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A255-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | PHASE CUT** A255-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| | A255-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 910 lm | 86% |
| | A255-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 940 lm | 86% |
| | DALI I PUSH** A255-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 960 lm | 86% |
| SWAP Square Asymmetric Super CRI CRI>97 | A355-32-10- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A355-32-11- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | A355-32-12- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A355-32-20- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A355-32-21- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | PHASE CUT** A355-32-22- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |
| | A355-32-30- W R G Z WN N W65 | 7W | 2700K | 200mA | 770 lm | 86% |
| | A355-32-31- W R G Z WN N W65 | 7W | 3000K | 200mA | 800 lm | 86% |
| | DALI I PUSH** A355-32-32- W R G Z WN N W65 | 7W | 4000K | 200mA | 820 lm | 86% |

220 V~ | IP20 | IP65* | L90B10 >55.000h

MacAdam Step 2 FAST | CONNEC INCL INCL | ACC. 85 X 85 52°

| | P | CCT | I | Flux | LOR | |
|---|--|-----|------------|-------|--------|-----|
| SWAP Square Asymmetric DIM to warm CRI>90 | A255-33-29- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |
| | DALI I PUSH** A255-33-39- W R G Z WN N W65 | 6W | 3000-1800K | 350mA | 640 lm | 80% |

220 V~ | IP20 | IP65* | L80B10 >55.000h

MacAdam Step 3 FAST | CONNEC INCL INCL | ACC. 85 X 85 52°

OPTIONAL ACCESSORY

*SWAP IP65


AFFECTS THE LIGHTING PARAMETERS

| WHITE - DIRECT REFERENCE | LOR |
|--------------------------|-----|
| W65 □ | 81% |
| W65 □ DIM TO WARM | 76% |

OTHER COLOURS

REFERENCE + A254-30-65- | W | N | IP65 ACCESSORY Square

PRE-ASSEMBLED. NOT SOLD SEPARATELY



COLOUR | W □ | R □ | G □ | Z □ | WN □ | N □ | MATERIAL | AL | PC | PC | RAL ⓘ >> 312

** OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓢ & Ⓜ >> 288





BISEL EXTRA

Extra Bezel
Collerette Extra
Cornice Extra
Zusatz-Zierring



Complemento siempre incluido pero de uso opcional. Extiende el bisel de la pieza para cubrir empotramientos mayores, conservando el minimalismo de Swap y su perfecta integración en el techo. Fácil instalación. Ideal para reformas en las que reemplazar puntos de luz, con agujeros preexistentes, sin obras en el techo ni volver a pintar. Swap es la mejor opción de actualización al LED, frente a las lámparas de sustitución 'retrofit'.


Accessory always included but for optional use. It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling. Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.

Complément toujours inclus mais à utiliser en option. Élargissement de la collerette de la pièce pour couvrir des encastres supérieurs tout en préservant le minimalisme de Swap et son intégration parfaite au plafond. Facile à installer. Idéal pour les réaménagements comprenant des points lumineux à remplacer avec des trous préexistants, sans travaux au plafond et sans besoin de repeindre. Swap est la meilleure option d'actualisation au LED, quand le LED et l'appareil d'éclairage sont intégrés, face aux lampes de substitution «retrofit».

Complemento sempre incluso, ma di uso facoltativo. Estende la cornice del pezzo per coprire incassi maggiori, conservando il minimalismo di Swap e la sua perfetta integrazione con il soffitto. Di facile installazione. Ideale per ristrutturazioni in cui è necessario sostituire punti luce, con fori pre-esistenti, senza lavori al soffitto né verniciatura. Swap è la migliore opzione di passaggio al LED rispetto alle lampade di sostituzione 'retrofit' che si limitano ad adeguare soltanto la fonte di luce.

Stets im Lieferumfang enthaltenes Zubehör-Teil, das optional verwendet werden kann, zur Verbreiterung des vorhandenen Zierrings und somit auch der Abdeckung größerer Lochmaße. Dabei bleiben der Minimalismus von Swap und die perfekte Integration in die Decke erhalten. Einfacher Einbau. Ideal bei Renovierungen, um Leuchten an bereits bestehenden Öffnungen ohne Eingriffe an der Decke oder zusätzliche Malerarbeiten auszutauschen. SWAP ist somit die ideale Option auf eine echte LED Leuchte mit integrierter LED aufzurüsten, statt nur mit einer ineffizienten Retrofit-Lampe das Leuchtmittel zu aktualisieren.



| | | | | | | | |
|--------------|---|---|---|---|---|---|---|
| Swap COLOUR | W | R | G | Z | W | N | N |
| bezel COLOUR | W | W | W | W | W | N | N |





NO WORKS, NO REPAINTING

CUT OUT

From 62 to 126 mm



CUT-OUT MEASURES



SWAP



| | P | CCT | I | Flux | LOR | |
|----------------|--------------------------------------|-----|-------|-------|--------|-----|
| SWAP S RT 2012 | A412-11-10- W R G Z WN N | 5W | 2700K | 150mA | 675 lm | 81% |
| | A412-11-11- W R G Z WN N | 5W | 3000K | 150mA | 700 lm | 81% |
| | A412-11-12- W R G Z WN N | 5W | 4000K | 150mA | 710 lm | 81% |
| | A412-12-10- W R G Z WN N | 7W | 2700K | 200mA | 910 lm | 81% |
| | A412-12-11- W R G Z WN N | 7W | 3000K | 200mA | 940 lm | 81% |
| | A412-12-12- W R G Z WN N | 7W | 4000K | 200mA | 960 lm | 81% |

220 V~ | IP65 | CRI>90 | L90B10 >55.000h


MacAdam Step 2 FAST | CONNEC INCL EXCL | ACC. Ø62 UGR <19 36°



| | P | CCT | I | Flux | LOR | |
|----------------|--------------------------------------|-----|-------|-------|--------|-----|
| SWAP M RT 2012 | A412-21-10- W R G Z WN N | 5W | 2700K | 150mA | 675 lm | 81% |
| | A412-21-11- W R G Z WN N | 5W | 3000K | 150mA | 700 lm | 81% |
| | A412-21-12- W R G Z WN N | 5W | 4000K | 150mA | 710 lm | 81% |
| | A412-22-10- W R G Z WN N | 7W | 2700K | 200mA | 910 lm | 81% |
| | A412-22-11- W R G Z WN N | 7W | 3000K | 200mA | 940 lm | 81% |
| | A412-22-12- W R G Z WN N | 7W | 4000K | 200mA | 960 lm | 81% |


220 V~ | IP65 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 FAST | CONNEC INCL EXCL | ACC. Ø75 UGR <19 46°




EXCL | COLLERETTE EXCLUE. NON COMPATIBLE

Swap. (S) RT 2012



Swap. (M) RT 2012



SPÉCIALE FRANCE

COLOUR | W □ | R ■ | G ■ | Z ■ | WN □ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS | ADD-ON BEZEL EXCLUDED. NOT COMPATIBLE

POINTER



MORE INFO >>


| | P | CCT | I | Flux | LOR | |
|---------|--------------------------|-----|-------|-------|---------|-----|
| POINTER | A271-11- (0) -0- W N | 5W | 2700K | 150mA | 680 lm | 78% |
| | A271-11- (0) -1- W N | 5W | 3000K | 150mA | 700 lm | 78% |
| | A271-11- (0) -2- W N | 5W | 4000K | 150mA | 720 lm | 78% |
| | A271-21- (0) -0- W N | 7W | 2700K | 200mA | 860 lm | 78% |
| | A271-21- (0) -1- W N | 7W | 3000K | 200mA | 900 lm | 78% |
| | A271-21- (0) -2- W N | 7W | 4000K | 200mA | 920 lm | 78% |
| | A271-31- (0) -0- W N | 11W | 2700K | 300mA | 1200 lm | 78% |
| | A271-31- (0) -1- W N | 11W | 3000K | 300mA | 1250 lm | 78% |
| | A271-31- (0) -2- W N | 11W | 4000K | 300mA | 1280 lm | 78% |
| | A271-32- (0) -0- W N | 11W | 2700K | 300mA | 1200 lm | 78% |
| | A271-32- (0) -1- W N | 11W | 3000K | 300mA | 1250 lm | 78% |
| | A271-32- (0) -2- W N | 11W | 4000K | 300mA | 1280 lm | 78% |
| | A271-33- (0) -0- W N | 11W | 2700K | 300mA | 1200 lm | 78% |
| | A271-33- (0) -1- W N | 11W | 3000K | 300mA | 1250 lm | 78% |
| | A271-33- (0) -2- W N | 11W | 4000K | 300mA | 1280 lm | 78% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 INCL 355° 30° Ø105 37° / 56°

BEAM OPTIONS

| | |
|---|-----|
| 1 | 37° |
| 2 | 56° |











COLOUR | W □ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312


* OTHER DIM OPTIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

» 288



MORE INFO >>


| | | P | CCT | I | Flux | LOR |
|--|--|--------------------------------------|-------|-------|---------|---------|
| LEX 1 | A070-01-25- W R G Z WN N | 10W | 2700K | 300mA | 1370 lm | 70% |
| | A070-01-01- W R G Z WN N | 10W | 3000K | 300mA | 1420 lm | 70% |
| | A070-01-02- W R G Z WN N | 10W | 4000K | 300mA | 1440 lm | 70% |
| LEX 2 | A070-01-26- W R G Z WN N | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A070-01-03- W R G Z WN N | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A070-01-04- W R G Z WN N | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A070-01-27- W R G Z WN N | 17W | 2700K | 500mA | 2070 lm | 70% |
| |  A070-01-07- W R G Z WN N | 17W | 3000K | 500mA | 2150 lm | 70% |
| |  A070-01-08- W R G Z WN N | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A070-01-29- W R G Z WN N | 17W | 2700K | 500mA | 2070 lm | 70% |
| |  A070-01-15- W R G Z WN N | 17W | 3000K | 500mA | 2150 lm | 70% |
| |  A070-01-16- W R G Z WN N | 17W | 4000K | 500mA | 2180 lm | 70% |
| | LEX 3 | A070-01-30- W R G Z WN N | 24W | 2700K | 700mA | 2690 lm |
| A070-01-17- W R G Z WN N | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A070-01-18- W R G Z WN N | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A070-01-31- W R G Z WN N | | 24W | 2700K | 700mA | 2690 lm | 70% |
|  A070-01-23- W R G Z WN N | | 24W | 3000K | 700mA | 2800 lm | 70% |
|  A070-01-24- W R G Z WN N | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A070-01-33- W R G Z WN N | | 24W | 2700K | 700mA | 2690 lm | 70% |
|  A070-01-21- W R G Z WN N | | 24W | 3000K | 700mA | 2800 lm | 70% |
|  A070-01-22- W R G Z WN N | | 24W | 4000K | 700mA | 2840 lm | 70% |

220 V~ |  IP20 | CRI>90 | L90B10 >55.000h
DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|-------------------|--------------------------------------|-------|------------|-------|---------|-----|
| LEX Tunable White | A368-01-00- W R G Z WN N | 21,5W | 2700-5000K | 600mA | 2300 lm | 70% |
| LEX DIM to warm | A368-02-00- W R G Z WN N | 20W | 1800-3000K | 600mA | 2150 lm | 70% |

220 V~ |  IP20 | CRI>90 | L80B10 >55.000h




COLOUR | W  | R  | G  | Z  | WN  | N  | MATERIAL |  AL |  PC | RAL  » 312
OTHER CCT PLEASE CONSULT | * ACCESSORY & COLOURS AFFECT THE LIGHTING PARAMETERS  &  » 288









MORE INFO >>




LEX BLUE ON




LEX BLUE OFF



| | | P | CCT | I | Flux | LOR |
|---|---|-----------------|-------|-------|---------|---------|
| LEX Blue 1 | A070-02-25- W | 10W | 2700K | 300mA | 1370 lm | 70% |
| | A070-02-01- W | 10W | 3000K | 300mA | 1420 lm | 70% |
| | A070-02-02- W | 10W | 4000K | 300mA | 1440 lm | 70% |
| LEX Blue 2 | A070-02-26- W | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A070-02-03- W | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A070-02-04- W | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A070-02-27- W | 17W | 2700K | 500mA | 2070 lm | 70% |
| |  A070-02-07- W | 17W | 3000K | 500mA | 2150 lm | 70% |
| |  A070-02-08- W | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A070-02-29- W | 17W | 2700K | 500mA | 2070 lm | 70% |
| |  A070-02-15- W | 17W | 3000K | 500mA | 2150 lm | 70% |
| |  A070-02-16- W | 17W | 4000K | 500mA | 2180 lm | 70% |
| | LEX Blue 3 | A070-02-30- W | 24W | 2700K | 700mA | 2690 lm |
| A070-02-17- W | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A070-02-18- W | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A070-02-31- W | | 24W | 2700K | 700mA | 2690 lm | 70% |
|  A070-02-23- W | | 24W | 3000K | 700mA | 2800 lm | 70% |
|  A070-02-24- W | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A070-02-33- W | | 24W | 2700K | 700mA | 2690 lm | 70% |
|  A070-02-21- W | | 24W | 3000K | 700mA | 2800 lm | 70% |
|  A070-02-22- W | | 24W | 4000K | 700mA | 2840 lm | 70% |

220 V~ |  IP20 | CRI>90 | L90B10 >55.000h
DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|------------------------|-----------------|-------|------------|-------|---------|-----|
| LEX Blue Tunable White | A368-11-00- W | 21,5W | 2700-5000K | 600mA | 2300 lm | 70% |
| LEX Blue DIM to warm | A368-12-00- W | 20W | 1800-3000K | 600mA | 2150 lm | 70% |

220 V~ |  IP20 | CRI>90 | L80B10 >55.000h



COLOUR | W  | MATERIAL |  AL |  PC | RAL  » 312
OTHER CCT PLEASE CONSULT  &  » 288



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------------------------------------|--------------------------------------|--------------------------------------|-------|-------|---------|---------|
| LEX Asymmetric 1 | A071-01-25- W R G Z WN N | 10W | 2700K | 300mA | 1370 lm | 70% |
| | A071-01-01- W R G Z WN N | 10W | 3000K | 300mA | 1420 lm | 70% |
| | A071-01-02- W R G Z WN N | 10W | 4000K | 300mA | 1440 lm | 70% |
| LEX Asymmetric 2 | A071-01-26- W R G Z WN N | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A071-01-03- W R G Z WN N | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A071-01-04- W R G Z WN N | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A071-01-27- W R G Z WN N | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A071-01-07- W R G Z WN N | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A071-01-08- W R G Z WN N | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A071-01-29- W R G Z WN N | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A071-01-15- W R G Z WN N | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A071-01-16- W R G Z WN N | 17W | 4000K | 500mA | 2180 lm | 70% |
| | LEX Asymmetric 3 | A071-01-30- W R G Z WN N | 24W | 2700K | 700mA | 2690 lm |
| A071-01-17- W R G Z WN N | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A071-01-18- W R G Z WN N | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A071-01-31- W R G Z WN N | | 24W | 2700K | 700mA | 2690 lm | 70% |
| A071-01-23- W R G Z WN N | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A071-01-24- W R G Z WN N | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A071-01-33- W R G Z WN N | | 24W | 2700K | 700mA | 2690 lm | 70% |
| A071-01-21- W R G Z WN N | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A071-01-22- W R G Z WN N | | 24W | 4000K | 700mA | 2840 lm | 70% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h


DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|------------------------------|--------------------------------------|-------|------------|-------|---------|-----|
| LEX Asymmetric Tunable White | A369-01-00- W R G Z WN N | 21,5W | 2700-5000K | 600mA | 2300 lm | 70% |
| LEX Asymmetric DIM to warm | A369-02-00- W R G Z WN N | 20W | 1800-3000K | 600mA | 2150 lm | 70% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | R ■ | G ■ | Z ■ | WN □ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

OTHER CCT PLEASE CONSULT | * ACCESSORY & COLOURS AFFECT THE LIGHTING PARAMETERS


Ⓜ & Ⓜ » 288



MORE INFO >>



LEX ASYMMETRIC BLUE ON



LEX ASYMMETRIC BLUE OFF

| | | P | CCT | I | Flux | LOR |
|-----------------------|-----------------------|-----------------|-------|-------|---------|---------|
| LEX Asymmetric Blue 1 | A071-02-25- W | 10W | 2700K | 300mA | 1370 lm | 70% |
| | A071-02-01- W | 10W | 3000K | 300mA | 1420 lm | 70% |
| | A071-02-02- W | 10W | 4000K | 300mA | 1440 lm | 70% |
| LEX Asymmetric Blue 2 | A071-02-26- W | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A071-02-03- W | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A071-02-04- W | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A071-02-27- W | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A071-02-07- W | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A071-02-08- W | 17W | 4000K | 500mA | 2180 lm | 70% |
| | A071-02-29- W | 17W | 2700K | 500mA | 2070 lm | 70% |
| | A071-02-15- W | 17W | 3000K | 500mA | 2150 lm | 70% |
| | A071-02-16- W | 17W | 4000K | 500mA | 2180 lm | 70% |
| | LEX Asymmetric Blue 3 | A071-02-30- W | 24W | 2700K | 700mA | 2690 lm |
| A071-02-17- W | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A071-02-18- W | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A071-02-31- W | | 24W | 2700K | 700mA | 2690 lm | 70% |
| A071-02-23- W | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A071-02-24- W | | 24W | 4000K | 700mA | 2840 lm | 70% |
| A071-02-33- W | | 24W | 2700K | 700mA | 2690 lm | 70% |
| A071-02-21- W | | 24W | 3000K | 700mA | 2800 lm | 70% |
| A071-02-22- W | | 24W | 4000K | 700mA | 2840 lm | 70% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h


DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|-----------------------------------|-----------------|-------|------------|-------|---------|-----|
| LEX Asymmetric Blue Tunable White | A369-11-00- W | 21,5W | 2700-5000K | 600mA | 2300 lm | 70% |
| LEX Asymmetric Blue DIM to warm | A369-12-00- W | 20W | 1800-3000K | 600mA | 2150 lm | 70% |

220 V~ | IP20 | CRI>90 | L80B10 >55.000h

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | MATERIAL | AL | PC | RAL ⓘ » 312

OTHER CCT PLEASE CONSULT


Ⓜ & Ⓜ » 288



MORE INFO >>



LEX MINI & LEX MINI BLUE ON



LEX MINI BLUE OFF

| | | P | CCT | I | Flux | LOR |
|-----------------|---|------|-------|-------|---------|-----|
| LEX Mini 1 | A378-01-10- W R G Z WN N | 6,5W | 2700K | 200mA | 910 lm | 70% |
| | A378-01-11- W R G Z WN N | 6,5W | 3000K | 200mA | 940 lm | 70% |
| | A378-01-12- W R G Z WN N | 6,5W | 4000K | 200mA | 960 lm | 70% |
| LEX Mini Blue 1 | A378-11-10- W | 6,5W | 2700K | 200mA | 910 lm | 70% |
| | A378-11-11- W | 6,5W | 3000K | 200mA | 940 lm | 70% |
| | A378-11-12- W | 6,5W | 4000K | 200mA | 960 lm | 70% |
| LEX Mini 2 | A378-02- Ⓞ -0- W R G Z WN N | 12W | 2700K | 350mA | 1400 lm | 70% |
| | A378-02- Ⓞ -1- W R G Z WN N | 12W | 3000K | 350mA | 1460 lm | 70% |
| | A378-02- Ⓞ -2- W R G Z WN N | 12W | 4000K | 350mA | 1480 lm | 70% |
| LEX Mini Blue 2 | A378-12- Ⓞ -0- W | 12W | 2700K | 350mA | 1400 lm | 70% |
| | A378-12- Ⓞ -1- W | 12W | 3000K | 350mA | 1460 lm | 70% |
| | A378-12- Ⓞ -2- W | 12W | 4000K | 350mA | 1480 lm | 70% |


220 V~ |  IP20 | CRI>90 | L90B10 >55.000h



Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT


OPTIONAL ACCESSORY
LEX High Chromatic LED **  » 281
NOT SOLD SEPARATELY

| | | P | CCT | I | Flux | LOR |
|-----------------------------|--------------------------------------|-------|------------|-------|---------|-----|
| LEX Mini Tunable White | A378-00-28- W R G Z WN N | 10,5W | 2700-5000K | 600mA | 1250 lm | 70% |
| LEX Mini Blue Tunable White | A378-10-28- W | 10,5W | 2700-5000K | 600mA | 1250 lm | 70% |

220 V~ |  IP20 | CRI>90 | L80B10 >55.000h




| | | P | CCT | I | Flux | LOR |
|---------------------------|--------------------------------------|-------|------------|-------|---------|-----|
| LEX Mini DIM to Warm | A378-00-29- W R G Z WN N | 11,5W | 1800-3000K | 350mA | 1265 lm | 70% |
| LEX Mini Blue dim to warm | A378-10-29- W | 11,5W | 1800-3000K | 350mA | 1265 lm | 70% |

220 V~ |  IP20 | CRI>90 | L80B10 >55.000h



DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W  | R  | G  | Z  | WN  | N 

MATERIAL |  AL |  PC |

RAL  » 312


** ACCESSORY & COLOURS AFFECT THE LIGHTING PARAMETERS

 &  » 288

MORE INFO >>



LEX MINI ASYMM. & MINI ASYMM. BLUE ON



LEX MINI ASYMMETRIC BLUE OFF

| | | P | CCT | I | Flux | LOR |
|----------------------------|---|------|-------|-------|---------|-----|
| LEX Mini Asymmetric 1 | A379-01-10- W R G Z WN N | 6,5W | 2700K | 200mA | 910 lm | 70% |
| | A379-01-11- W R G Z WN N | 6,5W | 3000K | 200mA | 940 lm | 70% |
| | A379-01-12- W R G Z WN N | 6,5W | 4000K | 200mA | 960 lm | 70% |
| LEX Mini Asymmetric Blue 1 | A379-11-10- W | 6,5W | 2700K | 200mA | 910 lm | 70% |
| | A379-11-11- W | 6,5W | 3000K | 200mA | 940 lm | 70% |
| | A379-11-12- W | 6,5W | 4000K | 200mA | 960 lm | 70% |
| LEX Mini Asymmetric 2 | A379-02- Ⓞ -0- W R G Z WN N | 12W | 2700K | 350mA | 1400 lm | 70% |
| | A379-02- Ⓞ -1- W R G Z WN N | 12W | 3000K | 350mA | 1460 lm | 70% |
| | A379-02- Ⓞ -2- W R G Z WN N | 12W | 4000K | 350mA | 1480 lm | 70% |
| LEX Mini Asymmetric Blue 2 | A379-12- Ⓞ -0- W | 12W | 2700K | 350mA | 1400 lm | 70% |
| | A379-12- Ⓞ -1- W | 12W | 3000K | 350mA | 1460 lm | 70% |
| | A379-12- Ⓞ -2- W | 12W | 4000K | 350mA | 1480 lm | 70% |


220 V~ |  IP20 | CRI>90 | L90B10 >55.000h




Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT


OPTIONAL ACCESSORY
LEX High Chromatic LED **  » 281
NOT SOLD SEPARATELY

| | | P | CCT | I | Flux | LOR |
|--|--------------------------------------|-------|------------|-------|---------|-----|
| LEX Mini Asymmetric Tunable White | A379-00-28- W R G Z WN N | 10,5W | 2700-5000K | 600mA | 1250 lm | 70% |
| LEX Mini Asymmetric Blue Tunable White | A379-10-28- W | 10,5W | 2700-5000K | 600mA | 1250 lm | 70% |

220 V~ |  IP20 | CRI>90 | L80B10 >55.000h




| | | P | CCT | I | Flux | LOR |
|--------------------------------------|--------------------------------------|-------|------------|-------|---------|-----|
| LEX Mini Asymmetric DIM to Warm | A379-00-29- W R G Z WN N | 11,5W | 1800-3000K | 350mA | 1265 lm | 70% |
| LEX Mini Asymmetric Blue DIM to warm | A379-10-29- W | 11,5W | 1800-3000K | 350mA | 1265 lm | 70% |

220 V~ |  IP20 | CRI>90 | L80B10 >55.000h



DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W  | R  | G  | Z  | WN  | N 


MATERIAL |  AL |  PC |

RAL  » 312

** ACCESSORY & COLOURS AFFECT THE LIGHTING PARAMETERS

 &  » 288

DUOMO



MORE INFO >>

| | P | CCT | I | Flux | LOR | | | |
|-----------------|---------------|-----|-------------|-------|-------|--------|---------|-----|
| DUOMO IP65/IP20 | A285-01-11- | W | IP65 / IP20 | 16,5W | 3000K | 500mA | 2450 lm | 80% |
| | A285-01-12- | W | IP65 / IP20 | 16,5W | 4000K | 500mA | 2500 lm | 80% |
| | A285-02-Ⓞ -1- | W | IP65 / IP20 | 41W | 3000K | 1200mA | 5100 lm | 80% |
| | A285-02-Ⓞ -2- | W | IP65 / IP20 | 41W | 4000K | 1200mA | 5200 lm | 80% |

220 V~ | CRI>90 | L90B10 >55.000h



| | P | CCT | I | Flux | LOR | | | |
|-----------------|-------------|-----|-------------|-------|-------|--------|---------|-----|
| DUOMO IP65/IP65 | A285-11-11- | W | IP65 / IP65 | 16,5W | 3000K | 500mA | 2450 lm | 80% |
| | A285-11-12- | W | IP65 / IP65 | 16,5W | 4000K | 500mA | 2500 lm | 80% |
| | A285-12-11- | W | IP65 / IP65 | 41W | 3000K | 1200mA | 5100 lm | 80% |
| | A285-12-12- | W | IP65 / IP65 | 41W | 4000K | 1200mA | 5200 lm | 80% |

220 V~ | CRI>90 | L90B10 >55.000h



*OPTIONS


| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT


OPTIONAL

DUOMO High Chromatic LED » 281
NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

DUOMO IP65 / IP20



DUOMO IP65 / IP65



COLOUR | W | MATERIAL | AL | PC | OPTICAL GLASS |

OTHER CCT PLEASE CONSULT


RAL » 312

& » 288


PUCK RECESSED



Extended Family
Puck_P.116



MORE INFO >>



MORE INFO >>



MORE INFO >>


*OPTIONS

| | |
|---|-----------------|
| 1 | No DIM |
| 2 | DIM DALI Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT


| | P | CCT | I | Flux | LOR | | | |
|----------------------|---------------|---------|------|------|-------|-------|--------|-----|
| PUCK S Recessed | A313-00-Ⓞ -0- | WT NT | IP20 | 5W | 2700K | 150mA | 670 lm | 80% |
| | A313-00-Ⓞ -1- | WT NT | IP20 | 5W | 3000K | 150mA | 700 lm | 80% |
| | A313-00-Ⓞ -2- | WT NT | IP20 | 5W | 4000K | 150mA | 710 lm | 80% |
| PUCK S Recessed IP54 | A314-00-Ⓞ -0- | WT NT | IP54 | 5W | 2700K | 150mA | 670 lm | 80% |
| | A314-00-Ⓞ -1- | WT NT | IP54 | 5W | 3000K | 150mA | 700 lm | 80% |
| | A314-00-Ⓞ -2- | WT NT | IP54 | 5W | 4000K | 150mA | 710 lm | 80% |

220 V~ | CRI>90 | L90B10 >55.000h




| | P | CCT | I | Flux | LOR | | | |
|----------------------|---------------|---------|------|------|-------|-------|---------|-----|
| PUCK M Recessed | A313-10-Ⓞ -0- | WT NT | IP20 | 9W | 2700K | 500mA | 1090 lm | 80% |
| | A313-10-Ⓞ -1- | WT NT | IP20 | 9W | 3000K | 500mA | 1160 lm | 80% |
| | A313-10-Ⓞ -2- | WT NT | IP20 | 9W | 4000K | 500mA | 1230 lm | 80% |
| PUCK M Recessed IP54 | A314-10-Ⓞ -0- | WT NT | IP54 | 9W | 2700K | 500mA | 1090 lm | 80% |
| | A314-10-Ⓞ -1- | WT NT | IP54 | 9W | 3000K | 500mA | 1160 lm | 80% |
| | A314-10-Ⓞ -2- | WT NT | IP54 | 9W | 4000K | 500mA | 1230 lm | 80% |

220 V~ | CRI>90 | L80B10 >60.000h




| | P | CCT | I | Flux | LOR | | | |
|----------------------|---------------|---------|------|------|-------|-------|---------|-----|
| PUCK L Recessed | A313-20-Ⓞ -0- | WT NT | IP20 | 12W | 2700K | 350mA | 1550 lm | 82% |
| | A313-20-Ⓞ -1- | WT NT | IP20 | 12W | 3000K | 350mA | 1610 lm | 82% |
| | A313-20-Ⓞ -2- | WT NT | IP20 | 12W | 4000K | 350mA | 1640 lm | 82% |
| PUCK L Recessed IP54 | A314-20-Ⓞ -0- | WT NT | IP54 | 12W | 2700K | 350mA | 1550 lm | 82% |
| | A314-20-Ⓞ -1- | WT NT | IP54 | 12W | 3000K | 350mA | 1610 lm | 82% |
| | A314-20-Ⓞ -2- | WT NT | IP54 | 12W | 4000K | 350mA | 1640 lm | 82% |


220 V~ | CRI>90 | L90B10 >55.000h




PUCK S RECESSED



PUCK M RECESSED



PUCK L RECESSED



COLOUR | WT | NT |

MATERIAL | AL | OPTICAL GLASS |


RAL » 312

& » 288

ALASKA TRIMLESS



Extended Family
Alaska_P.130
Alaska 24V_P.181
Alaska Fancy Shape_P.238



MORE INFO >>

| | | CCT | LOR |
|-----------------|-----------------|-------|-----|
| ALASKA Trimless | A401-00-00- N | 2700K | 30% |
| | A401-00-01- N | 3000K | 30% |

IP20 | CRI>90 | L90B10 >55.000h

 MacAdam Step 2
 EXCL**
 EXCL*
 21°

| *DRIVER OPTIONS | | P | I | CCT | Flux |
|-----------------|---|------|-------|----------------|------------------|
| NO DIM | 0434-00-42 1 to 4 Alaska Trimless | 4,5W | 500mA | 2700K 3000K | 475 lm 500 lm |
| DALI | 0434-00-44 1 to 4 Alaska Trimless | 4,5W | 500mA | 2700K 3000K | 475 lm 500 lm |

220 V~ | 240 V~ | DRIVER MUST BE PLACED ON REMOTE | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT » 282

ACCESSORY



ALASKA Trimless Accessory** A401-10-00

MANDATORY FOR INSTALLATION




OPTIONAL ACCESSORY

TRIMLESS TOOL D43 X D70mm A478-00-02



COLOUR | N ■ | MATERIAL | AL | OPTICAL GLASS | RAL » 312

OTHER CCT OPTIONS PLEASE CONSULT » 288



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------------------|---------------------|------|-------|-------|---------|-----|
| ALASKA Big Trimless | A426-00- 00 -0- N | 9,3W | 2700K | 550mA | 1130 lm | 37% |
| | A426-00- 00 -1- N | 9,3W | 3000K | 550mA | 1200 lm | 37% |

220 V~ | 240 V~ | IP20 | CRI>90 | L90B10 >60.000h

 MacAdam Step 2
 OPTIONS*
 EXCL**
 INCL
 44°

00 OPTIONS*


- 1 No DIM
- 2 DIM DALI
- 3 DIM Push

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

ACCESSORY



ALASKA BIG Trimless Accessory** A426-10-00

MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORY


TRIMLESS TOOL D59 X D100mm A478-00-03




COLOUR | N ■ | MATERIAL | AL | OPTICAL GLASS | RAL » 312

OTHER CCT OPTIONS PLEASE CONSULT » 288

OLYMPIA



MORE INFO >>



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------|--------------------|-------|-------|-------|---------|-----|
| OLYMPIA | A257-00- Ⓞ -1- W | 10,5W | 3000K | 350mA | 1550 lm | 67% |
| | A257-00- Ⓞ -2- W | 10,5W | 4000K | 350mA | 1575 lm | 67% |

220 V~ | IP54 | IK10 | CRI>90 | L80B10 >60.000h



| | | P | CCT | I | Flux | LOR |
|--------------|--------------------|------|-------|-------|--------|-----|
| OLYMPIA Mini | A258-00- Ⓞ -1- W | 5,5W | 3000K | 500mA | 800 lm | 63% |
| | A258-00- Ⓞ -2- W | 5,5W | 4000K | 500mA | 825 lm | 63% |


220 V~ | IP54 | IK10 | CRI>90 | L80B10 >60.000h



Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | MATERIAL | AL | PC | PC |


EASY CUT OUT INSTALLATION, TEMPLATE INCLUDED

RAL » 312

& » 288




DEEP



MORE INFO >>



MORE INFO >>



MORE INFO >>

○ *OPTIONS

| | |
|---|------|
| 0 | IP43 |
| 1 | IP54 |

Ⓞ **OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|-------------|------------------------|-----|-------|-------|---------|-----|
| DEEP Maxi 2 | A248- Ⓞ -2- Ⓞ -1- WT | 15W | 3000K | 350mA | 2450 lm | 85% |
| | A248- Ⓞ -2- Ⓞ -2- WT | 15W | 4000K | 350mA | 2500 lm | 85% |
| DEEP Maxi 3 | A248- Ⓞ -3- Ⓞ -1- WT | 22W | 3000K | 500mA | 3450 lm | 85% |
| | A248- Ⓞ -3- Ⓞ -2- WT | 22W | 4000K | 500mA | 3500 lm | 85% |
| DEEP Maxi 4 | A248- Ⓞ -4- Ⓞ -1- WT | 31W | 3000K | 700mA | 4700 lm | 85% |
| | A248- Ⓞ -4- Ⓞ -2- WT | 31W | 4000K | 700mA | 4775 lm | 85% |
| DEEP Maxi 5 | A248- Ⓞ -5- Ⓞ -1- WT | 40W | 3000K | 900mA | 5825 lm | 85% |
| | A248- Ⓞ -5- Ⓞ -2- WT | 40W | 4000K | 900mA | 5925 lm | 85% |

220 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h




| | | P | CCT | I | Flux | LOR |
|--------|------------------------|-------|-------|-------|---------|-----|
| DEEP 1 | A249- Ⓞ -1- Ⓞ -0- WT | 10,5W | 2700K | 350mA | 1525 lm | 85% |
| | A249- Ⓞ -1- Ⓞ -1- WT | 10,5W | 3000K | 350mA | 1650 lm | 85% |
| | A249- Ⓞ -1- Ⓞ -2- WT | 10,5W | 4000K | 350mA | 1675 lm | 85% |
| DEEP 2 | A249- Ⓞ -2- Ⓞ -0- WT | 15,5W | 2700K | 500mA | 2100 lm | 85% |
| | A249- Ⓞ -2- Ⓞ -1- WT | 15,5W | 3000K | 500mA | 2275 lm | 85% |
| | A249- Ⓞ -2- Ⓞ -2- WT | 15,5W | 4000K | 500mA | 2300 lm | 85% |
| DEEP 3 | A249- Ⓞ -3- Ⓞ -0- WT | 22W | 2700K | 700mA | 2800 lm | 85% |
| | A249- Ⓞ -3- Ⓞ -1- WT | 22W | 3000K | 700mA | 3025 lm | 85% |
| | A249- Ⓞ -3- Ⓞ -2- WT | 22W | 4000K | 700mA | 3075 lm | 85% |
| DEEP 4 | A249- Ⓞ -4- Ⓞ -1- WT | 27W | 3000K | 700mA | 4050 lm | 87% |
| | A249- Ⓞ -4- Ⓞ -2- WT | 27W | 4000K | 700mA | 4100 lm | 87% |

220 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h



| | | P | CCT | I | Flux | LOR |
|-------------|------------------------|-----|-------|-------|---------|-----|
| DEEP Mini 2 | A250- Ⓞ -2- Ⓞ -0- WT | 7W | 2700K | 500mA | 975 lm | 76% |
| | A250- Ⓞ -2- Ⓞ -1- WT | 7W | 3000K | 500mA | 1050 lm | 76% |
| | A250- Ⓞ -2- Ⓞ -2- WT | 7W | 4000K | 500mA | 1075 lm | 76% |
| DEEP Mini 3 | A250- Ⓞ -3- Ⓞ -0- WT | 10W | 2700K | 700mA | 1275 lm | 76% |
| | A250- Ⓞ -3- Ⓞ -1- WT | 10W | 3000K | 700mA | 1375 lm | 76% |
| | A250- Ⓞ -3- Ⓞ -2- WT | 10W | 4000K | 700mA | 1400 lm | 76% |

220 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h



COLOUR | WT □ | MATERIAL | AL | PMMA |

RAL » 312

& » 288

DROP



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------|------------------------|-----|-------|-------|---------|-----|
| DROP Maxi 2 | A235- ○ -2- Ⓞ -1- WT | 15W | 3000K | 350mA | 2450 lm | 84% |
| | A235- ○ -2- Ⓞ -2- WT | 15W | 4000K | 350mA | 2500 lm | 84% |
| DROP Maxi 3 | A235- ○ -3- Ⓞ -1- WT | 22W | 3000K | 500mA | 3450 lm | 84% |
| | A235- ○ -3- Ⓞ -2- WT | 22W | 4000K | 500mA | 3500 lm | 84% |
| DROP Maxi 4 | A235- ○ -4- Ⓞ -1- WT | 31W | 3000K | 700mA | 4700 lm | 84% |
| | A235- ○ -4- Ⓞ -2- WT | 31W | 4000K | 700mA | 4775 lm | 84% |
| DROP Maxi 5 | A235- ○ -5- Ⓞ -1- WT | 40W | 3000K | 900mA | 5825 lm | 84% |
| | A235- ○ -5- Ⓞ -2- WT | 40W | 4000K | 900mA | 5925 lm | 84% |

220 V~ | 240 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------|------------------------|-------|-------|-------|---------|-----|
| DROP 1 | A193- ○ -1- Ⓞ -0- WT | 10,5W | 2700K | 350mA | 1525 lm | 86% |
| | A193- ○ -1- Ⓞ -1- WT | 10,5W | 3000K | 350mA | 1650 lm | 86% |
| | A193- ○ -1- Ⓞ -2- WT | 10,5W | 4000K | 350mA | 1675 lm | 86% |
| DROP 2 | A193- ○ -2- Ⓞ -0- WT | 15,5W | 2700K | 500mA | 2100 lm | 86% |
| | A193- ○ -2- Ⓞ -1- WT | 15,5W | 3000K | 500mA | 2275 lm | 86% |
| | A193- ○ -2- Ⓞ -2- WT | 15,5W | 4000K | 500mA | 2300 lm | 86% |
| DROP 3 | A193- ○ -3- Ⓞ -0- WT | 22W | 2700K | 700mA | 2800 lm | 86% |
| | A193- ○ -3- Ⓞ -1- WT | 22W | 3000K | 700mA | 3025 lm | 86% |
| | A193- ○ -3- Ⓞ -2- WT | 22W | 4000K | 700mA | 3075 lm | 86% |
| DROP 4 | A193- ○ -4- Ⓞ -1- WT | 27W | 3000K | 700mA | 4050 lm | 88% |
| | A193- ○ -4- Ⓞ -2- WT | 27W | 4000K | 700mA | 4100 lm | 88% |

220 V~ | 240 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h




○ *OPTIONS

| | |
|---|------|
| 0 | IP43 |
| 1 | IP54 |

Ⓞ **OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | WT □ | MATERIAL | AL | PMMA |

RAL ⓘ » 312

Ⓞ ⓘ & ⓘ » 288




MORE INFO >>



Ⓞ **OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>



MORE INFO >>

Ⓞ *OPTIONS

| | |
|---|---------------|
| 1 | No DIM |
| 2 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|-------------|------------------------|-----|-------|-------|---------|-----|
| DROP Mini 2 | A194- ○ -2- Ⓞ -0- WT | 7W | 2700K | 500mA | 975 lm | 78% |
| | A194- ○ -2- Ⓞ -1- WT | 7W | 3000K | 500mA | 1050 lm | 78% |
| | A194- ○ -2- Ⓞ -2- WT | 7W | 4000K | 500mA | 1075 lm | 78% |
| DROP Mini 3 | A194- ○ -3- Ⓞ -0- WT | 10W | 2700K | 700mA | 1275 lm | 78% |
| | A194- ○ -3- Ⓞ -1- WT | 10W | 3000K | 700mA | 1375 lm | 78% |
| | A194- ○ -3- Ⓞ -2- WT | 10W | 4000K | 700mA | 1400 lm | 78% |

220 V~ | 240 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h



○ *OPTIONS

| | |
|---|------|
| 0 | IP43 |
| 1 | IP54 |


| | | P | CCT | I | Flux | LOR |
|--------------|--------------------------|------|-------|-------|---------|-----|
| DROP Micro 1 | A224-01-10- WT NT | 5W | 2700K | 140mA | 700 lm | 72% |
| | A224-01-11- WT NT | 5W | 3000K | 140mA | 730 lm | 72% |
| | A224-01-12- WT NT | 5W | 4000K | 140mA | 750 lm | 72% |
| DROP Micro 2 | A224-02- Ⓞ -0- WT NT | 7,5W | 2700K | 200mA | 950 lm | 72% |
| | A224-02- Ⓞ -1- WT NT | 7,5W | 3000K | 200mA | 1000 lm | 72% |
| | A224-02- Ⓞ -2- WT NT | 7,5W | 4000K | 200mA | 1030 lm | 72% |

220 V~ | 240 V~ | IP54 | CRI>80 | L90B10 >55.000h



| | | P | CCT | I | Flux | LOR |
|--------------------|--------------------------|------|-------|-------|---------|-----|
| DROP Micro Trans 1 | A223-01-10- WT NT | 5W | 2700K | 140mA | 700 lm | 80% |
| | A223-01-11- WT NT | 5W | 3000K | 140mA | 730 lm | 80% |
| | A223-01-12- WT NT | 5W | 4000K | 140mA | 750 lm | 80% |
| DROP Micro Trans 2 | A223-02- Ⓞ -0- WT NT | 7,5W | 2700K | 200mA | 950 lm | 80% |
| | A223-02- Ⓞ -1- WT NT | 7,5W | 3000K | 200mA | 1000 lm | 80% |
| | A223-02- Ⓞ -2- WT NT | 7,5W | 4000K | 200mA | 1030 lm | 80% |

220 V~ | 240 V~ | IP54 | CRI>80 | L90B10 >55.000h



COLOUR | WT □ | MATERIAL | AL | PMMA |


RAL ⓘ » 312

COLOUR | WT □ | NT ■ | MATERIAL | AL | PMMA | AL | GL-TRANS | ⓘ & ⓘ » 288

STRAM



MORE INFO >>



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------------|----------------------|-------|-------|-------|---------|-----|
| STRAM Prismatic 1 | A198-01- 00 -0- WT | 10,5W | 2700K | 350mA | 1525 lm | 87% |
| | A198-01- 00 -1- WT | 10,5W | 3000K | 350mA | 1650 lm | 87% |
| | A198-01- 00 -2- WT | 10,5W | 4000K | 350mA | 1675 lm | 87% |
| STRAM Prismatic 2 | A198-02- 00 -0- WT | 15,5W | 2700K | 500mA | 2100 lm | 87% |
| | A198-02- 00 -1- WT | 15,5W | 3000K | 500mA | 2275 lm | 87% |
| | A198-02- 00 -2- WT | 15,5W | 4000K | 500mA | 2300 lm | 87% |
| STRAM Prismatic 3 | A198-03- 00 -0- WT | 22W | 2700K | 700mA | 2800 lm | 87% |
| | A198-03- 00 -1- WT | 22W | 3000K | 700mA | 3025 lm | 87% |
| | A198-03- 00 -2- WT | 22W | 4000K | 700mA | 3075 lm | 87% |
| STRAM Prismatic 4 | A198-04- 00 -1- WT | 27W | 3000K | 700mA | 4050 lm | 89% |
| | A198-04- 00 -2- WT | 27W | 4000K | 700mA | 4100 lm | 89% |

220 V~ | 240 V~ | IP43 | IP54** | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | OPTIONS* | INCL | Ø205 | UGR <19 | 93°

| | | P | CCT | I | Flux | LOR |
|------------------------|----------------------|-----|-------|-------|---------|-----|
| STRAM Mini Prismatic 2 | A237-02- 00 -0- WT | 7W | 2700K | 500mA | 975 lm | 80% |
| | A237-02- 00 -1- WT | 7W | 3000K | 500mA | 1050 lm | 80% |
| | A237-02- 00 -2- WT | 7W | 4000K | 500mA | 1075 lm | 80% |
| STRAM Mini Prismatic 3 | A237-03- 00 -0- WT | 10W | 2700K | 700mA | 1275 lm | 80% |
| | A237-03- 00 -1- WT | 10W | 3000K | 700mA | 1375 lm | 80% |
| | A237-03- 00 -2- WT | 10W | 4000K | 700mA | 1400 lm | 80% |


220 V~ | 240 V~ | IP43 | IP54** | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | OPTIONS* | INCL | Ø122 | 87°


| ⊖ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

STRAM PRISMATIC



STRAM MINI PRISMATIC



COLOUR | WT □ | MATERIAL | AL | PMMA |


RAL ⓘ » 312

** IP54 PLEASE CONSULT

⊖ & ⊕ » 288



Extended Family
Stram Surface_P.117



MORE INFO >>



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------|-------------------------|-------|-------|-------|---------|-----|
| STRAM 1 | A197- 0 -1- 00 -0- WT | 10,5W | 2700K | 350mA | 1525 lm | 87% |
| | A197- 0 -1- 00 -1- WT | 10,5W | 3000K | 350mA | 1650 lm | 87% |
| | A197- 0 -1- 00 -2- WT | 10,5W | 4000K | 350mA | 1675 lm | 87% |
| STRAM 2 | A197- 0 -2- 00 -0- WT | 15,5W | 2700K | 500mA | 2100 lm | 87% |
| | A197- 0 -2- 00 -1- WT | 15,5W | 3000K | 500mA | 2275 lm | 87% |
| | A197- 0 -2- 00 -2- WT | 15,5W | 4000K | 500mA | 2300 lm | 87% |
| STRAM 3 | A197- 0 -3- 00 -0- WT | 22W | 2700K | 700mA | 2800 lm | 87% |
| | A197- 0 -3- 00 -1- WT | 22W | 3000K | 700mA | 3025 lm | 87% |
| | A197- 0 -3- 00 -2- WT | 22W | 4000K | 700mA | 3075 lm | 87% |
| STRAM 4 | A197- 0 -4- 00 -1- WT | 27W | 3000K | 700mA | 4050 lm | 89% |
| | A197- 0 -4- 00 -2- WT | 27W | 4000K | 700mA | 4100 lm | 89% |

220 V~ | 240 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | OPTIONS** | INCL | Ø205 | 99°

| | | P | CCT | I | Flux | LOR |
|--------------|-------------------------|-----|-------|-------|---------|-----|
| STRAM Mini 2 | A236- 0 -2- 00 -0- WT | 7W | 2700K | 500mA | 975 lm | 80% |
| | A236- 0 -2- 00 -1- WT | 7W | 3000K | 500mA | 1050 lm | 80% |
| | A236- 0 -2- 00 -2- WT | 7W | 4000K | 500mA | 1075 lm | 80% |
| STRAM Mini 3 | A236- 0 -3- 00 -0- WT | 10W | 2700K | 700mA | 1275 lm | 80% |
| | A236- 0 -3- 00 -1- WT | 10W | 3000K | 700mA | 1375 lm | 80% |
| | A236- 0 -3- 00 -2- WT | 10W | 4000K | 700mA | 1400 lm | 80% |

220 V~ | 240 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h


MacAdam Step 2 | OPTIONS** | INCL | Ø122 | 100°

| ○ | *OPTIONS |
|---|----------|
| 0 | IP43 |
| 1 | IP54 |


| ⊖ | **OPTIONS |
|---|-----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

STRAM



STRAM MINI



COLOUR | WT □ | MATERIAL | AL | PMMA |

RAL ⓘ » 312

** IP54 PLEASE CONSULT

⊖ & ⊕ » 288


FOX



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------|--------------------|-------|-------|-------|---------|-----|
| FOX 1 | A217-01- 0 -0- W | 10,5W | 2700K | 350mA | 1500 lm | 74% |
| | A217-01- 0 -1- W | 10,5W | 3000K | 350mA | 1625 lm | 74% |
| | A217-01- 0 -2- W | 10,5W | 4000K | 350mA | 1650 lm | 74% |
| FOX 2 | A217-02- 0 -0- W | 15,5W | 2700K | 500mA | 2050 lm | 74% |
| | A217-02- 0 -1- W | 15,5W | 3000K | 500mA | 2225 lm | 74% |
| | A217-02- 0 -2- W | 15,5W | 4000K | 500mA | 2250 lm | 74% |

220
240 V~ | IP54 | IK10 | CRI>90 | L80B10 >60.000h



MORE INFO >>



| | | P | CCT | I | Flux | LOR |
|------------|--------------------|-----|-------|-------|---------|-----|
| FOX Mini 2 | A218-02- 0 -0- W | 7W | 2700K | 500mA | 925 lm | 66% |
| | A218-02- 0 -1- W | 7W | 3000K | 500mA | 1000 lm | 66% |
| | A218-02- 0 -2- W | 7W | 4000K | 500mA | 1025 lm | 66% |
| FOX Mini 3 | A218-03- 0 -0- W | 10W | 2700K | 700mA | 1200 lm | 66% |
| | A218-03- 0 -1- W | 10W | 3000K | 700mA | 1300 lm | 66% |
| | A218-03- 0 -2- W | 10W | 4000K | 700mA | 1325 lm | 66% |

220
240 V~ | IP54 | IK10 | CRI>90 | L80B10 >60.000h



| 0 | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT




COLOUR | W □ | MATERIAL | PC | PC |

RAL » 312

& » 288




MIX



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------|-----------------------|-------|-------|-------|---------|-----|
| MIX 1 | A187- 0 -1- 0 -0- W | 10,5W | 2700K | 350mA | 1525 lm | 83% |
| | A187- 0 -1- 0 -1- W | 10,5W | 3000K | 350mA | 1650 lm | 83% |
| | A187- 0 -1- 0 -2- W | 10,5W | 4000K | 350mA | 1675 lm | 83% |
| MIX 2 | A187- 0 -2- 0 -0- W | 15,5W | 2700K | 500mA | 2100 lm | 83% |
| | A187- 0 -2- 0 -1- W | 15,5W | 3000K | 500mA | 2275 lm | 83% |
| | A187- 0 -2- 0 -2- W | 15,5W | 4000K | 500mA | 2300 lm | 83% |
| MIX 3 | A187- 0 -3- 0 -0- W | 22W | 2700K | 700mA | 2800 lm | 83% |
| | A187- 0 -3- 0 -1- W | 22W | 3000K | 700mA | 3025 lm | 83% |
| | A187- 0 -3- 0 -2- W | 22W | 4000K | 700mA | 3075 lm | 83% |
| MIX 4 | A187- 0 -4- 0 -1- W | 27W | 3000K | 700mA | 4050 lm | 85% |
| | A187- 0 -4- 0 -2- W | 27W | 4000K | 700mA | 4100 lm | 85% |

220
240 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------|-----------------------|-----|-------|-------|---------|-----|
| MIX Mini 2 | A188- 0 -2- 0 -0- W | 7W | 2700K | 500mA | 975 lm | 75% |
| | A188- 0 -2- 0 -1- W | 7W | 3000K | 500mA | 1050 lm | 75% |
| | A188- 0 -2- 0 -2- W | 7W | 4000K | 500mA | 1075 lm | 75% |
| MIX Mini 3 | A188- 0 -3- 0 -0- W | 10W | 2700K | 700mA | 1275 lm | 75% |
| | A188- 0 -3- 0 -1- W | 10W | 3000K | 700mA | 1375 lm | 75% |
| | A188- 0 -3- 0 -2- W | 10W | 4000K | 700mA | 1400 lm | 75% |



220
240 V~ | IP43 | IP54* | CRI>90 | L80B10 >60.000h



| 0 | *OPTIONS |
|---|----------|
| 0 | IP43 |
| 1 | IP54 |

| 0 | **OPTIONS |
|---|-----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT




COLOUR | W □ | MATERIAL | AL | PMMA |

RAL » 312

& » 288



MADISON



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-----------|--------------------|-------|-------|-------|---------|-----|
| MADISON 1 | A190-01- Ⓞ -1- W | 10,5W | 3000K | 350mA | 1650 lm | 82% |
| | A190-01- Ⓞ -2- W | 10,5W | 4000K | 350mA | 1675 lm | 82% |
| MADISON 2 | A190-02- Ⓞ -1- W | 15,5W | 3000K | 500mA | 2275 lm | 82% |
| | A190-02- Ⓞ -2- W | 15,5W | 4000K | 500mA | 2300 lm | 82% |
| MADISON 3 | A190-03- Ⓞ -1- W | 22W | 3000K | 700mA | 3025 lm | 82% |
| | A190-03- Ⓞ -2- W | 22W | 4000K | 700mA | 3075 lm | 82% |


220 V~ | IP43 | CRI>90 | L80B10 >60.000h



Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | MATERIAL | AL | PMMA |

RAL ⓘ » 312

Ⓞ & » 288


QUAD



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------|------------------------|-------|-------|-------|---------|-----|
| QUAD 2 | A189-02- Ⓞ -1- W Z | 15,5W | 3000K | 500mA | 2275 lm | 76% |
| | A189-02- Ⓞ -2- W Z | 15,5W | 4000K | 500mA | 2300 lm | 76% |
| QUAD 3 | A189-03- Ⓞ -1- W Z | 22W | 3000K | 700mA | 3000 lm | 76% |
| | A189-03- Ⓞ -2- W Z | 22W | 4000K | 700mA | 3050 lm | 76% |


220 V~ | IP43 | CRI>90 | L80B10 >60.000h



Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | Z ■ | MATERIAL | AL | PMMA |

RAL ⓘ » 312

Ⓞ & » 288



MORE INFO >>

| | | | P | CCT | I | Flux | LOR |
|--------------|----------------|---|------|-------|-------|---------|-----|
| DOT Fix | A061-01-10- | W | 5W | 2700K | 140mA | 700 lm | 92% |
| | A061-01-11- | W | 5W | 3000K | 140mA | 730 lm | 92% |
| | A061-01-12- | W | 5W | 4000K | 140mA | 750 lm | 92% |
| | A061-02- ① -0- | W | 7,5W | 2700K | 200mA | 950 lm | 92% |
| | A061-02- ① -1- | W | 7,5W | 3000K | 200mA | 1000 lm | 92% |
| | A061-02- ① -2- | W | 7,5W | 4000K | 200mA | 1030 lm | 92% |
| DOT Fix IP54 | A067-01-10- | W | 5W | 2700K | 140mA | 700 lm | 75% |
| | A067-01-11- | W | 5W | 3000K | 140mA | 730 lm | 75% |
| | A067-01-12- | W | 5W | 4000K | 140mA | 750 lm | 75% |
| | A067-02- ① -0- | W | 7,5W | 2700K | 200mA | 950 lm | 75% |
| | A067-02- ① -1- | W | 7,5W | 3000K | 200mA | 1000 lm | 75% |
| | A067-02- ① -2- | W | 7,5W | 4000K | 200mA | 1030 lm | 75% |

220 V~ | 240 | IP43 | CRI>80 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | FAST I CONNEC | Ø62 | UGR <19 | 38°

| | | | P | CCT | I | Flux | LOR |
|----------|----------------|---|------|-------|-------|---------|-----|
| DOT Tilt | A063-01-10- | W | 5W | 2700K | 140mA | 700 lm | 92% |
| | A063-01-11- | W | 5W | 3000K | 140mA | 730 lm | 92% |
| | A063-01-12- | W | 5W | 4000K | 140mA | 750 lm | 92% |
| | A063-02- ① -0- | W | 7,5W | 2700K | 200mA | 950 lm | 92% |
| | A063-02- ① -1- | W | 7,5W | 3000K | 200mA | 1000 lm | 92% |
| | A063-02- ① -2- | W | 7,5W | 4000K | 200mA | 1030 lm | 92% |

220 V~ | 240 | IP20 | CRI>80 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | FAST I CONNEC | 30° | 38°



MORE INFO >>

| | | | P | CCT | I | Flux | LOR |
|-----------------|----------------|---|------|-------|-------|---------|-----|
| DOT Square Tilt | A065-01-10- | W | 5W | 2700K | 140mA | 700 lm | 92% |
| | A065-01-11- | W | 5W | 3000K | 140mA | 730 lm | 92% |
| | A065-01-12- | W | 5W | 4000K | 140mA | 750 lm | 92% |
| | A065-02- ① -0- | W | 7,5W | 2700K | 200mA | 950 lm | 92% |
| | A065-02- ① -1- | W | 7,5W | 3000K | 200mA | 1000 lm | 92% |
| | A065-02- ① -2- | W | 7,5W | 4000K | 200mA | 1030 lm | 92% |


220 V~ | 240 | IP20 | CRI>80 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | FAST I CONNEC | 30° | Ø75 | 38°



MORE INFO >>

- ① *OPTIONS
- No DIM
 - DIM Phase Cut
 - DIM DALI | Push
- OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | MATERIAL | AL

RAL ⓘ » 312

Ⓢ & Ⓣ » 288



MORE INFO >>

| | | | P | CCT | I | Flux | LOR |
|------|----------------|---|------|-------|-------|---------|-----|
| BATH | A155-01-10- | W | 5W | 2700K | 140mA | 700 lm | 75% |
| | A155-01-11- | W | 5W | 3000K | 140mA | 730 lm | 75% |
| | A155-01-12- | W | 5W | 4000K | 140mA | 750 lm | 75% |
| | A155-02- ① -0- | W | 7,5W | 2700K | 200mA | 950 lm | 75% |
| | A155-02- ① -1- | W | 7,5W | 3000K | 200mA | 1000 lm | 75% |
| | A155-02- ① -2- | W | 7,5W | 4000K | 200mA | 1030 lm | 75% |

220 V~ | 240 | IP65 | CRI>80 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | FAST I CONNEC | Ø70 | UGR <19 | 38°

| | | | P | CCT | I | Flux | LOR |
|-----------|----------------|---|------|-------|-------|---------|-----|
| BATH Matt | A155-11-10- | W | 5W | 2700K | 140mA | 700 lm | 64% |
| | A155-11-11- | W | 5W | 3000K | 140mA | 730 lm | 64% |
| | A155-11-12- | W | 5W | 4000K | 140mA | 750 lm | 64% |
| | A155-12- ① -0- | W | 7,5W | 2700K | 200mA | 950 lm | 64% |
| | A155-12- ① -1- | W | 7,5W | 3000K | 200mA | 1000 lm | 64% |
| | A155-12- ① -2- | W | 7,5W | 4000K | 200mA | 1030 lm | 64% |

220 V~ | 240 | IP65 | CRI>80 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | FAST I CONNEC | Ø70 | 47°




MORE INFO >>

- ① *OPTIONS
- No DIM
 - DIM Phase Cut
- OTHER DIM OPTIONS PLEASE CONSULT

| | | | P |
|----------|-------------|---|---------|
| BATH 12V | 0350-00-00- | W | MAX 50W |

12V | IP65

EXCL | Ø70



COLOUR | W □ | MATERIAL | AL

RAL ⓘ » 312

Ⓢ & Ⓣ » 288

CERTIFICATES NOT APPLICABLE FOR BATH 12V





MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-----|---------------|------|-------|-------|---------|-----|
| GAP | A171-01-10- | 5W | 2700K | 140mA | 700 lm | 80% |
| | A171-01-11- | 5W | 3000K | 140mA | 730 lm | 80% |
| | A171-01-12- | 5W | 4000K | 140mA | 750 lm | 80% |
| | A171-02- 0-0- | 7,5W | 2700K | 200mA | 950 lm | 80% |
| | A171-02- 0-1- | 7,5W | 3000K | 200mA | 1000 lm | 80% |
| | A171-02- 0-2- | 7,5W | 4000K | 200mA | 1030 lm | 80% |

220
240 V~ | IP20 | CRI>80 | L90B10
>55.000h



P

GAP 12V 0354-00-00- | W | MAX 50W

6x53 | 12V | IP20



P

GAP 230V 0355-00-00- | W | MAX 50W


6210 | 220
240 V~ | IP20



Ⓞ *OPTIONS

| | |
|---|---------------|
| 1 | No DIM |
| 2 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | MATERIAL | AL

RAL ⓘ » 312

Ⓞ & ⓘ » 288



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|----------------|---------------|------|-------|-------|---------|-----|
| GAP Asymmetric | A173-01-10- | 5W | 2700K | 140mA | 700 lm | 78% |
| | A173-01-11- | 5W | 3000K | 140mA | 730 lm | 78% |
| | A173-01-12- | 5W | 4000K | 140mA | 750 lm | 78% |
| | A173-02- 0-0- | 7,5W | 2700K | 200mA | 950 lm | 78% |
| | A173-02- 0-1- | 7,5W | 3000K | 200mA | 1000 lm | 78% |
| | A173-02- 0-2- | 7,5W | 4000K | 200mA | 1030 lm | 78% |

220
240 V~ | IP20 | CRI>80 | L90B10
>55.000h



P

GAP Asymmetric 12V A181-01-01- | W | MAX 50W

6x53 | 12V | IP20



P

GAP Asymmetric 230V A182-01-01- | W | MAX 50W


6210 | 220
240 V~ | IP20



Ⓞ *OPTIONS

| | |
|---|---------------|
| 1 | No DIM |
| 2 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | W □ | MATERIAL | AL

RAL ⓘ » 312

Ⓞ & ⓘ » 288

POP UP



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|--------|--------------------------|------|-------|------|-------|-------|-----|
| POP UP | A278-2- Ⓞ -10- WT NT | 6,5W | 2700K | 20° | 700mA | 610Lm | 92% |
| | A278-2- Ⓞ -11- WT NT | 6,5W | 3000K | 20° | 700mA | 640Lm | 92% |
| | A278-2- Ⓞ -12- WT NT | 6,5W | 4000K | 20° | 700mA | 660Lm | 92% |
| | A278-2- Ⓞ -20- WT NT | 6,5W | 2700K | 30° | 700mA | 610Lm | 89% |
| | A278-2- Ⓞ -21- WT NT | 6,5W | 3000K | 30° | 700mA | 640Lm | 89% |
| | A278-2- Ⓞ -22- WT NT | 6,5W | 4000K | 30° | 700mA | 660Lm | 89% |
| | A278-2- Ⓞ -30- WT NT | 6,5W | 2700K | 56° | 700mA | 610Lm | 86% |
| | A278-2- Ⓞ -31- WT NT | 6,5W | 3000K | 56° | 700mA | 640Lm | 86% |
| | A278-2- Ⓞ -32- WT NT | 6,5W | 4000K | 56° | 700mA | 660Lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECT THE LIGHTING PARAMETERS


POP UP Beam Mixer Diffuser 0805-01-00



POP UP Anti-glare Honeycomb Louver 0806-00-00 | WT | NT |



POP UP High Chromatic LED ⓘ >> 281



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

RAL ⓘ >> 312

Ⓞ & ⓘ >> 288

HIDDEN



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|----------|--------------------------|-----|-------|-------|---------|-----|
| HIDDEN 1 | A200-11- Ⓞ -1- WT NT | 12W | 3000K | 350mA | 1600 lm | 90% |
| | A200-11- Ⓞ -2- WT NT | 12W | 4000K | 350mA | 1625 lm | 90% |
| HIDDEN 2 | A200-21- Ⓞ -1- WT NT | 17W | 3000K | 500mA | 2100 lm | 90% |
| | A200-21- Ⓞ -2- WT NT | 17W | 4000K | 500mA | 2140 lm | 90% |
| | A200-22- Ⓞ -1- WT NT | 17W | 3000K | 500mA | 2100 lm | 90% |
| | A200-22- Ⓞ -2- WT NT | 17W | 4000K | 500mA | 2140 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

* OTHER DIM OPTIONS PLEASE CONSULT



BEAM OPTIONS

| | |
|---|-----|
| 1 | 16° |
| 2 | 24° |
| 3 | 42° |

OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECT THE LIGHTING PARAMETERS

HIDDEN Anti-glare Honeycomb Louver 0702-02-00




HIDDEN Elliptical Refractor 0700-08-00



HIDDEN Beam Mixer Diffuser 0805-02-00



HIDDEN High Chromatic LED ⓘ >> 281



COLOUR | WT □ | NT ■ | MATERIAL | AL | GL-TRANS |

OTHER CCT PLEASE CONSULT

RAL ⓘ >> 312

Ⓞ & ⓘ >> 288




MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|---------|-----------------------|-------|-------|------|-------|---------|-----|
| TWIST 1 | A204-12-10- WT NT | 7W | 2700K | 19° | 200mA | 900 lm | 92% |
| | A204-12-11- WT NT | 7W | 3000K | 19° | 200mA | 930 lm | 92% |
| | A204-12-12- WT NT | 7W | 4000K | 19° | 200mA | 950 lm | 92% |
| | A204-12-20- WT NT | 7W | 2700K | 40° | 200mA | 900 lm | 86% |
| | A204-12-21- WT NT | 7W | 3000K | 40° | 200mA | 930 lm | 86% |
| | A204-12-22- WT NT | 7W | 4000K | 40° | 200mA | 950 lm | 86% |
| TWIST 2 | A204-32-10- WT NT | 10,5W | 2700K | 19° | 300mA | 1270 lm | 92% |
| | A204-32-11- WT NT | 10,5W | 3000K | 19° | 300mA | 1320 lm | 92% |
| | A204-32-12- WT NT | 10,5W | 4000K | 19° | 300mA | 1340 lm | 92% |
| | A204-32-20- WT NT | 10,5W | 2700K | 40° | 300mA | 1270 lm | 86% |
| | A204-32-21- WT NT | 10,5W | 3000K | 40° | 300mA | 1320 lm | 86% |
| | A204-32-22- WT NT | 10,5W | 4000K | 40° | 300mA | 1340 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

* OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------|-----------------------|-----------|-------|------|--|-------------|-----|
| TWIST Double 1 | A204-22-10- WT NT | 2 X 7W | 2700K | 19° | 200mA | 2 X 900 lm | 92% |
| | A204-22-11- WT NT | 2 X 7W | 3000K | 19° | 200mA | 2 X 930 lm | 92% |
| | A204-22-12- WT NT | 2 X 7W | 4000K | 19° | 200mA | 2 X 950 lm | 92% |
| | A204-22-20- WT NT | 2 X 7W | 2700K | 40° | 200mA | 2 X 900 lm | 86% |
| | A204-22-21- WT NT | 2 X 7W | 3000K | 40° | 200mA | 2 X 930 lm | 86% |
| | A204-22-22- WT NT | 2 X 7W | 4000K | 40° | 200mA | 2 X 950 lm | 86% |
| TWIST Double 2 | A204-42-10- WT NT | 2 X 10,5W | 2700K | 19° | 300mA | 2 X 1270 lm | 92% |
| | A204-42-11- WT NT | 2 X 10,5W | 3000K | 19° | 300mA | 2 X 1320 lm | 92% |
| | A204-42-12- WT NT | 2 X 10,5W | 4000K | 19° | 300mA | 2 X 1340 lm | 92% |
| | A204-42-20- WT NT | 2 X 10,5W | 2700K | 40° | 300mA | 2 X 1270 lm | 86% |
| | A204-42-21- WT NT | 2 X 10,5W | 3000K | 40° | 300mA | 2 X 1320 lm | 86% |
| | A204-42-22- WT NT | 2 X 10,5W | 4000K | 40° | 300mA </td <td>2 X 1340 lm</td> <td>86%</td> | 2 X 1340 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h


* OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | WT □ | NT ■ | MATERIAL | AL

RAL ⓘ » 312

Ⓜ & Ⓜ » 288



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|---------------|-----------------------|-------|-------|------|-------|---------|-----|
| TWIST Round 1 | A215-12-10- WT NT | 7W | 2700K | 19° | 200mA | 900 lm | 92% |
| | A215-12-11- WT NT | 7W | 3000K | 19° | 200mA | 930 lm | 92% |
| | A215-12-12- WT NT | 7W | 4000K | 19° | 200mA | 950 lm | 92% |
| | A215-12-20- WT NT | 7W | 2700K | 40° | 200mA | 900 lm | 86% |
| | A215-12-21- WT NT | 7W | 3000K | 40° | 200mA | 930 lm | 86% |
| | A215-12-22- WT NT | 7W | 4000K | 40° | 200mA | 950 lm | 86% |
| TWIST Round 2 | A215-22-10- WT NT | 10,5W | 2700K | 19° | 300mA | 1270 lm | 92% |
| | A215-22-11- WT NT | 10,5W | 3000K | 19° | 300mA | 1320 lm | 92% |
| | A215-22-12- WT NT | 10,5W | 4000K | 19° | 300mA | 1340 lm | 92% |
| | A215-22-20- WT NT | 10,5W | 2700K | 40° | 300mA | 1270 lm | 86% |
| | A215-22-21- WT NT | 10,5W | 3000K | 40° | 300mA | 1320 lm | 86% |
| | A215-22-22- WT NT | 10,5W | 4000K | 40° | 300mA | 1340 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h


* OTHER DIM OPTIONS PLEASE CONSULT



OPTIONAL

TWIST High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS




COLOUR | WT □ | NT ■ | MATERIAL | AL

RAL ⓘ » 312

Ⓜ & Ⓜ » 288





MORE INFO >>



MORE INFO >>



MORE INFO >>

P

ORBITAL Mini 1 Lark A196-11-00- | W | N | **MAX 1 X 7,5W**

LARK | EXCL* | 220 V~ | 240 | IP20 | EXCL | X30°Y30° | 113 X 113

ORBITAL Mini 1 230V A196-13-00- | W | N | **MAX 1 X 50W**

G210 | 220 V~ | 240 | IP20 | X30°Y30° | 113 X 113

P

ORBITAL Mini 2 Lark A196-21-00- | W | N | **MAX 2 X 7,5W**

LARK | EXCL* | 220 V~ | 240 | IP20 | EXCL | X30°Y30° | 113 X 204

ORBITAL Mini 2 230V A196-23-00- | W | N | **MAX 2 X 50W**

G210 | 220 V~ | 240 | IP20 | X30°Y30° | 113 X 204


P

ORBITAL Mini 3 Lark A196-31-00- | W | N | **MAX 3 X 7,5W**

LARK | EXCL* | 220 V~ | 240 | IP20 | EXCL | X30°Y30° | 113 X 295

ORBITAL Mini 3 230V A196-33-00- | W | N | **MAX 3 X 50W**

G210 | 220 V~ | 240 | IP20 | X30°Y30° | 113 X 295



COLOUR | W □ | N ■ | MATERIAL | AL

CERTIFICATES APPLICABLE FOR ORBITAL MINI LARK PRODUCTS

RAL ⓘ » 312

Ⓜ & Ⓜ » 288



Extended Family
Orbital Surface_P.118

*LAMP OPTIONS

| | P | CCT | I | Flux | Flux Out | LOR | |
|---------------|------------|------|-------|-------|----------|--------|-----|
| Lark ⓘ » 275 | 0434-00-96 | 5W | 2700K | 140mA | 700 lm | 644 lm | 92% |
| NO DIM | 0434-00-05 | 5W | 3000K | 140mA | 730 lm | 672 lm | 92% |
| | 0434-00-19 | 5W | 4000K | 140mA | 750 lm | 690 lm | 92% |
| NO DIM | 0434-01-02 | 7,5W | 2700K | 200mA | 950 lm | 874 lm | 92% |
| | 0434-00-09 | 7,5W | 3000K | 200mA | 1000 lm | 920 lm | 92% |
| NO DIM | 0434-00-17 | 7,5W | 4000K | 200mA | 1030 lm | 948 lm | 92% |
| | 0434-01-03 | 7,5W | 2700K | 200mA | 950 lm | 874 lm | 92% |
| PHASE CUT** | 0434-00-15 | 7,5W | 3000K | 200mA | 1000 lm | 920 lm | 92% |
| | 0434-00-18 | 7,5W | 4000K | 200mA | 1030 lm | 948 lm | 92% |
| DALI PUSH** | 0434-01-04 | 7,5W | 2700K | 200mA | 950 lm | 874 lm | 92% |
| | 0434-01-05 | 7,5W | 3000K | 200mA | 1000 lm | 920 lm | 92% |
| | 0434-01-06 | 7,5W | 4000K | 200mA | 1030 lm | 948 lm | 92% |


220 V~ | 240 | CRI>80 | L90B10 >55.000h

** OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>





MORE INFO >>



MORE INFO >>



MORE INFO >>



MORE INFO >>

ORBITAL 1 **LarK-111** A010-11-01- | W | N | P
MAX 1 X 12W





ORBITAL 2 **LarK-111** A010-12-01- | W | N | P
MAX 2 X 12W



ORBITAL 3 **LarK-111** A010-13-05- | W | N | P
MAX 3 X 12W



ORBITAL 4 **LarK-111** A010-14-01- | W | N | P
MAX 4 X 12W



COLOUR | W □ | N ■ | MATERIAL | AL

RAL ⓘ » 312

Ⓢ & Ⓜ » 288

*LAMP OPTIONS

| | | P | CCT | Beam | I | Flux | Flux Out | LOR | |
|---------------------|-----------------------|-----------------------|-------|-------|-------|---------|----------|---------|-----|
| LarK-111 ⓘ » 274 | A25 Ⓞ -10-10- W N | 6,5W | 2700K | 19° | 200mA | 900 lm | 828 lm | 92% | |
| | A25 Ⓞ -10-11- W N | 6,5W | 3000K | 19° | 200mA | 940 lm | 865 lm | 92% | |
| | A25 Ⓞ -10-12- W N | 6,5W | 4000K | 19° | 200mA | 950 lm | 874 lm | 92% | |
| | A25 Ⓞ -10-20- W N | 6,5W | 2700K | 40° | 200mA | 900 lm | 774 lm | 86% | |
| PHASE CUT** | A25 Ⓞ -10-21- W N | 6,5W | 3000K | 40° | 200mA | 940 lm | 808 lm | 86% | |
| | A25 Ⓞ -10-22- W N | 6,5W | 4000K | 40° | 200mA | 950 lm | 817 lm | 86% | |
| PHASE CUT** | A25 Ⓞ -20-10- W N | 12W | 2700K | 19° | 350mA | 1440 lm | 1325 lm | 92% | |
| | A25 Ⓞ -20-11- W N | 12W | 3000K | 19° | 350mA | 1500 lm | 1380 lm | 92% | |
| | A25 Ⓞ -20-12- W N | 12W | 4000K | 19° | 350mA | 1520 lm | 1398 lm | 92% | |
| | A25 Ⓞ -20-20- W N | 12W | 2700K | 40° | 350mA | 1440 lm | 1238 lm | 86% | |
| | A25 Ⓞ -20-21- W N | 12W | 3000K | 40° | 350mA | 1500 lm | 1290 lm | 86% | |
| | A25 Ⓞ -20-22- W N | 12W | 4000K | 40° | 350mA | 1520 lm | 1307 lm | 86% | |
| | DALI PUSH** | A25 Ⓞ -21-10- W N | 12W | 2700K | 19° | 350mA | 1440 lm | 1325 lm | 92% |
| | | A25 Ⓞ -21-11- W N | 12W | 3000K | 19° | 350mA | 1500 lm | 1380 lm | 92% |
| | | A25 Ⓞ -21-12- W N | 12W | 4000K | 19° | 350mA | 1520 lm | 1398 lm | 92% |
| | | A25 Ⓞ -21-20- W N | 12W | 2700K | 40° | 350mA | 1440 lm | 1238 lm | 86% |
| | DALI PUSH** | A25 Ⓞ -21-21- W N | 12W | 3000K | 40° | 350mA | 1500 lm | 1290 lm | 86% |
| | | A25 Ⓞ -21-22- W N | 12W | 4000K | 40° | 350mA | 1520 lm | 1307 lm | 86% |

220/240 V~ | CRI>90 | L90B10 >55.000 h

** OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>

Ⓞ OPTIONS

- 2 **LarK-111**
- 3 **LarK-111 Honeycomb*****



LarK-111



LarK-111 Honeycomb***


COLOUR | W □ | N ■ |

MATERIAL | AL

RAL ⓘ » 312

*** AFFECTS THE LIGHTING PARAMETERS

Ⓢ » 288



MORE INFO >>



MORE INFO >>



MORE INFO >>



MORE INFO >>

ORBITAL Trimless 1 LarK-111 A010-11-03- | W | N | MAX 1 X 12W




ORBITAL Trimless 2 LarK-111 A010-12-03- | W | N | MAX 2 X 12W



ORBITAL Trimless 3 LarK-111 A010-13-06- | W | N | MAX 3 X 12W



ORBITAL Trimless 4 LarK-111 A010-14-02- | W | N | MAX 4 X 12W



COLOUR | W □ | N ■ | MATERIAL | AL | RAL ⓘ » 312

Ⓜ & Ⓜ » 288



*LAMP OPTIONS P CCT Beam I Flux Flux Out LOR

| LarK-111 | Options | P | CCT | Beam | I | Flux | Flux Out | LOR | |
|-------------|-----------------------|-----------------------|-------|-------|-------|---------|----------|---------|-----|
| ⓘ » 274 | A25 Ⓜ -10-10- W N | 6,5W | 2700K | 19° | 200mA | 900 lm | 828 lm | 92% | |
| | A25 Ⓜ -10-11- W N | 6,5W | 3000K | 19° | 200mA | 940 lm | 865 lm | 92% | |
| | A25 Ⓜ -10-12- W N | 6,5W | 4000K | 19° | 200mA | 950 lm | 874 lm | 92% | |
| | A25 Ⓜ -10-20- W N | 6,5W | 2700K | 40° | 200mA | 900 lm | 774 lm | 86% | |
| PHASE CUT** | A25 Ⓜ -10-21- W N | 6,5W | 3000K | 40° | 200mA | 940 lm | 808 lm | 86% | |
| | A25 Ⓜ -10-22- W N | 6,5W | 4000K | 40° | 200mA | 950 lm | 817 lm | 86% | |
| PHASE CUT** | A25 Ⓜ -20-10- W N | 12W | 2700K | 19° | 350mA | 1440 lm | 1325 lm | 92% | |
| | A25 Ⓜ -20-11- W N | 12W | 3000K | 19° | 350mA | 1500 lm | 1380 lm | 92% | |
| | A25 Ⓜ -20-12- W N | 12W | 4000K | 19° | 350mA | 1520 lm | 1398 lm | 92% | |
| | A25 Ⓜ -20-20- W N | 12W | 2700K | 40° | 350mA | 1440 lm | 1238 lm | 86% | |
| | A25 Ⓜ -20-21- W N | 12W | 3000K | 40° | 350mA | 1500 lm | 1290 lm | 86% | |
| | A25 Ⓜ -20-22- W N | 12W | 4000K | 40° | 350mA | 1520 lm | 1307 lm | 86% | |
| | DALI PUSH** | A25 Ⓜ -21-10- W N | 12W | 2700K | 19° | 350mA | 1440 lm | 1325 lm | 92% |
| | | A25 Ⓜ -21-11- W N | 12W | 3000K | 19° | 350mA | 1500 lm | 1380 lm | 92% |
| | | A25 Ⓜ -21-12- W N | 12W | 4000K | 19° | 350mA | 1520 lm | 1398 lm | 92% |
| | | A25 Ⓜ -21-20- W N | 12W | 2700K | 40° | 350mA | 1440 lm | 1238 lm | 86% |
| | DALI PUSH** | A25 Ⓜ -21-21- W N | 12W | 3000K | 40° | 350mA | 1500 lm | 1290 lm | 86% |
| | | A25 Ⓜ -21-22- W N | 12W | 4000K | 40° | 350mA | 1520 lm | 1307 lm | 86% |

220/240 V~ | CRI>90 | L90B10 >55.000 h

** OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>

| Ⓜ | OPTIONS |
|---|-----------------------|
| 2 | LarK-111 |
| 3 | LarK-111 Honeycomb*** |



LarK-111



LarK-111 Honeycomb***

COLOUR | W □ | N ■ | MATERIAL | AL |

** AFFECTS THE LIGHTING PARAMETERS

RAL ⓘ » 312

Ⓜ » 288



MORE INFO >>

| | | | P | CCT | BEAM | I | Flux | LOR |
|------------|--------------|---------|----|-------|------|-------|--------|-----|
| WELLIT S 1 | A380-11-11- | WT NT | 5W | 3000K | 19° | 150mA | 700 lm | 80% |
| | A380-11-12- | WT NT | 5W | 4000K | 19° | 150mA | 710 lm | 80% |
| | A380-11-21- | WT NT | 5W | 3000K | 26° | 150mA | 700 lm | 89% |
| | A380-11-22- | WT NT | 5W | 4000K | 26° | 150mA | 710 lm | 89% |
| | A380-11-31- | WT NT | 5W | 3000K | 41° | 150mA | 700 lm | 84% |
| | A380-11-32- | WT NT | 5W | 4000K | 41° | 150mA | 710 lm | 84% |
| WELLIT S 2 | A380-2-Ⓞ-11- | WT NT | 7W | 3000K | 19° | 200mA | 940 lm | 80% |
| | A380-2-Ⓞ-12- | WT NT | 7W | 4000K | 19° | 200mA | 960 lm | 80% |
| | A380-2-Ⓞ-21- | WT NT | 7W | 3000K | 26° | 200mA | 940 lm | 89% |
| | A380-2-Ⓞ-22- | WT NT | 7W | 4000K | 26° | 200mA | 960 lm | 89% |
| | A380-2-Ⓞ-31- | WT NT | 7W | 3000K | 41° | 200mA | 940 lm | 84% |
| | A380-2-Ⓞ-32- | WT NT | 7W | 4000K | 41° | 200mA | 960 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



Ⓞ *OPTIONS


| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORY

WELLIT S Anti-glare Honeycomb Louver A380-00-00

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

RAL ⓘ » 312


Ⓞ & ⓘ » 288



MORE INFO >>


| | | | P | CCT | BEAM | I | Flux | LOR |
|------------|--------------|---------|-----|-------|------|-------|---------|-----|
| WELLIT M 1 | A381-11-11- | WT NT | 8W | 3000K | 19° | 250mA | 1190 lm | 81% |
| | A381-11-12- | WT NT | 8W | 4000K | 19° | 250mA | 1210 lm | 81% |
| | A381-11-21- | WT NT | 8W | 3000K | 24° | 250mA | 1190 lm | 83% |
| | A381-11-22- | WT NT | 8W | 4000K | 24° | 250mA | 1210 lm | 83% |
| | A381-11-31- | WT NT | 8W | 3000K | 39° | 250mA | 1190 lm | 83% |
| | A381-11-32- | WT NT | 8W | 4000K | 39° | 250mA | 1210 lm | 83% |
| WELLIT M 2 | A381-2-Ⓞ-11- | WT NT | 15W | 3000K | 19° | 450mA | 1970 lm | 81% |
| | A381-2-Ⓞ-12- | WT NT | 15W | 4000K | 19° | 450mA | 2000 lm | 81% |
| | A381-2-Ⓞ-21- | WT NT | 15W | 3000K | 24° | 450mA | 1970 lm | 83% |
| | A381-2-Ⓞ-22- | WT NT | 15W | 4000K | 24° | 450mA | 2000 lm | 83% |
| | A381-2-Ⓞ-31- | WT NT | 15W | 3000K | 39° | 450mA | 1970 lm | 83% |
| | A381-2-Ⓞ-32- | WT NT | 15W | 4000K | 39° | 450mA | 2000 lm | 83% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| | | | P | CCT | BEAM | I | Flux | LOR |
|------------------------|-------------|---------|-------|------------|------|-------|---------|-----|
| WELLIT M Tunable White | A381-02-18- | WT NT | 10,5W | 2700-5000K | 14° | 600mA | 1250 lm | 83% |
| | A381-02-28- | WT NT | 10,5W | 2700-5000K | 20° | 600mA | 1250 lm | 82% |
| | A381-02-38- | WT NT | 10,5W | 2700-5000K | 34° | 600mA | 1250 lm | 80% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



Ⓞ *OPTIONS


| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORY

WELLIT M Anti-glare Honeycomb Louver A381-00-00

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

RAL ⓘ » 312

Ⓞ & ⓘ » 288

WELLIT



MORE INFO >>

| | | | P | CCT | BEAM | I | Flux | LOR |
|------------|-------------|---------|-----|-------|------|-------|---------|-----|
| WELLIT L 1 | A382-11-11- | WT NT | 15W | 3000K | 14° | 450mA | 2060 lm | 90% |
| | A382-11-12- | WT NT | 15W | 4000K | 14° | 450mA | 2100 lm | 90% |
| | A382-11-21- | WT NT | 15W | 3000K | 22° | 450mA | 2060 lm | 91% |
| | A382-11-22- | WT NT | 15W | 4000K | 22° | 450mA | 2100 lm | 91% |
| | A382-11-31- | WT NT | 15W | 3000K | 42° | 450mA | 2060 lm | 91% |
| | A382-11-32- | WT NT | 15W | 4000K | 42° | 450mA | 2100 lm | 91% |
| WELLIT L 2 | A382-2-11- | WT NT | 25W | 3000K | 14° | 700mA | 2960 lm | 90% |
| | A382-2-12- | WT NT | 25W | 4000K | 14° | 700mA | 3000 lm | 90% |
| | A382-2-21- | WT NT | 25W | 3000K | 22° | 700mA | 2960 lm | 91% |
| | A382-2-22- | WT NT | 25W | 4000K | 22° | 700mA | 3000 lm | 91% |
| | A382-2-31- | WT NT | 25W | 3000K | 42° | 700mA | 2960 lm | 91% |
| | A382-2-32- | WT NT | 25W | 4000K | 42° | 700mA | 3000 lm | 91% |

220 V~ | IP20 | CRI>90 | L90B10 >55,000h




| | | | P | CCT | BEAM | I | Flux | LOR |
|------------------------|-------------|---------|-------|------------|------|-------|---------|-----|
| WELLIT L Tunable White | A382-02-18- | WT NT | 21,5W | 2700-5000K | 12° | 600mA | 2300 lm | 89% |
| | A382-02-28- | WT NT | 21,5W | 2700-5000K | 21° | 600mA | 2300 lm | 84% |
| | A382-02-38- | WT NT | 21,5W | 2700-5000K | 43° | 600mA | 2300 lm | 87% |

220 V~ | IP20 | CRI>90 | L80B10 >55,000h



| Ⓞ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT




OPTIONAL ACCESSORY

WELLIT L Anti-glare Honeycomb Louver A382-00-00

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



HUBBLE



MORE INFO >>

| | | | P | CCT | I | Flux | LOR | |
|----------|------------|------------|---------|-------|--------|---------|---------|-----|
| HUBBLE 1 | A276-11-1- | WT NT | 16,5W | 3000K | 500mA | 2450 lm | 90% | |
| | A276-11-2- | WT NT | 16,5W | 4000K | 500mA | 2475 lm | 90% | |
| HUBBLE 2 | A276-21-1- | WT NT | 30,5W | 3000K | 900mA | 4050 lm | 90% | |
| | A276-21-2- | WT NT | 30,5W | 4000K | 900mA | 4120 lm | 90% | |
| HUBBLE 3 | A276-31-1- | WT NT | 41W | 3000K | 1200mA | 5000 lm | 90% | |
| | A276-31-2- | WT NT | 41W | 4000K | 1200mA | 5100 lm | 90% | |
| | PUSH* | A276-32-1- | WT NT | 41W | 3000K | 1200mA | 5000 lm | 90% |
| | | A276-32-2- | WT NT | 41W | 4000K | 1200mA | 5100 lm | 90% |
| | DALI* | A276-34-1- | WT NT | 41W | 3000K | 1200mA | 5000 lm | 90% |
| | | A276-34-2- | WT NT | 41W | 4000K | 1200mA | 5100 lm | 90% |


220 V~ | IP20 | CRI>90 | L90B10 >55,000h



* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

| | | | P | CCT | I | Flux | LOR | |
|-----------------|------------|------------|-----------|---------|--------|-------------|-------------|-----|
| HUBBLE Double 1 | A277-11-1- | WT NT | 2 X 16,5W | 3000K | 500mA | 2 X 2450 lm | 90% | |
| | A277-11-2- | WT NT | 2 X 16,5W | 4000K | 500mA | 2 X 2475 lm | 90% | |
| HUBBLE Double 2 | A277-21-1- | WT NT | 2 X 30,5W | 3000K | 900mA | 2 X 4050 lm | 90% | |
| | A277-21-2- | WT NT | 2 X 30,5W | 4000K | 900mA | 2 X 4120 lm | 90% | |
| HUBBLE Double 3 | A277-31-1- | WT NT | 2 X 41W | 3000K | 1200mA | 2 X 5000 lm | 90% | |
| | A277-31-2- | WT NT | 2 X 41W | 4000K | 1200mA | 2 X 5100 lm | 90% | |
| | PUSH* | A277-32-1- | WT NT | 2 X 41W | 3000K | 1200mA | 2 X 5000 lm | 90% |
| | | A277-32-2- | WT NT | 2 X 41W | 4000K | 1200mA | 2 X 5100 lm | 90% |
| | DALI* | A277-34-1- | WT NT | 2 X 41W | 3000K | 1200mA | 2 X 5000 lm | 90% |
| | | A277-34-2- | WT NT | 2 X 41W | 4000K | 1200mA | 2 X 5100 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 >55,000h



* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORIES


NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS

HUBBLE Anti-glare Honeycomb Louver
0802-02-00





HUBBLE Elliptical Refractor
0802-04-00

HUBBLE Beam Mixer Diffuser
0805-03-00





HUBBLE High Chromatic LED ⓘ >> 281

HUBBLE



HUBBLE DOUBLE



| Ⓞ | BEAM OPTIONS |
|---|--------------|
| 1 | 17° |
| 2 | 28° |
| 3 | 40° |

COLOUR | WT □ | NT ■ | MATERIAL | AL | GL-TRANS |

OTHER CCT PLEASE CONSULT

RAL ⓘ >> 312

Ⓞ & ⓘ >> 288



MAGNETIC SYSTEM



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|--------------------------|-----------------------|------|-------|------|-------|---------|-----|
| MAGNETIC 24V COCO | A499-00-10- WT NT | 8,7W | 2700K | 20° | 500mA | 1200 lm | 87% |
| | A499-00-11- WT NT | 8,7W | 3000K | 20° | 500mA | 1250 lm | 87% |
| | A499-00-12- WT NT | 8,7W | 4000K | 20° | 500mA | 1340 lm | 87% |
| | A499-00-20- WT NT | 8,7W | 2700K | 34° | 500mA | 1200 lm | 89% |
| | A499-00-21- WT NT | 8,7W | 3000K | 34° | 500mA | 1250 lm | 89% |
| | A499-00-22- WT NT | 8,7W | 4000K | 34° | 500mA | 1340 lm | 89% |
| | A499-00-30- WT NT | 8,7W | 2700K | 48° | 500mA | 1200 lm | 86% |
| | A499-00-31- WT NT | 8,7W | 3000K | 48° | 500mA | 1250 lm | 86% |
| | A499-00-32- WT NT | 8,7W | 4000K | 48° | 500mA | 1340 lm | 86% |

24 V | IP20 | CRI>90 | L80B10 > 66.000h

MacAdam Step 2 | EXCL* | INCL | 360° | 90° | 20° / 34° / 48°

| | | P | CCT | Beam | I | Flux | LOR |
|-------------------------------------|-----------------------|----|-------|------|-------|--------|-----|
| MAGNETIC 24V COCO Super Spot | A499-00-00- WT NT | 6W | 2700K | 12° | 500mA | 750 lm | 66% |
| | A499-00-01- WT NT | 6W | 3000K | 12° | 500mA | 800 lm | 66% |
| | A499-00-02- WT NT | 6W | 4000K | 12° | 500mA | 850 lm | 66% |

24 V | IP20 | CRI>90 | L80B10 > 55.000h

MacAdam Step 2 | EXCL* | INCL | 360° | 90° | 12°

OPTIONAL ACCESSORIES

COCO Anti-glare Honeycomb Louver**

A498-90-00- | WT | NT |



COCO Linear Filter**

A498-90-02- | WT | NT |



SUITABLE FOR BEAM < 34°

COCO Anti-glare Screen**

A498-90-01- | WT | NT |




COCO High Chromatic Led** » 281

NOT SOLD SEPARATELY

TRIMLESS TOOL D16 X D34mm


A478-00-00



MAGNETIC 24V CONNECTOR A435-01-00 | W | N |

* MANDATORY FOR INSTALLATION

IP20 | Ø16



| | | P | V | D (A x B x C) |
|------------------|------------|------|-----|-----------------|
| 24V POWER SUPPLY | 0434-01-37 | 60W | 24V | 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V | 295 x 43 x 30mm |

220 V~ | MUST BE PLACED ON REMOTE

| | | | V | D (A x B x C) |
|------------|------------|-------------|-----|-----------------|
| 24V DIMMER | 0433-01-32 | DALI / Push | 24V | 181 x 42 x 20mm |
| | 0433-01-33 | CASAMBI | 24V | 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V | 105 x 44 x 23mm |

24 V | MUST BE PLACED ON REMOTE OTHER DIM OPTIONS PLEASE CONSULT

DROP VOLTAGE » 287

COLOUR | WT | NT | MATERIAL | AL | PC/PMMA |

RAL » 312

OTHER CCT OPTIONS PLEASE CONSULT » 288
** AFFECTS THE LIGHTING PARAMETERS




MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|--------------------------|------------------------------------|----|-------|------|-------|--------|-----|
| MAGNETIC 24V FLIP | A492-00-10- NT WT NTMG | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A492-00-11- NT WT NTMG | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A492-00-12- NT WT NTMG | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A492-00-20- NT WT NTMG WTW | 6W | 2700K | 40° | 500mA | 640 lm | 84% |
| | A492-00-21- NT WT NTMG WTW | 6W | 3000K | 40° | 500mA | 670 lm | 84% |
| | A492-00-22- NT WT NTMG WTW | 6W | 4000K | 40° | 500mA | 720 lm | 84% |

24 V | IP20 | CRI>90 | L80B10 > 60.000h

MacAdam Step 2 | EXCL* | INCL | 360° | 90° | 18° / 40°




| FINISHING** | Body | Lampshade |
|-------------|------|-----------|
| NT | NT | N |
| WT | WT | N |
| NTMG | NT | MG |
| WTW | WT | W |

MAGNETIC 24V CONNECTOR A435-01-00 | W | N |

* MANDATORY FOR INSTALLATION

IP20 | Ø16



| | | P | V | D (A x B x C) |
|------------------|------------|------|-----|-----------------|
| 24V POWER SUPPLY | 0434-01-37 | 60W | 24V | 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V | 295 x 43 x 30mm |

220 V~ | MUST BE PLACED ON REMOTE

| | | | V | D (A x B x C) |
|------------|------------|-------------|-----|-----------------|
| 24V DIMMER | 0433-01-32 | DALI / Push | 24V | 181 x 42 x 20mm |
| | 0433-01-33 | CASAMBI | 24V | 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V | 105 x 44 x 23mm |

24 V | MUST BE PLACED ON REMOTE OTHER DIM OPTIONS PLEASE CONSULT

DROP VOLTAGE » 287

COLOUR | NT | WT | NTMG | WTW

MATERIAL | AL | ABS+PC |

RAL » 312

** OTHER FINISHING COMBINATIONS PLEASE CONSULT
"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR WT, NT & NTMG COLOURS

MAGNETIC SYSTEM



MORE INFO >>



MORE INFO >>

| | P | CCT | Beam | I | Flux | LOR | |
|----------------------------|---------------------------|------|-------|-----|-------|--------|-----|
| MAGNETIC 24V FIT 20 | A431-01-10- WT NT G | 2,1W | 2700K | 12° | 700mA | 127 lm | 87% |
| | A431-01-11- WT NT G | 2,1W | 3000K | 12° | 700mA | 150 lm | 87% |
| | A431-01-20- WT NT G | 2,1W | 2700K | 30° | 700mA | 127 lm | 88% |
| | A431-01-21- WT NT G | 2,1W | 3000K | 30° | 700mA | 150 lm | 88% |
| | A431-01-30- WT NT G | 2,1W | 2700K | 54° | 700mA | 127 lm | 81% |
| | A431-01-31- WT NT G | 2,1W | 3000K | 54° | 700mA | 150 lm | 81% |

24 V | III IP20 | CRI>90 | L80B10 > 50.000h

MacAdam Step 3 | EXCL* | INCL | 360° | 90° | 12° / 30° / 54°

| | P | CCT | Beam | I | Flux | LOR | |
|----------------------------|---------------------------|------|-------|-----|-------|--------|-----|
| MAGNETIC 24V FIT 27 | A432-01-10- WT NT G | 4,5W | 2700K | 18° | 400mA | 440 lm | 84% |
| | A432-01-11- WT NT G | 4,5W | 3000K | 18° | 400mA | 470 lm | 84% |
| | A432-01-20- WT NT G | 4,5W | 2700K | 31° | 400mA | 440 lm | 82% |
| | A432-01-21- WT NT G | 4,5W | 3000K | 31° | 400mA | 470 lm | 82% |
| | A432-01-30- WT NT G | 4,5W | 2700K | 42° | 400mA | 440 lm | 84% |
| | A432-01-31- WT NT G | 4,5W | 3000K | 42° | 400mA | 470 lm | 84% |


24 V | III IP20 | CRI>90 | L90B10 > 108.000h

MacAdam Step 2 | EXCL* | INCL | 360° | 90° | 18° / 31° / 42°


MAGNETIC 24V CONNECTOR

A435-01-00 | W | N |


* MANDATORY FOR INSTALLATION



MAGNETIC 24V FIT 20




MAGNETIC 24V FIT 27



| | P | V | D (A x B x C) |
|------------------|------------|------|---------------------|
| 24V POWER SUPPLY | 0434-01-37 | 60W | 24V 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V 295 x 43 x 30mm |


220 V~ | 240 V~ | MUST BE PLACED ON REMOTE



OPTIONAL ACCESSORY

TRIMLESS TOOL D16 X D34mm


A478-00-00



| | P | V | D (A x B x C) |
|------------|------------|-------------|---------------------|
| 24V DIMMER | 0433-01-32 | DALI / Push | 24V 181 x 42 x 20mm |
| | 0433-01-33 | CASAMBI | 24V 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V 105 x 44 x 23mm |

24 V | MUST BE PLACED ON REMOTE OTHER DIM OPTIONS PLEASE CONSULT

ⓘ DROP VOLTAGE >> 287




COLOUR | WT □ | NT ■ | G ■

MATERIAL | AL | PC

RAL ⓘ >> 312

WALL MOUNTING PLEASE CONSULT

Ⓜ >> 288




MORE INFO >>

MAGNETIC 24V i0 Micro

| | P | CCT | Beam | I | Flux | LOR | |
|------------------------------|-----------------------|------|-------|-----|-------|--------|-----|
| MAGNETIC 24V i0 Micro | A434-01-10- WT NT | 4,7W | 2700K | 20° | 400mA | 500 lm | 88% |
| | A434-01-11- WT NT | 4,7W | 3000K | 20° | 400mA | 520 lm | 88% |
| | A434-01-12- WT NT | 4,7W | 4000K | 20° | 400mA | 570 lm | 88% |
| | A434-01-20- WT NT | 4,7W | 2700K | 40° | 400mA | 500 lm | 86% |
| | A434-01-21- WT NT | 4,7W | 3000K | 40° | 400mA | 520 lm | 86% |
| | A434-01-22- WT NT | 4,7W | 4000K | 40° | 400mA | 570 lm | 86% |
| | A434-01-30- WT NT | 4,7W | 2700K | 54° | 400mA | 500 lm | 86% |
| | A434-01-31- WT NT | 4,7W | 3000K | 54° | 400mA | 520 lm | 86% |
| | A434-01-32- WT NT | 4,7W | 4000K | 54° | 400mA | 570 lm | 86% |

24 V | III IP20 | CRI>90 | L80B10 > 50.000h


MacAdam Step 3 | EXCL* | INCL | 360° | 155° | 20° / 40° / 54°



MAGNETIC 24V CONNECTOR

A435-01-00 | W | N |

* MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORIES

i0 Micro Beam Mixer Diffuser**

A387-00-00




i0 Micro Anti-glare Honeycomb Louver**

A387-00-01 | WT | NT |




TRIMLESS TOOL D16 X D34mm

A478-00-00



| | P | V | D (A x B x C) |
|------------------|------------|------|---------------------|
| 24V POWER SUPPLY | 0434-01-37 | 60W | 24V 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V 295 x 43 x 30mm |


220 V~ | 240 V~ | MUST BE PLACED ON REMOTE



| | P | V | D (A x B x C) |
|------------|------------|-------------|---------------------|
| 24V DIMMER | 0433-01-32 | DALI / Push | 24V 181 x 42 x 20mm |
| | 0433-01-33 | CASAMBI | 24V 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V 105 x 44 x 23mm |

24 V | MUST BE PLACED ON REMOTE OTHER DIM OPTIONS PLEASE CONSULT

ⓘ DROP VOLTAGE >> 287



COLOUR | WT □ | NT ■

MATERIAL | AL | PC

RAL ⓘ >> 312


WALL MOUNTING PLEASE CONSULT | ** AFFECT THE LIGHTING PARAMETERS

Ⓜ >> 288

MAGNETIC SYSTEM



MORE INFO >>



MORE INFO >>

| | P | CCT | Beam | I | Flux | LOR | |
|--------------------------------|-----------------------|------|-------|---------|-------|--------|--------|
| MAGNETIC 24V PLUS Micro | A433-01-00- WT NT | 4,7W | 2700K | 10°-35° | 400mA | 500 lm | 10-17% |
| | A433-01-01- WT NT | 4,7W | 3000K | 10°-35° | 400mA | 520 lm | 10-17% |
| | A433-01-02- WT NT | 4,7W | 4000K | 10°-35° | 400mA | 570 lm | 10-17% |

24 V | III IP20 | CRI>90 | L90B10 > 50.000h

MacAdam Step 3 EXCL* INCL 360° 180° 10° - 35°

| | P | CCT | Beam | I | Flux | LOR | |
|-------------------------------|-----------------------|------|-------|-----|-------|--------|-----|
| MAGNETIC 24V TOP Micro | A430-01-10- WT NT | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| | A430-01-11- WT NT | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| | A430-01-20- WT NT | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| | A430-01-21- WT NT | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |


24 V | III IP20 | CRI>90 | L90B10 > 102.000h

MacAdam Step 3 EXCL* INCL 19° / 38°


MAGNETIC 24V CONNECTOR

A435-01-00 | W | N |


* MANDATORY FOR INSTALLATION



MAGNETIC 24V PLUS MICRO




MAGNETIC 24V TOP MICRO



| | P | V | D (A x B x C) |
|-------------------------|------------|------|---------------------|
| 24V POWER SUPPLY | 0434-01-37 | 60W | 24V 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V 295 x 43 x 30mm |


220 V~ | MUST BE PLACED ON REMOTE



OPTIONAL ACCESSORY

TRIMLESS TOOL D16 X D34mm


A478-00-00



| | P | V | D (A x B x C) |
|-------------------|------------|-------------|---------------------|
| 24V DIMMER | 0433-01-32 | DALI / Push | 24V 181 x 42 x 20mm |
| | 0433-01-33 | CASAMBI | 24V 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V 105 x 44 x 23mm |

24 V | MUST BE PLACED ON REMOTE OTHER DIM OPTIONS PLEASE CONSULT


i DROP VOLTAGE >> 287



COLOUR | WT □ | NT ■ | MATERIAL | AL | OPTICAL PMMA | AL | PC | RAL i >> 312

WALL MOUNTING PLEASE CONSULT

(=) & >> 288




MORE INFO >>

MAGNETIC 24V SIX XS

| | P | CCT | Beam | I | Flux | LOR | |
|----------------------------|-----------------------|------|-------|-----|-------|--------|-----|
| MAGNETIC 24V SIX XS | A429-01-10- WT NT | 4,5W | 2700K | 17° | 500mA | 470 lm | 90% |
| | A429-01-11- WT NT | 4,5W | 3000K | 17° | 500mA | 500 lm | 90% |
| | A429-01-12- WT NT | 4,5W | 4000K | 17° | 500mA | 530 lm | 90% |
| | A429-01-20- WT NT | 4,5W | 2700K | 23° | 500mA | 470 lm | 86% |
| | A429-01-21- WT NT | 4,5W | 3000K | 23° | 500mA | 500 lm | 86% |
| | A429-01-22- WT NT | 4,5W | 4000K | 23° | 500mA | 530 lm | 86% |
| | A429-01-30- WT NT | 4,5W | 2700K | 34° | 500mA | 470 lm | 88% |
| | A429-01-31- WT NT | 4,5W | 3000K | 34° | 500mA | 500 lm | 88% |
| | A429-01-32- WT NT | 4,5W | 4000K | 34° | 500mA | 530 lm | 88% |

24 V | III IP20 | CRI>90 | L90B10 > 55.000h


MacAdam Step 2 EXCL* INCL 360° 310° 17° / 23° / 34°



MAGNETIC 24V CONNECTOR


A435-01-00 | W | N |

* MANDATORY FOR INSTALLATION



| | P | V | D (A x B x C) |
|-------------------------|------------|------|---------------------|
| 24V POWER SUPPLY | 0434-01-37 | 60W | 24V 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V 295 x 43 x 30mm |

220 V~ | MUST BE PLACED ON REMOTE




OPTIONAL ACCESSORIES

SIX High Chromatic Led i >> 281

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D16 X D34mm


A478-00-00



| | P | V | D (A x B x C) |
|-------------------|------------|-------------|---------------------|
| 24V DIMMER | 0433-01-32 | DALI / Push | 24V 181 x 42 x 20mm |
| | 0433-01-33 | CASAMBI | 24V 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V 105 x 44 x 23mm |

24 V | MUST BE PLACED ON REMOTE OTHER DIM OPTIONS PLEASE CONSULT

i DROP VOLTAGE >> 287



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | RAL i >> 312

WALL MOUNTING PLEASE CONSULT

(=) >> 288

FLIP RECESSED



Extended Family
Magnetic 24V Flip_P.91
Flip Surface_P.123
Flip 48V_P.206



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|---------------|---------------------------------------|----|-------|------|-------|--------|-----|
| FLIP Recessed | A491-0- Ⓞ -10- NT WT NTMG | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A491-0- Ⓞ -11- NT WT NTMG | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A491-0- Ⓞ -12- NT WT NTMG | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A491-0- Ⓞ -20- NT WT NTMG WTW | 6W | 2700K | 40° | 500mA | 640 lm | 84% |
| | A491-0- Ⓞ -21- NT WT NTMG WTW | 6W | 3000K | 40° | 500mA | 670 lm | 84% |
| | A491-0- Ⓞ -22- NT WT NTMG WTW | 6W | 4000K | 40° | 500mA | 720 lm | 84% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h




*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT

| FINISHING** | Body | Lampshade |
|-------------|------|-----------|
| NT | NT ■ | N ■ |
| WT | WT □ | N ■ |
| NTMG | NT ■ | MG ■ |
| WTW | WT □ | W □ |



COLOUR | NT ■ | WT □ | NTMG ■ | WTW □ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

**OTHER FINISHING COMBINATIONS PLEASE CONSULT
"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR WT, NT & NTMG COLOURS

Ⓞ & ⓘ » 288

SIX RECESSED



Extended Family
Magnetic 24V Six XS_P.95
Six XS 24V_P.182
Six 48V_P.194
Six_P.226
Black Foster Six S_P.246



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR | |
|--------------------------|-----------------------|--------------------------|-------|-------|-------|---------|---------|-----|
| SIX L Recessed 1 | A287-11-10- WT NT | 11,5W | 2700K | 17° | 350mA | 1600 lm | 93% | |
| | A287-11-11- WT NT | 11,5W | 3000K | 17° | 350mA | 1650 lm | 93% | |
| | A287-11-12- WT NT | 11,5W | 4000K | 17° | 350mA | 1700 lm | 93% | |
| | A287-11-30- WT NT | 11,5W | 2700K | 26° | 350mA | 1600 lm | 93% | |
| | A287-11-31- WT NT | 11,5W | 3000K | 26° | 350mA | 1650 lm | 93% | |
| | A287-11-32- WT NT | 11,5W | 4000K | 26° | 350mA | 1700 lm | 93% | |
| | A287-11-20- WT NT | 11,5W | 2700K | 34° | 350mA | 1600 lm | 90% | |
| | A287-11-21- WT NT | 11,5W | 3000K | 34° | 350mA | 1650 lm | 90% | |
| | A287-11-22- WT NT | 11,5W | 4000K | 34° | 350mA | 1700 lm | 90% | |
| | SIX L Recessed 2 | A287-2- Ⓞ -10- WT NT | 24,5W | 2700K | 17° | 700mA | 2850 lm | 93% |
| | | A287-2- Ⓞ -11- WT NT | 24,5W | 3000K | 17° | 700mA | 2950 lm | 93% |
| A287-2- Ⓞ -12- WT NT | | 24,5W | 4000K | 17° | 700mA | 3000 lm | 93% | |
| A287-2- Ⓞ -30- WT NT | | 24,5W | 2700K | 26° | 700mA | 2850 lm | 93% | |
| A287-2- Ⓞ -31- WT NT | | 24,5W | 3000K | 26° | 700mA | 2950 lm | 93% | |
| A287-2- Ⓞ -32- WT NT | | 24,5W | 4000K | 26° | 700mA | 3000 lm | 93% | |
| A287-2- Ⓞ -20- WT NT | | 24,5W | 2700K | 34° | 700mA | 2850 lm | 90% | |
| A287-2- Ⓞ -21- WT NT | | 24,5W | 3000K | 34° | 700mA | 2950 lm | 90% | |
| A287-2- Ⓞ -22- WT NT | | 24,5W | 4000K | 34° | 700mA | 3000 lm | 90% | |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h




*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT

OPTIONAL


SIX L High Chromatic LED ⓘ » 281
NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | RAL ⓘ » 312

Ⓞ & ⓘ » 288

SIX RECESSED



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR | |
|-------------------------|-------------------------|--------------|---------|-------|-------|-------|---------|---------|
| SIX M Recessed 1 | A332-11-10- | WT NT | 11,5W | 2700K | 19° | 350mA | 1600 lm | 93% |
| | A332-11-11- | WT NT | 11,5W | 3000K | 19° | 350mA | 1650 lm | 93% |
| | A332-11-12- | WT NT | 11,5W | 4000K | 19° | 350mA | 1700 lm | 93% |
| | A332-11-20- | WT NT | 11,5W | 2700K | 28° | 350mA | 1600 lm | 91% |
| | A332-11-21- | WT NT | 11,5W | 3000K | 28° | 350mA | 1650 lm | 91% |
| | A332-11-22- | WT NT | 11,5W | 4000K | 28° | 350mA | 1700 lm | 91% |
| | A332-11-30- | WT NT | 11,5W | 2700K | 38° | 350mA | 1600 lm | 93% |
| | A332-11-31- | WT NT | 11,5W | 3000K | 38° | 350mA | 1650 lm | 93% |
| | A332-11-32- | WT NT | 11,5W | 4000K | 38° | 350mA | 1700 lm | 93% |
| | SIX M Recessed 2 | A332-2- -10- | WT NT | 17W | 2700K | 19° | 500mA | 2050 lm |
| A332-2- -11- | | WT NT | 17W | 3000K | 19° | 500mA | 2130 lm | 93% |
| A332-2- -12- | | WT NT | 17W | 4000K | 19° | 500mA | 2160 lm | 93% |
| A332-2- -20- | | WT NT | 17W | 2700K | 28° | 500mA | 2050 lm | 91% |
| A332-2- -21- | | WT NT | 17W | 3000K | 28° | 500mA | 2130 lm | 91% |
| A332-2- -22- | | WT NT | 17W | 4000K | 28° | 500mA | 2160 lm | 91% |
| A332-2- -30- | | WT NT | 17W | 2700K | 38° | 500mA | 2050 lm | 93% |
| A332-2- -31- | | WT NT | 17W | 3000K | 38° | 500mA | 2130 lm | 93% |
| A332-2- -32- | | WT NT | 17W | 4000K | 38° | 500mA | 2160 lm | 93% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h




Ⓜ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL


SIX M High Chromatic LED ⓘ » 281
NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

RAL ⓘ » 312

Ⓜ & ⓘ » 288



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR | |
|-----------------------|--------------|---------|------|-------|-----|-------|---------|-----|
| SIX S Recessed | A334-0- -10- | WT NT | 8,5W | 2700K | 17° | 500mA | 1070 lm | 86% |
| | A334-0- -11- | WT NT | 8,5W | 3000K | 17° | 500mA | 1140 lm | 86% |
| | A334-0- -12- | WT NT | 8,5W | 4000K | 17° | 500mA | 1210 lm | 86% |
| | A334-0- -20- | WT NT | 8,5W | 2700K | 24° | 500mA | 1070 lm | 84% |
| | A334-0- -21- | WT NT | 8,5W | 3000K | 24° | 500mA | 1140 lm | 84% |
| | A334-0- -22- | WT NT | 8,5W | 4000K | 24° | 500mA | 1210 lm | 84% |
| | A334-0- -30- | WT NT | 8,5W | 2700K | 34° | 500mA | 1070 lm | 89% |
| | A334-0- -31- | WT NT | 8,5W | 3000K | 34° | 500mA | 1140 lm | 89% |
| | A334-0- -32- | WT NT | 8,5W | 4000K | 34° | 500mA | 1210 lm | 89% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



| | | P | CCT | Beam | I | Flux | LOR | |
|------------------------|--------------|---------|------|-------|-----|-------|--------|-----|
| SIX XS Recessed | A336-0- -10- | WT NT | 4,5W | 2700K | 17° | 500mA | 470 lm | 90% |
| | A336-0- -11- | WT NT | 4,5W | 3000K | 17° | 500mA | 500 lm | 90% |
| | A336-0- -12- | WT NT | 4,5W | 4000K | 17° | 500mA | 530 lm | 90% |
| | A336-0- -20- | WT NT | 4,5W | 2700K | 23° | 500mA | 470 lm | 86% |
| | A336-0- -21- | WT NT | 4,5W | 3000K | 23° | 500mA | 500 lm | 86% |
| | A336-0- -22- | WT NT | 4,5W | 4000K | 23° | 500mA | 530 lm | 86% |
| | A336-0- -30- | WT NT | 4,5W | 2700K | 34° | 500mA | 470 lm | 88% |
| | A336-0- -31- | WT NT | 4,5W | 3000K | 34° | 500mA | 500 lm | 88% |
| | A336-0- -32- | WT NT | 4,5W | 4000K | 34° | 500mA | 530 lm | 88% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h





Ⓜ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL

SIX High Chromatic LED ⓘ » 281
NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |


RAL ⓘ » 312

Ⓜ & ⓘ » 288

FIT RECESSED



MORE INFO >>



MORE INFO >>

Extended Family
Fit_P.228
Black Foster Fit 35_P.246
Black Foster Fit 27_P.249

| | | Magnetic 24V Fit_P.92 Fit Surface_P.124 | Fit 24V_P.184 Fit 48V_P.197 Fit 65 1L_P.221 | | | | | | | |
|------------------------------|------------------------------|--|---|--------|---------|---------|-----|--|--|--|
| | | P | CCT | Beam | I | Flux | LOR | | | |
| FIT 50 Recessed | A346-2- ① -10- WT NT G | 12W | 2700K | 14° | 1050mA | 1090 lm | 84% | | | |
| | A346-2- ① -11- WT NT G | 12W | 3000K | 14° | 1050mA | 1180 lm | 84% | | | |
| | A346-2- ① -12- WT NT G | 12W | 4000K | 14° | 1050mA | 1260 lm | 84% | | | |
| | A346-2- ① -20- WT NT G | 12W | 2700K | 26° | 1050mA | 1090 lm | 83% | | | |
| | A346-2- ① -21- WT NT G | 12W | 3000K | 26° | 1050mA | 1180 lm | 83% | | | |
| | A346-2- ① -22- WT NT G | 12W | 4000K | 26° | 1050mA | 1260 lm | 83% | | | |
| | A346-2- ① -30- WT NT G | 12W | 2700K | 50° | 1050mA | 1090 lm | 79% | | | |
| | A346-2- ① -31- WT NT G | 12W | 3000K | 50° | 1050mA | 1180 lm | 79% | | | |
| A346-2- ① -32- WT NT G | 12W | 4000K | 50° | 1050mA | 1260 lm | 79% | | | | |

220 V~ | IP20 | CRI>90 | L90B10 >108.000h

MacAdam Step 2 | OPTIONS* | INCL | Ø62 | 350° | 90° | 14°/26°/50°

| | | P | CCT | Beam | I | Flux | LOR |
|------------------------------|------------------------------|-------|-------|-------|--------|--------|-----|
| FIT 35 Recessed | A345-2- ① -10- WT NT G | 5,5W | 2700K | 20° | 500mA | 620 lm | 85% |
| | A345-2- ① -11- WT NT G | 5,5W | 3000K | 20° | 500mA | 660 lm | 85% |
| | A345-2- ① -12- WT NT G | 5,5W | 4000K | 20° | 500mA | 710 lm | 85% |
| | A345-2- ① -20- WT NT G | 5,5W | 2700K | 29° | 500mA | 620 lm | 84% |
| | A345-2- ① -21- WT NT G | 5,5W | 3000K | 29° | 500mA | 660 lm | 84% |
| | A345-2- ① -22- WT NT G | 5,5W | 4000K | 29° | 500mA | 710 lm | 84% |
| | A345-2- ① -30- WT NT G | 5,5W | 2700K | 36° | 500mA | 620 lm | 85% |
| | A345-2- ① -31- WT NT G | 5,5W | 3000K | 36° | 500mA | 660 lm | 85% |
| A345-2- ① -32- WT NT G | 5,5W | 4000K | 36° | 500mA | 710 lm | 85% | |

220 V~ | IP20 | CRI>90 | L90B10 >108.000h


MacAdam Step 2 | OPTIONS* | INCL | Ø50 | 350° | 90° | 20°/29°/36°

- ① *OPTIONS
- No DIM
 - DIM DALI
- DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT


- OPTIONAL ACCESSORIES
- FIT 50 Anti-glare Honeycomb Louver **A346-00-00**
- FIT 35 Anti-glare Honeycomb Louver **A345-00-00**
- NOT SOLD SEPARATELY | AFFECT THE LIGHTING PARAMETERS



FIT50 RECESSED



FIT35 RECESSED




COLOUR | WT □ | NT ■ | G ■ | MATERIAL | AL | PC | RAL ⓘ » 312

Ⓜ & Ⓜ » 288

PLUS RECESSED



MORE INFO >>



MORE INFO >>



Extended Family
Plus Mini 1L_P.221
Plus_P.229
Black Foster Plus Mini_P.246

| | | Magnetic 24V Plus Micro_P.94 Plus Micro 24V_P.182 Plus 48V_P.201 | | | | | |
|---------------|--------------------------|--|-------|---------|-------|---------|--------|
| | | P | CCT | Beam | I | Flux | LOR |
| PLUS Recessed | A325-00- ① -0- WT NT | 18W | 2700K | 12°-51° | 500mA | 1920 lm | 26-40% |
| | A325-00- ① -1- WT NT | 18W | 3000K | 12°-51° | 500mA | 2000 lm | 26-40% |
| | A325-00- ① -2- WT NT | 18W | 4000K | 12°-51° | 500mA | 2030 lm | 26-40% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | Ø62 | 350° | 180° | 12°-51°

- ① *OPTIONS
- No DIM
 - DIM DALI
 - DIM Push
- DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

- OPTIONAL
- PLUS High Chromatic LED ⓘ » 281
- NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

| | | P | CCT | Beam | I | Flux | LOR |
|--------------------|--------------------------|------|-------|---------|-------|--------|--------|
| PLUS Mini Recessed | A328-00- ① -0- WT NT | 6,5W | 2700K | 10°-41° | 700mA | 630 lm | 20-40% |
| | A328-00- ① -1- WT NT | 6,5W | 3000K | 10°-41° | 700mA | 660 lm | 20-40% |
| | A328-00- ① -2- WT NT | 6,5W | 4000K | 10°-41° | 700mA | 680 lm | 20-40% |


220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | Ø50 | 350° | 180° | 10°-41°


- ① *OPTIONS
- No DIM
 - DIM DALI
- DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

- OPTIONAL
- PLUS MINI High Chromatic LED ⓘ » 281
- NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

PLUS RECESSED



PLUS MINI RECESSED



COLOUR | WT □ | NT ■ | MATERIAL | AL | OPTICAL PMMA | RAL ⓘ » 312

Ⓜ & Ⓜ » 288

BLACK FOSTER SURFACE_104

SHOT LIGHT SURFACE_110

SCOPE SURFACE_113

TOP_114

PUCK_116

STRAM SURFACE_117

ORBITAL SURFACE_118

VOLA_120

SKY_120

DRUM_121

FIFTY+ SURFACE_122

FLIP SURFACE_123

FIT SURFACE_124

IO SURFACE_126

ZEN TUBE SURFACE_127

BLACK FOSTER SURFACE



1:1 scale reproduction. The photo displays the real-size version of the product.



MORE INFO >>



MORE INFO >>



MORE INFO >>

| FINISHING | Body | Lampshade |
|-----------|------------|-----------|
| NT | NT ■ N ■ | |
| WT | WT □ N ■ | |

Extended Family
 Black Foster Micro_P10
 Black Foster_P12
 Black Foster Suspension_P133
 Black Foster Micro 24V_P180
 Black Foster 48V_P207
 Black Foster Custom_P242

| | | P | CCT | I | Flux | LOR |
|---------------------------------|-----------------------|----|-------|-------|--------|-----|
| BLACK FOSTER MICRO Surface 5 | A459-20-00- NT WT | 7W | 2700K | 500mA | 775 lm | 87% |
| | A459-20-01- NT WT | 7W | 3000K | 500mA | 800 lm | 87% |
| | A459-20-02- NT WT | 7W | 4000K | 500mA | 850 lm | 87% |

III IP20 | CRI>90 | L90B10 >60.000h

MacAdam Step 3 | OPTIONS* | EXCL | 37°

| | | P | CCT | I | Flux | LOR |
|-----------------------------------|-----------------------|------|-------|-------|--------|-----|
| BLACK FOSTER MICRO Surface 2x2 | A459-30-00- NT WT | 5,6W | 2700K | 500mA | 620 lm | 87% |
| | A459-30-01- NT WT | 5,6W | 3000K | 500mA | 640 lm | 87% |
| | A459-30-02- NT WT | 5,6W | 4000K | 500mA | 680 lm | 87% |

III IP20 | CRI>90 | L90B10 >60.000h

MacAdam Step 3 | OPTIONS* | EXCL | 37°


| | | P | CCT | I | Flux | LOR |
|-----------------------------------|-----------------------|-----|-------|-------|---------|-----|
| BLACK FOSTER MICRO Surface 3x3 | A459-40-00- NT WT | 10W | 2700K | 400mA | 1170 lm | 87% |
| | A459-40-01- NT WT | 10W | 3000K | 400mA | 1200 lm | 87% |
| | A459-40-02- NT WT | 10W | 4000K | 400mA | 1300 lm | 87% |

III IP20 | CRI>90 | L90B10 >60.000h

MacAdam Step 3 | OPTIONS* | EXCL | 37°

| *DRIVER OPTIONS | Black Foster Micro Surface 5 | Black Foster Micro Surface 2x2 | Black Foster Micro Surface 3x3 |
|-----------------|------------------------------|--------------------------------|--------------------------------|
| NO DIM | 0434-00-42 1 to 2 | 0434-01-53 1 to 3 | 0434-01-54 1 |
| DALI | 0434-00-44 1 to 3 | 0434-01-54 1 to 3 | 0434-01-54 1 |

220-240 V~ | DRIVER MUST BE PLACED ON REMOTE | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT | 282



COLOUR | NT ■ | WT □ | MATERIAL | AL | ABS+PC | RAL | 312

288

BLACK FOSTER SURFACE



MORE INFO >>



MORE INFO >>




MORE INFO >>




MORE INFO >>

| | | P | CCT | I | Flux |
|---------------------------|----------------|------|-------|-------|--------|
| BLACK FOSTER Surface 1 | A320-1- ○ -10- | 2,1W | 2700K | 700mA | 190 lm |
| | A320-1- ○ -11- | 2,1W | 3000K | 700mA | 210 lm |
| | A320-1- ○ -12- | 2,1W | 4000K | 700mA | 250 lm |

220 V~ |  IP20 | CRI>90 | L90B10 >102.000h
 MacAdam Step 3 |  INCL |  UGR <19 |  38° / 19°


| | | P | CCT | I | Flux |
|---------------------------|----------------|------|-------|-------|--------|
| BLACK FOSTER Surface 2 | A320-2- ○ -10- | 4,2W | 2700K | 700mA | 380 lm |
| | A320-2- ○ -11- | 4,2W | 3000K | 700mA | 420 lm |
| | A320-2- ○ -12- | 4,2W | 4000K | 700mA | 500 lm |

220 V~ |  IP20 | CRI>90 | L90B10 >102.000h
 MacAdam Step 3 |  INCL |  UGR <19 |  38° / 19°

| | | P | CCT | I | Flux |
|---------------------------|----------------|------|-------|-------|--------|
| BLACK FOSTER Surface 3 | A320-3- ○ -10- | 6,3W | 2700K | 700mA | 570 lm |
| | A320-3- ○ -11- | 6,3W | 3000K | 700mA | 630 lm |
| | A320-3- ○ -12- | 6,3W | 4000K | 700mA | 750 lm |

220 V~ |  IP20 | CRI>90 | L90B10 >102.000h
 MacAdam Step 3 |  INCL |  UGR <19 |  38° / 19°

| | | P | CCT | I | Flux |
|---------------------------|--|-------|-------|-------|---------|
| BLACK FOSTER Surface 5 | A320-4- ○ - 0- WT NT WTMG NTMG | 10,5W | 2700K | 700mA | 950 lm |
| | A320-4- ○ - 0- -1- WT NT WTMG NTMG | 10,5W | 3000K | 700mA | 1050 lm |
| | A320-4- ○ - 0- -2- WT NT WTMG NTMG | 10,5W | 4000K | 700mA | 1250 lm |

220 V~ |  IP20 | CRI>90 | L90B10 >102.000h
 MacAdam Step 3 |  OPTIONS* |  INCL |  UGR <19 |  38° / 19°

COLOUR | WT  | NT  | WTMG  | NTMG  | MATERIAL |  AL |  ABS+PC | RAL  » 312

 » 288



MORE INFO >>





MORE INFO >>

| | | P | CCT | I | Flux |
|----------------------------|--|-----|-------|-------|---------|
| BLACK FOSTER Surface 10 | A320-5- ○ - 0- WT NT WTMG NTMG | 21W | 2700K | 700mA | 1900 lm |
| | A320-5- ○ - 0- -1- WT NT WTMG NTMG | 21W | 3000K | 700mA | 2100 lm |
| | A320-5- ○ - 0- -2- WT NT WTMG NTMG | 21W | 4000K | 700mA | 2500 lm |

220 V~ |  IP20 | CRI>90 | L90B10 >102.000h
 MacAdam Step 3 |  OPTIONS* |  INCL |  UGR <19 |  38° / 19°









| | | P | CCT | I | Flux |
|----------------------------|--|-------|-------|-------|---------|
| BLACK FOSTER Surface 15 | A320-6- ○ - 0- WT NT WTMG NTMG | 31,5W | 2700K | 700mA | 2850 lm |
| | A320-6- ○ - 0- -1- WT NT WTMG NTMG | 31,5W | 3000K | 700mA | 3150 lm |
| | A320-6- ○ - 0- -2- WT NT WTMG NTMG | 31,5W | 4000K | 700mA | 3750 lm |

220 V~ |  IP20 | CRI>90 | L90B10 >102.000h
 MacAdam Step 3 |  OPTIONS* |  INCL |  UGR <19 |  38° / 19°


| | BEAM | LOR |
|---|------|-----|
| 0 | 38° | 92% |
| 1 | 19° | 90% |

| ⊞ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING** | Exterior | Lampshade |
|-------------|---|-----------|
| WT | WT  N  | |
| NT | NT  N  | |
| WTMG | WT  MG  | |
| NTMG | NT  MG  | |

**Interior always NT.



COLOUR | WT  | NT  | WTMG  | NTMG  | MATERIAL |  AL |  ABS+PC | RAL  » 312

 » 288

BLACK FOSTER SURFACE



MORE INFO >>



MORE INFO >>

| | P | CCT | Beam | I | Flux | LOR | | |
|----------------------------------|-------------|----------------------|------|-------|------|-------|--------|-----|
| BLACK FOSTER Surface Remote 3 | A480-30-00- | NT WT NTMG WTW | 6,3W | 2700K | 38° | 700mA | 570 lm | 92% |
| | A480-30-01- | NT WT NTMG WTW | 6,3W | 3000K | 38° | 700mA | 630 lm | 92% |
| | A480-30-02- | NT WT NTMG WTW | 6,3W | 4000K | 38° | 700mA | 750 lm | 92% |
| | A480-31-00- | NT WT NTMG | 6,3W | 2700K | 19° | 700mA | 570 lm | 90% |
| | A480-31-01- | NT WT NTMG | 6,3W | 3000K | 19° | 700mA | 630 lm | 90% |
| | A480-31-02- | NT WT NTMG | 6,3W | 4000K | 19° | 700mA | 750 lm | 90% |

 IP20 | CRI>90 | L90B10 >102.000h
 







| | P | CCT | Beam | I | Flux | LOR | | |
|----------------------------------|-------------|----------------------|-------|-------|------|-------|---------|-----|
| BLACK FOSTER Surface Remote 5 | A480-40-00- | NT WT NTMG WTW | 10,5W | 2700K | 38° | 700mA | 950 lm | 92% |
| | A480-40-01- | NT WT NTMG WTW | 10,5W | 3000K | 38° | 700mA | 1050 lm | 92% |
| | A480-40-02- | NT WT NTMG WTW | 10,5W | 4000K | 38° | 700mA | 1250 lm | 92% |
| | A480-41-00- | NT WT NTMG | 10,5W | 2700K | 19° | 700mA | 950 lm | 90% |
| | A480-41-01- | NT WT NTMG | 10,5W | 3000K | 19° | 700mA | 1050 lm | 90% |
| | A480-41-02- | NT WT NTMG | 10,5W | 4000K | 19° | 700mA | 1250 lm | 90% |

 IP20 | CRI>90 | L90B10 >102.000h
 





| *DRIVER OPTIONS | Black Foster Surface Remote 3 | Black Foster Surface Remote 5 | Black Foster Surface Remote 10 | Black Foster Surface Remote 15 |
|--|----------------------------------|----------------------------------|-----------------------------------|-----------------------------------|
|  NO DIM | 0434-00-40 | 1 to 4 | 1 to 2 | 1 |
| | 0434-01-43 | 1 to 6 | 1 to 3 | 1 |
|  DALI | 0434-00-46 | 1 to 4 | 1 to 2 | 1 |
| | 0434-01-25 | 1 to 6 | 1 to 3 | 1 |

220 V~ | DRIVER MUST BE PLACED ON REMOTE | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT  » 282


| FINISHING | Exterior | Lampshade |
|-----------|--|--|
| NT | <input checked="" type="checkbox"/> NT | <input checked="" type="checkbox"/> N |
| WT | <input type="checkbox"/> WT | <input checked="" type="checkbox"/> N |
| NTMG | <input checked="" type="checkbox"/> NT | <input checked="" type="checkbox"/> MG |
| WTW | <input type="checkbox"/> WT | <input type="checkbox"/> W |

COLOUR | NT | WT | NTMG | WTW | MATERIAL | AL | ABS+PC | RAL  » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR NT, WT & NTMG COLOURS  » 288



MORE INFO >>



MORE INFO >>


| | P | CCT | Beam | I | Flux | LOR | | |
|-----------------------------------|-------------|----------------------|------|-------|------|-------|---------|-----|
| BLACK FOSTER Surface Remote 10 | A480-50-00- | NT WT NTMG WTW | 21W | 2700K | 38° | 700mA | 1900 lm | 92% |
| | A480-50-01- | NT WT NTMG WTW | 21W | 3000K | 38° | 700mA | 2100 lm | 92% |
| | A480-50-02- | NT WT NTMG WTW | 21W | 4000K | 38° | 700mA | 2500 lm | 92% |
| | A480-51-00- | NT WT NTMG | 21W | 2700K | 19° | 700mA | 1900 lm | 90% |
| | A480-51-01- | NT WT NTMG | 21W | 3000K | 19° | 700mA | 2100 lm | 90% |
| | A480-51-02- | NT WT NTMG | 21W | 4000K | 19° | 700mA | 2500 lm | 90% |

 IP20 | CRI>90 | L90B10 >102.000h
 







| | P | CCT | Beam | I | Flux | LOR | | |
|-----------------------------------|-------------|----------------------|-------|-------|------|-------|---------|-----|
| BLACK FOSTER Surface Remote 15 | A480-60-00- | NT WT NTMG WTW | 31,5W | 2700K | 38° | 700mA | 2850 lm | 92% |
| | A480-60-01- | NT WT NTMG WTW | 31,5W | 3000K | 38° | 700mA | 3150 lm | 92% |
| | A480-60-02- | NT WT NTMG WTW | 31,5W | 4000K | 38° | 700mA | 3750 lm | 92% |
| | A480-61-00- | NT WT NTMG | 31,5W | 2700K | 19° | 700mA | 2850 lm | 90% |
| | A480-61-01- | NT WT NTMG | 31,5W | 3000K | 19° | 700mA | 3150 lm | 90% |
| | A480-61-02- | NT WT NTMG | 31,5W | 4000K | 19° | 700mA | 3750 lm | 90% |

 IP20 | CRI>90 | L90B10 >102.000h
 








COLOUR | NT | WT | NTMG | WTW | MATERIAL | AL | ABS+PC | RAL  » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR NT, WT & NTMG COLOURS  » 288

SHOT LIGHT SURFACE




Extended Family
Shot Light_P.22



MORE INFO >>

| | | CCT | Beam | LOR |
|-------------------------|------------------------------------|-------|------|-----|
| SHOT LIGHT S Surface | A486-00-00- WT NT NTMG | 2700K | 18° | 89% |
| | A486-00-01- WT NT NTMG | 3000K | 18° | 89% |
| | A486-00-02- WT NT NTMG | 4000K | 18° | 89% |
| | A486-00-10- WT NT NTMG WTW | 2700K | 40° | 89% |
| | A486-00-11- WT NT NTMG WTW | 3000K | 40° | 89% |
| | A486-00-12- WT NT NTMG WTW | 4000K | 40° | 89% |

III IP20 | CRI>90 | L80B10 >60,000h



MORE INFO >>

| | | CCT | Beam | LOR |
|-------------------------|--|-------|------|-----|
| SHOT LIGHT M Surface | A396-00-10- WT NT MG MC NTMG WTW | 2700K | 38° | 86% |
| | A396-00-11- WT NT MG MC NTMG WTW | 3000K | 38° | 86% |
| | A396-00-12- WT NT MG MC NTMG WTW | 4000K | 38° | 86% |

III IP20 | CRI>90 | L90B10 >55,000h




| *DRIVER OPTIONS | P | I | CCT | Flux |
|--|----|-------|-------|--------|
| 0434-00-39 1 to 3 Shot Light S Surface | 4W | 350mA | 2700K | 500 lm |
| | | | 3000K | 520 lm |
| | | | 4000K | 560 lm |
| 0434-00-42 1 to 3 Shot Light S Surface | 6W | 500mA | 2700K | 640 lm |
| | | | 3000K | 670 lm |
| | | | 4000K | 720 lm |
| 0434-00-40 1 to 3 Shot Light S Surface | 9W | 700mA | 2700K | 870 lm |
| | | | 3000K | 910 lm |
| | | | 4000K | 970 lm |
| 0434-00-46 1 to 3 Shot Light S Surface | 9W | 700mA | 2700K | 870 lm |
| | | | 3000K | 910 lm |
| | | | 4000K | 970 lm |
| 0434-01-25 1 to 5 Shot Light S Surface | 9W | 700mA | 2700K | 870 lm |
| | | | 3000K | 910 lm |
| | | | 4000K | 970 lm |



220 V~ | DRIVER MUST BE PLACED ON REMOTE
240 V~ | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

i » 282




| FINISHING | Body | Lampshade |
|-----------|------|-----------|
| WT | WT □ | N ■ |
| NT | NT ■ | N ■ |
| NTMG | NT ■ | MG ■ |
| WTW | WT □ | W □ |

| *DRIVER OPTIONS | P | I | CCT | Flux |
|-----------------|-------|-------|-------|---------|
| 0434-00-36 | 4,5W | 140mA | 2700K | 660 lm |
| | | | 3000K | 690 lm |
| | | | 4000K | 700 lm |
| | | | 2700K | 910 lm |
| 0434-00-37 | 6,5W | 200mA | 2700K | 910 lm |
| | | | 3000K | 940 lm |
| | | | 4000K | 960 lm |
| | | | 2700K | 1470 lm |
| 0434-00-39 | 12,4W | 350mA | 2700K | 1470 lm |
| | | | 3000K | 1530 lm |
| | | | 4000K | 1550 lm |
| | | | 2700K | 1470 lm |
| 0434-00-79 | 12,4W | 350mA | 2700K | 1470 lm |
| | | | 3000K | 1530 lm |
| | | | 4000K | 1550 lm |



220 V~ | DRIVER MUST BE PLACED ON REMOTE
240 V~ | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

i » 282



| FINISHING** | Body | Lampshade |
|-------------|------|-----------|
| WT | WT □ | N ■ |
| NT | NT ■ | N ■ |
| MG | MG ■ | N ■ |
| MC | MC ■ | N ■ |
| NTMG | NT ■ | MG ■ |
| WTW | WT □ | W □ |

SHOT LIGHT SURFACE



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------------|---------------------------------------|----|-------|------|-------|--------|-----|
| SHOT LIGHT S Surface 25 | A493-0- 00-00- WT NT NTMG | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A493-0- 00-01- WT NT NTMG | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A493-0- 00-02- WT NT NTMG | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A493-0- 00-10- WT NT NTMG WTW | 6W | 2700K | 40° | 500mA | 640 lm | 89% |
| | A493-0- 00-11- WT NT NTMG WTW | 6W | 3000K | 40° | 500mA | 670 lm | 89% |
| | A493-0- 00-12- WT NT NTMG WTW | 6W | 4000K | 40° | 500mA | 720 lm | 89% |


220 V~ | IP20 | CRI>90 | L90B10 >60,000h



| Ⓞ | *OPTIONS |
|---|---------------|
| 2 | DIM DALI |
| 3 | DIM Push |
| 5 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING | Body | Lampshade |
|-----------|--|--|
| WT | WT <input type="checkbox"/> | N <input checked="" type="checkbox"/> |
| NT | NT <input checked="" type="checkbox"/> | N <input checked="" type="checkbox"/> |
| NTMG | NT <input checked="" type="checkbox"/> | MG <input checked="" type="checkbox"/> |
| WTW | WT <input type="checkbox"/> | W <input type="checkbox"/> |



SCOPE SURFACE



Extended Family
Scope Suspension_P.149



MORE INFO >>



MORE INFO >>



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------------------|---|----|-------|-------|--------|-----|
| SCOPE 35 Surface | A260-30- 00-0- WW WG WR NN NG | 7W | 2700K | 200mA | 910 lm | 89% |
| | A260-30- 00-1- WW WG WR NN NG | 7W | 3000K | 200mA | 940 lm | 89% |
| | A260-30- 00-2- WW WG WR NN NG | 7W | 4000K | 200mA | 960 lm | 89% |

220 V~ | IP20 | CRI>90 | L90B10 >55,000h




| | | P | CCT | I | Flux | LOR |
|---------------------|---|----|-------|-------|--------|-----|
| SCOPE 27 Surface | A260-20- 00-0- WW WG WR NN NG | 7W | 2700K | 200mA | 910 lm | 89% |
| | A260-20- 00-1- WW WG WR NN NG | 7W | 3000K | 200mA | 940 lm | 89% |
| | A260-20- 00-2- WW WG WR NN NG | 7W | 4000K | 200mA | 960 lm | 89% |

220 V~ | IP20 | CRI>90 | L90B10 >55,000h





| | | P | CCT | I | Flux | LOR |
|---------------------|--------------------------------------|----|-------|-------|--------|-----|
| SCOPE 21 Surface | A260-10-00- WW WG WR NN NG | 7W | 2700K | 200mA | 910 lm | 89% |
| | A260-10-01- WW WG WR NN NG | 7W | 3000K | 200mA | 940 lm | 89% |
| | A260-10-02- WW WG WR NN NG | 7W | 4000K | 200mA | 960 lm | 89% |

220 V~ | IP20 | CRI>90 | L90B10 >55,000h




SCOPE 35 SURFACE SCOPE 27 SURFACE SCOPE 21 SURFACE



| Ⓞ | *OPTIONS |
|---|---------------|
| 0 | DIM Phase cut |
| 1 | DIM Push |
| 3 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|-----|-----------------------|------|-------|------|-------|--------|-----|
| TOP | A295-00-10- WT NT | 4,5W | 2700K | 20° | 500mA | 480 lm | 92% |
| | A295-00-11- WT NT | 4,5W | 3000K | 20° | 500mA | 500 lm | 92% |
| | A295-00-12- WT NT | 4,5W | 4000K | 20° | 500mA | 515 lm | 92% |
| | A295-00-20- WT NT | 4,5W | 2700K | 30° | 500mA | 480 lm | 89% |
| | A295-00-21- WT NT | 4,5W | 3000K | 30° | 500mA | 500 lm | 89% |
| | A295-00-22- WT NT | 4,5W | 4000K | 30° | 500mA | 515 lm | 89% |
| | A295-00-30- WT NT | 4,5W | 2700K | 56° | 500mA | 480 lm | 86% |
| | A295-00-31- WT NT | 4,5W | 3000K | 56° | 500mA | 500 lm | 86% |
| | A295-00-32- WT NT | 4,5W | 4000K | 56° | 500mA | 515 lm | 86% |

220 V~ | 240 V~ | IP20 | CRI>90 | L90B10 >55.000h



OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS


TOP Beam Mixer Diffuser 0805-01-00



TOP Anti-glare Honeycomb Louver 0807-00-00 | WT | NT |




TOP High Chromatic LED ⓘ » 281



COLOUR | WT □ | NT ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312



MORE INFO >>

| | | CCT | Beam | LOR |
|----------|-----------------------|-------|------|-----|
| TOP Mini | A296-00-10- WT NT | 2700K | 20° | 92% |
| | A296-00-11- WT NT | 3000K | 20° | 92% |
| | A296-00-12- WT NT | 4000K | 20° | 92% |
| | A296-00-20- WT NT | 2700K | 30° | 89% |
| | A296-00-21- WT NT | 3000K | 30° | 89% |
| | A296-00-22- WT NT | 4000K | 30° | 89% |
| | A296-00-30- WT NT | 2700K | 56° | 86% |
| | A296-00-31- WT NT | 3000K | 56° | 86% |
| | A296-00-32- WT NT | 4000K | 56° | 86% |

IP20 | CRI>90 | L90B10 >55.000h



*DRIVER OPTIONS

| | P | I | CCT | Flux |
|--------------|------|-------|-------|--------|
| NO DIM | 4,5W | 500mA | 2700K | 480 lm |
| | | | 3000K | 500 lm |
| | | | 4000K | 515 lm |
| PUSH / 1-10V | 6,5W | 700mA | 2700K | 610 lm |
| | | | 3000K | 640 lm |
| | | | 4000K | 655 lm |
| DALI | 4,5W | 500mA | 2700K | 480 lm |
| | | | 3000K | 500 lm |
| | | | 4000K | 515 lm |
| PUSH / 1-10V | 6,5W | 700mA | 2700K | 610 lm |
| | | | 3000K | 640 lm |
| | | | 4000K | 655 lm |
| DALI | 6,5W | 700mA | 2700K | 610 lm |
| | | | 3000K | 640 lm |
| | | | 4000K | 655 lm |

220 V~ | 240 V~ | DRIVER MUST BE PLACED ON REMOTE DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

ⓘ » 282



COLOUR | WT □ | NT ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312

Ⓜ » 288

PUCK



Extended Family
Puck Recessed_P.59



MORE INFO >>

| | | P | CCT | Flux | LOR |
|--------|---------------------------------|-----|-------|--------|-----|
| PUCK M | A251-10-00- WT NT MC MG | 10W | 2700K | 780 lm | 80% |
| | A251-10-01- WT NT MC MG | 10W | 3000K | 840 lm | 80% |
| | A251-10-02- WT NT MC MG | 10W | 4000K | 880 lm | 80% |


220
240 V~ | IP20 | CRI>90 | L70B10 >50.000h



MORE INFO >>

| | | P | CCT | Flux | LOR |
|--------|---------------------------------|-----|-------|---------|-----|
| PUCK L | A251-20-00- WT NT MC MG | 15W | 2700K | 1175 lm | 80% |
| | A251-20-01- WT NT MC MG | 15W | 3000K | 1280 lm | 80% |
| | A251-20-02- WT NT MC MG | 15W | 4000K | 1330 lm | 80% |

220
240 V~ | IP20 | CRI>90 | L70B10 >50.000h



COLOUR | WT □ | NT ■ | MC ■ | MG ■ | MATERIAL | AL | OPTICAL GLASS | RAL ⓘ » 312

STRAM SURFACE



Extended Family
Stram_P.66



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-----------------|--------------------------|-------|-------|-------|---------|-----|
| STRAM Surface 1 | A246-01-10- WT NT | 10,5W | 2700K | 350mA | 1525 lm | 87% |
| | A246-01-11- WT NT | 10,5W | 3000K | 350mA | 1650 lm | 87% |
| | A246-01-12- WT NT | 10,5W | 4000K | 350mA | 1675 lm | 87% |
| STRAM Surface 2 | A246-02-10- WT NT | 15,5W | 2700K | 500mA | 2100 lm | 87% |
| | A246-02-11- WT NT | 15,5W | 3000K | 500mA | 2275 lm | 87% |
| | A246-02-12- WT NT | 15,5W | 4000K | 500mA | 2300 lm | 87% |
| STRAM Surface 3 | A246-03- ① -0- WT NT | 22W | 2700K | 700mA | 2800 lm | 87% |
| | A246-03- ① -1- WT NT | 22W | 3000K | 700mA | 3025 lm | 87% |
| | A246-03- ① -2- WT NT | 22W | 4000K | 700mA | 3075 lm | 87% |

220
240 V~ | IP20 | CRI>90 | L80B10 >60.000h




① *OPTIONS

- 1 No DIM
- 2 DIM DALI | Push

DIM PHASE CUT & OTHER DIM OPTIONS
PLEASE CONSULT

| | | P | CCT | I | Flux | LOR |
|----------------------|--------------------------|-----|-------|-------|---------|-----|
| STRAM Surface Mini 2 | A377-02-10- WT NT | 7W | 2700K | 500mA | 975 lm | 80% |
| | A377-02-11- WT NT | 7W | 3000K | 500mA | 1050 lm | 80% |
| | A377-02-12- WT NT | 7W | 4000K | 500mA | 1075 lm | 80% |
| STRAM Surface Mini 3 | A377-03- ① -0- WT NT | 10W | 2700K | 700mA | 1275 lm | 80% |
| | A377-03- ① -1- WT NT | 10W | 3000K | 700mA | 1375 lm | 80% |
| | A377-03- ① -2- WT NT | 10W | 4000K | 700mA | 1400 lm | 80% |

220
240 V~ | IP20 | CRI>90 | L80B10 >60.000h




① *OPTIONS

- 1 No DIM
- 5 DIM Phase Cut

OTHER DIM OPTIONS PLEASE CONSULT

STRAM SURFACE STRAM SURFACE MINI



COLOUR | WT □ | NT ■ | MATERIAL | AL | PMMA | RAL ⓘ » 312

PRISMATIC DIFFUSER PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS
CERTIFICATES APPLICABLE FOR STRAM SURFACE

» 288



ORBITAL SURFACE



Extended Family
Orbital_P.80



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|---------------------------------------|------------------------|------|-------|------|-------|---------|-----|
| ORBITAL Surface 1 LarK-111 | A01- Ⓞ -11-10- W N | 6,5W | 2700K | 19° | 200mA | 900 lm | 92% |
| | A01- Ⓞ -11-11- W N | 6,5W | 3000K | 19° | 200mA | 940 lm | 92% |
| | A01- Ⓞ -11-12- W N | 6,5W | 4000K | 19° | 200mA | 950 lm | 92% |
| | A01- Ⓞ -11-20- W N | 6,5W | 2700K | 40° | 200mA | 900 lm | 86% |
| | A01- Ⓞ -11-21- W N | 6,5W | 3000K | 40° | 200mA | 940 lm | 86% |
| | A01- Ⓞ -11-22- W N | 6,5W | 4000K | 40° | 200mA | 950 lm | 86% |
| | A01- Ⓞ -13-10- W N | 12W | 2700K | 19° | 350mA | 1440 lm | 92% |
| | A01- Ⓞ -13-11- W N | 12W | 3000K | 19° | 350mA | 1500 lm | 92% |
| | A01- Ⓞ -13-12- W N | 12W | 4000K | 19° | 350mA | 1520 lm | 92% |
| | A01- Ⓞ -13-20- W N | 12W | 2700K | 40° | 350mA | 1440 lm | 86% |
| | A01- Ⓞ -13-21- W N | 12W | 3000K | 40° | 350mA | 1500 lm | 86% |
| | A01- Ⓞ -13-22- W N | 12W | 4000K | 40° | 350mA | 1520 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 PHASE CUT * INCL FAST I CONNEC X35°Y35° 19°/40°



MORE INFO >>



| | | P | CCT | Beam | I | Flux | LOR |
|---------------------------------------|------------------------|----------|-------|------|-------|-------------|-----|
| ORBITAL Surface 2 LarK-111 | A01- Ⓞ -21-10- W N | 2 X 6,5W | 2700K | 19° | 200mA | 2 X 900 lm | 92% |
| | A01- Ⓞ -21-11- W N | 2 X 6,5W | 3000K | 19° | 200mA | 2 X 940 lm | 92% |
| | A01- Ⓞ -21-12- W N | 2 X 6,5W | 4000K | 19° | 200mA | 2 X 950 lm | 92% |
| | A01- Ⓞ -21-20- W N | 2 X 6,5W | 2700K | 40° | 200mA | 2 X 900 lm | 86% |
| | A01- Ⓞ -21-21- W N | 2 X 6,5W | 3000K | 40° | 200mA | 2 X 940 lm | 86% |
| | A01- Ⓞ -21-22- W N | 2 X 6,5W | 4000K | 40° | 200mA | 2 X 950 lm | 86% |
| | A01- Ⓞ -23-10- W N | 2 X 12W | 2700K | 19° | 350mA | 2 X 1440 lm | 92% |
| | A01- Ⓞ -23-11- W N | 2 X 12W | 3000K | 19° | 350mA | 2 X 1500 lm | 92% |
| | A01- Ⓞ -23-12- W N | 2 X 12W | 4000K | 19° | 350mA | 2 X 1520 lm | 92% |
| | A01- Ⓞ -23-20- W N | 2 X 12W | 2700K | 40° | 350mA | 2 X 1440 lm | 86% |
| | A01- Ⓞ -23-21- W N | 2 X 12W | 3000K | 40° | 350mA | 2 X 1500 lm | 86% |
| | A01- Ⓞ -23-22- W N | 2 X 12W | 4000K | 40° | 350mA | 2 X 1520 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 PHASE CUT * INCL FAST I CONNEC X35°Y35° 19°/40°

Ⓞ OPTIONS

- 1 LarK-111
- 2 LarK-111 Honeycomb**



LarK-111



LarK-111 Honeycomb**

COLOUR | W □ | N ■ | MATERIAL | AL | RAL ⓘ » 312

* OTHER DIM OPTIONS PLEASE CONSULT | ** AFFECTS THE LIGHTING PARAMETERS



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|---------------------------------------|------------------------|----------|-------|------|-------|-------------|-----|
| ORBITAL Surface 3 LarK-111 | A01- Ⓞ -31-10- W N | 3 X 6,5W | 2700K | 19° | 200mA | 3 X 900 lm | 92% |
| | A01- Ⓞ -31-11- W N | 3 X 6,5W | 3000K | 19° | 200mA | 3 X 940 lm | 92% |
| | A01- Ⓞ -31-12- W N | 3 X 6,5W | 4000K | 19° | 200mA | 3 X 950 lm | 92% |
| | A01- Ⓞ -31-20- W N | 3 X 6,5W | 2700K | 40° | 200mA | 3 X 900 lm | 86% |
| | A01- Ⓞ -31-21- W N | 3 X 6,5W | 3000K | 40° | 200mA | 3 X 940 lm | 86% |
| | A01- Ⓞ -31-22- W N | 3 X 6,5W | 4000K | 40° | 200mA | 3 X 950 lm | 86% |
| | A01- Ⓞ -33-10- W N | 3 X 12W | 2700K | 19° | 350mA | 3 X 1440 lm | 92% |
| | A01- Ⓞ -33-11- W N | 3 X 12W | 3000K | 19° | 350mA | 3 X 1500 lm | 92% |
| | A01- Ⓞ -33-12- W N | 3 X 12W | 4000K | 19° | 350mA | 3 X 1520 lm | 92% |
| | A01- Ⓞ -33-20- W N | 3 X 12W | 2700K | 40° | 350mA | 3 X 1440 lm | 86% |
| | A01- Ⓞ -33-21- W N | 3 X 12W | 3000K | 40° | 350mA | 3 X 1500 lm | 86% |
| | A01- Ⓞ -33-22- W N | 3 X 12W | 4000K | 40° | 350mA | 3 X 1520 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 PHASE CUT * INCL FAST I CONNEC X35°Y35° 19°/40°



MORE INFO >>



| | | P | CCT | Beam | I | Flux | LOR |
|---------------------------------------|------------------------|----------|-------|------|-------|-------------|-----|
| ORBITAL Surface 4 LarK-111 | A01- Ⓞ -41-10- W N | 4 X 6,5W | 2700K | 19° | 200mA | 4 X 900 lm | 92% |
| | A01- Ⓞ -41-11- W N | 4 X 6,5W | 3000K | 19° | 200mA | 4 X 940 lm | 92% |
| | A01- Ⓞ -41-12- W N | 4 X 6,5W | 4000K | 19° | 200mA | 4 X 950 lm | 92% |
| | A01- Ⓞ -41-20- W N | 4 X 6,5W | 2700K | 40° | 200mA | 4 X 900 lm | 86% |
| | A01- Ⓞ -41-21- W N | 4 X 6,5W | 3000K | 40° | 200mA | 4 X 940 lm | 86% |
| | A01- Ⓞ -41-22- W N | 4 X 6,5W | 4000K | 40° | 200mA | 4 X 950 lm | 86% |
| | A01- Ⓞ -43-10- W N | 4 X 12W | 2700K | 19° | 350mA | 4 X 1440 lm | 92% |
| | A01- Ⓞ -43-11- W N | 4 X 12W | 3000K | 19° | 350mA | 4 X 1500 lm | 92% |
| | A01- Ⓞ -43-12- W N | 4 X 12W | 4000K | 19° | 350mA | 4 X 1520 lm | 92% |
| | A01- Ⓞ -43-20- W N | 4 X 12W | 2700K | 40° | 350mA | 4 X 1440 lm | 86% |
| | A01- Ⓞ -43-21- W N | 4 X 12W | 3000K | 40° | 350mA | 4 X 1500 lm | 86% |
| | A01- Ⓞ -43-22- W N | 4 X 12W | 4000K | 40° | 350mA | 4 X 1520 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 PHASE CUT * INCL FAST I CONNEC X35°Y35° 19°/40°

Ⓞ OPTIONS

- 1 LarK-111
- 2 LarK-111 Honeycomb**



LarK-111



LarK-111 Honeycomb**


COLOUR | W □ | N ■ | MATERIAL | AL | RAL ⓘ » 312

* OTHER DIM OPTIONS PLEASE CONSULT | ** AFFECTS THE LIGHTING PARAMETERS

VOLA





Extended Family
Vola Suspension_P.120



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------|--------------------------|-----|-------|-------|---------|-----|
| VOLTA | A441-00- Ⓞ -0- WT NT | 19W | 2700K | 500mA | 3080 lm | 80% |
| | A441-00- Ⓞ -1- WT NT | 19W | 3000K | 500mA | 3160 lm | 80% |
| | A441-00- Ⓞ -2- WT NT | 19W | 4000K | 500mA | 3320 lm | 80% |

220 V~ | IP65 | IK10 | CRI>90 | L80B10 >60.000h



Ⓞ *OPTIONS

| | |
|---|---------------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |
| 5 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT





SKY



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------|---------------------|-----|-------|-------|---------|-----|
| SKY 2 | A195-02- Ⓞ -1- WT | 15W | 3000K | 350mA | 2450 lm | 81% |
| | A195-02- Ⓞ -2- WT | 15W | 4000K | 350mA | 2500 lm | 81% |
| SKY 3 | A195-03- Ⓞ -1- WT | 22W | 3000K | 500mA | 3450 lm | 81% |
| | A195-03- Ⓞ -2- WT | 22W | 4000K | 500mA | 3500 lm | 81% |
| SKY 4 | A195-04- Ⓞ -1- WT | 31W | 3000K | 700mA | 4700 lm | 81% |
| | A195-04- Ⓞ -2- WT | 31W | 4000K | 700mA | 4775 lm | 81% |
| SKY 5 | A195-05- Ⓞ -1- WT | 40W | 3000K | 900mA | 5825 lm | 81% |
| | A195-05- Ⓞ -2- WT | 40W | 4000K | 900mA | 5925 lm | 81% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM Push |
| 4 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

RAL ⓘ » 312

COLOUR | WT □ | MATERIAL | AL | PMMA |

Ⓞ » 288

DRUM



Extended Family
Drum Suspension_P.153



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------|--------------------------|------|-------|-------|----------|-----|
| DRUM 90 | A239-20- Ⓞ -1- WT NT | 119W | 3000K | 700mA | 16100 lm | 87% |
| | A239-20- Ⓞ -2- WT NT | 119W | 4000K | 700mA | 16350 lm | 87% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------|--------------------------|-------|-------|-------|---------|-----|
| DRUM 70 | A239-10- Ⓞ -1- WT NT | 59,5W | 3000K | 700mA | 8050 lm | 87% |
| | A239-10- Ⓞ -2- WT NT | 59,5W | 4000K | 700mA | 8175 lm | 87% |



220 V~ | IP20 | CRI>90 | L80B10 >60.000h





Ⓞ *OPTIONS

| | |
|---|-----------|
| 2 | DIM DALI |
| 3 | DIM 1-10V |

DRUM 90



DRUM 70



COLOUR | WT □ | NT ■ |

MATERIAL | AL | PMMA |

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓞ » 288


FIFTY + SURFACE



MORE INFO >>

| Ⓞ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

OTHER DIM OPTIONS PLEASE CONSULT



Extended Family
Fifty + Suspension_P.158
Fifty + Custom_P.261

| | | P | CCT | I | Flux | LOR | L |
|------------------------|--------------------------|-------|-------|--------|----------|-----|--------|
| FIFTY + Surface 100 | A445-01- Ⓞ -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 70% | 1010mm |
| | A445-01- Ⓞ -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 70% | 1010mm |
| FIFTY + Surface 150 | A445-02- Ⓞ -1- WT NT | 23,1W | 3000K | 700mA | 3420 lm | 70% | 1510mm |
| | A445-02- Ⓞ -2- WT NT | 23,1W | 4000K | 700mA | 3600 lm | 70% | 1510mm |
| FIFTY + Surface 200 | A445-03- Ⓞ -1- WT NT | 30,8W | 3000K | 700mA | 4560 lm | 70% | 2010mm |
| | A445-03- Ⓞ -2- WT NT | 30,8W | 4000K | 700mA | 4800 lm | 70% | 2010mm |
| FIFTY + Surface 300 | A445-04- Ⓞ -1- WT NT | 46,2W | 3000K | 700mA | 6840 lm | 70% | 3010mm |
| | A445-04- Ⓞ -2- WT NT | 46,2W | 4000K | 700mA | 7200 lm | 70% | 3010mm |
| FIFTY + HO Surface 100 | A445-11- Ⓞ -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 70% | 1010mm |
| | A445-11- Ⓞ -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 70% | 1010mm |
| FIFTY + HO Surface 150 | A445-12- Ⓞ -1- WT NT | 35,4W | 3000K | 1050mA | 4890 lm | 70% | 1510mm |
| | A445-12- Ⓞ -2- WT NT | 35,4W | 4000K | 1050mA | 5160 lm | 70% | 1510mm |
| FIFTY + HO Surface 200 | A445-13- Ⓞ -1- WT NT | 47,2W | 3000K | 1050mA | 6520 lm | 70% | 2010mm |
| | A445-13- Ⓞ -2- WT NT | 47,2W | 4000K | 1050mA | 6880 lm | 70% | 2010mm |
| FIFTY + HO Surface 300 | A445-14- Ⓞ -1- WT NT | 70,8W | 3000K | 1050mA | 9780 lm | 70% | 3010mm |
| | A445-14- Ⓞ -2- WT NT | 70,8W | 4000K | 1050mA | 10320 lm | 70% | 3010mm |

220 V~ | 240 | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | OPTIONS* | INCL I DIFFUSER | INCL | 104°

| | | P | CCT | I | Flux | LOR | L |
|----------------------------|--------------------------|-------|-------|--------|----------|-----|--------|
| FIFTY + UGR Surface 100 | A445-21- Ⓞ -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 47% | 1010mm |
| | A445-21- Ⓞ -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 47% | 1010mm |
| FIFTY + UGR Surface 150 | A445-22- Ⓞ -1- WT NT | 23,1W | 3000K | 700mA | 3420 lm | 47% | 1510mm |
| | A445-22- Ⓞ -2- WT NT | 23,1W | 4000K | 700mA | 3600 lm | 47% | 1510mm |
| FIFTY + UGR Surface 200 | A445-23- Ⓞ -1- WT NT | 30,8W | 3000K | 700mA | 4560 lm | 47% | 2010mm |
| | A445-23- Ⓞ -2- WT NT | 30,8W | 4000K | 700mA | 4800 lm | 47% | 2010mm |
| FIFTY + UGR Surface 300 | A445-24- Ⓞ -1- WT NT | 46,2W | 3000K | 700mA | 6840 lm | 47% | 3010mm |
| | A445-24- Ⓞ -2- WT NT | 46,2W | 4000K | 700mA | 7200 lm | 47% | 3010mm |
| FIFTY + UGR HO Surface 100 | A445-31- Ⓞ -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 47% | 1010mm |
| | A445-31- Ⓞ -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 47% | 1010mm |
| FIFTY + UGR HO Surface 150 | A445-32- Ⓞ -1- WT NT | 35,4W | 3000K | 1050mA | 4890 lm | 47% | 1510mm |
| | A445-32- Ⓞ -2- WT NT | 35,4W | 4000K | 1050mA | 5160 lm | 47% | 1510mm |
| FIFTY + UGR HO Surface 200 | A445-33- Ⓞ -1- WT NT | 47,2W | 3000K | 1050mA | 6520 lm | 47% | 2010mm |
| | A445-33- Ⓞ -2- WT NT | 47,2W | 4000K | 1050mA | 6880 lm | 47% | 2010mm |
| FIFTY + UGR HO Surface 300 | A445-34- Ⓞ -1- WT NT | 70,8W | 3000K | 1050mA | 9780 lm | 47% | 3010mm |
| | A445-34- Ⓞ -2- WT NT | 70,8W | 4000K | 1050mA | 10320 lm | 47% | 3010mm |

220 V~ | 240 | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | OPTIONS* | INCL I UGR DIFFUSER | INCL | UGR <19 | 62°

COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | RAL ⓘ » 312

Ⓞ & ⓘ » 288

FLIP SURFACE



MORE INFO >>



Extended Family
Magnetic 24V Flip_P.91
Flip Recessed_P.96
Flip 48V_P.206

| | | CCT | Beam | LOR |
|--------------|------------------------------------|-------|------|-----|
| FLIP Surface | A490-00-10- NT WT NTMG | 2700K | 18° | 89% |
| | A490-00-11- NT WT NTMG | 3000K | 18° | 89% |
| | A490-00-12- NT WT NTMG | 4000K | 18° | 89% |
| | A490-00-20- NT WT NTMG WTW | 2700K | 40° | 84% |
| | A490-00-21- NT WT NTMG WTW | 3000K | 40° | 84% |
| | A490-00-22- NT WT NTMG WTW | 4000K | 40° | 84% |


IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | EXCL | 350° | 90° | 18° / 40°

| *DRIVER OPTIONS | P | I | CCT | Flux | |
|-----------------|-----------------------------------|----|-------|-------|--------|
| NO DIM | 0434-00-42 1 to 3 Flip Surface | 6W | 500mA | 2700K | 640 lm |
| | | | | 3000K | 670 lm |
| | | | | 4000K | 720 lm |
| DALI | 0434-00-44 1 to 3 Flip Surface | 6W | 500mA | 2700K | 640 lm |
| | | | | 3000K | 670 lm |
| | | | | 4000K | 720 lm |
| DALI Push | 0434-01-24 1 to 5 Flip Surface | 6W | 500mA | 2700K | 640 lm |
| | | | | 3000K | 670 lm |
| | | | | 4000K | 720 lm |

220 V~ | 240 | DRIVER MUST BE PLACED ON REMOTE DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT ⓘ » 282

| FINISHING** | Body | Lampshade |
|-------------|------|-----------|
| NT | NT ■ | N ■ |
| WT | WT □ | N ■ |
| NTMG | NT ■ | MG ■ |
| WTW | WT □ | W □ |



COLOUR | NT ■ | WT □ | NTMG ■ | WTW □ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

** OTHER FINISHING COMBINATIONS PLEASE CONSULT Ⓞ & ⓘ » 288

FIT SURFACE




MORE INFO >>



MORE INFO >>


| | | P | CCT | Beam | I | Flux | LOR |
|-------------------|---------------------------|------|-------|------|-------|--------|-----|
| FIT 35 Surface | A345-35-10- WT NT G | 5,5W | 2700K | 20° | 500mA | 620 lm | 85% |
| | A345-35-11- WT NT G | 5,5W | 3000K | 20° | 500mA | 660 lm | 85% |
| | A345-35-12- WT NT G | 5,5W | 4000K | 20° | 500mA | 710 lm | 85% |
| | A345-35-20- WT NT G | 5,5W | 2700K | 29° | 500mA | 620 lm | 84% |
| | A345-35-21- WT NT G | 5,5W | 3000K | 29° | 500mA | 660 lm | 84% |
| | A345-35-22- WT NT G | 5,5W | 4000K | 29° | 500mA | 710 lm | 84% |
| | A345-35-30- WT NT G | 5,5W | 2700K | 36° | 500mA | 620 lm | 85% |
| | A345-35-31- WT NT G | 5,5W | 3000K | 36° | 500mA | 660 lm | 85% |
| | A345-35-32- WT NT G | 5,5W | 4000K | 36° | 500mA | 710 lm | 85% |

220 V~ | IP20 | CRI>90 | L90B10 >108.000h




| | | P | CCT | Beam | I | Flux | LOR |
|-----------------------------|------------------------------|-----|-------|------|-------|------------|-----|
| FIT 35 Surface Double | A345-4- Ⓞ -10- WT NT G | 11W | 2700K | 20° | 500mA | 2 x 620 lm | 85% |
| | A345-4- Ⓞ -11- WT NT G | 11W | 3000K | 20° | 500mA | 2 x 660 lm | 85% |
| | A345-4- Ⓞ -12- WT NT G | 11W | 4000K | 20° | 500mA | 2 x 710 lm | 85% |
| | A345-4- Ⓞ -20- WT NT G | 11W | 2700K | 29° | 500mA | 2 x 620 lm | 84% |
| | A345-4- Ⓞ -21- WT NT G | 11W | 3000K | 29° | 500mA | 2 x 660 lm | 84% |
| | A345-4- Ⓞ -22- WT NT G | 11W | 4000K | 29° | 500mA | 2 x 710 lm | 84% |
| | A345-4- Ⓞ -30- WT NT G | 11W | 2700K | 36° | 500mA | 2 x 620 lm | 85% |
| | A345-4- Ⓞ -31- WT NT G | 11W | 3000K | 36° | 500mA | 2 x 660 lm | 85% |
| | A345-4- Ⓞ -32- WT NT G | 11W | 4000K | 36° | 500mA | 2 x 710 lm | 85% |


220 V~ | IP20 | CRI>90 | L90B10 >108.000h



| Ⓞ | *OPTIONS | FINISHING | Lamp | Base | OPTIONAL ACCESSORY |
|---|---------------|-----------|-------------|------|--|
| 1 | No DIM | WT | WT □ WT □ | | FIT 35 Anti-glare Honeycomb Louver |
| 2 | DIM DALI | NT | NT ■ NT ■ | | A345-00-00 |
| 5 | DIM Phase Cut | G | G ■ NT ■ | | NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS |



COLOUR | WT □ | NT ■ | G ■ | MATERIAL | AL | PC | RAL ⓘ » 312



MORE INFO >>



MORE INFO >>


Magnetic 24V Fit_P.92
Fit Recessed_P.100

Fit 24V_P.184
Fit 48V_P.197
Fit 65 1L_P.221

Extended Family
Fit_P.228
Black Foster Fit 35_P.246
Black Foster Fit 27_P.249


| | | P | CCT | Beam | I | Flux | LOR |
|-------------------|--------------------------|-------|-------|------|-------|---------|-----|
| FIT 65 Surface | A471-0- Ⓞ -11- WT NT | 10,3W | 3000K | 18° | 300mA | 1300 lm | 90% |
| | A471-0- Ⓞ -12- WT NT | 10,3W | 4000K | 18° | 300mA | 1320 lm | 90% |
| | A471-0- Ⓞ -21- WT NT | 10,3W | 3000K | 26° | 300mA | 1300 lm | 88% |
| | A471-0- Ⓞ -22- WT NT | 10,3W | 4000K | 26° | 300mA | 1320 lm | 88% |
| | A471-0- Ⓞ -31- WT NT | 10,3W | 3000K | 36° | 300mA | 1300 lm | 84% |
| | A471-0- Ⓞ -32- WT NT | 10,3W | 4000K | 36° | 300mA | 1320 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| | | P | CCT | Beam | I | Flux | LOR |
|-------------------|--------------------------|-----|-------|------|-------|---------|-----|
| FIT 80 Surface | A472-0- Ⓞ -11- WT NT | 19W | 3000K | 19° | 550mA | 2500 lm | 90% |
| | A472-0- Ⓞ -12- WT NT | 19W | 4000K | 19° | 550mA | 2540 lm | 90% |
| | A472-0- Ⓞ -21- WT NT | 19W | 3000K | 28° | 550mA | 2500 lm | 84% |
| | A472-0- Ⓞ -22- WT NT | 19W | 4000K | 28° | 550mA | 2540 lm | 84% |
| | A472-0- Ⓞ -31- WT NT | 19W | 3000K | 37° | 550mA | 2500 lm | 85% |
| | A472-0- Ⓞ -32- WT NT | 19W | 4000K | 37° | 550mA | 2540 lm | 85% |


220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| Ⓞ | *OPTIONS | OPTIONAL ACCESSORIES |
|---|----------|---|
| 1 | No DIM | FIT 65 Anti-glare Honeycomb Louver A356-00-00 |
| 2 | DIM DALI | FIT 80 Anti-glare Honeycomb Louver A357-00-00 |

OTHER DIM OPTIONS PLEASE CONSULT

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | RAL ⓘ » 312

» 288

iO SURFACE



Magnetic 24V iO Micro_P.93
iO Micro 24V_P.183


Extended Family
iO 48V_P.202
iO_P.220



MORE INFO >>

| | | | | P | CCT | Beam | I | Flux | LOR |
|------------|-------------|---------|--|------|-------|------|-------|--------|-----|
| iO Surface | A263-00-10- | WT NT | | 4,5W | 2700K | 20° | 500mA | 485 lm | 92% |
| | A263-00-11- | WT NT | | 4,5W | 3000K | 20° | 500mA | 505 lm | 92% |
| | A263-00-12- | WT NT | | 4,5W | 4000K | 20° | 500mA | 520 lm | 92% |
| | A263-00-20- | WT NT | | 4,5W | 2700K | 30° | 500mA | 485 lm | 89% |
| | A263-00-21- | WT NT | | 4,5W | 3000K | 30° | 500mA | 505 lm | 89% |
| | A263-00-22- | WT NT | | 4,5W | 4000K | 30° | 500mA | 520 lm | 89% |
| | A263-00-30- | WT NT | | 4,5W | 2700K | 56° | 500mA | 485 lm | 86% |
| | A263-00-31- | WT NT | | 4,5W | 3000K | 56° | 500mA | 505 lm | 86% |
| | A263-00-32- | WT NT | | 4,5W | 4000K | 56° | 500mA | 520 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS


iO Beam Mixer Diffuser 0805-01-00



iO Anti-glare Honeycomb Louver 0806-00-00 | WT | NT |



iO High Chromatic LED ⓘ » 281



COLOUR | WT □ | NT ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312

ZEN TUBE SURFACE



Extended Family
Zen Tube 48V_P.203
Zen Tube_P.230



MORE INFO >>

| | | | | P | CCT | I | Flux | LOR |
|--------------------|----------------|---------|--|-----|-------|-------|---------|-----|
| ZEN TUBE Surface 1 | A284-11- Ⓞ -1- | WT NT | | 12W | 3000K | 350mA | 1640 lm | 90% |
| | A284-11- Ⓞ -2- | WT NT | | 12W | 4000K | 350mA | 1670 lm | 90% |
| ZEN TUBE Surface 2 | A284-12- Ⓞ -1- | WT NT | | 17W | 3000K | 500mA | 2220 lm | 90% |
| | A284-12- Ⓞ -2- | WT NT | | 17W | 4000K | 500mA | 2250 lm | 90% |
| ZEN TUBE Surface 3 | A284-13- Ⓞ -1- | WT NT | | 23W | 3000K | 700mA | 3190 lm | 90% |
| | A284-13- Ⓞ -2- | WT NT | | 23W | 4000K | 700mA | 3240 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



Ⓞ BEAM OPTIONS

| | |
|---|-----|
| 1 | 16° |
| 2 | 24° |
| 3 | 42° |

OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

ZEN Anti-Glare Honeycomb Louver 0702-02-00




ZEN Elliptical Refractor 0700-08-00



ZEN Beam Mixer Diffuser 0805-02-00



ZEN High Chromatic LED ⓘ » 281




COLOUR | WT □ | NT ■ |

MATERIAL | AL | GL-TRANS |

RAL ⓘ » 312

OTHER CCT PLEASE CONSULT | DIM OPTIONS PLEASE CONSULT



ALASKA_130
LOOP_132
BLACK FOSTER SUSPENSION_133
ART_134
STICK_142
HOLLY_143
SPIN_144
DUNE_146
PIPE_148
SCOPE_149
SALT_150
VOLA SUSPENSION_152
DRUM SUSPENSION_153
LINE SUSPENSION_154
SLIMGOT_157
FIFTY+ SUSPENSION_158



Extended Family
Alaska Trimless_P.60
Alaska 24V_P.181
Alaska Fancy Shape_P.238



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------|--------------------------|------|-------|-------|--------|-----|
| ALASKA | A425- 00 -0-10- N BG | 4,5W | 2700K | 500mA | 475 lm | 30% |
| | A425- 00 -0-11- N BG | 4,5W | 3000K | 500mA | 500 lm | 30% |
| | A425- 00 -0-20- N BG | 4,5W | 2700K | 500mA | 475 lm | 30% |
| | A425- 00 -0-21- N BG | 4,5W | 3000K | 500mA | 500 lm | 30% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

* OTHER DIM OPTIONS PLEASE CONSULT



CORD LENGTH - L

| | |
|---|-----|
| 0 | 2 m |
| 2 | 5 m |

OTHER LENGTH PLEASE CONSULT

FINISHING*


| | Lamp | Base |
|----|-------------|------|
| N | N ■ NT ■ | |
| BG | BG ■ NT ■ | |

BASE NOT USED WITH WIRE TRIMLESS INSTALLATION.

OPTIONAL ACCESSORIES


TRIMLESS TOOL D20 X D52mm

A478-00-01



CORD Accessory



0223-00-00- | N |




WIRE TRIMLESS Accessory

Coaxial Trimless

A023-00-03- | W | N |



COAXIAL TRIMLESS




COLOUR | N ■ | NT ■ | BG ■ | W □ | MATERIAL | AL | OPTICAL GLASS |

RAL ⓘ » 312

OTHER CCT PLEASE CONSULT | * OTHER FINISHING COMBINATIONS PLEASE CONSULT

Ⓜ » 288



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------|------------------------------|------|-------|-------|---------|-----|
| ALASKA Big | A455- 00 -0- 00 -0- N BG | 8,4W | 2700K | 500mA | 1040 lm | 37% |
| | A455- 00 -0- 00 -1- N BG | 8,4W | 3000K | 500mA | 1100 lm | 37% |

220 V~ | IP20 | CRI>90 | L90B10 >60.000h



P CCT I Flux LOR

| | | | | | | |
|---------------|------------------------------|------|-------|-------|---------|-----|
| ALASKA Big | A455- 00 -1- 00 -0- N BG | 8,4W | 2700K | 500mA | 1040 lm | 37% |
| Wire Trimless | A455- 00 -1- 00 -1- N BG | 8,4W | 3000K | 500mA | 1100 lm | 37% |

220 V~ | IP20 | CRI>90 | L90B10 >60.000h



CORD LENGTH - L

| | |
|---|-----|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

OPTIONS*

| | |
|---|---------------|
| 2 | DIM DALI |
| 5 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT



FINISHING**

| | Lamp | Base |
|----|-------------|------|
| N | N ■ NT ■ | |
| BG | BG ■ NT ■ | |

OPTIONAL ACCESSORIES



TRIMLESS TOOL D20 X D52mm

A478-00-01




CORD Accessory

0223-00-00- | N |



COAXIAL WIRE TRIMLESS



COLOUR | N ■ | BG ■ | NT ■ | MATERIAL | AL | OPTICAL GLASS |

RAL ⓘ » 312

OTHER CCT PLEASE CONSULT | ** OTHER FINISHING COMBINATIONS PLEASE CONSULT



MORE INFO >>

| *OPTIONS | |
|----------|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |


DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING ** | | |
|--------------|-------|------|
| Lamp | Cable | Base |
| N ■ | N ■ | NT ■ |
| BG ■ | N ■ | NT ■ |

| | | P | CCT | I | Flux | LOR |
|--------------------|------------------------|-------|-------|-------|---------|-----|
| LOOP | A473-10- 0-0- N BG | 26,5W | 2700K | 700mA | 2800 lm | 38% |
| | A473-10- 0-1- N BG | 26,5W | 3000K | 700mA | 3060 lm | 38% |
| LOOP Base | A473-20- 0-0- N BG | 26,5W | 2700K | 700mA | 2800 lm | 38% |
| | A473-20- 0-1- N BG | 26,5W | 3000K | 700mA | 3060 lm | 38% |
| LOOP Indirect | A474-10- 0-0- N BG | 26,5W | 2700K | 700mA | 2800 lm | 38% |
| | A474-10- 0-1- N BG | 26,5W | 3000K | 700mA | 3060 lm | 38% |
| LOOP Indirect Base | A474-20- 0-0- N BG | 26,5W | 2700K | 700mA | 2800 lm | 38% |
| | A474-20- 0-1- N BG | 26,5W | 3000K | 700mA | 3060 lm | 38% |

220 V- | IP20 | CRI>90 | L90B10 >102.000h

MacAdam Step 3 INCL OPTIONS* Ø62 110°



COLOUR | N ■ | NT ■ | BG ■ | MATERIAL | OPTICAL GLASS | OPTICAL PMMA | AL | ABS+PC |

** OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288



MORE INFO >>


| | BEAM | LOR |
|---|------|-----|
| 0 | 38° | 92% |
| 1 | 19° | 90% |

| *OPTIONS | |
|----------|--------------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |
| 5 | DIM On Board |


| FINISHING** | Exterior | Lampshade |
|-------------|-------------|-----------|
| NT | NT ■ N ■ | N ■ |
| WT | WT □ N ■ | N ■ |
| WTMG | WT □ MG ■ | MG ■ |
| NTMG | NT ■ MG ■ | MG ■ |

**Interior always NT.


MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



Extended Family
 Black Foster Micro_P10
 Black Foster_P12
 Black Foster Surface_P104
 Black Foster Micro 24V_P180
 Black Foster 48V_P207
 Black Foster Custom_P242

| | | P | CCT | I | Flux |
|------------------------------|--------------------------------------|-------|-------|-------|---------|
| BLACK FOSTER Suspension 1200 | A321-1- 0-0- WT NT WTMG NTMG | 21W | 2700K | 700mA | 1900 lm |
| | A321-1- 0-1- WT NT WTMG NTMG | 21W | 3000K | 700mA | 2100 lm |
| | A321-1- 0-2- WT NT WTMG NTMG | 21W | 4000K | 700mA | 2500 lm |
| BLACK FOSTER Suspension 1600 | A321-2- 0-0- WT NT WTMG NTMG | 31,5W | 2700K | 700mA | 2850 lm |
| | A321-2- 0-1- WT NT WTMG NTMG | 31,5W | 3000K | 700mA | 3150 lm |
| | A321-2- 0-2- WT NT WTMG NTMG | 31,5W | 4000K | 700mA | 3750 lm |

220 V- | IP20 | CRI>90 | L90B10 >102.000h

MacAdam Step 3 INCL OPTIONS* 2m FAST UGR <19 38° / 19°

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories


FEED

Mains Trimless

A023-00-01- | W | N | NO DIM On Board

Mains Thick Trimless


A023-00-02- | W | N | DALI Push




FASTENING

Steel Cable Trimless



A023-00-05- | W | N | 2 Pcs. needed





TRIMLESS TOOL D20 X D52mm A478-00-01



BLACK FOSTER SUSPENSION 1200




BLACK FOSTER SUSPENSION 1600



COLOUR | WT □ | NT ■ | WTMG ■ | NTMG ■ | W □ | N ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

TO ACHIEVE A HOMOGENEOUS LIGHT DISTRIBUTION, A DISTANCE OF 80 CM BETWEEN THE LUMINAIRE AND THE WORK SURFACE IS RECOMMENDED.

» 288




MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-----|---------------------------------|------|-------|-------|--------|-----|
| ART | A342-00-10- WT NT BC BG | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A342-00-11- WT NT BC BG | 6,3W | 3000K | 700mA | 630 lm | 92% |
| | A342-00-20- WT NT BC BG | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A342-00-21- WT NT BC BG | 6,3W | 3000K | 700mA | 630 lm | 92% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-----------------------|---------------------------------|------|-------|-------|--------|-----|
| ART Direct & Indirect | A343-00-10- WT NT BC BG | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A343-00-11- WT NT BC BG | 6,3W | 3000K | 700mA | 630 lm | 92% |
| | A343-00-20- WT NT BC BG | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A343-00-21- WT NT BC BG | 6,3W | 3000K | 700mA | 630 lm | 92% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h



* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | WT □ | NT ■ | BC ■ | BG ■ | W □ | N ■ | MATERIAL | BR | ABS +PC | RAL ⓘ » 312

OTHER CCT PLEASE CONSULT

» 288



| FINISHING** | Lamp | Base |
|-------------|------|------|
| WT | WT □ | WT □ |
| NT | NT ■ | NT ■ |
| BC | BC ■ | WT □ |
| BG | BG ■ | WT □ |


BASE NOT USED WITH WIRE TRIMLESS INSTALLATION.

OPTIONAL ACCESSORIES


WIRE TRIMLESS Accessory

Unipolar Trimless A023-00-04- | W | N |

2 Pcs. needed



TRIMLESS TOOL D20 X D52mm A478-00-01





COLOUR | WT □ | NT ■ | BC ■ | BG ■ | W □ | N ■ | MATERIAL | BR | ABS +PC | RAL ⓘ » 312

** OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288

UNIPOLAR TRIMLESS





| | | P | CCT | I | Flux | LOR |
|---------------|-------------------|-------|-------|-------|---------|-----|
| ART Modular 3 | WT NT BC BG | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | WT NT BC BG | 6,3W | 3000K | 700mA | 630 lm | 92% |
| | WT NT BC BG | 6,3W | 3000K | 700mA | 630 lm | 92% |
| ART Modular 4 | WT NT BC BG | 8,4W | 2700K | 700mA | 760 lm | 92% |
| | WT NT BC BG | 8,4W | 3000K | 700mA | 840 lm | 92% |
| | WT NT BC BG | 8,4W | 3000K | 700mA | 840 lm | 92% |
| ART Modular 5 | WT NT BC BG | 10,5W | 2700K | 700mA | 950 lm | 92% |
| | WT NT BC BG | 10,5W | 3000K | 700mA | 1050 lm | 92% |
| | WT NT BC BG | 10,5W | 3000K | 700mA | 1050 lm | 92% |

220 V~ | IP20 | CRI>90 | L90B10 > 102.000h

* DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



OPTIONAL ACCESSORIES


| FINISHING** | Lamp | Base |
|-------------|------|------|
| WT | WT | WT |
| NT | NT | NT |
| BC | BC | WT |
| BG | BG | WT |

BASE NOT USED WITH WIRE TRIMLESS INSTALLATION.


WIRE TRIMLESS Accessory

Unipolar Trimless A023-00-04- | W | N |


2 Pcs. needed



TRIMLESS TOOL D20 X D52mm A478-00-01




UNIPOLAR TRIMLESS



COLOUR | WT | NT | BC | BG | W | N | MATERIAL | BR | ABS+PC | RAL » 312

OTHER CCT PLEASE CONSULT | ** OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288



Direct & Indirect Option



ATENCIÓN

Art Modular '3' tiene una longitud de 800 mm. Las versiones preexistentes de Art miden 1000 mm de largo.

REMEMINDER

Art Modular '3' has a length of 800mm. The standard Art versions are 1000 mm long.

ATTENTION


Art Modular '3' a une longueur de 800 mm. Les versions préexistantes de l'ART mesurent 1000 mm de long.

ATTENZIONE


Art Modular '3' ha una lunghezza di 800mm. Le versioni precedenti dell'Art misurano 1000mm.

ACHTUNG


Art Modular '3' hat eine Länge von 800 mm. Die vorhandenen Versionen von Art sind 1000 mm lang.



Direct & Indirect Option



Direct & Indirect Options






MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|----------|---------------------|------|-------|-------|--------|-----|
| ART Base | A342-10-10- ○ ⊙ | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A342-10-11- ○ ⊙ | 6,3W | 3000K | 700mA | 630 lm | 92% |
| | A342-10-20- ○ ⊙ | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A342-10-21- ○ ⊙ | 6,3W | 3000K | 700mA | 630 lm | 92% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h

* OTHER DIM OPTIONS PLEASE CONSULT



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|----------------------------|---------------------|------|-------|-------|--------|-----|
| ART Base Direct & Indirect | A343-10-10- ○ ⊙ | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A343-10-11- ○ ⊙ | 6,3W | 3000K | 700mA | 630 lm | 92% |
| | A343-10-20- ○ ⊙ | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | A343-10-21- ○ ⊙ | 6,3W | 3000K | 700mA | 630 lm | 92% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h


* OTHER DIM OPTIONS PLEASE CONSULT




COLOUR | WT □ | NT ■ | BC ■ | BG ■ | MATERIAL | AL | BR | ABS+PC | RAL ⓘ » 312

OTHER CCT PLEASE CONSULT

ART BASE



ART BASE DIRECT & INDIRECT



○ LAMP FINISHING**


| | |
|----|---|
| WT | □ |
| NT | ■ |
| BC | ■ |
| BG | ■ |

⊙ BASE FINISHING**

| | |
|----|---|
| WT | □ |
| NT | ■ |

COLOUR | WT □ | NT ■ | BC ■ | BG ■ | MATERIAL | AL | BR | ABS+PC | RAL ⓘ » 312

** OTHER FINISHING COMBINATIONS PLEASE CONSULT



| | | P | CCT | I | Flux | LOR |
|--------------------|---------------------------|-------|-------|-------|---------|-----|
| ART Modular 3 Base | ○ ○ ○ | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | ○ ○ ○ | 6,3W | 3000K | 700mA | 630 lm | 92% |
| | ▬ ○ ○ ○ | 6,3W | 2700K | 700mA | 570 lm | 92% |
| | DALI* ○ ○ ○ | 6,3W | 3000K | 700mA | 630 lm | 92% |
| ART Modular 4 Base | ○ ○ ○ ○ | 8,4W | 2700K | 700mA | 760 lm | 92% |
| | ○ ○ ○ ○ | 8,4W | 3000K | 700mA | 840 lm | 92% |
| | ▬ ○ ○ ○ ○ | 8,4W | 2700K | 700mA | 760 lm | 92% |
| | DALI* ○ ○ ○ ○ | 8,4W | 3000K | 700mA | 840 lm | 92% |
| ART Modular 5 Base | ○ ○ ○ ○ ○ | 10,5W | 2700K | 700mA | 950 lm | 92% |
| | ○ ○ ○ ○ ○ | 10,5W | 3000K | 700mA | 1050 lm | 92% |
| | ▬ ○ ○ ○ ○ ○ | 10,5W | 2700K | 700mA | 950 lm | 92% |
| | DALI* ○ ○ ○ ○ ○ | 10,5W | 3000K | 700mA | 1050 lm | 92% |

220 V~ | 240 V~ | IP20 | CRI>90 | L90B10 >102.000h
 * OTHER DIM OPTIONS PLEASE CONSULT




| ○ LAMP FINISHING** | |
|--------------------|---|
| WT | □ |
| NT | ■ |
| BC | ■ |
| BG | ■ |


| ○ BASE FINISHING** | |
|--------------------|---|
| WT | □ |
| NT | ■ |

COLOUR | WT □ | NT ■ | BC ■ | BG ■ | MATERIAL | AL | BR | ABS+PC | RAL ⓘ » 312


OTHER CCT PLEASE CONSULT | ** OTHER FINISHING COMBINATIONS PLEASE CONSULT




Direct & Indirect Option



Direct & Indirect Option



Direct & Indirect Options



ATENCIÓN
 Art Modular '3' tiene una longitud de 800 mm. Las versiones preexistentes de Art miden 1000 mm de largo.


REMIINDER
 Art Modular '3' has a length of 800mm. The standard Art versions are 1000 mm long.

ATTENTION
 Art Modular '3' a une longueur de 800 mm. Les versions préexistantes de l'ART mesurent 1000 mm de long.

ATTENZIONE
 Art Modular 3 ha una lunghezza di 800mm. Le versioni precedenti dell'Art misurano 1000mm.

ACHTUNG
 Art Modular '3' hat eine Länge von 800 mm. Die vorhandenen Versionen von Art sind 1000 mm lang.

STICK




MORE INFO >>

OPTIONAL ACCESSORIES

CORD Accessory


0223-00-00- | N |



WIRE TRIMLESS Accessory


Coaxial Trimless

A023-00-03- | W | N |




TRIMLESS TOOL D20 X D52mm

A478-00-01



COAXIAL TRIMLESS



COLOUR | WT □ | NT ■ | MG ■ | W □ | N ■ |

MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

Ⓢ » 288



Extended Family
Stick 22 24V_P.185
Stick 48V_P.214
Stick Fancy Shape_P.237

| | | P | CCT | Beam | I | Flux | LOR |
|-------|------------------------------------|------|-------|------|-------|--------|-----|
| STICK | A40- ○ - ○ - ○ -10- WT NT MG | 5,6W | 2700K | 18° | 500mA | 530 lm | 84% |
| | A40- ○ - ○ - ○ -11- WT NT MG | 5,6W | 3000K | 18° | 500mA | 570 lm | 84% |
| | A40- ○ - ○ - ○ -20- WT NT MG | 5,6W | 2700K | 31° | 500mA | 530 lm | 82% |
| | A40- ○ - ○ - ○ -21- WT NT MG | 5,6W | 3000K | 31° | 500mA | 570 lm | 82% |
| | A40- ○ - ○ - ○ -30- WT NT MG | 5,6W | 2700K | 42° | 500mA | 530 lm | 84% |
| | A40- ○ - ○ - ○ -31- WT NT MG | 5,6W | 3000K | 42° | 500mA | 570 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >108.000h



| | | P | CCT | Beam | I | Flux | LOR |
|------------|------------------------------------|------|-------|------|-------|--------|-----|
| STICK Base | A50- ○ - ○ - ○ -10- WT NT MG | 5,6W | 2700K | 18° | 500mA | 530 lm | 84% |
| | A50- ○ - ○ - ○ -11- WT NT MG | 5,6W | 3000K | 18° | 500mA | 570 lm | 84% |
| | A50- ○ - ○ - ○ -20- WT NT MG | 5,6W | 2700K | 31° | 500mA | 530 lm | 82% |
| | A50- ○ - ○ - ○ -21- WT NT MG | 5,6W | 3000K | 31° | 500mA | 570 lm | 82% |
| | A50- ○ - ○ - ○ -30- WT NT MG | 5,6W | 2700K | 42° | 500mA | 530 lm | 84% |
| | A50- ○ - ○ - ○ -31- WT NT MG | 5,6W | 3000K | 42° | 500mA | 570 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >108.000h




| ○ | STICK LENGTH |
|---|-----------------|
| 4 | STICK 22 220 mm |
| 5 | STICK 44 440 mm |
| 6 | STICK 66 660 mm |

| Ⓢ | CORD LENGTH-L |
|---|---------------|
| 0 | 2 m |
| 2 | 5 m |

| Ⓢ | OPTIONS* |
|---|---------------|
| 2 | DIM DALI |
| 5 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT



| | FINISHING ** | Lamp | Base |
|----|--------------|------|------|
| WT | WT □ | WT □ | WT □ |
| NT | NT ■ | NT ■ | NT ■ |
| MG | MG ■ | MG ■ | NT ■ |

BASE NOT USED WITH WIRE TRIMLESS INSTALLATION.

COLOUR | WT □ | NT ■ | MG ■ | W □ | N ■ |

MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

Ⓢ » 288

HOLLY



MORE INFO >>



Extended Family
Holly 48V_P.215
Holly Fancy Shape_P.241

| | | P | CCT | Beam | I | Flux | LOR |
|-------|------------------------------------|------|-------|------|-------|--------|-----|
| HOLLY | A281- ○ -0-00- WT NT MC MG | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| | A281- ○ -0-01- WT NT MC MG | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| | A281- ○ -0-10- WT NT MC MG | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| | A281- ○ -0-11- WT NT MC MG | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h

* OTHER DIM OPTIONS PLEASE CONSULT



| Ⓢ | CORD LENGTH - L |
|---|-----------------|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |


| | FINISHING ** | Lamp | Base |
|----|--------------|------|------|
| WT | WT □ | WT □ | WT □ |
| NT | NT ■ | NT ■ | NT ■ |
| MC | MC ■ | NT ■ | ■ |
| MG | MG ■ | NT ■ | ■ |

BASE NOT USED WITH WIRE TRIMLESS INSTALLATION.

OPTIONAL ACCESSORIES

CORD Accessory


0223-00-00- | W | N |



WIRE TRIMLESS Accessory


Coaxial Trimless

A023-00-03- | W | N |



TRIMLESS TOOL D20 X D52mm

A478-00-01




COLOUR | WT □ | NT ■ | MC ■ | MG ■ | W □ | N ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312

Ⓢ » 288

COAXIAL TRIMLESS






MORE INFO >>

OPTIONAL ACCESSORIES

CORD Accessory


A023-00-00- | W | N |



WIRE TRIMLESS Accessory


Coaxial Trimless

A023-00-03- | W | N |




TRIMLESS TOOL D20 X D52mm

A478-00-01



COAXIAL TRIMLESS



| | | P | CCT | Beam | I | Flux | LOR |
|------|----------------------------------|------|-------|------|-------|--------|-----|
| SPIN | A222- - -00- WT NT MC MG | 6,5W | 2700K | 24° | 700mA | 600 lm | 86% |
| | A222- - -01- WT NT MC MG | 6,5W | 3000K | 24° | 700mA | 630 lm | 86% |
| | A222- - -02- WT NT MC MG | 6,5W | 4000K | 24° | 700mA | 680 lm | 86% |
| | A222- - -10- WT NT MC MG | 6,5W | 2700K | 40° | 700mA | 630 lm | 84% |
| | A222- - -11- WT NT MC MG | 6,5W | 3000K | 40° | 700mA | 630 lm | 84% |
| | A222- - -12- WT NT MC MG | 6,5W | 4000K | 40° | 700mA | 680 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >40.000h | MacAdam Step 2 | OPTIONS* | INCL | Ø50 | 24°/40°

| | | P | CCT | Beam | I | Flux | LOR |
|-----------|----------------------------------|------|-------|------|-------|--------|-----|
| SPIN Base | A221- - -00- WT NT MC MG | 6,5W | 2700K | 24° | 700mA | 600 lm | 86% |
| | A221- - -01- WT NT MC MG | 6,5W | 3000K | 24° | 700mA | 630 lm | 86% |
| | A221- - -02- WT NT MC MG | 6,5W | 4000K | 24° | 700mA | 680 lm | 86% |
| | A221- - -10- WT NT MC MG | 6,5W | 2700K | 40° | 700mA | 630 lm | 84% |
| | A221- - -11- WT NT MC MG | 6,5W | 3000K | 40° | 700mA | 630 lm | 84% |
| | A221- - -12- WT NT MC MG | 6,5W | 4000K | 40° | 700mA | 680 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >40.000h | MacAdam Step 2 | OPTIONS* | INCL | 24°/40°


| Ⓞ | CORD LENGTH - L |
|---|-----------------|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

| Ⓞ | OPTIONS* |
|---|---------------|
| 2 | DIM Phase Cut |
| 3 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING ** | Lamp | Base |
|--------------|-------------|------|
| WT | WT □ NT □ | WT □ |
| NT | NT ■ NT ■ | NT ■ |
| MC | MC ■ NT ■ | MC ■ |
| MG | MG ■ NT ■ | MG ■ |

BASE NOT USED WITH WIRE TRIMLESS INSTALLATION.



COLOUR | WT □ | NT ■ | MC ■ | MG ■ | W □ | N ■ | MATERIAL | AL | PMMA | RAL ⓘ » 312

** OTHER FINISHING COMBINATIONS PLEASE CONSULT | *** SUGGESTED FOR WIRE TRIMLESS INSTALLATION

Ⓞ ⓘ » 288




MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|-------------|----------------------|----------|-------|------|-------|------------|-----|
| SPIN 3 Base | A391- -1-00- Ⓞ Ⓞ | 3 X 6,5W | 2700K | 24° | 700mA | 3 X 600 lm | 86% |
| | A391- -1-01- Ⓞ Ⓞ | 3 X 6,5W | 3000K | 24° | 700mA | 3 X 630 lm | 86% |
| | A391- -1-02- Ⓞ Ⓞ | 3 X 6,5W | 4000K | 24° | 700mA | 3 X 680 lm | 86% |
| | A391- -1-10- Ⓞ Ⓞ | 3 X 6,5W | 2700K | 40° | 700mA | 3 X 600 lm | 84% |
| | A391- -1-11- Ⓞ Ⓞ | 3 X 6,5W | 3000K | 40° | 700mA | 3 X 630 lm | 84% |
| | A391- -1-12- Ⓞ Ⓞ | 3 X 6,5W | 4000K | 40° | 700mA | 3 X 680 lm | 84% |
| | A391- -2-00- Ⓞ Ⓞ | 3 X 6,5W | 2700K | 24° | 700mA | 3 X 600 lm | 86% |
| | A391- -2-01- Ⓞ Ⓞ | 3 X 6,5W | 3000K | 24° | 700mA | 3 X 630 lm | 86% |
| | A391- -2-02- Ⓞ Ⓞ | 3 X 6,5W | 4000K | 24° | 700mA | 3 X 680 lm | 86% |
| | A391- -2-10- Ⓞ Ⓞ | 3 X 6,5W | 2700K | 40° | 700mA | 3 X 600 lm | 84% |
| | A391- -2-11- Ⓞ Ⓞ | 3 X 6,5W | 3000K | 40° | 700mA | 3 X 630 lm | 84% |
| | A391- -2-12- Ⓞ Ⓞ | 3 X 6,5W | 4000K | 40° | 700mA | 3 X 680 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >40.000h | MacAdam Step 2 | INCL | 24°/40°

* OTHER DIM OPTIONS PLEASE CONSULT



COLOUR | WT □ | NT ■ | MC ■ | MG ■ | MATERIAL | AL | PMMA | RAL ⓘ » 312

** OTHER FINISHING COMBINATIONS PLEASE CONSULT




MORE INFO >>

| Ø | CORD LENGTH - L |
|---|-----------------|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

OPTIONAL ACCESSORIES


CORD Accessory

0223-00-00- | N |




TRIMLESS TOOL D20 X D52mm

A478-00-01



DUNE 35 + CORD ACCESSORY



| | | P | CCT | I | Flux | LOR | |
|---------|-----------|---|-----|-------|-------|--------|-----|
| DUNE 35 | PHASE CUT | A482-0- Ø -50- WT NT PG OG BE | 4W | 2700K | 120mA | 570 lm | 83% |
| | | A482-0- Ø -51- WT NT PG OG BE | 4W | 3000K | 120mA | 600 lm | 83% |
| | DALI | A482-0- Ø -20- WT NT PG OG BE | 4W | 2700K | 120mA | 570 lm | 83% |
| | | A482-0- Ø -21- WT NT PG OG BE | 4W | 3000K | 120mA | 600 lm | 83% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| | | P | CCT | I | Flux | LOR | |
|-----------------------|-----------|---|-----|-------|-------|--------|-----|
| DUNE 35 Wire Trimless | PHASE CUT | A482-2- Ø -50- WT NT PG OG BE | 4W | 2700K | 120mA | 570 lm | 83% |
| | | A482-2- Ø -51- WT NT PG OG BE | 4W | 3000K | 120mA | 600 lm | 83% |
| | DALI | A482-2- Ø -20- WT NT PG OG BE | 4W | 2700K | 120mA | 570 lm | 83% |
| | | A482-2- Ø -21- WT NT PG OG BE | 4W | 3000K | 120mA | 600 lm | 83% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h




| | | P | CCT | I | Flux | LOR | |
|--------------|--------|---|-----|-------|-------|--------|-----|
| DUNE 35 Base | NO DIM | A482-1- Ø -10- WT NT PG OG BE | 4W | 2700K | 120mA | 570 lm | 83% |
| | | A482-1- Ø -11- WT NT PG OG BE | 4W | 3000K | 120mA | 600 lm | 83% |
| | DALI | A482-1- Ø -20- WT NT PG OG BE | 4W | 2700K | 120mA | 570 lm | 83% |
| | | A482-1- Ø -21- WT NT PG OG BE | 4W | 3000K | 120mA | 600 lm | 83% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| FINISHING | Lamp | Cable | Base |
|-----------|------|-------|------|
| WT | WT □ | N ■ | NT ■ |
| NT | NT ■ | N ■ | NT ■ |
| PG | PG ■ | N ■ | NT ■ |
| OG | OG ■ | N ■ | NT ■ |
| BE | BE ■ | N ■ | NT ■ |



COLOUR | WT □ | NT ■ | PG ■ | OG ■ | BE ■ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS | OTHER CCT & DIM OPTIONS PLEASE CONSULT




MORE INFO >>

| Ø | CORD LENGTH - L |
|---|-----------------|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

OPTIONAL ACCESSORIES


CORD Accessory

0223-00-00- | N |




TRIMLESS TOOL D20 X D52mm

A478-00-01



DUNE 55 + CORD ACCESSORY



| | | P | CCT | I | Flux | LOR | |
|---------|-----------|---|-----|-------|-------|--------|-----|
| DUNE 55 | PHASE CUT | A483-0- Ø -50- WT NT PG OG BE | 5W | 2700K | 150mA | 710 lm | 84% |
| | | A483-0- Ø -51- WT NT PG OG BE | 5W | 3000K | 150mA | 735 lm | 84% |
| | DALI | A483-0- Ø -20- WT NT PG OG BE | 5W | 2700K | 150mA | 710 lm | 84% |
| | | A483-0- Ø -21- WT NT PG OG BE | 5W | 3000K | 150mA | 735 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| | | P | CCT | I | Flux | LOR | |
|-----------------------|-----------|---|-----|-------|-------|--------|-----|
| DUNE 55 Wire Trimless | PHASE CUT | A483-2- Ø -50- WT NT PG OG BE | 5W | 2700K | 150mA | 710 lm | 84% |
| | | A483-2- Ø -51- WT NT PG OG BE | 5W | 3000K | 150mA | 735 lm | 84% |
| | DALI | A483-2- Ø -20- WT NT PG OG BE | 5W | 2700K | 150mA | 710 lm | 84% |
| | | A483-2- Ø -21- WT NT PG OG BE | 5W | 3000K | 150mA | 735 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h




| | | P | CCT | I | Flux | LOR | |
|--------------|--------|---|-----|-------|-------|--------|-----|
| DUNE 55 Base | NO DIM | A483-1- Ø -10- WT NT PG OG BE | 5W | 2700K | 150mA | 710 lm | 84% |
| | | A483-1- Ø -11- WT NT PG OG BE | 5W | 3000K | 150mA | 735 lm | 84% |
| | DALI | A483-1- Ø -20- WT NT PG OG BE | 5W | 2700K | 150mA | 710 lm | 84% |
| | | A483-1- Ø -21- WT NT PG OG BE | 5W | 3000K | 150mA | 735 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| FINISHING | Lamp | Cable | Base |
|-----------|------|-------|------|
| WT | WT □ | N ■ | NT ■ |
| NT | NT ■ | N ■ | NT ■ |
| PG | PG ■ | N ■ | NT ■ |
| OG | OG ■ | N ■ | NT ■ |
| BE | BE ■ | N ■ | NT ■ |



COLOUR | WT □ | NT ■ | PG ■ | OG ■ | BE ■ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS | OTHER CCT & DIM OPTIONS PLEASE CONSULT

PIPE




MORE INFO >>

OPTIONAL ACCESSORIES

CORD Accessory


0223-00-00- | W | N |



WIRE TRIMLESS Accessory


Coaxial Trimless

A023-00-03- | W | N |




TRIMLESS TOOL D20 X D52mm

A478-00-01



COAXIAL TRIMLESS



| | P | CCT | Beam | I | Flux | LOR |
|------|---|-----|-------|-----|-------|------------|
| PIPE | A487- () - () -00- WT NT NTMG | 6W | 2700K | 18° | 500mA | 640 lm 89% |
| | A487- () - () -01- WT NT NTMG | 6W | 3000K | 18° | 500mA | 670 lm 89% |
| | A487- () - () -02- WT NT NTMG | 6W | 4000K | 18° | 500mA | 720 lm 89% |
| | A487- () - () -10- WT NT NTMG WTW | 6W | 2700K | 40° | 500mA | 640 lm 84% |
| | A487- () - () -11- WT NT NTMG WTW | 6W | 3000K | 40° | 500mA | 670 lm 84% |
| | A487- () - () -12- WT NT NTMG WTW | 6W | 4000K | 40° | 500mA | 720 lm 84% |

220 V~ | IP20 | CRI>90 | L90B10 >60.000h



| | P | CCT | Beam | I | Flux | LOR |
|-----------|---|-----|-------|-----|-------|------------|
| PIPE Base | A488- () - () -00- WT NT NTMG | 6W | 2700K | 18° | 500mA | 640 lm 89% |
| | A488- () - () -01- WT NT NTMG | 6W | 3000K | 18° | 500mA | 670 lm 89% |
| | A488- () - () -02- WT NT NTMG | 6W | 4000K | 18° | 500mA | 720 lm 89% |
| | A488- () - () -10- WT NT NTMG WTW | 6W | 2700K | 40° | 500mA | 640 lm 84% |
| | A488- () - () -11- WT NT NTMG WTW | 6W | 3000K | 40° | 500mA | 670 lm 84% |
| | A488- () - () -12- WT NT NTMG WTW | 6W | 4000K | 40° | 500mA | 720 lm 84% |

220 V~ | IP20 | CRI>90 | L90B10 >60.000h




| Ⓞ | CORD LENGTH - L |
|---|-----------------|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

| Ⓞ | *OPTIONS |
|---|---------------|
| 2 | DIM DALI |
| 5 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT

| FINISHING | Lamp | Lampshade | Base |
|-----------|--------------------|-----------|------|
| WT | WT □ N ■ WT □ | | |
| NT | NT ■ N ■ NT ■ | | |
| NTMG | NT ■ MG ■ NT ■ | | |
| WTW | WT □ W □ WT □ | | |

BASE NOT USED WITH WIRE TRIMLESS INSTALLATION.



COLOUR | WT □ | NT ■ | NTMG ■ | WTW □ | W □ | N ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR WT, NT & NTMG COLOURS

Ⓞ ⓘ » 288

SCOPE



MORE INFO >>

Extended Family
Scope Surface_P.113


| | P | CCT | I | Flux | LOR |
|----------|--------------------------------------|-----|-------|-------|------------|
| SCOPE 35 | A261-30-00- WW WG WR NN NG | 7W | 2700K | 200mA | 910 lm 89% |
| | A261-30-01- WW WG WR NN NG | 7W | 3000K | 200mA | 940 lm 89% |
| | A261-30-02- WW WG WR NN NG | 7W | 4000K | 200mA | 960 lm 89% |
| SCOPE 27 | A261-20-00- WW WG WR NN NG | 7W | 2700K | 200mA | 910 lm 89% |
| | A261-20-01- WW WG WR NN NG | 7W | 3000K | 200mA | 940 lm 89% |
| | A261-20-02- WW WG WR NN NG | 7W | 4000K | 200mA | 960 lm 89% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| | P | CCT | I | Flux | LOR |
|----------|--------------------------------------|-----|-------|-------|------------|
| SCOPE 21 | A261-10-00- WW WG WR NN NG | 7W | 2700K | 200mA | 910 lm 89% |
| | A261-10-01- WW WG WR NN NG | 7W | 3000K | 200mA | 940 lm 89% |
| | A261-10-02- WW WG WR NN NG | 7W | 4000K | 200mA | 960 lm 89% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless A023-00-01- | W | N |




FASTENING

Steel Cable Regulator Trimless


A023-00-06- | W | N |




MAINS TRIMLESS



STEEL CABLE REGULATOR TRIMLESS



SCOPE 35 SCOPE 27 SCOPE 21 TRIMLESS TOOL D20 X D52mm A478-00-01



COLOUR | WW □ | WG □ | WR □ | NN ■ | NG ■ | W □ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

OTHER FINISHING COMBINATIONS PLEASE CONSULT | COLOURS MAY AFFECT THE LIGHTING PARAMETERS



MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|-----------------------|-----------------------------|-----|-------|-------|---------|-----|
| SALT Mini A280-00-10- | WW WG WR NW NG NR | 10W | 2700K | 700mA | 1300 lm | 67% |
| A280-00-11- | WW WG WR NW NG NR | 10W | 3000K | 700mA | 1400 lm | 67% |
| A280-00-12- | WW WG WR NW NG NR | 10W | 4000K | 700mA | 1425 lm | 67% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED


Mains Trimless A023-00-01- | W | N |




FASTENING

Steel Cable Trimless A023-00-05- | W | N |


3 Pcs. needed





TRIMLESS TOOL D20 X D52mm A478-00-01



MAINS TRIMLESS



STEEL CABLE TRIMLESS



COLOUR | WW □ | WG □ | WR □ | NW □ | NG □ | NR □ | MATERIAL | AL | PMMA | RAL ⓘ » 312

COLOUR | W □ | N □ | COLOURS MAY AFFECT THE LIGHTING PARAMETERS ⓘ » 288



MORE INFO >>

| | P | CCT | I | Flux | LOR | |
|-----------------------|-----------------------------|-------|-------|--------|---------|-----|
| SALT 3 A220-03- 1 -0- | WW WG WR NW NG NR | 22W | 2700K | 700mA | 2800 lm | 79% |
| A220-03- 1 -1- | WW WG WR NW NG NR | 22W | 3000K | 700mA | 3025 lm | 79% |
| A220-03- 1 -2- | WW WG WR NW NG NR | 22W | 4000K | 700mA | 3075 lm | 79% |
| SALT 4 A220-04- Ⓞ -1- | WW WG WR NW NG NR | 27W | 3000K | 700mA | 4100 lm | 79% |
| A220-04- Ⓞ -2- | WW WG WR NW NG NR | 27W | 4000K | 700mA | 4175 lm | 79% |
| SALT 5 A220-05- Ⓞ -1- | WW WG WR NW NG NR | 35W | 3000K | 900mA | 5125 lm | 79% |
| A220-05- Ⓞ -2- | WW WG WR NW NG NR | 35W | 4000K | 900mA | 5225 lm | 79% |
| SALT 6 A220-06- Ⓞ -1- | WW WG WR NW NG NR | 47,5W | 3000K | 1200mA | 6550 lm | 79% |
| A220-06- Ⓞ -2- | WW WG WR NW NG NR | 47,5W | 4000K | 1200mA | 6650 lm | 79% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



Ⓞ *OPTIONS

2 DIM Push

4 DIM DALI

DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless

A023-00-01- | W | N | NO DIM

Mains Thick Trimless

A023-00-02- | W | N | DIM





FASTENING

Steel Cable Trimless


A023-00-05- | W | N | 3 Pcs. needed



TRIMLESS TOOL D20 X D52mm A478-00-01



MAINS THICK TRIMLESS



COLOUR | WW □ | WG □ | WR □ | NW □ | NG □ | NR □ | MATERIAL | AL | PMMA | RAL ⓘ » 312

COLOUR | W □ | N □ | COLOURS MAY AFFECT THE LIGHTING PARAMETERS ⓘ » 288

VOLA SUSPENSION

Extended Family
Vola_P.120



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------------|-------------------------|-----|-------|-------|---------|-----|
| VOLTA Suspension | A442-00- 0-0- WT NT | 19W | 2700K | 500mA | 3080 lm | 80% |
| | A442-00- 0-1- WT NT | 19W | 3000K | 500mA | 3160 lm | 80% |
| | A442-00- 0-2- WT NT | 19W | 4000K | 500mA | 3320 lm | 80% |

220 V~ | IP20 | IK10 | CRI>90 | L80B10 >60.000h



| Ⓞ | *OPTIONS |
|---|---------------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |
| 5 | DIM Phase Cut |

OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Trimless

A023-00-01- | W | N | NO DIM

Mains Thick Trimless

A023-00-02- | W | N | DIM




FASTENING

Steel Cable Trimless

A023-00-05- | W | N | 3 Pcs. needed



TRIMLESS TOOL D20 X D52mm A478-00-01




COLOUR | WT □ | NT ■ | W □ | N ■ |

MATERIAL | AL | PC |


RAL ⓘ » 312

Ⓞ » 288



MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



COLOURS MAY AFFECT THE LIGHTING PARAMETERS

DRUM SUSPENSION

Extended Family
Drum_P.121



MORE INFO >>



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------------------|-------------------------|------|-------|-------|----------|-----|
| DRUM 90 Suspension | A358-20- 0-1- WT NT | 119W | 3000K | 700mA | 16100 lm | 87% |
| | A358-20- 0-2- WT NT | 119W | 4000K | 700mA | 16350 lm | 87% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



| | | P | CCT | I | Flux | LOR |
|--------------------|-------------------------|-------|-------|-------|---------|-----|
| DRUM 70 Suspension | A358-10- 0-1- WT NT | 59,5W | 3000K | 700mA | 8050 lm | 87% |
| | A358-10- 0-2- WT NT | 59,5W | 4000K | 700mA | 8175 lm | 87% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



| Ⓞ | *OPTIONS |
|---|------------|
| 2 | DIM DALI |
| 3 | DIM 1-10 V |


OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Mains Thick Trimless


A023-00-02- | W | N |




FASTENING

Steel Cable Trimless



A023-00-05- | W | N | 4 Pcs. needed





TRIMLESS TOOL D20 X D52mm A478-00-01



DRUM 90 SUSPENSION



DRUM 70 SUSPENSION



COLOUR | WT □ | NT ■ | W □ | N ■ |

MATERIAL | AL | PMMA |

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

LINE SUSPENSION



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------------------|-------------------------|-------|-------|--------|---------|-----|
| LINE Suspension 1500 | A436-10- 0-0- WT NT | 31,5W | 2700K | 1050mA | 4500 lm | 61% |
| | A436-10- 0-1- WT NT | 31,5W | 3000K | 1050mA | 4800 lm | 61% |
| | A436-10- 0-2- WT NT | 31,5W | 4000K | 1050mA | 4950 lm | 61% |
| LINE Suspension 2000 | A436-20- 0-0- WT NT | 42W | 2700K | 1400mA | 6000 lm | 61% |
| | A436-20- 0-1- WT NT | 42W | 3000K | 1400mA | 6400 lm | 61% |
| | A436-20- 0-2- WT NT | 42W | 4000K | 1400mA | 6600 lm | 61% |

220 V- | 240 V- | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | INCL | OPTIONS* | 2 m | FAST | Ø62 | 100°

| | | P | CCT | I | Flux | LOR |
|------------------------------|-------------------------|-------|-------|--------|---------|-----|
| LINE Suspension 1500 Base | A436-11- 0-0- WT NT | 31,5W | 2700K | 1050mA | 4500 lm | 61% |
| | A436-11- 0-1- WT NT | 31,5W | 3000K | 1050mA | 4800 lm | 61% |
| | A436-11- 0-2- WT NT | 31,5W | 4000K | 1050mA | 4950 lm | 61% |
| LINE Suspension 2000 Base | A436-21- 0-0- WT NT | 42W | 2700K | 1400mA | 6000 lm | 61% |
| | A436-21- 0-1- WT NT | 42W | 3000K | 1400mA | 6400 lm | 61% |
| | A436-21- 0-2- WT NT | 42W | 4000K | 1400mA | 6600 lm | 61% |

220 V- | 240 V- | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | INCL | OPTIONS* | 2 m | FAST | 100°

| | | P | CCT | I | Flux Up | Flux Down | LOR |
|---|-------------------------|-----|-------|--------|---------|-----------|-----|
| LINE Suspension Direct & Indirect 1500 | A437-10- 0-0- WT NT | 35W | 2700K | 1200mA | 2100 lm | 3120 lm | 61% |
| | A437-10- 0-1- WT NT | 35W | 3000K | 1200mA | 2140 lm | 3210 lm | 61% |
| | A437-10- 0-2- WT NT | 35W | 4000K | 1200mA | 2250 lm | 3360 lm | 61% |
| LINE Suspension Direct & Indirect 2000 | A437-20- 0-0- WT NT | 41W | 2700K | 1400mA | 2030 lm | 4060 lm | 61% |
| | A437-20- 0-1- WT NT | 41W | 3000K | 1400mA | 2080 lm | 4160 lm | 61% |
| | A437-20- 0-2- WT NT | 41W | 4000K | 1400mA | 2180 lm | 4370 lm | 61% |

220 V- | 240 V- | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | INCL | OPTIONS* | 2 m | FAST | Ø62 | 100°

| | | P | CCT | I | Flux Up | Flux Down | LOR |
|---|-------------------------|-----|-------|--------|---------|-----------|-----|
| LINE Suspension Direct & Indirect 1500 Base | A437-11- 0-0- WT NT | 35W | 2700K | 1200mA | 2100 lm | 3120 lm | 61% |
| | A437-11- 0-1- WT NT | 35W | 3000K | 1200mA | 2140 lm | 3210 lm | 61% |
| | A437-11- 0-2- WT NT | 35W | 4000K | 1200mA | 2250 lm | 3360 lm | 61% |
| LINE Suspension Direct & Indirect 2000 Base | A437-21- 0-0- WT NT | 41W | 2700K | 1400mA | 2030 lm | 4060 lm | 61% |
| | A437-21- 0-1- WT NT | 41W | 3000K | 1400mA | 2080 lm | 4160 lm | 61% |
| | A437-21- 0-2- WT NT | 41W | 4000K | 1400mA | 2180 lm | 4370 lm | 61% |

220 V- | 240 V- | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | INCL | OPTIONS* | 2 m | FAST | 100°

Ⓞ *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |









COLOUR | WT □ | NT ■ | W □ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓞ » 288



Extended Family
Line Micro 24V_P.183
Line 48V_P.209




OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Coaxial Trimless


A023-00-03- | W | N |



FASTENING


Steel Cable Trimless

A023-00-05- | W | N |




TRIMLESS TOOL D20 X D52mm


A478-00-01



COAXIAL TRIMLESS



STEEL CABLE TRIMLESS




COLOUR | WT □ | NT ■ | W □ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓞ » 288

LINE SUSPENSION



MORE INFO >>



OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories

FEED

Coaxial Trimless


A023-00-03- | W | N |



FASTENING


Steel Cable Trimless

A023-00-05- | W | N |




TRIMLESS TOOL D20 X D52mm


A478-00-01



COAXIAL TRIMLESS



STEEL CABLE TRIMLESS



| | | P | CCT | I | Flux | LOR |
|----------------------------|--------------------------|-------|-------|-------|---------|-----|
| LINE Micro Suspension 1400 | A438-10- Ⓞ -0- WT NT | 13,5W | 2700K | 350mA | 2160 lm | 66% |
| | A438-10- Ⓞ -1- WT NT | 13,5W | 3000K | 350mA | 2200 lm | 66% |
| LINE Micro Suspension 2000 | A438-20- Ⓞ -0- WT NT | 18W | 2700K | 700mA | 2860 lm | 66% |
| | A438-20- Ⓞ -1- WT NT | 18W | 3000K | 700mA | 3000 lm | 66% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h





| | | P | CCT | I | Flux | LOR |
|---------------------------------|--------------------------|-------|-------|-------|---------|-----|
| LINE Micro Suspension 1400 Base | A438-11- Ⓞ -0- WT NT | 13,5W | 2700K | 350mA | 2160 lm | 66% |
| | A438-11- Ⓞ -1- WT NT | 13,5W | 3000K | 350mA | 2200 lm | 66% |
| LINE Micro Suspension 2000 Base | A438-21- Ⓞ -0- WT NT | 18W | 2700K | 700mA | 2860 lm | 66% |
| | A438-21- Ⓞ -1- WT NT | 18W | 3000K | 700mA | 3000 lm | 66% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



*OPTIONS

- 1 No DIM
- 2 DIM DALI
- 3 DIM Push




COLOUR | WT □ | NT ■ | W □ | N ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

SLIMGOT



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------|--------------------------|-------|-------|-------|---------|-----|
| SLIMGOT 120 | A203-1- Ⓞ -01- WT NT | 14,8W | 3000K | 500mA | 2360 lm | 85% |
| | A203-1- Ⓞ -02- WT NT | 14,8W | 4000K | 500mA | 2400 lm | 85% |
| SLIMGOT 150 | A203-2- Ⓞ -01- WT NT | 21W | 3000K | 700mA | 3300 lm | 85% |
| | A203-2- Ⓞ -02- WT NT | 21W | 4000K | 700mA | 3350 lm | 85% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



*OPTIONS



- 1 No DIM
- 2 DIM DALI / Push

OPTIONAL ACCESSORIES




WIRE TRIMLESS Accessory

Coaxial Trimless A023-00-03- | W | N |

Feeding: Only 1 piece needed. Fasteners not available



TRIMLESS TOOL D20 X D52mm A478-00-01



COLOUR | WT □ | NT ■ | W □ | N ■ |

MATERIAL | AL | PMMA |


RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

FIFTY + SUSPENSION



Extended Family
Fifty + Surface_P.122
Fifty + Custom_P.261



MORE INFO >>

| Ⓞ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

| | | P | CCT | I | Flux | LOR | L |
|------------------------------|--------------------------|-------|-------|--------|----------|-----|--------|
| FIFTY + Suspension 100 | A446-01- Ⓞ -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 70% | 1010mm |
| | A446-01- Ⓞ -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 70% | 1010mm |
| FIFTY + Suspension 150 | A446-02- Ⓞ -1- WT NT | 23,1W | 3000K | 700mA | 3420 lm | 70% | 1510mm |
| | A446-02- Ⓞ -2- WT NT | 23,1W | 4000K | 700mA | 3600 lm | 70% | 1510mm |
| FIFTY + Suspension 200 | A446-03- Ⓞ -1- WT NT | 30,8W | 3000K | 700mA | 4560 lm | 70% | 2010mm |
| | A446-03- Ⓞ -2- WT NT | 30,8W | 4000K | 700mA | 4800 lm | 70% | 2010mm |
| FIFTY + Suspension 300 | A446-04- Ⓞ -1- WT NT | 46,2W | 3000K | 700mA | 6840 lm | 70% | 3010mm |
| | A446-04- Ⓞ -2- WT NT | 46,2W | 4000K | 700mA | 7200 lm | 70% | 3010mm |
| FIFTY + HO Suspension 100 | A446-11- Ⓞ -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 70% | 1010mm |
| | A446-11- Ⓞ -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 70% | 1010mm |
| FIFTY + HO Suspension 150 | A446-12- Ⓞ -1- WT NT | 35,4W | 3000K | 1050mA | 4890 lm | 70% | 1510mm |
| | A446-12- Ⓞ -2- WT NT | 35,4W | 4000K | 1050mA | 5160 lm | 70% | 1510mm |
| FIFTY + HO Suspension 200 | A446-13- Ⓞ -1- WT NT | 47,2W | 3000K | 1050mA | 6520 lm | 70% | 2010mm |
| | A446-13- Ⓞ -2- WT NT | 47,2W | 4000K | 1050mA | 6880 lm | 70% | 2010mm |
| FIFTY + HO Suspension 300 | A446-14- Ⓞ -1- WT NT | 70,8W | 3000K | 1050mA | 9780 lm | 70% | 3010mm |
| | A446-14- Ⓞ -2- WT NT | 70,8W | 4000K | 1050mA | 10320 lm | 70% | 3010mm |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories


FEED

Mains Trimless

A023-00-01- | W | N | NO DIM

Mains Thick Trimless

A023-00-02- | W | N | DALI | Push




FASTENING

Steel Cable Trimless**

A023-00-05- | W | N | 2 Pcs. needed



TRIMLESS TOOL D20 X D52mm A478-00-01



COLOUR | WT □ | NT ■ | W □ | N ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312


** AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

Ⓞ » 288



MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



MORE INFO >>

| Ⓞ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

| | | P | CCT | I | Flux | LOR | L |
|----------------------------------|--------------------------|-------|-------|--------|----------|-----|--------|
| FIFTY + UGR Suspension 100 | A446-21- Ⓞ -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 47% | 1010mm |
| | A446-21- Ⓞ -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 47% | 1010mm |
| FIFTY + UGR Suspension 150 | A446-22- Ⓞ -1- WT NT | 23,1W | 3000K | 700mA | 3420 lm | 47% | 1510mm |
| | A446-22- Ⓞ -2- WT NT | 23,1W | 4000K | 700mA | 3600 lm | 47% | 1510mm |
| FIFTY + UGR Suspension 200 | A446-23- Ⓞ -1- WT NT | 30,8W | 3000K | 700mA | 4560 lm | 47% | 2010mm |
| | A446-23- Ⓞ -2- WT NT | 30,8W | 4000K | 700mA | 4800 lm | 47% | 2010mm |
| FIFTY + UGR Suspension 300 | A446-24- Ⓞ -1- WT NT | 46,2W | 3000K | 700mA | 6840 lm | 47% | 3010mm |
| | A446-24- Ⓞ -2- WT NT | 46,2W | 4000K | 700mA | 7200 lm | 47% | 3010mm |
| FIFTY + UGR HO Suspension 100 | A446-31- Ⓞ -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 47% | 1010mm |
| | A446-31- Ⓞ -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 47% | 1010mm |
| FIFTY + UGR HO Suspension 150 | A446-32- Ⓞ -1- WT NT | 35,4W | 3000K | 1050mA | 4890 lm | 47% | 1510mm |
| | A446-32- Ⓞ -2- WT NT | 35,4W | 4000K | 1050mA | 5160 lm | 47% | 1510mm |
| FIFTY + UGR HO Suspension 200 | A446-33- Ⓞ -1- WT NT | 47,2W | 3000K | 1050mA | 6520 lm | 47% | 2010mm |
| | A446-33- Ⓞ -2- WT NT | 47,2W | 4000K | 1050mA | 6880 lm | 47% | 2010mm |
| FIFTY + UGR HO Suspension 300 | A446-34- Ⓞ -1- WT NT | 70,8W | 3000K | 1050mA | 9780 lm | 47% | 3010mm |
| | A446-34- Ⓞ -2- WT NT | 70,8W | 4000K | 1050mA | 10320 lm | 47% | 3010mm |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories


FEED

Mains Trimless

A023-00-01- | W | N | NO DIM

Mains Thick Trimless

A023-00-02- | W | N | DALI | Push





FASTENING

Steel Cable Trimless**

A023-00-05- | W | N | 2 Pcs. needed



TRIMLESS TOOL D20 X D52mm A478-00-01



COLOUR | WT □ | NT ■ | W □ | N ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312

** AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

Ⓞ » 288

SUSPENSION

STANDUP_162

UP_163

YORU_164

LIP_165

AURAE_165

REC_166

DREAM_169

RHINO_170

WALLY_171

WALL, FLOOR & PORTABLE




STANDUP




MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------|-----------------------|-----|-------|--------|---------|-----|
| STANDUP | A494-00-00- NT WT | 27W | 2700K | 1050mA | 4210 lm | 66% |
| | A494-00-01- NT WT | 27W | 3000K | 1050mA | 4320 lm | 66% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



18




COLOUR | NT ■ | WT □ |

MATERIAL | AL | PC |

RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS


UP



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|----|-----------------------|-----|-------|-------|---------|-----|
| UP | A402-00-00- WT NT | 30W | 2700K | 900mA | 3725 lm | 76% |
| | A402-00-01- WT NT | 30W | 3000K | 900mA | 3875 lm | 76% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



COLOUR | WT □ | NT ■ |

MATERIAL | AL | FE |

RAL ⓘ » 312

YORU



Extended Family
Yoru Spike_P.267



MORE INFO >>


| | | P | CCT | Flux | LOR |
|------|---|------|-------|--------|-----|
| YORU | A456-00-00- WT NT PG LG SP OX | 2,6W | 2700K | 400 lm | 84% |

IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | DIM | LI-ION Battery | USB-C Connect | 5V 1.5A EXCL | 100°

ACCESSORY

| | |
|-----------------------|------------|
| Universal USB Charger | 0434-01-65 |
|-----------------------|------------|



COLOUR | WT | NT | PG | LG | SP | OX | MATERIAL | AL | PC | RAL » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

LIP



MORE INFO >>




| ⓪ | *OPTIONS |
|---|-----------------|
| 0 | No DIM |
| 1 | DIM DALI Push |

| | | P | CCT | I | Flux | LOR |
|-----|------------------------|-----|-------|-------|---------|-----|
| LIP | A288-00-⓪-0- WT NT | 24W | 2700K | 700mA | 2970 lm | 86% |
| | A288-00-⓪-1- WT NT | 24W | 3000K | 700mA | 3210 lm | 86% |
| | A288-00-⓪-2- WT NT | 24W | 4000K | 700mA | 3270 lm | 86% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | OPTIONS* | INCL | 100°



AURAE




MORE INFO >>



| | | P | CCT | I | Flux | LOR |
|---------|-----------------------|-------|-------|-------|---------|-----|
| AURAE 1 | A439-01-00- WT NT | 13W | 2700K | 400mA | 1850 lm | 77% |
| | A439-01-01- WT NT | 13W | 3000K | 400mA | 1900 lm | 77% |
| AURAE 2 | A439-02-00- WT NT | 23,5W | 2700K | 700mA | 3040 lm | 77% |
| | A439-02-01- WT NT | 23,5W | 3000K | 700mA | 3120 lm | 77% |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | INCL | 100°



COLOUR | WT | NT | MATERIAL | AL | PMMA | RAL » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS



MORE INFO >>


| | | P | CCT | I | Flux | LOR |
|-----|-------------------------------|-------|-------|-------|---------|-----|
| REC | A256-00- ① -0- WT NT PR | 39,5W | 2700K | 400mA | 5200 lm | 85% |
| | A256-00- ① -1- WT NT PR | 39,5W | 3000K | 400mA | 5625 lm | 85% |
| | A256-00- ① -2- WT NT PR | 39,5W | 4000K | 400mA | 5725 lm | 85% |

220-240 V~ | IP20 | CRI>90 | L80B10 >60.000h



① *OPTIONS

| | |
|---|-----------------|
| 1 | No DIM |
| 2 | DIM DALI Push |



MORE INFO >>



| | | P | CCT | I | Flux | LOR |
|----------|-------------------------------|-----|-------|-------|---------|-----|
| REC Mini | A308-00- ① -0- WT NT PR | 20W | 2700K | 700mA | 2450 lm | 75% |
| | A308-00- ① -1- WT NT PR | 20W | 3000K | 700mA | 2650 lm | 75% |
| | A308-00- ① -2- WT NT PR | 20W | 4000K | 700mA | 2700 lm | 75% |

220-240 V~ | IP20 | CRI>90 | L80B10 >60.000h



① *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |



COLOUR | WT □ | NT ■ | PR ■■ |

MATERIAL | AL | PMMA |

RAL ⓘ » 312

PR: PRIMER COATING FINISHING
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓜ » 288



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------------------|-------------------------------|-----------|-------|-----------|-------------|-----|
| REC Double | A309-00- ① -0- WT NT PR | 29,5W | 2700K | 900mA | 4150 lm | 76% |
| | A309-00- ① -1- WT NT PR | 29,5W | 3000K | 900mA | 4500 lm | 76% |
| | A309-00- ① -2- WT NT PR | 29,5W | 4000K | 900mA | 4560 lm | 76% |
| REC Double Engine | A309-01- ① -0- WT NT PR | 2 x 14,7W | 2700K | 2 x 450mA | 2 x 2075 lm | 76% |
| | A309-01- ① -1- WT NT PR | 2 x 14,7W | 3000K | 2 x 450mA | 2 x 2250 lm | 76% |
| | A309-01- ① -2- WT NT PR | 2 x 14,7W | 4000K | 2 x 450mA | 2 x 2280 lm | 76% |

220-240 V~ | IP20 | CRI>90 | L80B10 >60.000h



① *OPTIONS

| | |
|---|-----------------|
| 1 | No DIM |
| 2 | DIM DALI Push |



MORE INFO >>



| | | P | CCT | I | Flux | LOR |
|-----------------|-------------------------------|-------|-------|-------|---------|-----|
| REC Double Mini | A310-00- ① -0- WT NT PR | 16,5W | 2700K | 500mA | 2300 lm | 72% |
| | A310-00- ① -1- WT NT PR | 16,5W | 3000K | 500mA | 2500 lm | 72% |
| | A310-00- ① -2- WT NT PR | 16,5W | 4000K | 500mA | 2530 lm | 72% |

220-240 V~ | IP20 | CRI>90 | L80B10 >60.000h



① *OPTIONS

| | |
|---|-----------------|
| 1 | No DIM |
| 2 | DIM DALI Push |



COLOUR | WT □ | NT ■ | PR ■■ |

MATERIAL | AL | PMMA |

RAL ⓘ » 312


PR: PRIMER COATING FINISHING
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

Ⓜ » 288

REC



MORE INFO >>



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|----------|--------------------------------|-----|-------|-------|---------|-----|
| REC Slim | A457-00- 00 -0- WT NT PR | 27W | 2700K | 700mA | 3700 lm | 86% |
| | A457-00- 00 -1- WT NT PR | 27W | 3000K | 700mA | 3800 lm | 86% |
| | A457-00- 00 -2- WT NT PR | 27W | 4000K | 700mA | 4000 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >60.000h



*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

| | | CCT | LOR |
|-----------|----------------------------|-------|-----|
| REC Micro | A461-00-00- WT NT PR | 2700K | 79% |
| | A461-00-01- WT NT PR | 3000K | 79% |
| | A461-00-02- WT NT PR | 4000K | 79% |

IP20 | CRI>90 | L90B10 >60.000h




** DRIVER OPTIONS

| | P | I | CCT | Flux |
|--------------------------------|-------|-------|-------|---------|
| 0434-00-40 1 to 2 Rec Micro | 12,8W | 700mA | 2700K | 1465 lm |
| | | | 3000K | 1560 lm |
| | | | 4000K | 1650 lm |
| 0434-01-43 1 to 3 Rec Micro | 12,8W | 700mA | 2700K | 1465 lm |
| | | | 3000K | 1560 lm |
| | | | 4000K | 1650 lm |
| 0434-00-46 1 to 2 Rec Micro | 12,8W | 700mA | 2700K | 1465 lm |
| | | | 3000K | 1560 lm |
| | | | 4000K | 1650 lm |
| 0434-01-25 1 to 3 Rec Micro | 12,8W | 700mA | 2700K | 1465 lm |
| | | | 3000K | 1560 lm |
| | | | 4000K | 1650 lm |

220 V~ | DRIVER MUST BE PLACED ON REMOTE
240 V~ | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

» 282



COLOUR | WT | NT | PR


MATERIAL | AL | PMMA

RAL » 312


PR: PRIMER COATING FINISHING
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

» 288

DREAM



MORE INFO >>



MORE INFO >>





| | | P | CCT | I | Flux | LOR |
|-------|-------------------------|------|-------|-------|--------|-----|
| DREAM | A279-00-00- W R N | 2,1W | 2700K | 700mA | 195 lm | 94% |
| | A279-00-01- W R N | 2,1W | 3000K | 700mA | 215 lm | 94% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h



| | | P | CCT | I | Flux | LOR |
|----------------|-------------------------|------|-------|-------|--------|-----|
| DREAM Recessed | A279-00-10- W R N | 2,1W | 2700K | 700mA | 195 lm | 94% |
| | A279-00-11- W R N | 2,1W | 3000K | 700mA | 215 lm | 94% |

220 V~ | IP20 | CRI>90 | L90B10 >102.000h



COLOUR | W | R | N

MATERIAL | AL | SILICONE

RAL » 312

RHINO



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------|-----------------------|----|-------|-------|--------|-----|
| RHINO | A351-00-10- WT NT | 2W | 2700K | 700mA | 190 lm | 90% |
| | A351-00-11- WT NT | 2W | 3000K | 700mA | 205 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 >102,000h



CCT LOR

| | | | | | | |
|------------------|-----------------------|--|-------|--|--|-----|
| RHINO w/o Driver | A351-00-00- WT NT | | 2700K | | | 90% |
| | A351-00-01- WT NT | | 3000K | | | 90% |

III IP20 | CRI>90 | L90B10 >102,000h



| *DRIVER OPTIONS | P | I | CCT | Flux |
|--|----|--------|-------|--------|
| NO DIM 0434-00-39 1 to 12 Rhino | 1W | 350mA | 2700K | 105 lm |
| | | | 3000K | 115 lm |
| 0434-00-40 1 to 12 Rhino | 2W | 700mA | 2700K | 190 lm |
| | | | 3000K | 205 lm |
| 0434-00-41 1 to 11 Rhino | 3W | 1050mA | 2700K | 255 lm |
| | | | 3000K | 280 lm |
| 0434-01-23 1 to 20 Rhino | 1W | 350mA | 2700K | 105 lm |
| | | | 3000K | 115 lm |
| 0434-01-25 1 to 20 Rhino | 2W | 700mA | 2700K | 190 lm |
| | | | 3000K | 205 lm |
| DALI PUSH 0434-01-26 1 to 16 Rhino | 3W | 1050mA | 2700K | 255 lm |
| | | | 3000K | 280 lm |

220 V~ | DRIVER MUST BE PLACED ON REMOTE


i » 282

OPTIONAL ACCESSORY

RHINO Concrete Box Accessory A351-90-00

Only needed when installed in concrete walls.

Boxes can be ordered in advance, in order to place the housings in the wall before the final Rhino installation.



COLOUR | WT □ | NT ■ |

MATERIAL | AL | PC |

RAL i » 312

(©) » 288

WALLY



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-------|---------------------|------|-------|-------|--------|-----|
| WALLY | A353-00-10- W N | 2,1W | 2700K | 250mA | 260 lm | 23% |
| | A353-00-11- W N | 2,1W | 3000K | 250mA | 270 lm | 23% |
| | A353-00-12- W N | 2,1W | 4000K | 250mA | 290 lm | 23% |

220 V~ | IP20 | CRI>90 | L90B10 >55,000h



CCT LOR

| | | | | | | |
|------------------|---------------------|--|-------|--|--|-----|
| WALLY w/o Driver | A353-00-00- W N | | 2700K | | | 23% |
| | A353-00-01- W N | | 3000K | | | 23% |
| | A353-00-02- W N | | 4000K | | | 23% |

III IP20 | CRI>90 | L90B10 >55,000h



| *DRIVER OPTIONS | P | I | CCT | Flux |
|--|------|-------|-------|--------|
| NO DIM 0434-01-30 1 to 3 Wally | 2,1W | 250mA | 2700K | 260 lm |
| | | | 3000K | 270 lm |
| | | | 4000K | 290 lm |
| 0486-04-35 1 Wally | 3W | 350mA | 2700K | 350 lm |
| | | | 3000K | 360 lm |
| | | | 4000K | 390 lm |
| NO DIM 0434-00-39** 1 to 4 Wally | 3W | 350mA | 2700K | 350 lm |
| | | | 3000K | 360 lm |
| | | | 4000K | 390 lm |
| DALI 0434-01-29** 1 to 3 Wally | 2,1W | 250mA | 2700K | 260 lm |
| | | | 3000K | 270 lm |
| | | | 4000K | 290 lm |
| DALI 0434-00-79** 1 to 4 Wally | 3W | 350mA | 2700K | 350 lm |
| | | | 3000K | 360 lm |
| | | | 4000K | 390 lm |

220 V~ | **DRIVER MUST BE PLACED ON REMOTE


i » 282

OPTIONAL ACCESSORY

WALLY Concrete Box Accessory A353-90-00

Only needed when installed in concrete walls.

Boxes can be ordered in advance, in order to place the housings in the wall before the final Wally installation.



COLOUR | W □ | N ■ |

MATERIAL | AL | PC |

RAL i » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

(©) » 288

MINIMAL TRACK_174
TRACK 48V_186
TRACK 1L_216
TRACK 3L_222

TRACK LIGHTS



24V SYSTEM

MINIMAL TRACK



TRACK LIGHTS

LINE MICRO 24V
—
250 / 500 / 1000
2 / 5 / 9 W
2700 / 3000 K
330 - 1500 Lm
113° BEAM
70% LOR

BLACK FOSTER
MICRO 24V
7W
2700 / 3000 / 4000 K
775 - 850 Lm
37° BEAM
87% LOR

TOP MICRO 24V
2,1W
2700 / 3000 K
190 / 210 Lm
19 / 38° BEAM
90 / 92 % LOR

IO MICRO 24V
4,7W
2700 / 3000 / 4000 K
500 - 570 Lm
20 / 40 / 54° BEAM
86 / 88 % LOR

SIX XS 24V
3,5W
2700 / 3000 / 4000 K
400 - 450 Lm
17 / 23 / 34° BEAM
86 - 90 % LOR



ALASKA 24V
3,5W
2700 / 3000 K
390 / 410 Lm
21° BEAM
30% LOR

FIT 24V
—
FIT 20 / FIT 27
2,1 / 4,5 W
2700 / 3000 K
127 - 560 Lm
12 - 54° BEAM
81 - 88 % LOR


PLUS MICRO 24V
4,7 W
2700 / 3000 / 4000 K
500 - 570 Lm
10 - 35° BEAM
10 - 17 % LOR

STICK 22 24V
4,5 W
2700 / 3000 K
440 / 470 Lm
18 / 31 / 42° BEAM
82 - 84 % LOR

24V SYSTEM MINIMAL TRACK



MINIMAL TRACK 24V Profile 2m A384-02-00- | N | WT |



MINIMAL TRACK 24V Rubber Cable n x 1m A384-00-01- | N |


n = Total length of System.

24 V | Max. 4A

MINIMAL TRACK 24V Corner 90° 1 Plane

A384-00-02- | N | WT |


Cable length = 35mm.



MINIMAL TRACK 24V Corner 90° 1 Plane Rounded

A384-00-03- | N | WT |


Cable length = 35mm.



MINIMAL TRACK 24V Corner 90° 2 Planes

A384-00-04- | N | WT |

Cable length = 100mm.




MINIMAL TRACK 24V End Cap

A384-00-05- | N | WT |



MINIMAL TRACK 24V Connection Box

A384-00-06- | N | WT |



| | P | V | D (A x B x C) | |
|------------------------------------|-----------------------|------|---------------|-----------------|
| MINIMAL TRACK 24V Power Supply Box | A384-00-07- NT WT | 40W | 24V | 280 x 30 x 24mm |
| | A384-00-08- NT WT | 100W | 24V | 280 x 30 x 24mm |

220 V~ | 240 V~ | Included ON/OFF 24Vdc Power Supply.

| | P | V | D (A x B x C) | |
|---------------------------------------|------------|------|---------------|-----------------|
| MINIMAL TRACK 24V Remote Power Supply | 0434-01-37 | 60W | 24V | 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V | 295 x 43 x 30mm |

220 V~ | 240 V~

» 282


| MINIMAL TRACK 24V Remote Constant Voltage Dimmer | 0433-01-32 | DALI / Push | 24V | 181 x 42 x 20mm |
|--|------------|-------------|-----|-----------------|
| | 0433-01-33 | CASAMBI | 24V | 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V | 105 x 44 x 23mm |

24 V | OTHER DIM OPTIONS PLEASE CONSULT

» 288


DROP VOLTAGE TABLE

| POWER [W] | CABLE SECTION [mm ²] | CABLE LENGTH (m) | | | |
|-----------|----------------------------------|------------------|-----|-----|-----|
| | | <5 | <10 | <20 | <30 |
| 40 | 0,75 | 30 | 30 | 30 | 30 |
| | 1,5 | 30 | 30 | 30 | 30 |
| 60 | 0,75 | 30 | 30 | 20 | 10 |
| | 1,5 | 30 | 30 | 30 | 20 |
| 100 | 0,75 | 20 | 10 | X | X |
| | 1,5 | 20 | 20 | 10 | X |




PRODUCT CONFIGURATOR

Configure your own custom product layout. Our tool will calculate the required drivers and accessories.




COLOUR | N ■ | NT ■ | WT □ |

RAL ⓘ » 312



MINIMAL TRACK 24V Trimless Profile 2m A467-02-00- | N |



MINIMAL TRACK 24V Trimless Rubber Cable n x 1m A467-00-01- | N |


n = Total length of System.

24 V | Max. 4A

MINIMAL TRACK 24V Trimless Corner 90° 1 Plane


A467-00-02- | N |

Cable length = 140mm.



MINIMAL TRACK 24V Trimless Corner 90° 1 Plane Connector


A467-00-03- | N |



MINIMAL TRACK 24V Trimless Corner 90° 2 Planes

A467-00-04- | N |

Cable length = 200mm.



MINIMAL TRACK 24V Trimless End Caps

A467-00-05- | N |

Two End Caps Included



MINIMAL TRACK 24V Trimless Straight Joiner

A467-00-06



MINIMAL TRACK 24V Trimless Connection Box

A467-00-07- | N |



| | P | V | D (A x B x C) | |
|---------------------------------------|------------|------|---------------|-----------------|
| MINIMAL TRACK 24V Remote Power Supply | 0434-01-37 | 60W | 24V | 180 x 52 x 30mm |
| | 0433-10-22 | 100W | 24V | 295 x 43 x 30mm |

220 V~ | 240 V~

» 282

| MINIMAL TRACK 24V Remote Constant Voltage Dimmer | 0433-01-32 | DALI / Push | 24V | 181 x 42 x 20mm |
|--|------------|-------------|-----|-----------------|
| | 0433-01-33 | CASAMBI | 24V | 172 x 42 x 20mm |
| | 0434-01-64 | WIFI | 24V | 105 x 44 x 23mm |



24 V | OTHER DIM OPTIONS PLEASE CONSULT

» 288

DROP VOLTAGE TABLE

| POWER [W] | CABLE SECTION [mm ²] | CABLE LENGTH (m) | | | |
|-----------|----------------------------------|------------------|-----|-----|-----|
| | | <5 | <10 | <20 | <30 |
| 60 | 0,75 | 30 | 30 | 20 | 10 |
| | 1,5 | 30 | 30 | 30 | 20 |
| 100 | 0,75 | 20 | 10 | X | X |
| | 1,5 | 20 | 20 | 10 | X |

Reduce 5 meters per each 'Corner 90° 1 Plane CONNECTOR' used.



COLOUR | N ■ |

RAL ⓘ » 312

24V SYSTEM
MINIMAL TRACK




PRODUCT CONFIGURATOR
Configure your own custom product layout. Our tool will calculate the required drivers and accessories.

OPTIONAL ACCESSORIES


WIRE TRIMLESS Accessories

Coaxial Trimless A023-00-03- | W | N |




FASTENERS NOT AVAILABLE.



TRIMLESS TOOL D20 X D52mm A478-00-01



COAXIAL TRIMLESS



MINIMAL TRACK 24V Suspension

Profile 2m

A384-02-00- | N | WT |

Profile 2m Initial feed kit

A400-02-10- | N | WT |

Profile 2m Middle feed kit*



A400-02-20- | N | WT |

* Unidirectional Middle Feed.

MINIMAL TRACK 24V Suspension Corner 90°

A400-00-03- | N | WT |

Cable length = 85mm.



MINIMAL TRACK 24V Suspension

Rubber Cable n x 1m

A400-00-01- | N |

n = Total length of System.

24 V | Max. 4A

MINIMAL TRACK 24V Suspension Straight Joiner

A400-00-02- | N | WT |

MINIMAL TRACK 24V Suspension Kit


A400-02-04- | N | WT |

Max distance between suspension kits = 100 cm.

MINIMAL TRACK 24V Suspension End Caps

A400-00-05- | N | WT |

Two End Caps Included.





| | P | V | D (A x B x C) |
|--|-------------|-----|-----------------|
| MINIMAL TRACK 24V Suspension Power Supply Box | | | |
| A400-00-06- NT WT | 40W | 24V | 280 x 30 x 36mm |
| A400-00-07- NT WT | 100W | 24V | 280 x 30 x 36mm |
| 220-240 V~ Included ON/OFF 24Vdc Power Supply. | | | |
| MINIMAL TRACK 24V Remote Power Supply | | | |
| 0434-01-37 | 60W | 24V | 180 x 52 x 30mm |
| 0433-10-22 | 100W | 24V | 295 x 43 x 30mm |
| 220-240 V~ | | | » 282 |
| MINIMAL TRACK 24V Remote Constant Voltage Dimmer | | | |
| 0433-01-32 | DALI / Push | 24V | 181 x 42 x 20mm |
| 0433-01-33 | CASAMBI | 24V | 172 x 42 x 20mm |
| 0434-01-64 | WIFI | 24V | 105 x 44 x 23mm |

24 V | OTHER DIM OPTIONS PLEASE CONSULT

» 288

DROP VOLTAGE TABLE

| POWER [W] | CABLE SECTION [mm ²] | CABLE LENGTH (m) | | | |
|-----------|----------------------------------|------------------|-----|-----|-----|
| | | <5 | <10 | <20 | <30 |
| 40 | 0,75 | 30 | 30 | 30 | 30 |
| | 1,5 | 30 | 30 | 30 | 30 |
| 60 | 0,75 | 30 | 30 | 20 | 10 |
| | 1,5 | 30 | 30 | 30 | 20 |
| 100 | 0,75 | 20 | 10 | X | X |
| | 1,5 | 20 | 20 | 10 | X |



COLOUR | N ■ | NT ■ | WT □ |

RAL » 312

BLACK FOSTER MICRO 24V




MORE INFO >>



BLACK FOSTER MICRO 24V 5 NOT VALID FOR MINIMAL TRACK 24V TRIMLESS

| | | P | CCT | I | Flux | LOR |
|-----------------------------|-----------------|----|-------|-------|--------|-----|
| BLACK FOSTER Micro 24V 5 | A415-20-10- N | 7W | 2700K | 500mA | 775 lm | 87% |
| | A415-20-11- N | 7W | 3000K | 500mA | 800 lm | 87% |
| | A415-20-12- N | 7W | 4000K | 500mA | 850 lm | 87% |

24 V | III IP20 | CRI>90 | L90B10 >60.000h



Extended Family
Black Foster Micro_P10
Black Foster_P12
Black Foster Surface_P104
Black Foster Suspension_P133
Black Foster 48V_P207
Black Foster Custom_P242

BLACK FOSTER MICRO 24V




MORE INFO >>



BLACK FOSTER MICRO 24V SURFACE 5 RECOMMENDED FOR MINIMAL TRACK 24V TRIMLESS ONLY

| | | P | CCT | I | Flux | LOR |
|-------------------------------------|-----------------------|----|-------|-------|--------|-----|
| BLACK FOSTER Micro 24V Surface 5 | A468-20-10- NT WT | 7W | 2700K | 500mA | 775 lm | 87% |
| | A468-20-11- NT WT | 7W | 3000K | 500mA | 800 lm | 87% |
| | A468-20-12- NT WT | 7W | 4000K | 500mA | 850 lm | 87% |

24 V | III IP20 | CRI>90 | L90B10 >60.000h



| FINISHING | Body | Lampshade |
|-----------|------------|-----------|
| NT | NT ■ N ■ | |
| WT | WT □ N ■ | |

COLOUR | N ■ |

MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

COLOUR | NT ■ | WT □ |

MATERIAL | AL | ABS+PC |

Ⓜ » 288

ALASKA 24V




MORE INFO >>



| | | P | CCT | I | Flux | LOR |
|------------|-----------------|------|-------|-------|--------|-----|
| ALASKA 24V | A385-00-00- N | 3,5W | 2700K | 400mA | 390 lm | 30% |
| | A385-00-01- N | 3,5W | 3000K | 400mA | 410 lm | 30% |

24 V | III IP20 | CRI>90 | L90B10 >55.000h



Alaska Trimless_P.60
Alaska_P.130
Alaska Fancy Shape_P.238

TOP MICRO 24V




MORE INFO >>



| | | P | CCT | BEAM | I | Flux | LOR |
|---------------|-----------------------|------|-------|------|-------|--------|-----|
| TOP Micro 24V | A383-00-10- WT NT | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| | A383-00-11- WT NT | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| | A383-00-20- WT NT | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| | A383-00-21- WT NT | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |

24 V | III IP20 | CRI>90 | L90B10 >102.000h



COLOUR | N ■ |

MATERIAL | AL | OPTICAL GLASS |

RAL ⓘ » 312

COLOUR | WT □ | NT ■ |

MATERIAL | AL | PC |

Ⓜ » 288

24V SYSTEM PLUS MICRO 24V



Magnetic 24V Plus Micro_P.94
Plus Recessed_P.101
Plus 48V_P.201

Extended Family
Plus Mini 1L_P.221
Plus_P.229
Black Foster Plus Mini_P.246


MORE INFO >>



| | | P | CCT | BEAM | I | Flux | LOR |
|----------------|-----------------------|------|-------|---------|-------|--------|--------|
| PLUS Micro 24V | A388-00-00- WT NT | 4,7W | 2700K | 10°-35° | 400mA | 500 lm | 10-17% |
| | A388-00-01- WT NT | 4,7W | 3000K | 10°-35° | 400mA | 520 lm | 10-17% |
| | A388-00-02- WT NT | 4,7W | 4000K | 10°-35° | 400mA | 570 lm | 10-17% |

24 V | III | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 3 INCL MINIMAL TRACK 355° 180° 10-35°



SIX XS 24V

Magnetic 24V Six XS_P.95
Six Recessed_P.97

Extended Family
Six 48V_P.194
Six_P.226
Black Foster Six_P.246


MORE INFO >>



| | | P | CCT | BEAM | I | Flux | LOR |
|------------|-----------------------|------|-------|------|-------|--------|-----|
| SIX XS 24V | A389-00-10- WT NT | 3,5W | 2700K | 17° | 400mA | 400 lm | 90% |
| | A389-00-11- WT NT | 3,5W | 3000K | 17° | 400mA | 420 lm | 90% |
| | A389-00-12- WT NT | 3,5W | 4000K | 17° | 400mA | 450 lm | 90% |
| | A389-00-20- WT NT | 3,5W | 2700K | 23° | 400mA | 400 lm | 86% |
| | A389-00-21- WT NT | 3,5W | 3000K | 23° | 400mA | 420 lm | 86% |
| | A389-00-22- WT NT | 3,5W | 4000K | 23° | 400mA | 450 lm | 86% |
| | A389-00-30- WT NT | 3,5W | 2700K | 34° | 400mA | 400 lm | 88% |
| | A389-00-31- WT NT | 3,5W | 3000K | 34° | 400mA | 420 lm | 88% |
| | A389-00-32- WT NT | 3,5W | 4000K | 34° | 400mA | 450 lm | 88% |

24 V | III | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 INCL MINIMAL TRACK 355° 310° 17° / 23° / 34°



OPTIONAL

SIX High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

COLOUR | WT □ | NT ■ | MATERIAL | AL | OPTICAL PMMA | RAL ⓘ » 312


COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | ⓘ » 288

24V SYSTEM LINE MICRO 24V



Extended Family
Line Suspension_P.154
Line 48V_P.209

MORE INFO >>




LINE MICRO 24V NOT VALID FOR MINIMAL TRACK 24V TRIMLESS | COLOURS MAY AFFECT THE LIGHTING PARAMETERS

| | | P | CCT | I | Flux | LOR |
|---------------------|----------------------|----|-------|-------|---------|-----|
| LINE Micro 250 24V | A395-00-00- N WT | 2W | 2700K | 400mA | 330 lm | 70% |
| | A395-00-01- N WT | 2W | 3000K | 400mA | 340 lm | 70% |
| LINE Micro 500 24V | A395-10-00- N WT | 5W | 2700K | 400mA | 820 lm | 70% |
| | A395-10-01- N WT | 5W | 3000K | 400mA | 840 lm | 70% |
| LINE Micro 1000 24V | A395-20-00- N WT | 9W | 2700K | 700mA | 1430 lm | 70% |
| | A395-20-01- N WT | 9W | 3000K | 700mA | 1500 lm | 70% |

24 V | III | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 INCL MINIMAL TRACK 113°



iO MICRO 24V

Magnetic 24V iO Micro_P.93
iO surface_P.126

Extended Family
iO 48V_P.202
iO_P.220


MORE INFO >>



| | | P | CCT | BEAM | I | Flux | LOR |
|--------------|-----------------------|------|-------|------|-------|--------|-----|
| iO Micro 24V | A387-00-10- WT NT | 4,7W | 2700K | 20° | 400mA | 500 lm | 88% |
| | A387-00-11- WT NT | 4,7W | 3000K | 20° | 400mA | 520 lm | 88% |
| | A387-00-12- WT NT | 4,7W | 4000K | 20° | 400mA | 570 lm | 88% |
| | A387-00-20- WT NT | 4,7W | 2700K | 40° | 400mA | 500 lm | 86% |
| | A387-00-21- WT NT | 4,7W | 3000K | 40° | 400mA | 520 lm | 86% |
| | A387-00-22- WT NT | 4,7W | 4000K | 40° | 400mA | 570 lm | 86% |
| | A387-00-30- WT NT | 4,7W | 2700K | 54° | 400mA | 500 lm | 86% |
| | A387-00-31- WT NT | 4,7W | 3000K | 54° | 400mA | 520 lm | 86% |
| | A387-00-32- WT NT | 4,7W | 4000K | 54° | 400mA | 570 lm | 86% |

24 V | III | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 3 INCL MINIMAL TRACK 355° 155° 20° / 40° / 54°



OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS


iO Micro 24V Beam Mixer Diffuser
A387-00-00



iO Micro 24V Anti-glare

Honeycomb Louver

A387-00-01- | WT | NT |



COLOUR | N ■ | WT □ | MATERIAL | AL | PC | RAL ⓘ » 312

COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | ⓘ » 288



Magnetic 24V Fit_P.92
Fit Recessed_P.100

Fit Surface_P.124
Fit 48V_P.197
Fit 65 1L_P.221

Extended Family
Fit_P.228
Black Foster Fit 35_P.246
Black Foster Fit 27_P.249

MORE INFO >>



| | | P | CCT | BEAM | I | Flux | LOR |
|------------|---------------------------|------|-------|------|-------|--------|-----|
| FIT 20 24V | A386-00-10- WT NT G | 2,1W | 2700K | 12° | 700mA | 127 lm | 87% |
| | A386-00-11- WT NT G | 2,1W | 3000K | 12° | 700mA | 150 lm | 87% |
| | A386-00-20- WT NT G | 2,1W | 2700K | 30° | 700mA | 127 lm | 88% |
| | A386-00-21- WT NT G | 2,1W | 3000K | 30° | 700mA | 150 lm | 88% |
| | A386-00-30- WT NT G | 2,1W | 2700K | 54° | 700mA | 127 lm | 81% |
| | A386-00-31- WT NT G | 2,1W | 3000K | 54° | 700mA | 150 lm | 81% |

24 V | III IP20 | CRI>90 | L80B10 >50.000h




MORE INFO >>



| | | P | CCT | BEAM | I | Flux | LOR |
|--------------|---------------------------|------|-------|------|-------|--------|-----|
| FIT 27 24V 1 | A399-00-10- WT NT G | 4,5W | 2700K | 18° | 400mA | 440 lm | 84% |
| | A399-00-11- WT NT G | 4,5W | 3000K | 18° | 400mA | 470 lm | 84% |
| | A399-00-20- WT NT G | 4,5W | 2700K | 31° | 400mA | 440 lm | 82% |
| | A399-00-21- WT NT G | 4,5W | 3000K | 31° | 400mA | 470 lm | 82% |
| | A399-00-30- WT NT G | 4,5W | 2700K | 42° | 400mA | 440 lm | 84% |
| | A399-00-31- WT NT G | 4,5W | 3000K | 42° | 400mA | 470 lm | 84% |
| FIT 27 24V 2 | A399-10-10- WT NT G | 5,5W | 2700K | 18° | 500mA | 520 lm | 84% |
| | A399-10-11- WT NT G | 5,5W | 3000K | 18° | 500mA | 560 lm | 84% |
| | A399-10-20- WT NT G | 5,5W | 2700K | 31° | 500mA | 520 lm | 82% |
| | A399-10-21- WT NT G | 5,5W | 3000K | 31° | 500mA | 560 lm | 82% |
| | A399-10-30- WT NT G | 5,5W | 2700K | 42° | 500mA | 520 lm | 84% |
| | A399-10-31- WT NT G | 5,5W | 3000K | 42° | 500mA | 560 lm | 84% |

24 V | III IP20 | CRI>90 | L90B10 >108.000h



COLOUR | WT □ | NT ■ | G ■ | MATERIAL | AL | PC | RAL ⓘ » 312

» 288




Extended Family
Stick_P.142
Stick 48V_P.214
Stick Fancy Shape_P.237

MORE INFO >>



| | | P | CCT | Beam | I | Flux | LOR |
|--------------|----------------------------|------|-------|------|-------|--------|-----|
| STICK 22 24V | A410-01-10- WT NT MG | 4,5W | 2700K | 18° | 400mA | 440 lm | 84% |
| | A410-01-11- WT NT MG | 4,5W | 3000K | 18° | 400mA | 470 lm | 84% |
| | A410-01-20- WT NT MG | 4,5W | 2700K | 31° | 400mA | 440 lm | 82% |
| | A410-01-21- WT NT MG | 4,5W | 3000K | 31° | 400mA | 470 lm | 82% |
| | A410-01-30- WT NT MG | 4,5W | 2700K | 42° | 400mA | 440 lm | 84% |
| | A410-01-31- WT NT MG | 4,5W | 3000K | 42° | 400mA | 470 lm | 84% |


24 V | III IP20 | CRI>90 | L90B10 >108.000h



OPTIONAL ACCESSORY


CORD Accessory

0223-00-00- | N |



STICK 22 24V


STICK 22 24V + CORD ACCESSORY



COLOUR | WT □ | NT ■ | MG ■ | N ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

» 288

48V SYSTEM
TRACK 48V



LINE 48V
—
500 / 1000 / 2000

10,5 / 21 / 42 W
2700 / 3000 / 4000 K
1500 - 6600 Lm
98° BEAM
43% LOR

**BLACK FOSTER
MICRO 48V**
—
5 / 10

7 / 14 W
2700 / 3000 / 4000 K
775 - 1700 Lm
37° BEAM
87% LOR

**BLACK FOSTER
48V TILT 5**
—

10,5 W
2700 / 3000 / 4000 K
950 / 1050 / 1250 Lm
19 / 38° BEAM
90 - 92 % LOR

WIZ 48V

12,4 W
2700 / 3000 / 4000 K
1470 / 1530 / 1550 Lm
38° BEAM
86 % LOR

COCO 48V

6 - 8,7 W
2700 - 5000 K
750 - 1340 Lm
12 - 54° BEAM
66 - 89 % LOR

PLUS 48V
—
PLUS MINI / PLUS

6,5 / 18 W
2700 / 3000 / 4000 K
630 - 2030 Lm
10 - 41° / 12 - 51° BEAM
20 - 40 % LOR

FLIP 48V

6 W
2700 / 3000 / 4000 K
640 / 670 / 720 Lm
18 / 40° BEAM
89 % LOR

TOP 48V
—
TOP MINI / TOP

6,5 W
2700 / 3000 K
610 / 640 Lm
20 / 30 / 56° BEAM
86 - 92 % LOR

iO 48V

4,5 W
2700 / 3000 K
485 / 505 Lm
20 / 30 / 56° BEAM
86 - 92 % LOR

FIT 48V
—
20 / 35 / 50

2,1 - 12 W
2700 / 3000 / 4000 K
127 - 1260 Lm
12 - 54° BEAM
79 - 88 % LOR

SIX 48V
—
XS / S / M / L

4,5 - 24,5 W
2700 / 3000 / 4000 K
470 - 3000 Lm
17 - 38° BEAM
84 - 93 % LOR

ZEN TUBE 48V

12 / 17 / 23 W
2700 / 3000 K
1580 - 3190 Lm
16 / 24 / 42° BEAM
90% LOR

SPIN 48V

6,5 W
2700 / 3000 K
600 / 630 Lm
24 / 40° BEAM
84 / 86 % LOR



HOLLY 48V

2,1 W
2700 / 3000 K
190 / 210 Lm
19 / 38° BEAM
90 / 92 % LOR

STICK 48V
—
22 / 44 / 66

5,6 W
2700 / 3000 K
530 / 570 Lm
18 / 31 / 42° BEAM
82 - 84 % LOR

TRACK 48V




TRACK 48V TRIMLESS

| | |
|--|----------------------|
| TRACK 48V TRIMLESS 1m | A338-01-00- N WT |
| TRACK 48V TRIMLESS 2m | A338-02-00- N WT |
| TRACK 48V TRIMLESS 3m | A338-03-00- N WT |
| TRACK 48V TRIMLESS Corner 90° One Plane | A338-06-00- N WT |
| TRACK 48V TRIMLESS Corner 90° Two Planes | A338-07-00- N WT |

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm.
RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE
INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING.




TRACK 48V TRIMLESS Corner 90° One Plane




*Electrical connection not included

TRACK 48V TRIMLESS Corner 90° Two Planes



*Electrical connection not included




TRACK 48V SURFACE

| | |
|--|-----------------------|
| TRACK 48V SURFACE 1m | A338-11-00- NT WT |
| TRACK 48V SURFACE 2m | A338-12-00- NT WT |
| TRACK 48V SURFACE 3m | A338-13-00- NT WT |
| TRACK 48V SURFACE Corner 90° One Plane | A338-14-00- NT WT |




TRACK 48V SURFACE Corner 90° One Plane




Electrical connection not included
Straight joiner included

TRACK 48V SURFACE SHORT Corner 90° One Plane



Electrical connection not included
Straight joiner included




TRACK 48V SURFACE SHORT

| | |
|--|-----------------------|
| TRACK 48V SURFACE SHORT 1m | A338-21-00- NT WT |
| TRACK 48V SURFACE SHORT 2m | A338-22-00- NT WT |
| TRACK 48V SURFACE SHORT 3m | A338-23-00- NT WT |
| TRACK 48V SURFACE SHORT Corner 90° One Plane | A338-24-00- NT WT |




| | P | V | D [A x B x C] |
|-----------------------------------|---------------------|----------|-----------------|
| CONSTANT VOLTAGE LED POWER SUPPLY | 0434-01-61* N W | 100W 48V | 298 x 19 x 16mm |
| | 0434-01-62 | 150W 48V | 350 x 30 x 18mm |
| | 0434-01-80 | 250W 48V | 400 x 40 x 22mm |

220 V~ | *To be installed inside the track.



PRODUCT CONFIGURATOR


Configure your own custom product layout. Our tool will calculate the required drivers and accessories.



DROP VOLTAGE TABLE

| POWER (W) | CABLE SECTION (mm ²) | CABLE LENGTH (m) | | | |
|-----------|----------------------------------|------------------|----|----|----|
| | | 5 | 10 | 20 | 30 |
| 100 | 0,75 | 50 | 50 | X | X |
| | 1,5 | 50 | 50 | 40 | 25 |
| 150 | 0,75 | 40 | 15 | X | X |
| | 1,5 | 50 | 40 | 20 | X |
| 250 | 0,75 | 20 | X | X | X |
| | 1,5 | 35 | 20 | X | X |

ALL 48V TRACKS




Live-End Connector 48V
A338-00-01- | N | W |

Corner Connector 48V
A338-00-12- | N | W |

Corner 90° Connector One Plane 48V
A338-00-24- | N | W |

*Not suitable for trimless version




Central Connector 48V
A338-00-02- | N | W |

Wireless Control 48V
0434-01-31- | N | W | Casambi

Cover Gap 1m 48V
A338-00-30- | N | W |

TRIMLESS 48V



Trimless Short T-Bracket 48V
A338-00-03

Trimless Long T-Bracket 48V
A338-00-04

Trimless Straight Joiners (2 units) 48V
A338-00-05- | N | WT |

Trimless Plaster Installation Guard 1m 48V
A338-00-21


SURFACE, SUSPENSION, SURFACE SHORT & SUSPENSION SHORT 48V

Surface Straight Joiner 48V
A338-00-11

COLOUR | N ■ | W □ | NT ■ | WT □ |

RAL ⓘ » 312


SUSPENSION & SUSPENSION SHORT 48V



SURFACE Suspension Kit (2 units) 48V
A338-00-15- | NT | WT |

Wired Power Supply Case 48V
A338-00-25- | NT | WT | 150W NO DIM
A338-00-26- | NT | WT | 150W DIM

220 V~
240 V~
INCL




Surface Suspension Feed Kit 48V
A338-00-16- | N | W | NO DIM
A338-00-17- | N | W | DIM

*For remote power supply

A338-00-27- | N | W | NO DIM
A338-00-28- | N | W | DIM

*For power supply inside the track

SURFACE & SURFACE SHORT 48V



Power Supply Case 48V
A338-00-29- | NT | WT | 150W


220 V~
240 V~
INCL
*To be installed aside 48V Surface Tracks

TRIMLESS, SURFACE & SUSPENSION 48V



End 48V
A338-00-06- | NT | WT |


End Feed 48V
A338-00-07- | NT | WT |




Short End 48V
A338-00-18- | NT | WT |

Short End Feed 48V
A338-00-19- | NT | WT |


MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS




WIRE TRIMLESS ACCESSORIES

FEED

Mains Trimless*
A023-00-01- | W | N | NO DIM

Mains Thick Trimless*
A023-00-02- | W | N | DIM




FASTENING

Steel Cable Trimless*
A023-00-05- | W | N |



TRIMLESS TOOL D20 X D52mm A478-00-01



COLOUR | N ■ | W □ | NT ■ | WT □ |

RAL ⓘ » 312

* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

48V SYSTEM
TRACK 48V





| | | P | CCT | Flux | LOR | L |
|--------------------------------|-----------------------|-------|-------|--------|-----|--------|
| TRACK 48V + IND. LIGHT 1400 | A466-01-20- NT WT | 18,3W | 2700K | 2320lm | 70% | 1402mm |
| | A466-01-21- NT WT | 18,3W | 3000K | 2380lm | 70% | 1402mm |
| | A466-01-22- NT WT | 18,3W | 4000K | 2585lm | 70% | 1402mm |
| TRACK 48V + IND. LIGHT 2800 | A466-02-20- NT WT | 39,2W | 2700K | 5210lm | 70% | 2802mm |
| | A466-02-21- NT WT | 39,2W | 3000K | 5360lm | 70% | 2802mm |
| | A466-02-22- NT WT | 39,2W | 4000K | 5820lm | 70% | 2802mm |


48V | III | IP20 | CRI>90 | L90B5 >50.000h




TRACK 48V + INDIRECT LIGHT
1400 / 2800



Indirect Light Suspension kit 48V (2 units)
A466-00-03- | NT | WT |



Suspension straight joiner kit 48V
A466-00-04- | NT | WT |




Suspension 90° Corner joiner kit 48V
A466-00-05- | NT | WT |

P V D (A x B x C)

| CONSTANT VOLTAGE LED POWER SUPPLY | | P | V | D (A x B x C) |
|-----------------------------------|------|-----|-----------------|---------------|
| 0434-01-61* N W | 100W | 48V | 298 x 19 x 16mm | |
| 0434-01-62 | 150W | 48V | 350 x 30 x 18mm | |
| 0434-01-80 | 250W | 48V | 400 x 40 x 22mm | |

220 V~ 240 V~ *To be installed inside the track. ⓘ » 282



PRODUCT CONFIGURATOR

Configure your own custom product layout. Our tool will calculate the required drivers and accessories.

DROP VOLTAGE TABLE


| POWER (W) | CABLE SECTION (mm²) | CABLE LENGTH (m) | | | |
|-----------|---------------------|------------------|----|----|----|
| | | 5 | 10 | 20 | 30 |
| 100 | 0,75 | 50 | 50 | X | X |
| | 1,5 | 50 | 50 | 40 | 25 |
| 150 | 0,75 | 40 | 15 | X | X |
| | 1,5 | 50 | 40 | 20 | X |
| 250 | 0,75 | 20 | X | X | X |
| | 1,5 | 35 | 20 | X | X |

For calculations, you must consider indirect light power.

COLOUR | WT □ | NT ■ | W □ | N ■ | MATERIAL | AL | PC |


RAL ⓘ » 312

Ⓜ » 288




Live-End Connector 48V

A338-00-01- | N | W |




L-JOINT Connector 48V

A338-00-12- | N | W |




Corner 90° Connector One Plane 48V

A338-00-24- | N | W |



End 48V

A338-00-06- | NT | WT |




Wired Power Supply Case 48V

A338-00-25- | NT | WT | 150W NO DIM


A338-00-26- | NT | WT | 150W DIM

220 V~ 240 V~ INCL




Central Connector 48V

A338-00-02- | N | W |



Wireless Control 48V

0434-01-31- | N | W | Casambi




Cover Gap 1m 48V

A338-00-30- | N | W |



End Feed 48V

A338-00-07- | NT | WT |



Suspension Feed Kit

A338-00-16- | N | W | NO DIM

A338-00-17- | N | W | DIM


For remote power supply

A338-00-27- | N | W | NO DIM


A338-00-28- | N | W | DIM

For power supply inside the track


MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



WIRE TRIMLESS ACCESSORIES


FEED

Mains Trimless*

A023-00-01- | W | N | NO DIM

Mains Thick Trimless*

A023-00-02- | W | N | DIM




FASTENING

Steel Cable Trimless*

A023-00-05- | W | N |



TRIMLESS TOOL D20 X D52mm A478-00-01




COLOUR | WT □ | NT ■ | W □ | N ■ |

MATERIAL | AL | PC |

RAL ⓘ » 312

* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

Ⓜ » 288



MORE INFO >>

| SIX L 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|-------|-------|------|-------|---------|-----|
| A329-0- ① -10- WT NT WTW NTW -S | | 24,5W | 2700K | 17° | 700mA | 2850 lm | 93% |
| A329-0- ① -11- WT NT WTW NTW -S | | 24,5W | 3000K | 17° | 700mA | 2950 lm | 93% |
| A329-0- ① -12- WT NT WTW NTW -S | | 24,5W | 4000K | 17° | 700mA | 3000 lm | 93% |
| A329-0- ① -30- WT NT WTW NTW -S | | 24,5W | 2700K | 26° | 700mA | 2850 lm | 93% |
| A329-0- ① -31- WT NT WTW NTW -S | | 24,5W | 3000K | 26° | 700mA | 2950 lm | 93% |
| A329-0- ① -32- WT NT WTW NTW -S | | 24,5W | 4000K | 26° | 700mA | 3000 lm | 93% |
| A329-0- ① -20- WT NT WTW NTW -S | | 24,5W | 2700K | 34° | 700mA | 2850 lm | 90% |
| A329-0- ① -21- WT NT WTW NTW -S | | 24,5W | 3000K | 34° | 700mA | 2950 lm | 90% |
| A329-0- ① -22- WT NT WTW NTW -S | | 24,5W | 4000K | 34° | 700mA | 3000 lm | 90% |

48 V | III IP20 | CRI>90 | L90B10 >55.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT


| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3290110WT |
| -S | Track 48V Short | A3290110WT-S |

OPTIONAL

SIX L High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS

| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |




MATERIAL | AL | PC |

RAL ⓘ » 312

+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288



MORE INFO >>


| SIX M 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|-----|-------|------|-------|---------|-----|
| A330-0- ① -10- WT NT WTW NTW -S | | 17W | 2700K | 19° | 500mA | 2050 lm | 93% |
| A330-0- ① -11- WT NT WTW NTW -S | | 17W | 3000K | 19° | 500mA | 2130 lm | 93% |
| A330-0- ① -12- WT NT WTW NTW -S | | 17W | 4000K | 19° | 500mA | 2160 lm | 93% |
| A330-0- ① -20- WT NT WTW NTW -S | | 17W | 2700K | 28° | 500mA | 2050 lm | 91% |
| A330-0- ① -21- WT NT WTW NTW -S | | 17W | 3000K | 28° | 500mA | 2130 lm | 91% |
| A330-0- ① -22- WT NT WTW NTW -S | | 17W | 4000K | 28° | 500mA | 2160 lm | 91% |
| A330-0- ① -30- WT NT WTW NTW -S | | 17W | 2700K | 38° | 500mA | 2050 lm | 93% |
| A330-0- ① -31- WT NT WTW NTW -S | | 17W | 3000K | 38° | 500mA | 2130 lm | 93% |
| A330-0- ① -32- WT NT WTW NTW -S | | 17W | 4000K | 38° | 500mA | 2160 lm | 93% |

48 V | III IP20 | CRI>90 | L90B10 >55.000h



| SIX S 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|------|-------|------|-------|---------|-----|
| A333-0- ① -10- WT NT WTW NTW -S | | 8,5W | 2700K | 17° | 500mA | 1070 lm | 86% |
| A333-0- ① -11- WT NT WTW NTW -S | | 8,5W | 3000K | 17° | 500mA | 1140 lm | 86% |
| A333-0- ① -12- WT NT WTW NTW -S | | 8,5W | 4000K | 17° | 500mA | 1210 lm | 86% |
| A333-0- ① -20- WT NT WTW NTW -S | | 8,5W | 2700K | 24° | 500mA | 1070 lm | 84% |
| A333-0- ① -21- WT NT WTW NTW -S | | 8,5W | 3000K | 24° | 500mA | 1140 lm | 84% |
| A333-0- ① -22- WT NT WTW NTW -S | | 8,5W | 4000K | 24° | 500mA | 1210 lm | 84% |
| A333-0- ① -30- WT NT WTW NTW -S | | 8,5W | 2700K | 34° | 500mA | 1070 lm | 89% |
| A333-0- ① -31- WT NT WTW NTW -S | | 8,5W | 3000K | 34° | 500mA | 1140 lm | 89% |
| A333-0- ① -32- WT NT WTW NTW -S | | 8,5W | 4000K | 34° | 500mA | 1210 lm | 89% |

48 V | III IP20 | CRI>90 | L80B10 >60.000h




| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3300110WT |
| -S | Track 48V Short | A3300110WT-S |

NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS

| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |




MATERIAL | AL | PC |

RAL ⓘ » 312


+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288





MORE INFO >>



MORE INFO >>

| SIX XS 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|------|-------|------|-------|--------|-----|
| A335-0- ① -10- WT NT WTW NTW -S | | 4,5W | 2700K | 17° | 500mA | 470 lm | 90% |
| A335-0- ① -11- WT NT WTW NTW -S | | 4,5W | 3000K | 17° | 500mA | 500 lm | 90% |
| A335-0- ① -12- WT NT WTW NTW -S | | 4,5W | 4000K | 17° | 500mA | 530 lm | 90% |
| A335-0- ① -20- WT NT WTW NTW -S | | 4,5W | 2700K | 23° | 500mA | 470 lm | 86% |
| A335-0- ① -21- WT NT WTW NTW -S | | 4,5W | 3000K | 23° | 500mA | 500 lm | 86% |
| A335-0- ① -22- WT NT WTW NTW -S | | 4,5W | 4000K | 23° | 500mA | 530 lm | 86% |
| A335-0- ① -30- WT NT WTW NTW -S | | 4,5W | 2700K | 34° | 500mA | 470 lm | 88% |
| A335-0- ① -31- WT NT WTW NTW -S | | 4,5W | 3000K | 34° | 500mA | 500 lm | 88% |
| A335-0- ① -32- WT NT WTW NTW -S | | 4,5W | 4000K | 34° | 500mA | 530 lm | 88% |

48 V | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 360° | 310° | 17° / 23° / 34°

| SIX XS 48V Double | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|----|-------|------|-------|------------|-----|
| A335-1- ① -10- WT NT WTW NTW -S | | 9W | 2700K | 17° | 500mA | 2 X 470 lm | 90% |
| A335-1- ① -11- WT NT WTW NTW -S | | 9W | 3000K | 17° | 500mA | 2 X 500 lm | 90% |
| A335-1- ① -12- WT NT WTW NTW -S | | 9W | 4000K | 17° | 500mA | 2 X 530 lm | 90% |
| A335-1- ① -20- WT NT WTW NTW -S | | 9W | 2700K | 23° | 500mA | 2 X 470 lm | 86% |
| A335-1- ① -21- WT NT WTW NTW -S | | 9W | 3000K | 23° | 500mA | 2 X 500 lm | 86% |
| A335-1- ① -22- WT NT WTW NTW -S | | 9W | 4000K | 23° | 500mA | 2 X 530 lm | 86% |
| A335-1- ① -30- WT NT WTW NTW -S | | 9W | 2700K | 34° | 500mA | 2 X 470 lm | 88% |
| A335-1- ① -31- WT NT WTW NTW -S | | 9W | 3000K | 34° | 500mA | 2 X 500 lm | 88% |
| A335-1- ① -32- WT NT WTW NTW -S | | 9W | 4000K | 34° | 500mA | 2 X 530 lm | 88% |

48 V | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 360° | 310° | 17° / 23° / 34°


| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| OPTIONAL |
|--|
| SIX XS High Chromatic LED » 281 |
| NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS |


| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| 0 | Track 48V | A3350110WT |
| -S | Track 48V Short | A3350110WT-S |

| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |



MATERIAL | AL | PC | RAL » 312

+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT). » 288



MORE INFO >>

| FIT 50 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|-----|-------|------|--------|---------|-----|
| A346-0- ① -10- WT NT G WTW NTW GW -S | | 12W | 2700K | 14° | 1050mA | 1090 lm | 84% |
| A346-0- ① -11- WT NT G WTW NTW GW -S | | 12W | 3000K | 14° | 1050mA | 1180 lm | 84% |
| A346-0- ① -12- WT NT G WTW NTW GW -S | | 12W | 4000K | 14° | 1050mA | 1260 lm | 84% |
| A346-0- ① -20- WT NT G WTW NTW GW -S | | 12W | 2700K | 26° | 1050mA | 1090 lm | 83% |
| A346-0- ① -21- WT NT G WTW NTW GW -S | | 12W | 3000K | 26° | 1050mA | 1180 lm | 83% |
| A346-0- ① -22- WT NT G WTW NTW GW -S | | 12W | 4000K | 26° | 1050mA | 1260 lm | 83% |
| A346-0- ① -30- WT NT G WTW NTW GW -S | | 12W | 2700K | 50° | 1050mA | 1090 lm | 79% |
| A346-0- ① -31- WT NT G WTW NTW GW -S | | 12W | 3000K | 50° | 1050mA | 1180 lm | 79% |
| A346-0- ① -32- WT NT G WTW NTW GW -S | | 12W | 4000K | 50° | 1050mA | 1260 lm | 79% |

48 V | IP20 | CRI>90 | L90B10 >108.000h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 360° | 90° | 14°/26°/50°

| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| 0 | Track 48V | A3460110WT |
| -S | Track 48V Short | A3460110WT-S |


OPTIONAL ACCESSORY

FIT 50 Anti-glare Honeycomb Louver

A346-00-00

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS


| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| G | G ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |
| GW | G ■ W □ | |



MATERIAL | AL | PC | RAL » 312

+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT). » 288





MORE INFO >>

| FIT 35 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|------|-------|------|-------|--------|-----|
| A345-0- ① -10- WT NT G WTW NTW GW -S | | 5,5W | 2700K | 20° | 500mA | 620 lm | 85% |
| A345-0- ① -11- WT NT G WTW NTW GW -S | | 5,5W | 3000K | 20° | 500mA | 660 lm | 85% |
| A345-0- ① -12- WT NT G WTW NTW GW -S | | 5,5W | 4000K | 20° | 500mA | 710 lm | 85% |
| A345-0- ① -20- WT NT G WTW NTW GW -S | | 5,5W | 2700K | 29° | 500mA | 620 lm | 84% |
| A345-0- ① -21- WT NT G WTW NTW GW -S | | 5,5W | 3000K | 29° | 500mA | 660 lm | 84% |
| A345-0- ① -22- WT NT G WTW NTW GW -S | | 5,5W | 4000K | 29° | 500mA | 710 lm | 84% |
| A345-0- ① -30- WT NT G WTW NTW GW -S | | 5,5W | 2700K | 36° | 500mA | 620 lm | 85% |
| A345-0- ① -31- WT NT G WTW NTW GW -S | | 5,5W | 3000K | 36° | 500mA | 660 lm | 85% |
| A345-0- ① -32- WT NT G WTW NTW GW -S | | 5,5W | 4000K | 36° | 500mA | 710 lm | 85% |

48 V | III IP20 | CRI>90 | L90B10 >108.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3450110WT |
| -S | Track 48V Short | A3450110WT-S |

OPTIONAL ACCESSORY


FIT 35 Anti-glare Honeycomb Louver

A345-00-00

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS





| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| G | G ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |
| GW | G ■ W □ | |



VISIBLE LIMIT

FIT35 48V SHORT (-S)



MORE INFO >>

| FIT 35 48V DOUBLE | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|-----|-------|------|-------|------------|-----|
| A345-1- ① -10- WT NT G WTW NTW GW -S | | 11W | 2700K | 20° | 500mA | 2 x 620 lm | 85% |
| A345-1- ① -11- WT NT G WTW NTW GW -S | | 11W | 3000K | 20° | 500mA | 2 x 660 lm | 85% |
| A345-1- ① -12- WT NT G WTW NTW GW -S | | 11W | 4000K | 20° | 500mA | 2 x 710 lm | 85% |
| A345-1- ① -20- WT NT G WTW NTW GW -S | | 11W | 2700K | 29° | 500mA | 2 x 620 lm | 84% |
| A345-1- ① -21- WT NT G WTW NTW GW -S | | 11W | 3000K | 29° | 500mA | 2 x 660 lm | 84% |
| A345-1- ① -22- WT NT G WTW NTW GW -S | | 11W | 4000K | 29° | 500mA | 2 x 710 lm | 84% |
| A345-1- ① -30- WT NT G WTW NTW GW -S | | 11W | 2700K | 36° | 500mA | 2 x 620 lm | 85% |
| A345-1- ① -31- WT NT G WTW NTW GW -S | | 11W | 3000K | 36° | 500mA | 2 x 660 lm | 85% |
| A345-1- ① -32- WT NT G WTW NTW GW -S | | 11W | 4000K | 36° | 500mA | 2 x 710 lm | 85% |

48 V | III IP20 | CRI>90 | L90B10 >108.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3451110WT |
| -S | Track 48V Short | A3451110WT-S |

OPTIONAL ACCESSORY


FIT 35 Anti-glare Honeycomb Louver

A345-00-00

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS




| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| G | G ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |
| GW | G ■ W □ | |



VISIBLE LIMIT

FIT35 48V DOUBLE - SHORT (-S)



MATERIAL | AL | PC

RAL ⓘ » 312

+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288

MATERIAL | AL | PC

RAL ⓘ » 312


+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288

48V SYSTEM
FIT 48V



MORE INFO >>



MORE INFO >>

| FIT 20 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|------|-------|------|-------|--------|-----|
| A344-0- ① -10- WT NT G WTW NTW GW -S | | 2,1W | 2700K | 12° | 700mA | 127 lm | 87% |
| A344-0- ① -11- WT NT G WTW NTW GW -S | | 2,1W | 3000K | 12° | 700mA | 150 lm | 87% |
| A344-0- ① -20- WT NT G WTW NTW GW -S | | 2,1W | 2700K | 30° | 700mA | 127 lm | 88% |
| A344-0- ① -21- WT NT G WTW NTW GW -S | | 2,1W | 3000K | 30° | 700mA | 150 lm | 88% |
| A344-0- ① -30- WT NT G WTW NTW GW -S | | 2,1W | 2700K | 54° | 700mA | 127 lm | 81% |
| A344-0- ① -31- WT NT G WTW NTW GW -S | | 2,1W | 3000K | 54° | 700mA | 150 lm | 81% |

48 V | III | IP20 | CRI>90 | L90B10 >50.000 h



| FIT 20 48V DOUBLE | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|------|-------|------|-------|------------|-----|
| A344-1- ① -10- WT NT G WTW NTW GW -S | | 4,2W | 2700K | 12° | 700mA | 2 x 127 lm | 87% |
| A344-1- ① -11- WT NT G WTW NTW GW -S | | 4,2W | 3000K | 12° | 700mA | 2 x 150 lm | 87% |
| A344-1- ① -20- WT NT G WTW NTW GW -S | | 4,2W | 2700K | 30° | 700mA | 2 x 127 lm | 88% |
| A344-1- ① -21- WT NT G WTW NTW GW -S | | 4,2W | 3000K | 30° | 700mA | 2 x 150 lm | 88% |
| A344-1- ① -30- WT NT G WTW NTW GW -S | | 4,2W | 2700K | 54° | 700mA | 2 x 127 lm | 81% |
| A344-1- ① -31- WT NT G WTW NTW GW -S | | 4,2W | 3000K | 54° | 700mA | 2 x 150 lm | 81% |

48 V | III | IP20 | CRI>90 | L90B10 >50.000 h




| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |


OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3440110WT |
| -S | Track 48V Short | A3440110WT-S |


FIT20 48V




FIT20 48V DOUBLE



FIT20 48V SHORT (-S)



FIT20 48V DOUBLE - SHORT (-S)



| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| G | G ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |
| GW | G ■ W □ | |

MATERIAL | AL | PC

RAL ⓘ » 312

*RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓜ » 288

48V SYSTEM
PLUS 48V



MORE INFO >>



MORE INFO >>

| PLUS 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|-----|-------|---------|-------|---------|--------|
| A323-00- ① -0- WT NT WTW NTW -S | | 18W | 2700K | 12°-51° | 500mA | 1920 lm | 26-40% |
| A323-00- ① -1- WT NT WTW NTW -S | | 18W | 3000K | 12°-51° | 500mA | 2000 lm | 26-40% |
| A323-00- ① -2- WT NT WTW NTW -S | | 18W | 4000K | 12°-51° | 500mA | 2030 lm | 26-40% |

48 V | III | IP20 | CRI>90 | L90B10 >55.000 h



| PLUS Mini 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|------|-------|---------|-------|--------|--------|
| A326-00- ① -0- WT NT WTW NTW -S | | 6,5W | 2700K | 10°-41° | 700mA | 630 lm | 20-40% |
| A326-00- ① -1- WT NT WTW NTW -S | | 6,5W | 3000K | 10°-41° | 700mA | 660 lm | 20-40% |
| A326-00- ① -2- WT NT WTW NTW -S | | 6,5W | 4000K | 10°-41° | 700mA | 680 lm | 20-40% |

48 V | III | IP20 | CRI>90 | L90B10 >55.000 h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3230010WT |
| -S | Track 48V Short | A3230010WT-S |

OPTIONAL


PLUS High Chromatic LED

PLUS MINI High Chromatic LED


ⓘ » 281

NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS


PLUS 48V




PLUS MINI 48V



PLUS 48V SHORT (-S)



PLUS MINI 48V SHORT (-S)



| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |

MATERIAL | AL | OPTICAL GLASS || OPTICAL PMMA

RAL ⓘ » 312


*RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓜ » 288



Magnetic 24V iO Micro_P.93
iO surface_P.126

Extended Family
iO 24V_P.183
iO_P.220



MORE INFO >>

| iO 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|------|-------|------|-------|--------|-----|
| A348-0- ① -10- WT NT WTW NTW -S | | 4,5W | 2700K | 20° | 500mA | 485 lm | 92% |
| A348-0- ① -11- WT NT WTW NTW -S | | 4,5W | 3000K | 20° | 500mA | 505 lm | 92% |
| A348-0- ① -20- WT NT WTW NTW -S | | 4,5W | 2700K | 30° | 500mA | 485 lm | 89% |
| A348-0- ① -21- WT NT WTW NTW -S | | 4,5W | 3000K | 30° | 500mA | 505 lm | 89% |
| A348-0- ① -30- WT NT WTW NTW -S | | 4,5W | 2700K | 56° | 500mA | 485 lm | 86% |
| A348-0- ① -31- WT NT WTW NTW -S | | 4,5W | 3000K | 56° | 500mA | 505 lm | 86% |

48 V | III IP20 | CRI>90 | L90B10 >55.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3480110WT |
| -S | Track 48V Short | A3480110WT-S |

OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECT THE LIGHTING PARAMETERS

iO Beam Mixer Diffuser 0805-01-00




iO Anti-glare Honeycomb Louver 0806-00-00 | WT | NT |



iO High Chromatic LED ⓘ » 281

| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |



MATERIAL | AL | PC |


RAL ⓘ » 312

*RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288



Extended Family
Zen Tube Surface_P.127
Zen Tube_P.230



MORE INFO >>

| | +RE | P | CCT | I | Flux | LOR |
|----------------|--|-----|-------|-------|---------|-----|
| ZEN TUBE 48V 1 | A341-11- ① -0- WT NT WTW NTW -S | 12W | 2700K | 350mA | 1580 lm | 90% |
| | A341-11- ① -1- WT NT WTW NTW -S | 12W | 3000K | 350mA | 1640 lm | 90% |
| ZEN TUBE 48V 2 | A341-12- ① -0- WT NT WTW NTW -S | 17W | 2700K | 500mA | 2130 lm | 90% |
| | A341-12- ① -1- WT NT WTW NTW -S | 17W | 3000K | 500mA | 2220 lm | 90% |
| ZEN TUBE 48V 3 | A341- ① -3- ① -0- WT NT WTW NTW -S | 23W | 2700K | 700mA | 3070 lm | 90% |
| | A341- ① -3- ① -1- WT NT WTW NTW -S | 23W | 3000K | 700mA | 3190 lm | 90% |

48 V | III IP20 | CRI>90 | L90B10 >55.000h





| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A3411110WT |
| -S | Track 48V Short | A3411110WT-S |

① BEAM OPTIONS

| | |
|---|-----|
| 1 | 16° |
| 2 | 24° |
| 3 | 42° |



| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |

MATERIAL | AL | GL-TRANS |

RAL ⓘ » 312

*RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288

48V SYSTEM
COCO 48V



MORE INFO >>

OPTIONAL ACCESSORIES

AFFECT THE LIGHTING PARAMETERS

COCO Anti-glare Honeycomb Louver

A498-90-00- | WT | NT |




COCO Anti-glare Screen

A498-90-01- | WT | NT |




COCO Linear Filter

A498-90-02- | WT | NT |



SIUTABLE FOR BEAM $\leq 34^\circ$

COCO High Chromatic Led  >> 281

NOT SOLD SEPARATELY

FINISHING Lamp Adaptor

| | | |
|-----|-----------------------------|----------------------------|
| WT | WT <input type="checkbox"/> | N <input type="checkbox"/> |
| NT | NT <input type="checkbox"/> | N <input type="checkbox"/> |
| WTW | WT <input type="checkbox"/> | W <input type="checkbox"/> |
| NTW | NT <input type="checkbox"/> | W <input type="checkbox"/> |

Extended Family
Magnetic 24V Coco_P.90

| COCO 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|------|-------|------|-------|---------|-----|
| A498-0- -10- WT NT WTW NTW -S | | 8,7W | 2700K | 20° | 500mA | 1200 lm | 87% |
| A498-0- -11- WT NT WTW NTW -S | | 8,7W | 3000K | 20° | 500mA | 1250 lm | 87% |
| A498-0- -12- WT NT WTW NTW -S | | 8,7W | 4000K | 20° | 500mA | 1340 lm | 87% |
| A498-0- -20- WT NT WTW NTW -S | | 8,7W | 2700K | 34° | 500mA | 1200 lm | 89% |
| A498-0- -21- WT NT WTW NTW -S | | 8,7W | 3000K | 34° | 500mA | 1250 lm | 89% |
| A498-0- -22- WT NT WTW NTW -S | | 8,7W | 4000K | 34° | 500mA | 1340 lm | 89% |
| A498-0- -30- WT NT WTW NTW -S | | 8,7W | 2700K | 48° | 500mA | 1200 lm | 86% |
| A498-0- -31- WT NT WTW NTW -S | | 8,7W | 3000K | 48° | 500mA | 1250 lm | 86% |
| A498-0- -32- WT NT WTW NTW -S | | 8,7W | 4000K | 48° | 500mA | 1340 lm | 86% |

48 V IP20 | CRI>90 | L80B10 > 66.000h



| COCO 48V Super Spot | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|----|-------|------|-------|--------|-----|
| A498-0- -00- WT NT WTW NTW -S | | 6W | 2700K | 12° | 500mA | 750 lm | 66% |
| A498-0- -01- WT NT WTW NTW -S | | 6W | 3000K | 12° | 500mA | 800 lm | 66% |
| A498-0- -02- WT NT WTW NTW -S | | 6W | 4000K | 12° | 500mA | 850 lm | 66% |

48 V IP20 | CRI>90 | L80B10 > 55.000h



| COCO 48V Tunable White | +RE | P | CCT | Beam | I | Flux | LOR |
|--|-----|------|------------|------|-------|---------|-----|
| A498-12-18- WT NT WTW NTW -S | | 8,5W | 2700-5000K | 28° | 500mA | 1010 lm | 85% |
| A498-12-28- WT NT WTW NTW -S | | 8,5W | 2700-5000K | 42° | 500mA | 1010 lm | 87% |
| A498-12-38- WT NT WTW NTW -S | | 8,5W | 2700-5000K | 54° | 500mA | 1010 lm | 84% |


48 V IP20 | CRI>90 | L80B10 > 55.000h



| | *OPTIONS |
|---|--------------|
| 1 | No DIM |
| 2 | DIM DALI |
| 7 | DIM ON BOARD |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| | Track 48V | A4980110WT |
| -S | Track 48V Short | A4980110WT-S |



MATERIAL AL | PC/PMMA |

RAL >> 312

OTHER CCT PLEASE CONSULT

*RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

>> 288



48V SYSTEM
FLIP 48V




Extended Family
Magnetic 24V Flip_P.91
Flip Recessed_P.96
Flip Surface_P.123



MORE INFO >>

| | | +RE | P | CCT | Beam | I | Flux | LOR |
|----------|---------------------------------------|-----|----|-------|------|-------|--------|-----|
| FLIP 48V | A489-0- ① -10- NT WT NTMG | -S | 6W | 2700K | 18° | 500mA | 640 lm | 89% |
| | A489-0- ① -11- NT WT NTMG | -S | 6W | 3000K | 18° | 500mA | 670 lm | 89% |
| | A489-0- ① -12- NT WT NTMG | -S | 6W | 4000K | 18° | 500mA | 720 lm | 89% |
| | A489-0- ① -20- NT WT NTMG WTW | -S | 6W | 2700K | 40° | 500mA | 640 lm | 84% |
| | A489-0- ① -21- NT WT NTMG WTW | -S | 6W | 3000K | 40° | 500mA | 670 lm | 84% |
| | A489-0- ① -22- NT WT NTMG WTW | -S | 6W | 4000K | 40° | 500mA | 720 lm | 84% |


48 V | III IP20 | CRI>90 | L80B10 >60.000h



| ① | OPTIONS* |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A4890110WT |
| -S | Track 48V Short | A4890110WT-S |



FINISHING Body Lampshade Adaptor

| | | | |
|------|------|------|-----|
| NT | NT ■ | N ■ | N ■ |
| WT | WT □ | N ■ | N ■ |
| NTMG | NT ■ | MG ■ | N ■ |
| WTW | WT □ | W □ | W □ |

OTHER FINISHING COMBINATIONS PLEASE CONSULT

MATERIAL | AL | ABS+PC

RAL ⓘ » 312

"THE INVISIBLE BLACK" IS ONLY AVAILABLE FOR WT, NT & NTMG COLOURS
*RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE
(AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288

48V SYSTEM
BLACK FOSTER 48V




Extended Family
Black Foster Micro_P.10
Black Foster_P.12
Black Foster Surface_P.104
Black Foster Suspension_P.133
Black Foster Micro 24V_P.180
Black Foster Custom_P.242

MORE INFO >>



| | | +RE | P | CCT | Beam | I | Flux | LOR |
|-------------------------|--------------------------------------|-----|-------|-------|------|-------|---------|-----|
| BLACK FOSTER 48V Tilt 5 | A481-40- ① -0- NT WT NTMG -S | | 10,5W | 2700K | 38° | 700mA | 950 lm | 92% |
| | A481-40- ① -1- NT WT NTMG -S | | 10,5W | 3000K | 38° | 700mA | 1050 lm | 92% |
| | A481-40- ① -2- NT WT NTMG -S | | 10,5W | 4000K | 38° | 700mA | 1250 lm | 92% |
| | A481-41- ① -0- NT WT NTMG -S | | 10,5W | 2700K | 19° | 700mA | 950 lm | 90% |
| | A481-41- ① -1- NT WT NTMG -S | | 10,5W | 3000K | 19° | 700mA | 1050 lm | 90% |
| | A481-41- ① -2- NT WT NTMG -S | | 10,5W | 4000K | 19° | 700mA | 1250 lm | 90% |


48 V | III IP20 | CRI>90 | L90B10 >102.000h



| ① | OPTIONS* |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| ∅ | Track 48V | A4814011WT |
| -S | Track 48V Short | A4814011WT-S |



| FINISHING | Body | Lampshade |
|-----------|------|-----------|
| NT | NT ■ | N ■ |
| WT | WT □ | N ■ |
| NTMG | NT ■ | MG ■ |

MATERIAL | AL | ABS+PC

RAL ⓘ » 312

*RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE
(AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓢ » 288

48V SYSTEM
BLACK FOSTER 48V



MORE INFO >>



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|-----------------------------|-------------------|----|-------|-------|--------|-----|
| BLACK FOSTER Micro 48V 5 | A416-20- 0-0- N | 7W | 2700K | 500mA | 775 lm | 87% |
| | A416-20- 0-1- N | 7W | 3000K | 500mA | 800 lm | 87% |
| | A416-20- 0-2- N | 7W | 4000K | 500mA | 850 lm | 87% |

48V | III | IP20 | CRI>90 | L90B10 >60.000h


MacAdam Step 3 | OPTIONS* | INCL | TRACK 48V | 37°

| | | P | CCT | I | Flux | LOR |
|------------------------------|-------------------|-----|-------|-------|---------|-----|
| BLACK FOSTER Micro 48V 10 | A416-50- 0-0- N | 14W | 2700K | 500mA | 1550 lm | 87% |
| | A416-50- 0-1- N | 14W | 3000K | 500mA | 1600 lm | 87% |
| | A416-50- 0-2- N | 14W | 4000K | 500mA | 1700 lm | 87% |

48V | III | IP20 | CRI>90 | L90B10 >60.000h

MacAdam Step 3 | OPTIONS* | INCL | TRACK 48V | 37°

- Ⓞ OPTIONS*
- | | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
- OTHER DIM OPTIONS PLEASE CONSULT



FINISHING | N ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

» 288

48V SYSTEM
LINE 48V



Extended Family
Line Suspension_P.154
Line Micro 24V_P.183




MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|---------------|------------------------|-------|-------|-------|---------|-----|
| LINE 500 48V | A376-10- 0-0- N WT | 10,5W | 2700K | 350mA | 1500 lm | 65% |
| | A376-10- 0-1- N WT | 10,5W | 3000K | 350mA | 1600 lm | 65% |
| | A376-10- 0-2- N WT | 10,5W | 4000K | 350mA | 1650 lm | 65% |
| LINE 1000 48V | A376-20- 0-0- N WT | 21W | 2700K | 700mA | 3000 lm | 65% |
| | A376-20- 0-1- N WT | 21W | 3000K | 700mA | 3200 lm | 65% |
| | A376-20- 0-2- N WT | 21W | 4000K | 700mA | 3300 lm | 65% |
| LINE 2000 48V | A376-30- 0-0- N WT | 42W | 2700K | 700mA | 6000 lm | 65% |
| | A376-30- 0-1- N WT | 42W | 3000K | 700mA | 6400 lm | 65% |
| | A376-30- 0-2- N WT | 42W | 4000K | 700mA | 6600 lm | 65% |

48V | III | IP20 | CRI>90 | L80B10 >60.000h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 48V | 98°

- Ⓞ *OPTIONS
- | | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
- OTHER DIM OPTIONS PLEASE CONSULT



FINISHING | N ■ | WT □ | MATERIAL | AL | PC | RAL ⓘ » 312

COLOURS MAY AFFECT THE LIGHTING PARAMETERS » 288



MORE INFO >>

| TOP 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|------|-------|------|-------|--------|-----|
| A339-0- ① -10- WT NT WTW NTW -S | | 6,5W | 2700K | 20° | 700mA | 610 lm | 92% |
| A339-0- ① -11- WT NT WTW NTW -S | | 6,5W | 3000K | 20° | 700mA | 640 lm | 92% |
| A339-0- ① -20- WT NT WTW NTW -S | | 6,5W | 2700K | 30° | 700mA | 610 lm | 89% |
| A339-0- ① -21- WT NT WTW NTW -S | | 6,5W | 3000K | 30° | 700mA | 640 lm | 89% |
| A339-0- ① -30- WT NT WTW NTW -S | | 6,5W | 2700K | 56° | 700mA | 610 lm | 86% |
| A339-0- ① -31- WT NT WTW NTW -S | | 6,5W | 3000K | 56° | 700mA | 640 lm | 86% |



48 V | III | IP20 | CRI>90 | L90B10 > 55.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| 0 | Track 48V | A3390110WT |
| -S | Track 48V Short | A3390110WT-S |



| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |

OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECT THE LIGHTING PARAMETERS

TOP Beam Mixer Diffuser 0805-01-00



TOP Anti-glare Honeycomb Louver 0807-00-00 | WT | NT |



TOP High Chromatic LED ⓘ » 281

MATERIAL | AL | PC |

RAL ⓘ » 312

+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓜ » 288



MORE INFO >>

| TOP Mini 48V | +RE | P | CCT | Beam | I | Flux | LOR |
|---|-----|------|-------|------|-------|--------|-----|
| A340-0- ① -10- WT NT WTW NTW -S | | 6,5W | 2700K | 20° | 700mA | 610 lm | 92% |
| A340-0- ① -11- WT NT WTW NTW -S | | 6,5W | 3000K | 20° | 700mA | 640 lm | 92% |
| A340-0- ① -20- WT NT WTW NTW -S | | 6,5W | 2700K | 30° | 700mA | 610 lm | 89% |
| A340-0- ① -21- WT NT WTW NTW -S | | 6,5W | 3000K | 30° | 700mA | 640 lm | 89% |
| A340-0- ① -30- WT NT WTW NTW -S | | 6,5W | 2700K | 56° | 700mA | 610 lm | 86% |
| A340-0- ① -31- WT NT WTW NTW -S | | 6,5W | 3000K | 56° | 700mA | 640 lm | 86% |



48 V | III | IP20 | CRI>90 | L90B10 > 55.000h



| ① | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| 0 | Track 48V | A3400110WT |
| -S | Track 48V Short | A3400110WT-S |



| FINISHING | Lamp | Adaptor |
|-----------|------------|---------|
| WT | WT □ N ■ | |
| NT | NT ■ N ■ | |
| WTW | WT □ W □ | |
| NTW | NT ■ W □ | |

OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY | AFFECT THE LIGHTING PARAMETERS

TOP Beam Mixer Diffuser 0805-01-00



TOP Anti-glare Honeycomb Louver 0807-00-00 | WT | NT |



TOP High Chromatic LED ⓘ » 281


MATERIAL | AL | PC |

RAL ⓘ » 312

+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

Ⓜ » 288

48V SYSTEM
WIZ 48V



MORE INFO >>

| WIZ 48V | +RE | P | CCT | I | Flux | LOR |
|--|-----|-------|-------|-------|---------|-----|
| A465-0- 00 -10- WT NT WTW NTW -S | | 12,4W | 2700K | 350mA | 1470 lm | 86% |
| A465-0- 00 -11- WT NT WTW NTW -S | | 12,4W | 3000K | 350mA | 1530 lm | 86% |
| A465-0- 00 -12- WT NT WTW NTW -S | | 12,4W | 4000K | 350mA | 1550 lm | 86% |

48 V | III | IP20 | CRI>90 | L90B10 >55.000h



| ⓪ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| +RE | REF. ENDING | EXAMPLE |
|-----|-----------------|--------------|
| 0 | Track 48V | A4650110WT |
| -S | Track 48V Short | A4650110WT-S |


OPTIONAL

WIZ High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS

FINISHING Body Lampshade Adaptor

| | | | |
|-----|------|-----|-----|
| WT | WT □ | N ■ | N ■ |
| NT | NT ■ | N ■ | N ■ |
| WTW | WT □ | N ■ | W □ |
| NTW | NT ■ | N ■ | W □ |




MATERIAL | AL | ABS+PC

RAL ⓘ » 312

+RE >> THE PRODUCTS FOR THE TRACK 48V SHORT, ADD "-S" AT THE END OF THE SALES REFERENCE (AFTER THE LETTERS WHICH INDICATE THE COLOUR OF THE PRODUCT).

⓪ » 288

48V SYSTEM
SPIN 48V



MORE INFO >>

Extended Family
Spin_P144
Spin Fancy Shape_P240

| SPIN 48V | P | CCT | Beam | I | Flux | LOR |
|---|------|-------|------|-------|--------|-----|
| A350- 00 - 00-00- WT NT MC MG WTW NTW MCW MGW | 6,5W | 2700K | 24° | 700mA | 600 lm | 86% |
| A350- 00 - 00-01- WT NT MC MG WTW NTW MCW MGW | 6,5W | 3000K | 24° | 700mA | 630 lm | 86% |
| A350- 00 - 00-10- WT NT MC MG WTW NTW MCW MGW | 6,5W | 2700K | 40° | 700mA | 600 lm | 84% |
| A350- 00 - 00-11- WT NT MC MG WTW NTW MCW MGW | 6,5W | 3000K | 40° | 700mA | 630 lm | 84% |

48 V | III | IP20 | CRI>90 | L90B10 >60.000h





| ⓪ | SUSPENSION DISTANCE |
|---|---------------------|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

ADJUSTMENT RANGE 2m

| ⓪ | OPTIONS* |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT

| OPTIONAL ACCESSORY |
|-----------------------|
| CORD Accessory |
| 0223-00-00- W N |



| FINISHING | Lamp | Adaptor | Cord |
|-----------|------|---------|------|
| WT | WT □ | N ■ | W □ |
| NT | NT ■ | N ■ | N ■ |
| MC | MC ■ | N ■ | N ■ |
| MG | MG ■ | N ■ | N ■ |
| WTW | WT □ | W □ | W □ |
| NTW | NT ■ | W □ | N ■ |
| MCW | MC ■ | W □ | W □ |
| MGW | MG ■ | W □ | W □ |

MATERIAL | AL | PMMA

RAL ⓘ » 312

⓪ » 288

48V SYSTEM
STICK 48V



Extended Family
Stick_P.142
Stick 24V_P.185
Stick Fancy Shape_P.237



MORE INFO >>

| STICK 48V | P | CCT | Beam | I | Flux | LOR |
|--|------|-------|------|-------|--------|-----|
| A40- ○ - ○ - ○ - ○ -10- WT NT MG WTW NTW MGW | 5,6W | 2700K | 18° | 500mA | 530 lm | 84% |
| A40- ○ - ○ - ○ - ○ -11- WT NT MG WTW NTW MGW | 5,6W | 3000K | 18° | 500mA | 570 lm | 84% |
| A40- ○ - ○ - ○ - ○ -20- WT NT MG WTW NTW MGW | 5,6W | 2700K | 31° | 500mA | 530 lm | 82% |
| A40- ○ - ○ - ○ - ○ -21- WT NT MG WTW NTW MGW | 5,6W | 3000K | 31° | 500mA | 570 lm | 82% |
| A40- ○ - ○ - ○ - ○ -30- WT NT MG WTW NTW MGW | 5,6W | 2700K | 42° | 500mA | 530 lm | 84% |
| A40- ○ - ○ - ○ - ○ -31- WT NT MG WTW NTW MGW | 5,6W | 3000K | 42° | 500mA | 570 lm | 84% |

48 V | IP20 | CRI>90 | L90B10 > 108.000h



| ○ | STICK LENGTH |
|---|-----------------|
| 7 | STICK 22 220 mm |
| 8 | STICK 44 440 mm |
| 9 | STICK 66 660 mm |

| ⊖ | CORD LENGTH-L |
|---|---------------|
| 0 | 2 m |
| 2 | 5 m |


| ⊖ | OPTIONS* |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT


OPTIONAL ACCESSORY

CORD Accessory

0223-00-00- | N |



| FINISHING | Lamp | Adaptor |
|-----------|--|---------|
| WT | WT <input type="checkbox"/> N <input type="checkbox"/> | |
| NT | NT <input type="checkbox"/> N <input type="checkbox"/> | |
| MG | MG <input type="checkbox"/> N <input type="checkbox"/> | |
| WTW | WT <input type="checkbox"/> W <input type="checkbox"/> | |
| NTW | NT <input type="checkbox"/> W <input type="checkbox"/> | |
| MGW | MG <input type="checkbox"/> W <input type="checkbox"/> | |



MATERIAL | AL | ABS+PC |

RAL » 312

» 288

48V SYSTEM
HOLLY 48V



Extended Family
Holly_P.143
Holly Fancy Shape_P.241



MORE INFO >>

| HOLLY 48V | P | CCT | Beam | I | Flux | LOR |
|--|------|-------|------|-------|--------|-----|
| A349- ⊖ - ⊖ - ⊖ -00- WT NT MC MG WTW NTW MCW MGW | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| A349- ⊖ - ⊖ - ⊖ -01- WT NT MC MG WTW NTW MCW MGW | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| A349- ⊖ - ⊖ - ⊖ -10- WT NT MC MG WTW NTW MCW MGW | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| A349- ⊖ - ⊖ - ⊖ -11- WT NT MC MG WTW NTW MCW MGW | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |

48 V | IP20 | CRI>90 | L90B10 > 102.000h



| ⊖ | SUSPENSION DISTANCE |
|---|---------------------|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

ADJUSTMENT RANGE 2m


| ⊖ | OPTIONS* |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OTHER DIM OPTIONS PLEASE CONSULT


OPTIONAL ACCESSORY

CORD Accessory

0223-00-00- | W | N |



| FINISHING | Lamp | Adaptor | Cord |
|-----------|---|---------|------|
| WT | WT <input type="checkbox"/> N <input type="checkbox"/> W <input type="checkbox"/> | | |
| NT | NT <input type="checkbox"/> N <input type="checkbox"/> W <input type="checkbox"/> | | |
| MC | MC <input type="checkbox"/> N <input type="checkbox"/> W <input type="checkbox"/> | | |
| MG | MG <input type="checkbox"/> N <input type="checkbox"/> W <input type="checkbox"/> | | |
| WTW | WT <input type="checkbox"/> W <input type="checkbox"/> W <input type="checkbox"/> | | |
| NTW | NT <input type="checkbox"/> W <input type="checkbox"/> W <input type="checkbox"/> | | |
| MCW | MC <input type="checkbox"/> W <input type="checkbox"/> W <input type="checkbox"/> | | |
| MGW | MG <input type="checkbox"/> W <input type="checkbox"/> W <input type="checkbox"/> | | |





MATERIAL | AL | PC |

RAL » 312

» 288

TRACK SYSTEM
TRACK 1L

TRACK SYSTEM
TRACK 3L



iO
4,5W
2700 / 3000 / 4000 K
485 - 520 Lm
20 / 30 / 56° BEAM
86 - 92 % LOR

PLUS MINI 1L
4,5W
2700 / 3000 / 4000 K
480 - 515 Lm
10 - 41° BEAM
20 - 40 % LOR

FIT 65 1L
10,3W
3000 / 4000 K
1300 / 1320 Lm
18 / 26 / 36° BEAM
84 - 90 % LOR

SIX
M / L
11,5 - 24,5 W
2700 / 3000 / 4000 K
1600 - 3000 Lm
17 - 38° BEAM
90 - 93 % LOR

PLUS
PLUS MINI / PLUS
4,5 / 10,4 W
2700 / 3000 / 4000 K
480 - 1330 Lm
10 - 14° / 12 - 51° BEAM
20 - 40 % LOR

ZEN TUBE
12 / 17 / 23 W
3000 / 4000 K
1640 - 3240 Lm
16 / 24 / 42° BEAM
90% LOR


FIT
65 / 80
10,3 / 19 W
3000 / 4000 K
1300 - 2540 Lm
18 - 37° BEAM
84 - 93 % LOR

THOR
27 / 36 W
3000 / 4000 K
3750 - 4820 Lm
17 / 28 / 40° BEAM
90% LOR

SURFACE & SUSPENDED




MORE INFO >>




| | |
|-------------|---------------------|
| TRACK 1L 1m | A264-01-00- B N |
| TRACK 1L 2m | A264-02-00- B N |
| TRACK 1L 3m | A264-03-00- B N |




POLARITY
GROOVE




| | |
|-----------------------------|---------------------|
| TRACK 1L Live-End Connector | A264-00-01- B N |
| A264-00-02- B N | |




| | |
|----------------------------|---------------------|
| TRACK 1L Central Connector | A264-00-03- B N |
|----------------------------|---------------------|




| | |
|---------------------|---------------------|
| TRACK 1L 90° Angle | A264-00-06- B N |
| A264-00-07- B N | |



| | |
|---------------------------|---------------------|
| TRACK 1L Corner Connector | A264-00-15- B N |
|---------------------------|---------------------|




| | |
|---------------------|---------------------|
| TRACK 1L T-Joint | A264-00-16- B N |
| A264-00-17- B N | |




| | |
|------------------------|---------------------|
| TRACK 1L Contact Joint | A264-00-04- B N |
|------------------------|---------------------|



| | |
|--------------|---------------------|
| TRACK 1L End | A264-00-13- B N |
|--------------|---------------------|



| | |
|-------------------------|-----------------------|
| TRACK 1L Suspension Kit | A264-00-14- WT NT |
| At least 2 units needed | |



*minimum distance (mm.)


COLOUR | B □ | N ■ | WT □ | NT ■ |

RAL ⓘ » 312

FLUSH MOUNTING




MORE INFO >>




| | |
|-------------------|---------------------|
| TRACK 1L FLUSH 1m | A264-11-00- B N |
| TRACK 1L FLUSH 2m | A264-12-00- B N |
| TRACK 1L FLUSH 3m | A264-13-00- B N |



POLARITY
GROOVE




| | |
|-----------------------------------|---------------------|
| TRACK 1L FLUSH Live-End Connector | A264-00-01- B N |
| A264-00-02- B N | |



| | |
|----------------------------|---------------------|
| TRACK 1L FLUSH Cover Plate | A264-10-19- B N |
| Mandatory for installation | |


| | |
|----------------------------------|---------------------|
| TRACK 1L FLUSH Central Connector | A264-00-03- B N |
|----------------------------------|---------------------|

| | |
|-----------------------------------|---------------------|
| TRACK 1L FLUSH Corner Cover Plate | A264-10-20- B N |
| Mandatory for installation | |




| | |
|--------------------------|---------------------|
| TRACK 1L FLUSH 90° Angle | A264-00-06- B N |
| A264-00-07- B N | |

| | |
|-----------------------------------|---------------------|
| TRACK 1L FLUSH Corner Cover Plate | A264-10-20- B N |
| Mandatory for installation | |




| | |
|------------------------|---------------------|
| TRACK 1L FLUSH T-Joint | A264-00-16- B N |
| A264-00-17- B N | |

| | |
|-----------------------------------|---------------------|
| TRACK 1L FLUSH Corner Cover Plate | A264-10-20- B N |
| Mandatory for installation | |




| | |
|------------------------------|---------------------|
| TRACK 1L FLUSH Contact Joint | A264-00-04- B N |
|------------------------------|---------------------|



| | |
|--------------------|---------------------|
| TRACK 1L FLUSH End | A264-00-13- B N |
|--------------------|---------------------|



| | |
|--------------------------------|------------|
| TRACK 1L FLUSH Suspension Kit | A264-10-15 |
| For wire 1,5 mm (Not Included) | |



*minimum distance (mm.)

COLOUR | B □ | N ■ |

RAL ⓘ » 312

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)



Magnetic 24V iO Micro_P.93
iO surface_P.126

Extended Family
iO 24V_P.183
iO 48V_P.202



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----|-----------------------|------|-------|------|-------|--------|-----|
| iO | A262-00-10- WT NT | 4,5W | 2700K | 20° | 500mA | 485 lm | 92% |
| | A262-00-11- WT NT | 4,5W | 3000K | 20° | 500mA | 505 lm | 92% |
| | A262-00-12- WT NT | 4,5W | 4000K | 20° | 500mA | 520 lm | 92% |
| | A262-00-20- WT NT | 4,5W | 2700K | 30° | 500mA | 485 lm | 89% |
| | A262-00-21- WT NT | 4,5W | 3000K | 30° | 500mA | 505 lm | 89% |
| | A262-00-22- WT NT | 4,5W | 4000K | 30° | 500mA | 520 lm | 89% |
| | A262-00-30- WT NT | 4,5W | 2700K | 56° | 500mA | 485 lm | 86% |
| | A262-00-31- WT NT | 4,5W | 3000K | 56° | 500mA | 505 lm | 86% |
| | A262-00-32- WT NT | 4,5W | 4000K | 56° | 500mA | 520 lm | 86% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS


iO Beam Mixer Diffuser 0805-01-00



iO Anti-glare Honeycomb Louver 0806-00-00 | WT | NT |



iO High Chromatic LED ⓘ » 281



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

TRACK 1L ⓘ » 218

PLUS MINI 1L



Magnetic 24V Plus Micro_P.94
Plus Recessed_P.101
Plus 24V_P.182



Extended Family
Plus 48V_P.201
Plus_P.229
Black Foster Plus Mini_P.246



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|--------------|-----------------------|------|-------|---------|-------|--------|--------|
| PLUS Mini 1L | A327-00-20- WT NT | 4,5W | 2700K | 10°-41° | 500mA | 480 lm | 20-40% |
| | A327-00-21- WT NT | 4,5W | 3000K | 10°-41° | 500mA | 500 lm | 20-40% |
| | A327-00-22- WT NT | 4,5W | 4000K | 10°-41° | 500mA | 515 lm | 20-40% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



OPTIONAL

PLUS MINI High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS



FIT 65 1L

Magnetic 24V Fit_P.92
Fit Recessed_P.100

Fit Surface_P.124
Fit 24V_P.184
Fit 48V_P.197


Extended Family
Fit_P.228
Black Foster Fit 35_P.246
Black Foster Fit 27_P.249



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|-----------|-----------------------|-------|-------|------|-------|---------|-----|
| FIT 65 1L | A366-01-11- WT NT | 10,3W | 3000K | 18° | 300mA | 1300 lm | 90% |
| | A366-01-12- WT NT | 10,3W | 4000K | 18° | 300mA | 1320 lm | 90% |
| | A366-01-21- WT NT | 10,3W | 3000K | 26° | 300mA | 1300 lm | 88% |
| | A366-01-22- WT NT | 10,3W | 4000K | 26° | 300mA | 1320 lm | 88% |
| | A366-01-31- WT NT | 10,3W | 3000K | 36° | 300mA | 1300 lm | 84% |
| | A366-01-32- WT NT | 10,3W | 4000K | 36° | 300mA | 1320 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



OPTIONAL ACCESSORY

FIT 65 Anti-glare Honeycomb Louver A356-00-00

NOT SOLD SEPARATELY
AFFECTS THE LIGHTING PARAMETERS




COLOUR | WT □ | NT ■ | MATERIAL | AL | OPTICAL PMMA |

TRACK 1L ⓘ » 218

COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

TRACK SYSTEM TRACK 3L

TRACK 3L SURFACE & SUSPENDED



MORE INFO >>

| | |
|-------------|---------------------|
| TRACK 3L 1m | A282-01-00- B N |
| TRACK 3L 2m | A282-02-00- B N |
| TRACK 3L 3m | A282-03-00- B N |



WEIGHT BEAR CAPACITY


Distancia de fijación y capacidad de carga.
Distancia fijación recomendada l- 1000 mm.

Fastening distance and loading capacity.
Recommended fastening distance l- 1000 mm.

Distance de fixation et capacité de charge.
Distance de fixation recommandée l- 1000 mm.


Distanza di installazione e capacità di carico.
Distanza consigliata di fissazione l- 1000 mm.

Befestigungsabstand und Belastbarkeit.
Empfohlener Abstand l- 1000 mm.



*minimum distance [mm.]

TRACK 3L FLUSH MOUNTING*



MORE INFO >>

| | |
|-------------------|---------------------|
| TRACK 3L FLUSH 1m | A282-11-00- B N |
| TRACK 3L FLUSH 2m | A282-12-00- B N |
| TRACK 3L FLUSH 3m | A282-13-00- B N |



OPTIONAL ACCESSORIES


FIT MODEL: ACCESSORIES ONLY IN BLACK FINISH
SIX MODEL: ACCESSORIES NOT AVAILABLE

TRACKLIGHT Surface Adapter

| |
|-----------------|
| 0000-55-43- W |
| 0000-55-39- N |



NO DIM



TRACKLIGHT Recessed Adapter


| |
|-----------------|
| 0000-55-44- W |
| 0000-55-40- N |



NO DIM Ø105




SURFACE & SUSPENDED



POLARITY GROOVE


| |
|---------------------|
| A282-00-01- B N |
| A282-00-02- B N |




| |
|----------------------------|
| TRACK 3L Central Connector |
| A282-00-03- B N |




| |
|-----------------------|
| TRACK 3L Fixation Kit |
| A219-21-06- B N |




| |
|--------------------------|
| TRACK 3L Universal Angle |
| A282-00-15- B N |



| |
|---------------------|
| TRACK 3L 90° Angle |
| A282-00-06- B N |
| A282-00-07- B N |



| |
|---------------------|
| TRACK 3L T Joint |
| A282-00-16- B N |
| A282-00-17- B N |




| |
|---------------------------|
| TRACK 3L Mechanical Joint |
| A219-21-11- B N |




| |
|-------------------------|
| TRACK 3L Suspension Kit |
| A219-21-10- B N |
| At least 2 units needed |

FLUSH MOUNTING*




POLARITY GROOVE

| |
|---------------------|
| A282-00-01- B N |
| A282-00-02- B N |



| |
|----------------------------|
| TRACK 3L FLUSH Cover Plate |
| A282-10-19- B N |


Mandatory for installation



| |
|----------------------------|
| TRACK 3L Central Connector |
| A282-00-03- B N |

| |
|----------------------------|
| TRACK 3L FLUSH Cover Plate |
| A282-10-19- B N |


Mandatory for installation



| |
|---------------------|
| TRACK 3L 90° Angle |
| A282-00-06- B N |
| A282-00-07- B N |

| |
|-----------------------------------|
| TRACK 3L FLUSH Corner Cover Plate |
| A282-10-20- B N |

Mandatory for installation




| |
|---------------------|
| TRACK 3L T Joint |
| A282-00-16- B N |
| A282-00-17- B N |

| |
|-----------------------------------|
| TRACK 3L FLUSH Corner Cover Plate |
| A282-10-20- B N |

Mandatory for installation


SURFACE & SUSP. / FLUSH MOUNTING




| |
|---------------------|
| TRACK Contact Joint |
| A282-00-04- B N |



| |
|---------------------|
| TRACK End |
| A219-20-02- B N |



| |
|----------------------------|
| TRACK Clamp Kit for M6 ROD |
| A219-21-21- B |



| |
|--------------------|
| TRACK Bending Tool |
| A282-00-00 |


For tracks its length has been modified

COLOUR | B □ | N ■ | W □ |

RAL ⓘ » 312

* RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)

TRACK 3L SURFACE & SUSPENDED



MORE INFO >>

| | |
|-------------|---------------------|
| TRACK 3L 1m | A219-21-01- B N |
| TRACK 3L 2m | A219-21-02- B N |
| TRACK 3L 3m | A219-21-03- B N |



WEIGHT BEAR CAPACITY

Distancia de fijación y capacidad de carga.

Distancia fijación recomendada l- 1000 mm.

Fastening distance and loading capacity.

Recommended fastening distance l- 1000 mm.

Distance de fixation et capacité de charge.


Distance de fixation recommandée l- 1000 mm.

Distanza di installazione e capacità di carico.

Distanza consigliata di fissazione l- 1000 mm.


Befestigungsabstand und Belastbarkeit.

Empfohlener Abstand l- 1000 mm.



*minimum distance [mm.]

TRACK 3L FLUSH MOUNTING*




MORE INFO >>

| | |
|-------------------|---------------------|
| TRACK 3L FLUSH 1m | A219-22-01- B N |
| TRACK 3L FLUSH 2m | A219-22-02- B N |
| TRACK 3L FLUSH 3m | A219-22-03- B N |



SURFACE & SUSPENDED




POLARITY GROOVE



TRACK 3L Live-End Connector

A219-21-04- | B | N |

A219-21-12- | B | N |




TRACK 3L Central Connector

A219-21-05- | B | N |




TRACK 3L Fixation Kit

A219-21-06- | B | N |



TRACK 3L Universal Angle


A219-21-07- | B | N |



TRACK 3L 90° Angle

A219-21-08- | B | N |


A219-21-13- | B | N |



TRACK 3L T Joint


A219-21-09- | B | N |

A219-21-14- | B | N |



TRACK 3L Mechanical Joint

A219-21-11- | B | N |




TRACK 3L Suspension Kit

A219-21-10- | B | N |

At least 2 units needed

FLUSH MOUNTING*



POLARITY GROOVE



TRACK 3L FLUSH Live-End Connector


A219-21-04- | B | N |

A219-21-12- | B | N |

TRACK 3L FLUSH Cover Plate

A219-22-10- | B | N |

Mandatory for installation



TRACK 3L FLUSH Central Connector

A219-21-05- | B | N |

TRACK 3L FLUSH COVER Plate


A219-22-10- | B | N |

Mandatory for installation



TRACK 3L FLUSH Ceiling Kit


A219-22-06- | B |



TRACK 3L FLUSH 90° Angle

A219-21-08- | B | N |

A219-21-13- | B | N |



TRACK 3L FLUSH Corner Cover Plate

A219-22-11- | B | N |

Mandatory for installation

TRACK 3L T Joint

A219-21-09- | B | N |


A219-21-14- | B | N |

TRACK 3L FLUSH Corner Cover Plate

A219-22-11- | B | N |

Mandatory for installation

SURFACE & SUSP. / FLUSH MOUNTING



TRACK Contact Joint

A219-20-01- | B | N |




TRACK End

A219-20-02- | B | N |



TRACK Clamp Kit for M6 ROD

A219-21-21- | B |



TRACK Bending Tool

A282-00-00

For tracks its length has been modified

COLOUR | B □ | N ■ |

RAL ⓘ » 312

* RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)



MORE INFO >>


| | | P | CCT | Beam | I | Flux | LOR |
|--------------------------|-----------------------|--------------------------|-------|-------|-------|---------|---------|
| SIX L 1 | A286-11-10- WT NT | 11,5W | 2700K | 17° | 350mA | 1600 lm | 93% |
| | A286-11-11- WT NT | 11,5W | 3000K | 17° | 350mA | 1650 lm | 93% |
| | A286-11-12- WT NT | 11,5W | 4000K | 17° | 350mA | 1700 lm | 93% |
| | A286-11-30- WT NT | 11,5W | 2700K | 26° | 350mA | 1600 lm | 93% |
| | A286-11-31- WT NT | 11,5W | 3000K | 26° | 350mA | 1650 lm | 93% |
| | A286-11-32- WT NT | 11,5W | 4000K | 26° | 350mA | 1700 lm | 93% |
| | A286-11-20- WT NT | 11,5W | 2700K | 34° | 350mA | 1600 lm | 90% |
| | A286-11-21- WT NT | 11,5W | 3000K | 34° | 350mA | 1650 lm | 90% |
| | A286-11-22- WT NT | 11,5W | 4000K | 34° | 350mA | 1700 lm | 90% |
| | SIX L 2 | A286-2- Ⓞ -10- WT NT | 24,5W | 2700K | 17° | 700mA | 2850 lm |
| A286-2- Ⓞ -11- WT NT | | 24,5W | 3000K | 17° | 700mA | 2950 lm | 93% |
| A286-2- Ⓞ -12- WT NT | | 24,5W | 4000K | 17° | 700mA | 3000 lm | 93% |
| A286-2- Ⓞ -30- WT NT | | 24,5W | 2700K | 26° | 700mA | 2850 lm | 93% |
| A286-2- Ⓞ -31- WT NT | | 24,5W | 3000K | 26° | 700mA | 2950 lm | 93% |
| A286-2- Ⓞ -32- WT NT | | 24,5W | 4000K | 26° | 700mA | 3000 lm | 93% |
| A286-2- Ⓞ -20- WT NT | | 24,5W | 2700K | 34° | 700mA | 2850 lm | 90% |
| A286-2- Ⓞ -21- WT NT | | 24,5W | 3000K | 34° | 700mA | 2950 lm | 90% |
| A286-2- Ⓞ -22- WT NT | | 24,5W | 4000K | 34° | 700mA | 3000 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| Ⓞ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 4 | DIM DALI |

OPTIONAL
SIX L High Chromatic LED ⓘ » 281
 NOT SOLD SEPARATELY
 AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | TRACK 3L ⓘ » 222

Ⓞ ⓘ » 288



MORE INFO >>


| | | P | CCT | Beam | I | Flux | LOR | |
|--------------------------|-----------------------|--------------------------|-------|-------|-------|---------|---------|-----|
| SIX M 1 | A331-11-10- WT NT | 11,5W | 2700K | 19° | 350mA | 1600 lm | 93% | |
| | A331-11-11- WT NT | 11,5W | 3000K | 19° | 350mA | 1650 lm | 93% | |
| | A331-11-12- WT NT | 11,5W | 4000K | 19° | 350mA | 1700 lm | 93% | |
| | A331-11-20- WT NT | 11,5W | 2700K | 28° | 350mA | 1600 lm | 91% | |
| | A331-11-21- WT NT | 11,5W | 3000K | 28° | 350mA | 1650 lm | 91% | |
| | A331-11-22- WT NT | 11,5W | 4000K | 28° | 350mA | 1700 lm | 91% | |
| | A331-11-30- WT NT | 11,5W | 2700K | 38° | 350mA | 1600 lm | 93% | |
| | A331-11-31- WT NT | 11,5W | 3000K | 38° | 350mA | 1650 lm | 93% | |
| | A331-11-32- WT NT | 11,5W | 4000K | 38° | 350mA | 1700 lm | 93% | |
| | SIX M 2 | A331-2- Ⓞ -10- WT NT | 17W | 2700K | 19° | 500mA | 2050 lm | 93% |
| | | A331-2- Ⓞ -11- WT NT | 17W | 3000K | 19° | 500mA | 2130 lm | 93% |
| | | A331-2- Ⓞ -12- WT NT | 17W | 4000K | 19° | 500mA | 2160 lm | 93% |
| A331-2- Ⓞ -20- WT NT | | 17W | 2700K | 28° | 500mA | 2050 lm | 91% | |
| A331-2- Ⓞ -21- WT NT | | 17W | 3000K | 28° | 500mA | 2130 lm | 91% | |
| A331-2- Ⓞ -22- WT NT | | 17W | 4000K | 28° | 500mA | 2160 lm | 91% | |
| A331-2- Ⓞ -30- WT NT | | 17W | 2700K | 38° | 500mA | 2050 lm | 93% | |
| A331-2- Ⓞ -31- WT NT | | 17W | 3000K | 38° | 500mA | 2130 lm | 93% | |
| A331-2- Ⓞ -32- WT NT | | 17W | 4000K | 38° | 500mA | 2160 lm | 93% | |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| Ⓞ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OPTIONAL
SIX M High Chromatic LED ⓘ » 281
 NOT SOLD SEPARATELY
 AFFECTS THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | TRACK 3L ⓘ » 222

Ⓞ ⓘ » 288



Magnetic 24V Fit_P.92
Fit Recessed_P.100

Fit Surface_P.124
Fit 24V_P.184
Fit 48V_P.197

Extended Family
Fit 65 1L_P.221
Black Foster Fit 35_P.246
Black Foster Fit 27_P.249



MORE INFO >>



MORE INFO >>

| ⊗ | *OPTIONS |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |

OPTIONAL ACCESSORIES

FIT 80 Anti-glare Honeycomb Louver
A357-00-00

FIT 65 Anti-glare Honeycomb Louver
A356-00-00

NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS



| | | P | CCT | Beam | I | Flux | LOR |
|--------|-------------------------|-----|-------|------|-------|---------|-----|
| FIT 80 | A357-0-⊗ -11- WT NT | 19W | 3000K | 19° | 550mA | 2500 lm | 90% |
| | A357-0-⊗ -12- WT NT | 19W | 4000K | 19° | 550mA | 2540 lm | 90% |
| | A357-0-⊗ -21- WT NT | 19W | 3000K | 28° | 550mA | 2500 lm | 84% |
| | A357-0-⊗ -22- WT NT | 19W | 4000K | 28° | 550mA | 2540 lm | 84% |
| | A357-0-⊗ -31- WT NT | 19W | 3000K | 37° | 550mA | 2500 lm | 85% |
| | A357-0-⊗ -32- WT NT | 19W | 4000K | 37° | 550mA | 2540 lm | 85% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | OPTIONS* | INCL | TRACK 3L | 360° | 90° | 19°/28°/37°

| | | P | CCT | Beam | I | Flux | LOR |
|--------|-----------------------|-------|-------|------|-------|---------|-----|
| FIT 65 | A356-01-11- WT NT | 10,3W | 3000K | 18° | 300mA | 1300 lm | 90% |
| | A356-01-12- WT NT | 10,3W | 4000K | 18° | 300mA | 1320 lm | 90% |
| | A356-01-21- WT NT | 10,3W | 3000K | 26° | 300mA | 1300 lm | 88% |
| | A356-01-22- WT NT | 10,3W | 4000K | 26° | 300mA | 1320 lm | 88% |
| | A356-01-31- WT NT | 10,3W | 3000K | 36° | 300mA | 1300 lm | 84% |
| | A356-01-32- WT NT | 10,3W | 4000K | 36° | 300mA | 1320 lm | 84% |


220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | INCL | TRACK 3L | 360° | 90° | 18°/26°/36°

| | | P | CCT | Beam | I | Flux | LOR |
|--------|-------------------------|-------|-------|------|-------|---------|-----|
| FIT 65 | A356-0-⊗ -11- WT NT | 10,3W | 3000K | 18° | 300mA | 1300 lm | 90% |
| | A356-0-⊗ -12- WT NT | 10,3W | 4000K | 18° | 300mA | 1320 lm | 90% |
| | A356-0-⊗ -21- WT NT | 10,3W | 3000K | 26° | 300mA | 1300 lm | 88% |
| | A356-0-⊗ -22- WT NT | 10,3W | 4000K | 26° | 300mA | 1320 lm | 88% |
| | A356-0-⊗ -31- WT NT | 10,3W | 3000K | 36° | 300mA | 1300 lm | 84% |
| | A356-0-⊗ -32- WT NT | 10,3W | 4000K | 36° | 300mA | 1320 lm | 84% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | DALI | INCL | TRACK 3L | 360° | 90° | 18°/26°/36°



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | TRACK 3L ⓘ » 222

Ⓜ » 288



Magnetic 24V Plus Micro_P.94
Plus Recessed_P.101
Plus 24V_P.182

Extended Family
Plus 48V_P.201
Plus Mini 1L_P.221
Black Foster Plus Mini_P.246



MORE INFO >>



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|------|-----------------------|-------|-------|---------|-------|---------|--------|
| PLUS | A324-00-00- WT NT | 10,4W | 2700K | 12°-51° | 300mA | 1260 lm | 26-40% |
| | A324-00-01- WT NT | 10,4W | 3000K | 12°-51° | 300mA | 1310 lm | 26-40% |
| | A324-00-02- WT NT | 10,4W | 4000K | 12°-51° | 300mA | 1330 lm | 26-40% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | INCL | TRACK 3L | 350° | 180° | 12°-51°

| | | P | CCT | Beam | I | Flux | LOR |
|-----------|-----------------------|------|-------|---------|-------|--------|--------|
| PLUS Mini | A327-00-10- WT NT | 4,5W | 2700K | 10°-41° | 500mA | 480 lm | 20-40% |
| | A327-00-11- WT NT | 4,5W | 3000K | 10°-41° | 500mA | 500 lm | 20-40% |
| | A327-00-12- WT NT | 4,5W | 4000K | 10°-41° | 500mA | 515 lm | 20-40% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h

MacAdam Step 2 | INCL | TRACK 3L | 350° | 180° | 10°-41°

OPTIONAL

PLUS High Chromatic LED ⓘ » 281

PLUS MINI High Chromatic LED ⓘ » 281

NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS



COLOUR | WT □ | NT ■ | MATERIAL | AL | OPTICAL GLASS | TRACK 3L ⓘ » 222

Ⓜ » 288

TRACK SYSTEM
ZEN TUBE



Extended Family
Zen Tube Surface_P.127
Zen Tube 48V_P.203



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------|--------------------------|-----|-------|-------|---------|-----|
| ZEN TUBE 1 | A284-21- Ⓞ -1- WT NT | 12W | 3000K | 350mA | 1640 lm | 90% |
| | A284-21- Ⓞ -2- WT NT | 12W | 4000K | 350mA | 1670 lm | 90% |
| ZEN TUBE 2 | A284-22- Ⓞ -1- WT NT | 17W | 3000K | 500mA | 2220 lm | 90% |
| | A284-22- Ⓞ -2- WT NT | 17W | 4000K | 500mA | 2250 lm | 90% |
| ZEN TUBE 3 | A284-23- Ⓞ -1- WT NT | 23W | 3000K | 700mA | 3190 lm | 90% |
| | A284-23- Ⓞ -2- WT NT | 23W | 4000K | 700mA | 3240 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| Ⓞ | BEAM OPTIONS |
|---|--------------|
| 1 | 16° |
| 2 | 24° |
| 3 | 42° |

OPTIONAL ACCESSORIES

NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS

ZEN Anti-glare Honeycomb Louver 0702-02-00




ZEN Elliptical Refractor 0700-08-00



ZEN Beam Mixer Diffuser 0805-02-00



ZEN High Chromatic LED ⓘ » 281



COLOUR | WT □ | NT ■ |

MATERIAL | AL | GL-TRANS |

TRACK 3L ⓘ » 222

OTHER CCT PLEASE CONSULT

Ⓞ » 288


TRACK 3L SYSTEM
THOR



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------|--------------------------|-----|-------|--------|---------|-----|
| THOR 1 | A226-11- Ⓞ -1- WT NT | 27W | 3000K | 800mA | 3750 lm | 90% |
| | A226-11- Ⓞ -2- WT NT | 27W | 4000K | 800mA | 3820 lm | 90% |
| THOR 2 | A226-21- Ⓞ -1- WT NT | 36W | 3000K | 1050mA | 4750 lm | 90% |
| | A226-21- Ⓞ -2- WT NT | 36W | 4000K | 1050mA | 4820 lm | 90% |
| DALI | A226-24- Ⓞ -1- WT NT | 36W | 3000K | 1050mA | 4750 lm | 90% |
| | A226-24- Ⓞ -2- WT NT | 36W | 4000K | 1050mA | 4820 lm | 90% |

220 V~ | IP20 | CRI>90 | L90B10 >55.000h



| Ⓞ | BEAM OPTIONS |
|---|--------------|
| 1 | 17° |
| 2 | 28° |
| 3 | 40° |

OPTIONAL ACCESSORIES

AFFECT THE LIGHTING PARAMETERS

THOR Anti-glare Screen 0802-00-00- | WT |
0802-00-00- | NT |



THOR Beam Mixer Diffuser 0805-03-00

NOT SOLD SEPARATELY



THOR Anti-glare Honeycomb Louver 0802-02-00

NOT SOLD SEPARATELY



THOR Elliptical Refractor 0802-04-00

NOT SOLD SEPARATELY



THOR High Chromatic Led ⓘ » 281

NOT SOLD SEPARATELY

COLOUR | WT □ | NT ■ |

MATERIAL | AL | GL-TRANS |

TRACK 3L ⓘ » 222

OTHER CCT PLEASE CONSULT

Ⓞ » 288

FANCY SHAPE_234

BLACK FOSTER CUSTOM_242

BLACK FOSTER CUSTOM SYSTEM_248

BLACK FOSTER MICRO

CUSTOM SURFACE_254

BRIGHT LINE_258


FIFTY+ CUSTOM_261






EL SISTEMA FANCY SHAPE PERMITE CREAR DISTINTAS CONFIGURACIONES DE PRODUCTO COMBINADAS EN UNA MISMA BASE. EN EL ESQUEMA SE MUESTRAN LAS COMPATIBILIDADES ENTRE PRODUCTOS MONTADOS EN UNA MISMA BASE. EN PROYECTOS AD HOC SE PUEDEN CREAR COMBINACIONES INFINITAS SIN LIMITACIONES DE COMPATIBILIDAD MÁS ALLÁ DE LAS SUGERIDAS EN LA ILUSTRACIÓN.

COMPATIBILITY



SPIN HOLLY TOP



ALASKA STICK



ALASKA BIG

FANCY SHAPE BASES

○ Ø 155 | Max. 2 Luminaires

○ Ø 270 | Max. 6 Luminaires

○ Ø 330 | Max. 12 Luminaires

○ Ø 155 | Max. 2 Luminaires

○ Ø 270 | Max. 6 Luminaires

○ Ø 330 | Max. 12 Luminaires

○ Ø 155 | Max. 2 Luminaires

○ Ø 270 | Max. 3 Luminaires

○ Ø 330 | Max. 6 Luminaires

The Fancy Shape system allows for the creation of different product configurations combined on the same base. The diagram shows the compatibilities between products assembled on the same base. In *ad hoc* projects, infinite combinations can be created with no compatibility limitations beyond those suggested in the image.

Le système Fancy Shape permet de créer différentes configurations de produits regroupées sur une même base. Le schéma indique la compatibilité entre produits montés sur une même base. Les projets *ad hoc* permettent donc la création d'une infinité de combinaisons, sans restriction de compatibilité autre que celles indiquées dans le schéma.

Il sistema Fancy Shape consente di creare varie configurazioni di prodotto, combinate su un'unica base. Nello schema si indicano le compatibilità tra prodotti montati su una stessa base. Per i progetti *ad hoc* è possibile creare infinite combinazioni, senza limiti di compatibilità, oltre a quelle suggerite nell'illustrazione.

Das Fancy Shape-System ermöglicht es Ihnen, verschiedene Produktkonfigurationen auf einer einzigen Basis zu kombinieren. Das Diagramm zeigt die Kompatibilität zwischen Produkten, die auf der gleichen Grundfläche montiert sind. In *Ad hoc*-Projekten können unendlich viele Kombinationen erstellt werden, ohne dass die Kompatibilität über die in der Abbildung genannten Einschränkungen hinausgeht.

CUSTOM SYSTEM
TOP FANCY SHAPE



MORE INFO >>

OPTIONAL ACCESSORIES

TOP Beam Mixer Diffuser

0805-01-00

NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS



TOP Anti-glare Louver


0807-00-00 | NT |

NOT SOLD SEPARATELY
AFFECT THE LIGHTING PARAMETERS




Cord Accessory

0223-00-00- | N |



Cord Accessory One Plane

0224-00-00- | N |



Extended Family
Magnetic 24V Top Micro_P.94
Top_P.114
Top Micro 24V_P.181
Top 48V_P.210

| | | P | CCT | Beam | I | Flux | LOR |
|--------------------|---------------------|------|-------|------|-------|--------|-----|
| TOP Fancy Shape | A427- Ⓞ -0-10- NT | 6,5W | 2700K | 20° | 700mA | 610 lm | 92% |
| | A427- Ⓞ -0-11- NT | 6,5W | 3000K | 20° | 700mA | 640 lm | 92% |
| | A427- Ⓞ -0-12- NT | 6,5W | 4000K | 20° | 700mA | 655 lm | 92% |
| | A427- Ⓞ -0-20- NT | 6,5W | 2700K | 30° | 700mA | 610 lm | 89% |
| | A427- Ⓞ -0-21- NT | 6,5W | 3000K | 30° | 700mA | 640 lm | 89% |
| | A427- Ⓞ -0-22- NT | 6,5W | 4000K | 30° | 700mA | 655 lm | 89% |
| | A427- Ⓞ -0-30- NT | 6,5W | 2700K | 56° | 700mA | 610 lm | 86% |
| | A427- Ⓞ -0-31- NT | 6,5W | 3000K | 56° | 700mA | 640 lm | 86% |
| | A427- Ⓞ -0-32- NT | 6,5W | 4000K | 56° | 700mA | 655 lm | 86% |


IP20 | CRI>90 | L90B10 >55.000h



CORD LENGTH - L

| | |
|---|-----|
| 0 | 2 m |
| 2 | 5 m |

OTHER LENGTH PLEASE CONSULT



MANDATORY FOR INSTALLATION

FANCY SHAPE BASE 2 700mA 1 to 2 Lamps

A417-03-11- | WT | NT |
DALI A417-03-12- | WT | NT |

2 Equidistant Fixing Points



FANCY SHAPE BASE 12 700mA 7 to 12 Lamps

A417-03-31- | WT | NT |
DALI A417-03-32- | WT | NT |

12 Equidistant Fixing Points



FANCY SHAPE BASE 6 700mA 3 to 6 Lamps

A417-03-21- | WT | NT |
DALI A417-03-22- | WT | NT |


6 Equidistant Fixing Points



TOP Fancy Shape
Application example 2 Lamps

TOP Fancy Shape
Application example 4 Lamps

TOP Fancy Shape
Application example 10 Lamps



COLOUR | NT ■ | WT □ | N ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

» 288

CUSTOM SYSTEM
STICK FANCY SHAPE



MORE INFO >>

STICK LENGTH


| | | |
|---|----------|--------|
| 2 | STICK 22 | 220 mm |
| 3 | STICK 44 | 440 mm |
| 4 | STICK 66 | 660 mm |

OPTIONAL ACCESSORIES

Cord Accessory


0223-00-00- | N |

Included 1 unit x lamp



Cord Accessory One Plane

0224-00-00- | N |



WT

NT

Extended Family
Stick_P.142
Stick 24V_P.185
Stick 48V_P.214

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------|----------------------------------|------|-------|------|-------|--------|-----|
| STICK Fancy Shape | A42- ○ - Ⓞ -0-10- WT NT MG | 5,6W | 2700K | 18° | 500mA | 530 lm | 84% |
| | A42- ○ - Ⓞ -0-11- WT NT MG | 5,6W | 3000K | 18° | 500mA | 570 lm | 84% |
| | A42- ○ - Ⓞ -0-20- WT NT MG | 5,6W | 2700K | 31° | 500mA | 530 lm | 82% |
| | A42- ○ - Ⓞ -0-21- WT NT MG | 5,6W | 3000K | 31° | 500mA | 570 lm | 82% |
| | A42- ○ - Ⓞ -0-30- WT NT MG | 5,6W | 2700K | 42° | 500mA | 530 lm | 84% |
| | A42- ○ - Ⓞ -0-31- WT NT MG | 5,6W | 3000K | 42° | 500mA | 570 lm | 84% |


IP20 | CRI>90 | L90B10 >108.000h



CORD LENGTH - L1 + L2

| | |
|---|-----|
| 0 | 2 m |
| 2 | 5 m |


OTHER LENGTH PLEASE CONSULT



STICK Fancy Shape
Application example 2 Lamps

STICK Fancy Shape
Application example 6 Lamps

STICK Fancy Shape
Application example 12 Lamps



COLOUR | WT □ | NT ■ | MG ■ | N ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

OTHER CCT & DIM OPTIONS PLEASE CONSULT | OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288

ALASKA FANCY SHAPE



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|------------------------|-----------------------|------|-------|-------|---------|-----|
| ALASKA Big Fancy Shape | A419- -0-00- N BG | 9,3W | 2700K | 550mA | 1130 lm | 37% |
| | A419- -0-01- N BG | 9,3W | 3000K | 550mA | 1200 lm | 37% |

IP20 | CRI>90 | L90B10 >60.000h



CORD LENGTH - L1 + L2

| | |
|---|-----|
| 1 | 3 m |
| 2 | 5 m |

OTHER LENGTH PLEASE CONSULT

MANDATORY FOR INSTALLATION

FANCY SHAPE BASE 2 550mA 1 to 2 Lamps

| |
|----------------------------|
| A417-02-11- WT NT |
| DALI A417-02-12- WT NT |

2 Equidistant Fixing Points



FANCY SHAPE BASE 6 550mA 4 to 6 Lamps

| |
|----------------------------|
| A417-02-31- WT NT |
| DALI A417-02-32- WT NT |

12 Equidistant Fixing Points



FANCY SHAPE BASE 3 550mA 3 Lamps

| |
|----------------------------|
| A417-02-21- WT NT |
| DALI A417-02-22- WT NT |

6 Equidistant Fixing Points




OPTIONAL ACCESSORIES

Cord Accessory


0223-00-00- | N |

Included 1 unit x lamp




Cord Accessory One Plane


0224-00-00- | N |




ALASKA BIG Fancy Shape Application example 2 Lamps



ALASKA BIG Fancy Shape Application example 3 Lamps



ALASKA BIG Fancy Shape Application example 6 Lamps



COLOUR | N ■ | BG ■ | WT □ | NT ■ | MATERIAL | AL | OPTICAL GLASS | RAL ⓘ » 312

OTHER CCT & DIM OPTIONS PLEASE CONSULT | OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288



Extended Family
Alaska Trimless_P.60
Alaska_P.130
Alaska 24V_P.181



MORE INFO >>

| | | P | CCT | I | Flux | LOR |
|--------------------|-----------------------|------|-------|-------|--------|-----|
| ALASKA Fancy Shape | A418- -0-00- N BG | 4,5W | 2700K | 500mA | 475 lm | 30% |
| | A418- -0-01- N BG | 4,5W | 3000K | 500mA | 500 lm | 30% |

IP20 | CRI>90 | L90B10 >55.000h



CORD LENGTH - L1 + L2

| | |
|---|-----|
| 0 | 2 m |
| 2 | 5 m |

OTHER LENGTH PLEASE CONSULT

MANDATORY FOR INSTALLATION

FANCY SHAPE BASE 2 500mA 1 to 2 Lamps

| |
|----------------------------|
| A417-01-11- WT NT |
| DALI A417-01-12- WT NT |

2 Equidistant Fixing Points



FANCY SHAPE BASE 12 500mA 7 to 12 Lamps

| |
|----------------------------|
| A417-01-51- WT NT |
| DALI A417-01-52- WT NT |

12 Equidistant Fixing Points



FANCY SHAPE BASE 6 500mA 3 to 6 Lamps

| |
|----------------------------|
| A417-01-31- WT NT |
| DALI A417-01-32- WT NT |

6 Equidistant Fixing Points




OPTIONAL ACCESSORIES

Cord Accessory


0223-00-00- | N |

Included 1 unit x lamp




Cord Accessory One Plane


0224-00-00- | N |




ALASKA Fancy Shape Application example 2 Lamps



ALASKA Fancy Shape Application example 6 Lamps



ALASKA Fancy Shape Application example 12 Lamps



COLOUR | N ■ | BG ■ | WT □ | NT ■ | MATERIAL | AL | OPTICAL GLASS | RAL ⓘ » 312


OTHER CCT & DIM OPTIONS PLEASE CONSULT | OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288

CUSTOM SYSTEM SPIN FANCY SHAPE



Extended Family
Spin_P.144
Spin 48V_P.213



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|---------------------|--------------------------------|------|-------|------|-------|--------|-----|
| SPIN Fancy Shape | A420- 00 -0-00- NT MC MG | 6,5W | 2700K | 24° | 700mA | 600 lm | 86% |
| | A420- 00 -0-01- NT MC MG | 6,5W | 3000K | 24° | 700mA | 630 lm | 86% |
| | A420- 00 -0-10- NT MC MG | 6,5W | 2700K | 40° | 700mA | 600 lm | 84% |
| | A420- 00 -0-11- NT MC MG | 6,5W | 3000K | 40° | 700mA | 630 lm | 84% |

III IP20 | CRI>90 | L90B10 >60.000h



CORD LENGTH - L1 + L2

| | |
|---|-----|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

OTHER LENGTH PLEASE CONSULT

MANDATORY FOR INSTALLATION

FANCY SHAPE BASE 2 700mA 1 to 2 Lamps

A417-03-11- | WT | NT |
DALI A417-03-12- | WT | NT |

2 Equidistant Fixing Points



FANCY SHAPE BASE 6 700mA 3 to 6 Lamps

A417-03-21- | WT | NT |
DALI A417-03-22- | WT | NT |


6 Equidistant Fixing Points



FANCY SHAPE BASE 12 700mA 7 to 12 Lamps

A417-03-31- | WT | NT |
DALI A417-03-32- | WT | NT |

12 Equidistant Fixing Points




OPTIONAL ACCESSORIES

Cord Accessory


0223-00-00- | N |

Included 1 unit x lamp




Cord Accessory One Plane


0224-00-00- | N |




SPIN Fancy Shape
Application example 2 Lamps



SPIN Fancy Shape
Application example 6 Lamps



SPIN Fancy Shape
Application example 12 Lamps



COLOUR | WT □ | NT ■ | MC ■ | MG ■ | N ■ | MATERIAL | AL | PMMA | RAL ⓘ » 312

OTHER CCT & DIM OPTIONS PLEASE CONSULT | OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288

CUSTOM SYSTEM HOLLY FANCY SHAPE



Extended Family
Holly_P.143
Holly 48V_P.215



MORE INFO >>

| | | P | CCT | Beam | I | Flux | LOR |
|----------------------|--------------------------------|------|-------|------|-------|--------|-----|
| HOLLY Fancy Shape | A421- 00 -0-00- NT MC MG | 2,1W | 2700K | 19° | 700mA | 190 lm | 90% |
| | A421- 00 -0-01- NT MC MG | 2,1W | 3000K | 19° | 700mA | 210 lm | 90% |
| | A421- 00 -0-10- NT MC MG | 2,1W | 2700K | 38° | 700mA | 190 lm | 92% |
| | A421- 00 -0-11- NT MC MG | 2,1W | 3000K | 38° | 700mA | 210 lm | 92% |

III IP20 | CRI>90 | L90B10 >102.000h



CORD LENGTH - L1 + L2

| | |
|---|-----|
| 0 | 2 m |
| 1 | 3 m |
| 2 | 5 m |

OTHER LENGTH PLEASE CONSULT

MANDATORY FOR INSTALLATION

FANCY SHAPE BASE 2 700mA 1 to 2 Lamps

A417-03-11- | WT | NT |
DALI A417-03-12- | WT | NT |

2 Equidistant Fixing Points



FANCY SHAPE BASE 6 700mA 3 to 6 Lamps

A417-03-21- | WT | NT |
DALI A417-03-22- | WT | NT |


6 Equidistant Fixing Points



FANCY SHAPE BASE 12 700mA 7 to 12 Lamps

A417-03-31- | WT | NT |
DALI A417-03-32- | WT | NT |

12 Equidistant Fixing Points




OPTIONAL ACCESSORIES

Cord Accessory


0223-00-00- | N |

Included 1 unit x lamp




Cord Accessory One Plane


0224-00-00- | N |




HOLLY Fancy Shape
Application example 2 Lamps



HOLLY Fancy Shape
Application example 6 Lamps



HOLLY Fancy Shape
Application example 12 Lamps





COLOUR | WT □ | NT ■ | MC ■ | MG ■ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

OTHER CCT & DIM OPTIONS PLEASE CONSULT | OTHER FINISHING COMBINATIONS PLEASE CONSULT

» 288

BLACK FOSTER CUSTOM



BLACK FOSTER CUSTOM

| BLACK FOSTER CUSTOM | BLACK FOSTER ASYMMETRIC CUSTOM | BLACK FOSTER SIX S | BLACK FOSTER PLUS MINI | BLACK FOSTER FIT 35 |
|----------------------|--------------------------------|----------------------|------------------------|---------------------|
| — | — | — | — | — |
| 2 / 3 / 5 / 10 / 15 | 2 / 3 / 5 / 10 / 15 | | | |
| 4,2 - 31,5 W | 4,2 - 31,5 W | 8,5W | 6,5W | 5,5 W |
| 2700 / 3000 / 4000 K | 2700 / 3000 / 4000 K | 2700 / 3000 / 4000 K | 2700 / 3000 / 4000 K | 2700 / 3000 K |
| 380 - 3750 Lm | 380 - 3750 Lm | 1030 - 1100 Lm | 630 - 680 Lm | 590 / 630 Lm |
| 19 / 38° BEAM | 38° ASYMMETRIC BEAM | 17 / 24 / 34° BEAM | 10 - 41° BEAM | 19 / 29 / 38° BEAM |
| 90 / 92 % LOR | 90 % LOR | 84 - 89 % LOR | 20 - 40 % LOR | 80 - 82 % LOR |

BLACK FOSTER CUSTOM SYSTEM

| BLACK FOSTER CUSTOM MODULE | BLACK FOSTER CUSTOM MODULE FIT 27 |
|----------------------------|-----------------------------------|
| — | — |
| 3 / 5 / 10 | |
| 6,3 / 10,5 / 21 W | 5,5W |
| 2700 / 3000 / 4000 K | 2700 / 3000 / 4000 K |
| 570 - 2500 Lm | 550 - 640 Lm |
| 19 / 38° BEAM | 22 / 37 / 46° BEAM |
| 90 / 92 % LOR | 81 - 84 % LOR |

BLACK FOSTER MICRO CUSTOM SURFACE

| BLACK FOSTER MICRO CUSTOM MODULE |
|----------------------------------|
| — |
| 3 / 5 / 10 |
| 4,2 / 7 / 14 W |
| 2700 / 3000 / 4000 K |
| 465 - 1700 Lm |
| 37° BEAM |
| 87% LOR |

BLACK FOSTER CUSTOM



MORE INFO >>


| | | P | CCT | I | Flux | L |
|------------------------|--------------------------|-------|-------|-------|---------|-------|
| BLACK FOSTER Custom 2 | A317-2- ○ -00- N NMG | 4,2W | 2700K | 700mA | 380 lm | 87mm |
| | A317-2- ○ -01- N NMG | 4,2W | 3000K | 700mA | 420 lm | 87mm |
| | A317-2- ○ -02- N NMG | 4,2W | 4000K | 700mA | 500 lm | 87mm |
| BLACK FOSTER Custom 3 | A317-3- ○ -00- N NMG | 6,3W | 2700K | 700mA | 570 lm | 130mm |
| | A317-3- ○ -01- N NMG | 6,3W | 3000K | 700mA | 630 lm | 130mm |
| | A317-3- ○ -02- N NMG | 6,3W | 4000K | 700mA | 750 lm | 130mm |
| BLACK FOSTER Custom 5 | A317-4- ○ -00- N NMG | 10,5W | 2700K | 700mA | 950 lm | 216mm |
| | A317-4- ○ -01- N NMG | 10,5W | 3000K | 700mA | 1050 lm | 216mm |
| | A317-4- ○ -02- N NMG | 10,5W | 4000K | 700mA | 1250 lm | 216mm |
| BLACK FOSTER Custom 10 | A317-5- ○ -00- N NMG | 21W | 2700K | 700mA | 1900 lm | 431mm |
| | A317-5- ○ -01- N NMG | 21W | 3000K | 700mA | 2100 lm | 431mm |
| | A317-5- ○ -02- N NMG | 21W | 4000K | 700mA | 2500 lm | 431mm |
| BLACK FOSTER Custom 15 | A317-6- ○ -00- N NMG | 31,5W | 2700K | 700mA | 2850 lm | 646mm |
| | A317-6- ○ -01- N NMG | 31,5W | 3000K | 700mA | 3150 lm | 646mm |
| | A317-6- ○ -02- N NMG | 31,5W | 4000K | 700mA | 3750 lm | 646mm |

III IP20 | CRI>90 | L90B10 >102.000h



| ○ BEAM | LOR |
|--------|-----|
| 0 38° | 92% |
| 1 19° | 90% |

| FINISHING | Body | Lampshade |
|-----------|------|-----------|
| N | N ■ | N ■ |
| NMG | N ■ | MG ■ |



COLOUR | N ■ | NMG ■ | MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm. RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING.

Ⓢ » 288



Black Foster Micro_P10
Black Foster_P12
Black Foster Surface_P104


Extended Family
Black Foster Suspension_P133
Black Foster Micro 24V_P180
Black Foster 48V_P207



MORE INFO >>

| | | P | CCT | I | Flux | LOR | L |
|-----------------------------------|-----------------|-------|-------|-------|---------|-----|-------|
| BLACK FOSTER Asymmetric Custom 2 | A372-20-00- N | 4,2W | 2700K | 700mA | 380 lm | 90% | 87mm |
| | A372-20-01- N | 4,2W | 3000K | 700mA | 420 lm | 90% | 87mm |
| | A372-20-02- N | 4,2W | 4000K | 700mA | 500 lm | 90% | 87mm |
| BLACK FOSTER Asymmetric Custom 3 | A372-30-00- N | 6,3W | 2700K | 700mA | 570 lm | 90% | 130mm |
| | A372-30-01- N | 6,3W | 3000K | 700mA | 630 lm | 90% | 130mm |
| | A372-30-02- N | 6,3W | 4000K | 700mA | 750 lm | 90% | 130mm |
| BLACK FOSTER Asymmetric Custom 5 | A372-40-00- N | 10,5W | 2700K | 700mA | 950 lm | 90% | 216mm |
| | A372-40-01- N | 10,5W | 3000K | 700mA | 1050 lm | 90% | 216mm |
| | A372-40-02- N | 10,5W | 4000K | 700mA | 1250 lm | 90% | 216mm |
| BLACK FOSTER Asymmetric Custom 10 | A372-50-00- N | 21W | 2700K | 700mA | 1900 lm | 90% | 431mm |
| | A372-50-01- N | 21W | 3000K | 700mA | 2100 lm | 90% | 431mm |
| | A372-50-02- N | 21W | 4000K | 700mA | 2500 lm | 90% | 431mm |
| BLACK FOSTER Asymmetric Custom 15 | A372-60-00- N | 31,5W | 2700K | 700mA | 2850 lm | 90% | 646mm |
| | A372-60-01- N | 31,5W | 3000K | 700mA | 3150 lm | 90% | 646mm |
| | A372-60-02- N | 31,5W | 4000K | 700mA | 3750 lm | 90% | 646mm |

III IP20 | CRI>90 | L90B10 >102.000h



COLOUR | N ■ | MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm. RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING.

Ⓢ » 288

BLACK FOSTER CUSTOM



MORE INFO >>




MORE INFO >>



MORE INFO >>

- *OPTIONS**
- 1 No DIM
 - 2 DIM DALI
- DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT



| | | P | CCT | BEAM | I | Flux | LOR |
|------------------------|---------------------------|------|-------|---------|-------|--------|--------|
| BLACK FOSTER PLUS Mini | A362-00- 00 -0- WT NT | 6,5W | 2700K | 10°-41° | 700mA | 630 lm | 20-40% |
| | A362-00- 00 -1- WT NT | 6,5W | 3000K | 10°-41° | 700mA | 660 lm | 20-40% |
| | A362-00- 00 -2- WT NT | 6,5W | 4000K | 10°-41° | 700mA | 680 lm | 20-40% |

220 V~ | 240 | IP20 | CRI>90 | L90B10 +55.000h

MacAdam Step 2 | OPTIONS* | INCL | 350° | 180° | 10° - 41°

| | | P | CCT | BEAM | I | Flux | LOR |
|---------------------|-------------------------------|------|-------|------|-------|--------|-----|
| BLACK FOSTER FIT 35 | A363-0- 00 -10- WT NT G | 5,5W | 2700K | 20° | 500mA | 620 lm | 85% |
| | A363-0- 00 -11- WT NT G | 5,5W | 3000K | 20° | 500mA | 660 lm | 85% |
| | A363-0- 00 -20- WT NT G | 5,5W | 2700K | 29° | 500mA | 620 lm | 84% |
| | A363-0- 00 -21- WT NT G | 5,5W | 3000K | 29° | 500mA | 660 lm | 84% |
| | A363-0- 00 -30- WT NT G | 5,5W | 2700K | 36° | 500mA | 620 lm | 85% |
| | A363-0- 00 -31- WT NT G | 5,5W | 3000K | 36° | 500mA | 660 lm | 85% |

220 V~ | 240 | IP20 | CRI>90 | L90B10 +108.000h

MacAdam Step 2 | OPTIONS* | INCL | 350° | 90° | 20° / 29° / 36°


| | | P | CCT | BEAM | I | Flux | LOR |
|--------------------|---------------------------|------|-------|------|-------|---------|-----|
| BLACK FOSTER SIX S | A360-0- 00 -10- WT NT | 8,5W | 2700K | 17° | 500mA | 1070 lm | 86% |
| | A360-0- 00 -11- WT NT | 8,5W | 3000K | 17° | 500mA | 1140 lm | 86% |
| | A360-0- 00 -12- WT NT | 8,5W | 4000K | 17° | 500mA | 1210 lm | 86% |
| | A360-0- 00 -20- WT NT | 8,5W | 2700K | 24° | 500mA | 1070 lm | 84% |
| | A360-0- 00 -21- WT NT | 8,5W | 3000K | 24° | 500mA | 1140 lm | 84% |
| | A360-0- 00 -22- WT NT | 8,5W | 4000K | 24° | 500mA | 1210 lm | 84% |
| | A360-0- 00 -30- WT NT | 8,5W | 2700K | 34° | 500mA | 1070 lm | 89% |
| | A360-0- 00 -31- WT NT | 8,5W | 3000K | 34° | 500mA | 1140 lm | 89% |
| | A360-0- 00 -32- WT NT | 8,5W | 4000K | 34° | 500mA | 1210 lm | 89% |

220 V~ | 240 | IP20 | CRI>90 | L80B10 +60.000h

MacAdam Step 2 | OPTIONS* | INCL | 350° | 310° | 17° / 24° / 34°

OPTIONAL ACCESSORIES

- NOT SOLD SEPARATELY | AFFECT THE LIGHTING PARAMETERS
- PLUS Mini High Chromatic LED ⓘ » 281
 - SIX S High Chromatic LED ⓘ » 281
 - FIT 35 Anti-glare Honeycomb Louver A345-00-00 ⓘ » 281




- COLOUR | WT □ | NT ■ | MATERIAL | AL | OPTICAL GLASS | ABS+PC |
- COLOUR | WT □ | NT ■ | G ■ | MATERIAL | AL | PC | ABS+PC |
- COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | ABS+PC | RAL ⓘ » 312

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm. RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING. ⓘ » 288



PRODUCT CONFIGURATOR
Configure your own custom product layout. Our tool will calculate the required drivers and accessories.

| | | | L |
|---------------------|----------------|-----------------|-------------|
| BLACK FOSTER Custom | GAP Corner 90° | A317-00-07- N | 200 x 200mm |
| | GAP 250 | A317-00-01- N | 250mm |
| | GAP 500 | A317-00-02- N | 500mm |
| | GAP 1000 | A317-00-03- N | 1000mm |
| | GAP 2000 | A317-00-04- N | 2000mm |



- BLACK FOSTER End Caps Kit A317-00-05- | N | Thickness of each cover=2 mm.
- BLACK FOSTER Straight Joiner A317-00-06


| | | P | I | D | |
|-----------------|---------------------|------------|-----|-------|-----------------|
| *DRIVER OPTIONS | NO DIM | 0434-01-18 | 50W | 700mA | 124 x 79 x 22mm |
| | DALI PUSH / 1-10V | 0433-00-23 | 50W | 700mA | 124 x 79 x 22mm |

220 V~ | 240 | DRIVER MUST BE PLACED ON REMOTE | CONNECT IN SERIES | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT ⓘ » 282

MOUNTING ACCESSORIES

- Fixation Kit A219-21-06- | B |
- Flush Ceiling Kit A219-22-06- | B |
- Track Clamp Kit for M6 ROD A219-21-21- | B |
- Suspension Kit A219-21-10- | B |

SUGGESTED MOUNTING ACCESSORIES QUANTITIES
Black Foster custom 2, 3, 5: 1 Pcs.
Black Foster custom 10, 15: 2 Pcs.
Gap 250, 500: 1 Pcs.
Gap 1000, 2000: 2 Pcs.



- COLOUR | N ■ | B □ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

PLASTERBOARD CEILING, MANDATORY THICKNESS 12,5mm. RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING. ⓘ » 288



CUSTOM SYSTEM BLACK FOSTER CUSTOM SYSTEM

Black Foster Micro_P10
Black Foster_P12
Black Foster Surface_P104

Extended Family
Black Foster Suspension_P133
Black Foster Micro 24V_P180
Black Foster 48V_P207

| | | P | CCT | I | Flux |
|----------------------------------|-----------------------------|-------|-------|-------|---------|
| BLACK FOSTER Custom Module 3 | A453-3- ○ - ○ -0- N NMG | 6,3W | 2700K | 700mA | 570 lm |
| | A453-3- ○ - ○ -1- N NMG | 6,3W | 3000K | 700mA | 630 lm |
| | A453-3- ○ - ○ -2- N NMG | 6,3W | 4000K | 700mA | 750 lm |
| BLACK FOSTER Custom Module 5 | A453-4- ○ - ○ -0- N NMG | 10,5W | 2700K | 700mA | 950 lm |
| | A453-4- ○ - ○ -1- N NMG | 10,5W | 3000K | 700mA | 1050 lm |
| | A453-4- ○ - ○ -2- N NMG | 10,5W | 4000K | 700mA | 1250 lm |
| BLACK FOSTER Custom Module 10 | A453-5- ○ - ○ -0- N NMG | 21W | 2700K | 700mA | 1900 lm |
| | A453-5- ○ - ○ -1- N NMG | 21W | 3000K | 700mA | 2100 lm |
| | A453-5- ○ - ○ -2- N NMG | 21W | 4000K | 700mA | 2500 lm |




MORE INFO >>

| *OPTIONS | |
|----------|----------|
| 1 | No DIM |
| 2 | DIM DALI |

| | BEAM | LOR |
|---|------|-----|
| 0 | 38° | 92% |
| 1 | 19° | 90% |

48 V | IP20 | CRI>90 | L90B10 >102.000 h



IEC IEC60598-1 Pending




MORE INFO >>

| *OPTIONS | |
|----------|----------|
| 1 | No DIM |
| 2 | DIM DALI |

| | BEAM | LOR |
|---|------|-----|
| 1 | 18° | 84% |
| 2 | 31° | 82% |
| 3 | 42° | 84% |

| | | P | CCT | I | Flux |
|---|---------------------------------|------|-------|-------|--------|
| BLACK FOSTER Custom Module FIT 27 | A454-0- ○ - ○ -0- WT NT G | 5,5W | 2700K | 500mA | 520 lm |
| | A454-0- ○ - ○ -1- WT NT G | 5,5W | 3000K | 500mA | 560 lm |
| | A454-0- ○ - ○ -2- WT NT G | 5,5W | 4000K | 500mA | 600 lm |


48 V | IP20 | CRI>90 | L90B10 >108.000 h



COLOUR | N ■ | NMG ■ | MATERIAL | AL | ABS+PC | RAL ⓘ » 312

COLOUR | WT □ | NT ■ | G ■ | MATERIAL | AL | PC | ⓘ » 288

BLACK FOSTER CUSTOM SYSTEM




| | |
|--------------------------------|-----------------------|
| BLACK FOSTER Custom Surface 1m | A452-01-00- NT WT |
| BLACK FOSTER Custom Surface 2m | A452-02-00- NT WT |
| BLACK FOSTER Custom Surface 3m | A452-03-00- NT WT |

| | |
|-------------------------------------|-----------------------|
| BLACK FOSTER Custom Surface L-Joint | A452-04-00- NT WT |
| BLACK FOSTER Custom Surface T-Joint | A452-05-00- NT WT |
| BLACK FOSTER Custom Surface X-Joint | A452-06-00- NT WT |


| | | |
|-------------------------------|-----------------|-------|
| BLACK FOSTER Custom Cover 250 | A452-00-01- N | 250mm |
| BLACK FOSTER Custom Cover 500 | A452-00-02- N | 500mm |

BLACK FOSTER SURFACE CUSTOM L-JOINT




Electrical connection not included

BLACK FOSTER SURFACE CUSTOM T-JOINT



Electrical connection not included

BLACK FOSTER SURFACE CUSTOM X-JOINT




Electrical connection not included

P V D (A x B x C)



| | | | | |
|-----------------------------------|-----------------|------|-----|-----------------|
| CONSTANT VOLTAGE LED POWER SUPPLY | 0434-01-61* N | 100W | 48V | 298 x 19 x 16mm |
| | 0434-01-62 | 150W | 48V | 350 x 30 x 18mm |
| | 0434-01-80 | 250W | 48V | 400 x 40 x 22mm |

220 V~ | 240 V~ | *To be installed inside the track. (i) » 282



DROP VOLTAGE TABLE


| POWER [W] | CABLE SECTION [mm²] | CABLE LENGTH [m] | | | |
|-----------|---------------------|------------------|----|----|----|
| | | 5 | 10 | 20 | 30 |
| 100 | 0,75 | 50 | 50 | X | X |
| | 1,5 | 50 | 50 | 40 | 25 |
| 150 | 0,75 | 40 | 15 | X | X |
| | 1,5 | 50 | 40 | 20 | X |
| 250 | 0,75 | 20 | X | X | X |
| | 1,5 | 35 | 20 | X | X |



COLOUR | NT ■ | WT □ | N ■ |


RAL (i) » 312

(cc) » 288




Live-End Connector 48V

A338-00-01- | N |




Central Connector 48V

A338-00-02- | N |




L-Joint Connector 48V

A338-00-12- | N |




T-Joint Connector 48V

A450-00-07- | N |



X-Joint Connector 48V

A450-00-08- | N |




Wired Power Supply Case 48V

A338-00-25- | NT | WT | 150W NO DIM

A338-00-26- | NT | WT | 150W DIM


220 V~ 240 V~ INCL



Black Foster Suspension Kit (2 Units)

A450-00-09- | NT | WT |

Suggested mounting accessories quantities:
1000mm - 2 Pcs.
2000mm - 2 Pcs.
3000mm - 3 Pcs.



Suspension Feed Kit 48V

A338-00-16- | N | W | NO DIM

A338-00-17- | N | W | DIM

For remote power supply

A338-00-27- | N | W | NO DIM

A338-00-28- | N | W | DIM

For power supply inside the track

SUSPENSION COMPONENTS

WIRE TRIMLESS ACCESSORIES


FEED

Mains Trimless*

A023-00-01- | W | N | NO DIM

Mains Thick Trimless*

A023-00-02- | W | N | DIM




COLOUR | N ■ | W □ | NT ■ | WT □ |

* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT


FASTENING

Steel Cable Trimless*

A023-00-05- | W | N |




TRIMLESS TOOL D20 X D52mm A478-00-01




RAL (i) » 312


MAINS TRIMLESS




MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



BLACK FOSTER CUSTOM SYSTEM



PRODUCT CONFIGURATOR
Configure your own custom product layout. Our tool will calculate the required drivers and accessories.

| | |
|---------------------------------|-----------------|
| BLACK FOSTER Custom Trimless 1m | A458-01-00- N |
| BLACK FOSTER Custom Trimless 2m | A458-02-00- N |
| BLACK FOSTER Custom Trimless 3m | A458-03-00- N |




| | |
|------------------------------|-----------------|
| BLACK FOSTER Custom Trimless | A458-04-00- N |
|------------------------------|-----------------|

L-Joint



L

| | | |
|-----------------------------------|-----------------|-------|
| BLACK FOSTER Custom Cover Gap 250 | A452-00-01- N | 250mm |
| BLACK FOSTER Custom Cover Gap 500 | A452-00-02- N | 500mm |




| | P | V | D (A x B x C) |
|-----------------------------------|-----------------|----------|-----------------|
| CONSTANT VOLTAGE LED POWER SUPPLY | 0434-01-61* N | 100W 48V | 298 x 19 x 16mm |
| | 0434-01-62 | 150W 48V | 350 x 30 x 18mm |
| | 0434-01-80 | 250W 48V | 400 x 40 x 22mm |


220 V~ | 240 V~ | *To be installed inside the track.



BLACK FOSTER CUSTOM TRIMLESS L-JOINT



| | |
|-------------------------------|------------|
| BLACK FOSTER Custom Trimless | A458-05-00 |
| Plaster Installation Guard 1m | |



DROP VOLTAGE TABLE

| POWER (W) | CABLE SECTION (mm²) | CABLE LENGTH (m) | | | |
|-----------|---------------------|------------------|----|----|----|
| | | 5 | 10 | 20 | 30 |
| 100 | 0,75 | 50 | 50 | X | X |
| | 1,5 | 50 | 50 | 40 | 25 |
| 150 | 0,75 | 40 | 15 | X | X |
| | 1,5 | 50 | 40 | 20 | X |
| 250 | 0,75 | 20 | X | X | X |
| | 1,5 | 35 | 20 | X | X |

COLOUR | N ■ |

RAL ⓘ » 312

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)



BLACK FOSTER Custom Trimless End

A458-00-01- | N |

Cover Thickness = 2 mm.



BLACK FOSTER Custom Trimless End Feed


A458-00-02- | N |

Cover Thickness = 2 mm.




BLACK FOSTER Straight Joiner

A317-00-06




Live-End Connector 48V

A338-00-01- | N |



L-Joint Connector 48V

A338-00-12- | N |



Central Connector 48V

A338-00-02- | N |

MOUNTING ACCESSORIES

Track Fixation Kit A219-21-06- | B |

Track Flush Ceiling Kit A219-22-06- | B |

Track Clamp Kit for M6 ROD A219-21-21- | B |

Track Suspension Kit A219-21-10- | B |

SUGGESTED MOUNTING ACCESSORIES QUANTITIES

1000 mm - 2 Pcs
2000 mm - 2 Pcs
3000 mm - 3 Pcs

COLOUR | N ■ | B □ |

RAL ⓘ » 312

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)

CUSTOM SYSTEM

BLACK FOSTER MICRO CUSTOM SURFACE



Black Foster Micro_P10
Black Foster_P12
Black Foster Surface_P104

Extended Family
Black Foster Suspension_P133
Black Foster Micro 24V_P180
Black Foster 48V_P207



MORE INFO >>


| | | P | CCT | I | Flux | LOR |
|---|--------------------|------|-------|-------|---------|-----|
| BLACK FOSTER Micro Custom Module 3 | A451-10- ① -0- N | 4,2W | 2700K | 500mA | 465 lm | 87% |
| | A451-10- ① -1- N | 4,2W | 3000K | 500mA | 480 lm | 87% |
| | A451-10- ① -2- N | 4,2W | 4000K | 500mA | 510 lm | 87% |
| BLACK FOSTER Micro Custom Module 5 | A451-20- ① -0- N | 7W | 2700K | 500mA | 775 lm | 87% |
| | A451-20- ① -1- N | 7W | 3000K | 500mA | 800 lm | 87% |
| | A451-20- ① -2- N | 7W | 4000K | 500mA | 850 lm | 87% |
| BLACK FOSTER Micro Custom Module 10 | A451-50- ① -0- N | 14W | 2700K | 500mA | 1550 lm | 87% |
| | A451-50- ① -1- N | 14W | 3000K | 500mA | 1600 lm | 87% |
| | A451-50- ① -2- N | 14W | 4000K | 500mA | 1700 lm | 87% |

48 V | III IP20 | CRI>90 | L90B10 >60.000 h



① *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |




COLOUR | N ■ | MATERIAL | AL | ABS+PC |

RAL ⓘ » 312

© » 288

BLACK FOSTER MICRO CUSTOM SURFACE




| | |
|--------------------------------------|-----------------------|
| BLACK FOSTER Micro Custom Surface 1m | A450-01-00- NT WT |
| BLACK FOSTER Micro Custom Surface 2m | A450-02-00- NT WT |
| BLACK FOSTER Micro Custom Surface 3m | A450-03-00- NT WT |

| | |
|---|-----------------------|
| BLACK FOSTER Micro Custom Surface L-Joint | A450-04-00- NT WT |
| BLACK FOSTER Micro Custom Surface T-Joint | A450-05-00- NT WT |
| BLACK FOSTER Micro Custom Surface X-Joint | A450-06-00- NT WT |


| | |
|--|--------------------------|
| BLACK FOSTER Micro Custom Cover Gap 250 | A450-00-01- N 250mm |
| BLACK FOSTER Micro Custom Cover Gap 500 | A450-00-02- N 500mm |
| BLACK FOSTER Micro Custom Cover Gap 1000 | A450-00-03- N 1000mm |

BLACK FOSTER MICRO CUSTOM SURFACE L-JOINT




Electrical connection not included

BLACK FOSTER MICRO CUSTOM SURFACE T-JOINT



Electrical connection not included

BLACK FOSTER MICRO CUSTOM SURFACE X-JOINT



Electrical connection not included





L

P V D (A x B x C)



| | | | | |
|-----------------------------------|-----------------|------|-----|-----------------|
| CONSTANT VOLTAGE LED POWER SUPPLY | 0434-01-61* N | 100W | 48V | 298 x 19 x 16mm |
| | 0434-01-62 | 150W | 48V | 350 x 30 x 18mm |
| | 0434-01-80 | 250W | 48V | 400 x 40 x 22mm |

220 V~ | 240 V~ | *To be installed inside the track. ⓘ » 282



DROP VOLTAGE TABLE


| POWER [W] | CABLE SECTION [mm²] | CABLE LENGTH [m] | | | |
|-----------|---------------------|------------------|----|----|----|
| | | 5 | 10 | 20 | 30 |
| 100 | 0,75 | 50 | 50 | X | X |
| | 1,5 | 50 | 50 | 40 | 25 |
| 150 | 0,75 | 40 | 15 | X | X |
| | 1,5 | 50 | 40 | 20 | X |
| 250 | 0,75 | 20 | X | X | X |
| | 1,5 | 35 | 20 | X | X |



COLOUR | NT ■ | WT □ | N ■ |

RAL ⓘ » 312

Ⓜ » 288



Live-End Connector 48V

A338-00-01- | N |

Central Connector 48V

A338-00-02- | N |

L-Joint Connector 48V

A338-00-12- | N |

T-Joint Connector 48V

A450-00-07- | N |

X-Joint Connector 48V

A450-00-08- | N |



BLACK FOSTER Micro Custom Surface

End A450-00-04- | N | W |



BLACK FOSTER Micro Custom Surface

End Feed A450-00-05- | N | W |



BLACK FOSTER Micro Custom Surface

Straight Joiner A450-00-06



PRODUCT CONFIGURATOR

Configure your own custom product layout. Our tool will calculate the required drivers and accessories.


SUSPENSION COMPONENTS

Wired Power Supply Case 48V

A338-00-25- | NT | WT | 150W NO DIM

A338-00-26- | NT | WT | 150W DIM

220 V~ | 240 V~ | INCL



Suspension Feed Kit 48V

A338-00-16- | N | W | NO DIM

A338-00-17- | N | W | DIM

For remote power supply

A338-00-27- | N | W | NO DIM

A338-00-28- | N | W | DIM


For power supply inside the track

Black Foster Suspension Kit (2 units)


A450-00-09- | NT | WT |

Suggested mounting accessories quantities:
1000mm - 2 Pcs.
2000mm - 2 Pcs.
3000mm - 3 Pcs.


MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



WIRE TRIMLESS ACCESSORIES

FEED

Mains Trimless*

A023-00-01- | W | N | NO DIM

Mains Thick Trimless*

A023-00-02- | W | N | DIM




FASTENING

Steel Cable Trimless*

A023-00-05- | W | N |



TRIMLESS TOOL D20 X D52mm A478-00-01



COLOUR | N ■ | W □ | NT ■ | WT □ |

RAL ⓘ » 312

* AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT

CUSTOM SYSTEM
BRIGHT LINE




MORE INFO >>

| | | P | CCT | Flux | LOR | L |
|------------------|-----------------|-------|-------|---------|-----|--------|
| BRIGHT LINE 250 | A303-00-11- W | 2,9W | 3000K | 307 lm | 43% | 250mm |
| | A303-00-12- W | 2,9W | 4000K | 313 lm | 43% | 250mm |
| BRIGHT LINE 500 | A303-00-21- W | 5,8W | 3000K | 615 lm | 43% | 500mm |
| | A303-00-22- W | 5,8W | 4000K | 625 lm | 43% | 500mm |
| BRIGHT LINE 1000 | A303-00-31- W | 11,5W | 3000K | 1230 lm | 43% | 1000mm |
| | A303-00-32- W | 11,5W | 4000K | 1250 lm | 43% | 1000mm |
| BRIGHT LINE 2000 | A303-00-41- W | 23W | 3000K | 2460 lm | 43% | 2000mm |
| | A303-00-42- W | 23W | 4000K | 2500 lm | 43% | 2000mm |
| BRIGHT LINE 3000 | A303-00-51- W | 34,5W | 3000K | 3690 lm | 43% | 3000mm |
| | A303-00-52- W | 34,5W | 4000K | 3750 lm | 43% | 3000mm |

| | | | | | | |
|---------------------|-----------------|-------|-------|---------|-----|--------|
| BRIGHT LINE HO 250 | A304-00-11- W | 5,8W | 3000K | 596 lm | 43% | 250mm |
| | A304-00-12- W | 5,8W | 4000K | 605 lm | 43% | 250mm |
| BRIGHT LINE HO 500 | A304-00-21- W | 11,5W | 3000K | 1191 lm | 43% | 500mm |
| | A304-00-22- W | 11,5W | 4000K | 1211 lm | 43% | 500mm |
| BRIGHT LINE HO 1000 | A304-00-31- W | 23W | 3000K | 2382 lm | 43% | 1000mm |
| | A304-00-32- W | 23W | 4000K | 2422 lm | 43% | 1000mm |
| BRIGHT LINE HO 2000 | A304-00-41- W | 46W | 3000K | 4764 lm | 43% | 2000mm |
| | A304-00-42- W | 46W | 4000K | 4844 lm | 43% | 2000mm |
| BRIGHT LINE HO 3000 | A304-00-51- W | 69W | 3000K | 7146 lm | 43% | 3000mm |
| | A304-00-52- W | 69W | 4000K | 7266 lm | 43% | 3000mm |

24 V | III | IP20 | CRI>90 | L80B10 >60.000h




COLOUR | W □ | MATERIAL | AL

RAL ⓘ » 312

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)

Ⓢ » 288




MORE INFO >>

| | | P | CCT | Flux | LOR | L |
|--------------------------------------|-----------------|-------|-------|---------|-----|-------------|
| BRIGHT LINE CORNER 90° Two Planes | A303-00-61- W | 11,5W | 3000K | 1230 lm | 43% | 530 x 530mm |
| | A303-00-62- W | 11,5W | 4000K | 1250 lm | 43% | 530 x 530mm |
| BRIGHT LINE HO CORNER 90° Two Planes | A304-00-61- W | 23W | 3000K | 2382 lm | 43% | 530 x 530mm |
| | A304-00-62- W | 23W | 4000K | 2422 lm | 43% | 530 x 530mm |

24 V | III | IP20 | CRI>90 | L80B10 >60.000h



BRIGHT LINE CORNER 90° TWO PLANES




| | | P | CCT | Flux | LOR | L |
|---|-----------------|-------|-------|---------|-----|-------------|
| BRIGHT LINE CORNER 90° One Plane Polarized A | A303-00-71- W | 11,5W | 3000K | 1230 lm | 43% | 555 x 555mm |
| | A303-00-72- W | 11,5W | 4000K | 1250 lm | 43% | 555 x 555mm |
| BRIGHT LINE HO CORNER 90° One Plane Polarized A | A304-00-71- W | 23W | 3000K | 2382 lm | 43% | 555 x 555mm |
| | A304-00-72- W | 23W | 4000K | 2422 lm | 43% | 555 x 555mm |
| BRIGHT LINE CORNER 90° One Plane Polarized B | A303-00-81- W | 11,5W | 3000K | 1230 lm | 43% | 555 x 555mm |
| | A303-00-82- W | 11,5W | 4000K | 1250 lm | 43% | 555 x 555mm |
| BRIGHT LINE HO CORNER 90° One Plane Polarized B | A304-00-81- W | 23W | 3000K | 2382 lm | 43% | 555 x 555mm |
| | A304-00-82- W | 23W | 4000K | 2422 lm | 43% | 555 x 555mm |


24 V | III | IP20 | CRI>90 | L80B10 >60.000h



BRIGHT LINE CORNER 90° ONE PLANE POLARIZED A



BRIGHT LINE CORNER 90° ONE PLANE POLARIZED B



COLOUR | W □ | MATERIAL | AL | PC

RAL ⓘ » 312

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)

Ⓢ » 288


CUSTOM SYSTEM BRIGHT LINE



PRODUCT CONFIGURATOR


Configure your own custom product layout. Our tool will calculate the required drivers and accessories.

| BRIGHT LINE Diffuser | A303-10-01 | 1000mm |
|----------------------|------------|--------|
| | A303-10-02 | 2000mm |
| | A303-10-03 | 3000mm |




| BRIGHT LINE End Caps Kit | A303-10-00- W |
|--------------------------|-----------------|
|--------------------------|-----------------|

Thickness of each cover = 2 mm.



| BRIGHT LINE Straight Joiner | A303-10-04 |
|-----------------------------|------------|
|-----------------------------|------------|



| BRIGHT LINE Power Line | A303-10-05 |
|------------------------|------------|
|------------------------|------------|



MOUNTING ACCESSORIES

| Track Fixation Kit | A219-21-06- B |
|--------------------|-----------------|
|--------------------|-----------------|




| Track Flush Ceiling Kit | A219-22-06- B |
|-------------------------|-----------------|
|-------------------------|-----------------|



| Track Track Clamp Kit for M6 ROD | A219-21-21- B |
|----------------------------------|-----------------|
|----------------------------------|-----------------|



| Track Suspension Kit | A219-21-10- B |
|----------------------|-----------------|
|----------------------|-----------------|



SUGGESTED MOUNTING ACCESSORIES QUANTITIES

- 250 mm - 1 Pcs
- 500 mm - 1 Pcs
- 1000 mm - 2 Pcs
- 2000 mm - 2 Pcs
- 3000 mm - 3 Pcs


Corner 90° One Plane - 2Pcs.

Corner 90° Two Planes - 3 Pcs - One unit (in the ceiling) and two units (in the wall) can be combined.

| | | P | V | Max Length | Max Length HO | D |
|------------------------------------|---------------------------------------|------|-----|------------|---------------|-----------------|
| *CONSTANT VOLTAGE LED POWER SUPPLY | ON/OFF 0433-10-22 | 96W | 24V | 7000mm | 3750mm | 300 x 40 x 21mm |
| | 80W 24V 6250mm 3000mm 345 x 32 x 22mm | 80W | 24V | 6250mm | 3000mm | 345 x 32 x 22mm |
| | DALI PUSH 0433-10-24 | 160W | 24V | 7000mm | 5000mm | 300 x 50 x 35mm |

220 V~ | DRIVER MUST BE PLACED ON REMOTE

» 282



COLOUR | W □ | B □ | MATERIAL | AL | PC |

RAL ⓘ » 312

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)

» 288

CUSTOM SYSTEM FIFTY + CUSTOM



Extended Family
Fifty + Surface_P.122
Fifty + Suspension_P.158



MORE INFO >>

*OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |

| | | P | CCT | I | Flux | L |
|-------------------------------|--------------------------|-------|-------|-------|---------|-------------|
| FIFTY + Surface Custom 100 | A443-01- Ⓞ -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 1000mm |
| | A443-01- Ⓞ -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 1000mm |
| FIFTY + Surface Custom 150 | A443-02- Ⓞ -1- WT NT | 23,1W | 3000K | 700mA | 3420 lm | 1500mm |
| | A443-02- Ⓞ -2- WT NT | 23,1W | 4000K | 700mA | 3600 lm | 1500mm |
| FIFTY + Surface Custom 200 | A443-03- Ⓞ -1- WT NT | 30,8W | 3000K | 700mA | 4560 lm | 2000mm |
| | A443-03- Ⓞ -2- WT NT | 30,8W | 4000K | 700mA | 4800 lm | 2000mm |
| FIFTY + Surface Custom 300 | A443-04- Ⓞ -1- WT NT | 46,2W | 3000K | 700mA | 6840 lm | 3000mm |
| | A443-04- Ⓞ -2- WT NT | 46,2W | 4000K | 700mA | 7200 lm | 3000mm |
| FIFTY + Surface Custom Corner | A443-05- Ⓞ -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 525 x 525mm |
| | A443-05- Ⓞ -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 525 x 525mm |

| | | | | | | |
|----------------------------------|--------------------------|-------|-------|--------|----------|-------------|
| FIFTY + HO Surface Custom 100 | A443-11- Ⓞ -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 1000mm |
| | A443-11- Ⓞ -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 1000mm |
| FIFTY + HO Surface Custom 150 | A443-12- Ⓞ -1- WT NT | 35,4W | 3000K | 1050mA | 4890 lm | 1500mm |
| | A443-12- Ⓞ -2- WT NT | 35,4W | 4000K | 1050mA | 5160 lm | 1500mm |
| FIFTY + HO Surface Custom 200 | A443-13- Ⓞ -1- WT NT | 47,2W | 3000K | 1050mA | 6520 lm | 2000mm |
| | A443-13- Ⓞ -2- WT NT | 47,2W | 4000K | 1050mA | 6880 lm | 2000mm |
| FIFTY + HO Surface Custom 300 | A443-14- Ⓞ -1- WT NT | 70,8W | 3000K | 1050mA | 9780 lm | 3000mm |
| | A443-14- Ⓞ -2- WT NT | 70,8W | 4000K | 1050mA | 10320 lm | 3000mm |
| FIFTY + HO Surface Custom Corner | A443-15- Ⓞ -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 525 x 525mm |
| | A443-15- Ⓞ -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 525 x 525mm |

220 V~ | IP20 | CRI>90 | L80B10 >60.000h



ACCESSORIES



| | | | |
|-----------------------------|-----|---------------------------------|-----|
| FIFTY + Diffuser [x meter] | LOR | FIFTY + UGR Diffuser [x meter] | LOR |
| A447-00-00 | 70% | A447-00-10 | 47% |

Max length 30 m.

Max length 30 m.

| | |
|-----------------------|-------------------------|
| FIFTY + End Caps Kit | FIFTY + Straight Joiner |
| A447-00-20- WT NT | A447-00-30 |


| |
|--------------------|
| FIFTY + Power Line |
| A443-00-00 |






COLOUR | WT □ | NT ■ | MATERIAL | AL | PC |

RAL ⓘ » 312

» 288



MORE INFO >>




| | | P | CCT | I | Flux | L |
|--|--------------------------|-------|-------|--------|----------|-------------|
| FIFTY + Suspension Custom 100 | A444-01- ① -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 1000mm |
| | A444-01- ① -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 1000mm |
| FIFTY + Suspension Custom 150 | A444-02- ① -1- WT NT | 23,1W | 3000K | 700mA | 3420 lm | 1510mm |
| | A444-02- ① -2- WT NT | 23,1W | 4000K | 700mA | 3600 lm | 1510mm |
| FIFTY + Suspension Custom 200 | A444-03- ① -1- WT NT | 30,8W | 3000K | 700mA | 4560 lm | 2000mm |
| | A444-03- ① -2- WT NT | 30,8W | 4000K | 700mA | 4800 lm | 2000mm |
| FIFTY + Suspension Custom 300 | A444-04- ① -1- WT NT | 46,2W | 3000K | 700mA | 6840 lm | 3000mm |
| | A444-04- ① -2- WT NT | 46,2W | 4000K | 700mA | 7200 lm | 3000mm |
| FIFTY + Suspension Custom Corner | A444-05- ① -1- WT NT | 15,4W | 3000K | 700mA | 2280 lm | 525 x 525mm |
| | A444-05- ① -2- WT NT | 15,4W | 4000K | 700mA | 2400 lm | 525 x 525mm |
| FIFTY + HO Suspension Custom 100 | A444-11- ① -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 1000mm |
| | A444-11- ① -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 1000mm |
| FIFTY + HO Suspension Custom 150 | A444-12- ① -1- WT NT | 35,4W | 3000K | 1050mA | 4890 lm | 1510mm |
| | A444-12- ① -2- WT NT | 35,4W | 4000K | 1050mA | 5160 lm | 1510mm |
| FIFTY + HO Suspension Custom 200 | A444-13- ① -1- WT NT | 47,2W | 3000K | 1050mA | 6520 lm | 2000mm |
| | A444-13- ① -2- WT NT | 47,2W | 4000K | 1050mA | 6880 lm | 2000mm |
| FIFTY + HO Suspension Custom 300 | A444-14- ① -1- WT NT | 70,8W | 3000K | 1050mA | 9780 lm | 3000mm |
| | A444-14- ① -2- WT NT | 70,8W | 4000K | 1050mA | 10320 lm | 3000mm |
| FIFTY + HO Suspension Custom Corner | A444-15- ① -1- WT NT | 23,6W | 3000K | 1050mA | 3260 lm | 525 x 525mm |
| | A444-15- ① -2- WT NT | 23,6W | 4000K | 1050mA | 3440 lm | 525 x 525mm |



① *OPTIONS

| | |
|---|----------|
| 1 | No DIM |
| 2 | DIM DALI |
| 3 | DIM Push |



COLOUR | WT □ | NT ■ | MATERIAL | AL | PC | RAL ⓘ » 312

» 288



PRODUCT CONFIGURATOR

Configure your own custom product layout. Our tool will calculate the required drivers and accessories.

ACCESSORIES

| | | | |
|-------------------------------|--------|--|-----|
| FIFTY + Diffuser (x meter) | LOR | FIFTY + UGR Diffuser (x meter) | LOR |
| A447-00-00 | 70% | A447-00-10 | 47% |
| Max length 30m. | | Max length 30m. | |
| FIFTY + End Caps Kit | | FIFTY + Straight Joiner | |
| A447-00-20- WT NT | | A447-00-30 | |
| FIFTY + Suspension Power Line | | FIFTY + Suspension Kit | |
| A444-00-00- WT NT | NO DIM | A444-00-20- WT NT | |
| A444-00-10- WT NT | DIM | At least 2 units needed. Extra unit each 100 cm. required | |

OPTIONAL ACCESSORIES

WIRE TRIMLESS Accessories


FEED

Mains Trimless

A023-00-01- | W | N |

Mains Thick Trimless


A023-00-02- | W | N |




FASTENING

Steel Cable Trimless**


A023-00-05- | W | N |




TRIMLESS TOOL D20 X D52mm A478-00-01




MAINS TRIMLESS



MAINS THICK TRIMLESS



STEEL CABLE TRIMLESS



COLOUR | WT □ | NT ■ | W □ | N ■ | MATERIAL | AL | PC | RAL ⓘ » 312

** AS MANY PIECES AS NEEDED ACCORDING TO YOUR PRODUCT


» 288

SKIP_266
YORU SPIKE_267
STEP_268
DARK_270



OUTDOOR

SKIP



MORE INFO >>

| | | P | CCT | BEAM | I | Flux | LOR |
|------|-------------------------|------|-------|------|-------|--------|-----|
| SKIP | A497-01 - 10- GT OX | 5,5W | 2700K | 19° | 500mA | 620 lm | 87% |
| | A497-01 - 11- GT OX | 5,5W | 3000K | 19° | 500mA | 660 lm | 87% |
| | A497-01 - 20- GT OX | 5,5W | 2700K | 29° | 500mA | 620 lm | 91% |
| | A497-01 - 21- GT OX | 5,5W | 3000K | 29° | 500mA | 660 lm | 91% |
| | A497-01 - 30- GT OX | 5,5W | 2700K | 35° | 500mA | 620 lm | 89% |
| | A497-01 - 31- GT OX | 5,5W | 3000K | 35° | 500mA | 660 lm | 89% |

220 V~ | IP65 | CRI>90 | L90B10 >108.000h




| | | P | CCT | BEAM | I | Flux | LOR |
|------|-------------------------|------|-------|------|-------|--------|-----|
| SKIP | A497-02 - 10- GT OX | 5,5W | 2700K | 19° | 500mA | 620 lm | 87% |
| | A497-02 - 11- GT OX | 5,5W | 3000K | 19° | 500mA | 660 lm | 87% |
| | A497-02 - 20- GT OX | 5,5W | 2700K | 29° | 500mA | 620 lm | 91% |
| | A497-02 - 21- GT OX | 5,5W | 3000K | 29° | 500mA | 660 lm | 91% |
| | A497-02 - 30- GT OX | 5,5W | 2700K | 35° | 500mA | 620 lm | 89% |
| | A497-02 - 31- GT OX | 5,5W | 3000K | 35° | 500mA | 660 lm | 89% |

48 V | IP65 | CRI>90 | L90B10 >108.000h



| | P | V |
|-----------------------------------|------------|----------|
| CONSTANT VOLTAGE LED POWER SUPPLY | 0434-01-62 | 150W 48V |

220 V~ | IP20 | DRIVER MUST BE PLACED ON REMOTE



| POWER [W] | CABLE SECTION [mm²] | CABLE LENGTH [m] | | | |
|-----------|---------------------|------------------|-----|-----|------|
| | | <25 | <50 | <75 | <100 |
| 150 | 0,75 | ✓ | ✓ | X | X |
| | 1,0 | ✓ | ✓ | ✓ | X |
| | 1,5 | ✓ | ✓ | ✓ | ✓ |

OPTIONAL ACCESSORIES

Connector IP67 No DIM 0434-01-81- | N |



Connector IP67 No DIM T-Shape 0434-01-82- | N |

For cable Ø4,5-7,5mm, section <1,5mm²

Connector IP67 DIM DALI 0434-01-83- | N |

Connector IP67 DIM DALI T-Shape 0434-01-84- | N |

For cable Ø5,5-7,5mm, section <1,0mm²



SKIP Anti-glare Screen A497-00 - 00- | GT | OX |

AFFECTS THE LIGHTING PARAMETERS



COLOUR | GT ■ | OX ■ | MATERIAL | AL | GL-TRANS | PC | RAL ⓘ » 312

OTHER CCT PLEASE CONSULT ((Ⓞ)) » 288

YORU SPIKE



Extended Family
Yoru_P.164



MORE INFO >>

| | | P | CCT | Flux | LOR |
|----------------|--------------------------|----|-------|--------|-----|
| YORU Spike 24V | A475- -0 - 00- WT NT | 3W | 2700K | 400 lm | 84% |
| | A475- -0 - 01- WT NT | 3W | 3000K | 410 lm | 84% |

24 V | IP65 | CRI>90 | L80B10 >60.000h



Ⓞ TOTAL HEIGHT - H



| | |
|---|--------|
| 1 | 400 mm |
| 2 | 500 mm |

OPTIONAL ACCESSORY

Connector IP67 0434-01-67- | N |


Connector IP67 T-Shape 0434-01-68- | N |

For cable Ø3,5-7,5mm, section <1,5mm²




| | P | V | D [A x B x C] |
|------------------------|------------|----------|-----------------|
| YORU Spike 24V | 0434-01-37 | 60W 24V | 180 x 52 x 30mm |
| ** Remote Power Supply | 0433-10-22 | 100W 24V | 295 x 43 x 30mm |

220 V~ | IP20



| | | P | V | D [A x B x C] |
|----------------|----------------------------------|------------|-----------------|-----------------|
| YORU Spike 24V | * Remote Constant Voltage Dimmer | 0433-01-32 | DALI / Push 24V | 181 x 42 x 20mm |
| | | 0433-01-33 | CASAMBI 24V | 172 x 42 x 20mm |
| | | 0434-01-64 | WIFI 24V | 105 x 44 x 23mm |

24 V | IP20




| POWER [W] | CABLE SECTION [mm²] | CABLE LENGTH [m] | | | |
|-----------|---------------------|------------------|-----|-----|------|
| | | <25 | <50 | <75 | <100 |
| 60 | 0,75 | ✓ | ✓ | X | X |
| | 1,5 | ✓ | ✓ | ✓ | ✓ |
| 100 | 0,75 | ✓ | X | X | X |
| | 1,5 | ✓ | ✓ | ✓ | X |

COLOUR | WT □ | NT ■ | MATERIAL | INOX AISI 304 | AL | PC | RAL ⓘ » 312

((Ⓞ)) » 288

STEP



MORE INFO >>

| STEP | CCT | LOR |
|--------------------------|-------|-----|
| A275-00-00- NX W N | 2700K | 15% |
| A275-00-01- NX W N | 3000K | 15% |
| A275-00-02- NX W N | 4000K | 15% |
| A275-00-03- NX W N | blue | 1% |



III IP67 | IK08 | CRI>90 | L90B10 > 102,000h



| *DRIVER OPTIONS | P | I | CCT | Flux |
|-----------------|----|-------|-------|--------|
| 0434-00-39 | 1W | 350mA | 2700K | 100 lm |
| | | | 3000K | 120 lm |
| | | | 4000K | 130 lm |
| | | | blue | 130 lm |

NO DIM | IP20*


220 V~ | DRIVER MUST BE PLACED ON REMOTE | OTHER DIM OPTIONS PLEASE CONSULT

i » 282


OPTIONAL ACCESSORY

Connector IP67 0434-01-66- | N |

For cable Ø4,5-6,5mm, section <1,5mm²



STEP




COLOUR | NX ■ | W □ | N ■ |


MATERIAL | INOX AISI 304 | AL | PMMA |

RAL i » 312

((©)) » 288



MORE INFO >>



MORE INFO >>

| STEP S | CCT | LOR |
|--------------------------|-------|-----|
| A392-00-00- NX W N | 2700K | 10% |
| A392-00-01- NX W N | 3000K | 10% |
| A392-00-02- NX W N | 4000K | 10% |



III IP65 | IK06 | CRI>90 | L90B10 > 102,000h



| STEP XS | CCT | LOR |
|--------------------------|-------|-----|
| A393-00-00- NX W N | 2700K | 7% |
| A393-00-01- NX W N | 3000K | 7% |
| A393-00-02- NX W N | 4000K | 7% |



III IP65 | IK10 | CRI>90 | L90B10 > 102,000h




| *DRIVER OPTIONS | P | I | CCT | Flux |
|-----------------|----|-------|-------|--------|
| 0434-00-39 | 1W | 350mA | 2700K | 100 lm |
| | | | 3000K | 120 lm |
| | | | 4000K | 130 lm |
| | | | blue | 130 lm |
| | | | 2700K | 100 lm |
| | | | 3000K | 120 lm |
| | | | 4000K | 130 lm |

NO DIM | IP20*




220 V~ | DRIVER MUST BE PLACED ON REMOTE | OTHER DIM OPTIONS PLEASE CONSULT

i » 282

STEP S



STEP XS



COLOUR | NX ■ | W □ | N ■ |

MATERIAL | INOX AISI 304 | AL | PMMA |

RAL i » 312

((©)) » 288

DARK



MORE INFO >>



MORE INFO >>

| | | CCT | Beam | LOR |
|------|----------------------|-------|------|-----|
| DARK | A274-00-10- NX N | 2700K | 19° | 80% |
| | A274-00-11- NX N | 3000K | 19° | 80% |
| | A274-00-12- NX N | 4000K | 19° | 80% |
| | A274-00-20- NX N | 2700K | 40° | 83% |
| | A274-00-21- NX N | 3000K | 40° | 83% |
| | A274-00-22- NX N | 4000K | 40° | 83% |



IP67 | IK08 | CRI>90 | L90B10 >102,000h



| | | CCT | Beam | LOR |
|----------------|----------------------|-------|------|-----|
| DARK Honeycomb | A513-00-10- NX N | 2700K | 17° | 54% |
| | A513-00-11- NX N | 3000K | 17° | 54% |
| | A513-00-12- NX N | 4000K | 17° | 54% |
| | A513-00-20- NX N | 2700K | 30° | 53% |
| | A513-00-21- NX N | 3000K | 30° | 53% |
| | A513-00-22- NX N | 4000K | 30° | 53% |



IP67 | IK08 | CRI>90 | L90B10 >102,000h



| *DRIVER OPTIONS | P | I | CCT | Flux |
|-----------------------------|------|--------|-------|--------|
| 0434-00-39 1 to 12 Darks | 1W | 350mA | 2700K | 100 lm |
| | | | 3000K | 120 lm |
| | | | 4000K | 130 lm |
| NO DIM IP20 | | | | |
| 0434-00-40 1 to 12 Darks | 2,1W | 700mA | 2700K | 180 lm |
| | | | 3000K | 200 lm |
| | | | 4000K | 240 lm |
| NO DIM IP20 | | | | |
| 0434-00-41 1 to 11 Darks | 3,2W | 1050mA | 2700K | 250 lm |
| | | | 3000K | 280 lm |
| | | | 4000K | 325 lm |
| NO DIM IP20 | | | | |


220 V~ | OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORY



Connector IP67

0434-01-66- | N |



For cable Ø4,5-6,5mm, section <1,5mm²





DARK & DARK HONEYCOMB



DARK M & DARK M HONEYCOMB



DARK M ASYMMETRIC



COLOUR | NX ■ | N ■ |

MATERIAL | INOX AISI 304 | AL | GL-TRANS |

RAL ⓘ » 312

Ⓜ » 288



MORE INFO >>



MORE INFO >>



MORE INFO >>

| | | CCT | LOR |
|--------|----------------------|-------|-----|
| DARK M | A301-00-10- NX N | 2700K | 75% |
| | A301-00-11- NX N | 3000K | 75% |
| | A301-00-12- NX N | 4000K | 75% |



IP67 | IK08 | CRI>90 | L90B10 >55,000h



| | | CCT | LOR |
|------------------|----------------------|-------|-----|
| DARK M Honeycomb | A514-00-10- NX N | 2700K | 53% |
| | A514-00-11- NX N | 3000K | 53% |
| | A514-00-12- NX N | 4000K | 53% |



IP67 | IK08 | CRI>90 | L90B10 >55,000h



| | | CCT | LOR |
|-------------------|----------------------|-------|-----|
| DARK M Asymmetric | A440-00-10- NX N | 2700K | 75% |
| | A440-00-11- NX N | 3000K | 75% |
| | A440-00-12- NX N | 4000K | 75% |



IP67 | IK08 | CRI>90 | L90B10 >55,000h



| *DRIVER OPTIONS | P | I | CCT | Flux |
|------------------------|-------|-------|-------|---------|
| 0434-00-36 1 Dark M | 4,6W | 140mA | 2700K | 640 lm |
| | | | 3000K | 665 lm |
| NO DIM IP20 | | | 4000K | 675 lm |
| 0434-00-37 1 Dark M | 6,7W | 200mA | 2700K | 865 lm |
| | | | 3000K | 900 lm |
| NO DIM IP20 | | | 4000K | 915 lm |
| 0434-00-38 1 Dark M | 10,5W | 300mA | 2700K | 1220 lm |
| | | | 3000K | 1265 lm |
| NO DIM IP20 | | | 4000K | 1290 lm |

220 V~ | DRIVER MUST BE PLACED ON REMOTE PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT


ⓘ » 282

OPTIONAL ACCESSORY

Connector IP67

0434-01-66- | N |

For cable Ø4,5-6,5mm, section <1,5mm²



COLOUR | NX ■ | N ■ |

MATERIAL | INOX AISI 304 | AL | GL-TRANS |

RAL ⓘ » 312

Ⓜ » 288

LARK-111_274

LARK_275

BASIC_275

TRIMLESS TOOL_276

WIRE TRIMLESS_278

DRIVERS_282

ARK-CONTROL_288

TECHNICAL INFO_295

GLOSSARY_302

COLOURS_312

SIMBOLS GLOSSARY_314

REFERENCE INDEX_316

PRODUCT INDEX_318

LARK-111



| | | P | CCT | Beam | I | Flux | Flux Out | LOR | | |
|---------------|-----------------------------|-----------------------------|-----------------------------|-------|-------|---------|----------|---------|---------|-----|
| Lark-111 | A25 \odot -10-10- W N | 6,5W | 2700K | 19° | 200mA | 900 lm | 828 lm | 92% | | |
| | A25 \odot -10-11- W N | 6,5W | 3000K | 19° | 200mA | 940 lm | 865 lm | 92% | | |
| | A25 \odot -10-12- W N | 6,5W | 4000K | 19° | 200mA | 950 lm | 874 lm | 92% | | |
| | A25 \odot -10-20- W N | 6,5W | 2700K | 40° | 200mA | 900 lm | 774 lm | 86% | | |
| | PHASE CUT * | A25 \odot -10-21- W N | 6,5W | 3000K | 40° | 200mA | 940 lm | 808 lm | 86% | |
| | | A25 \odot -10-22- W N | 6,5W | 4000K | 40° | 200mA | 950 lm | 817 lm | 86% | |
| | PHASE CUT * | A25 \odot -20-10- W N | 12W | 2700K | 19° | 350mA | 1440 lm | 1325 lm | 92% | |
| | | A25 \odot -20-11- W N | 12W | 3000K | 19° | 350mA | 1500 lm | 1380 lm | 92% | |
| | | A25 \odot -20-12- W N | 12W | 4000K | 19° | 350mA | 1520 lm | 1398 lm | 92% | |
| | | A25 \odot -20-20- W N | 12W | 2700K | 40° | 350mA | 1440 lm | 1238 lm | 86% | |
| | | PHASE CUT * | A25 \odot -20-21- W N | 12W | 3000K | 40° | 350mA | 1500 lm | 1290 lm | 86% |
| | | | A25 \odot -20-22- W N | 12W | 4000K | 40° | 350mA | 1520 lm | 1307 lm | 86% |
| DALI I PUSH * | A25 \odot -21-10- W N | 12W | 2700K | 19° | 350mA | 1440 lm | 1325 lm | 92% | | |
| | A25 \odot -21-11- W N | 12W | 3000K | 19° | 350mA | 1500 lm | 1380 lm | 92% | | |
| | A25 \odot -21-12- W N | 12W | 4000K | 19° | 350mA | 1520 lm | 1398 lm | 92% | | |
| | A25 \odot -21-20- W N | 12W | 2700K | 40° | 350mA | 1440 lm | 1238 lm | 86% | | |
| | DALI I PUSH * | A25 \odot -21-21- W N | 12W | 3000K | 40° | 350mA | 1500 lm | 1290 lm | 86% | |
| | | A25 \odot -21-22- W N | 12W | 4000K | 40° | 350mA | 1520 lm | 1307 lm | 86% | |

220 V~ | CRI>90 | L90B10 >55.000h

* OTHER DIM OPTIONS PLEASE CONSULT





MORE INFO >>

Lark-111



MORE INFO >>

Lark-111 · HONEYCOMB LOUVER



⊙ OPTIONS

- 2 Lark-111
- 3 Lark-111 Honeycomb**

** HONEYCOMB AFFECTS LIGHTING PARAMETERS

COLOUR | W □ | N ■ |

MATERIAL | AL |

RAL » 312


» PLEASE CONSULT

LARK



MORE INFO >>

Lark



BASIC




OPTIONAL ACCESSORIES

SAFETY SEPARATOR

0458-00-00

with connection box covered



HALOGEN LAMPHOLDER GZ10


0419-00-00



| | | P | CCT | I | Flux | Flux Out | LOR | |
|------|---------------|------------|-------|-------|---------|----------|--------|-----|
| Lark | 0434-00-96 | 5W | 2700K | 140mA | 700 lm | 644 lm | 92% | |
| | 0434-00-05 | 5W | 3000K | 140mA | 730 lm | 672 lm | 92% | |
| | 0434-00-19 | 5W | 4000K | 140mA | 750 lm | 690 lm | 92% | |
| | 0434-01-02 | 7,5W | 2700K | 200mA | 950 lm | 874 lm | 92% | |
| | 0434-00-09 | 7,5W | 3000K | 200mA | 1000 lm | 920 lm | 92% | |
| | 0434-00-17 | 7,5W | 4000K | 200mA | 1030 lm | 948 lm | 92% | |
| | 0434-01-03 | 7,5W | 2700K | 200mA | 950 lm | 874 lm | 92% | |
| | 0434-00-15 | 7,5W | 3000K | 200mA | 1000 lm | 920 lm | 92% | |
| | PHASE CUT * | 0434-00-18 | 7,5W | 4000K | 200mA | 1030 lm | 948 lm | 92% |
| | | 0434-01-04 | 7,5W | 2700K | 200mA | 950 lm | 874 lm | 92% |
| | DALI I PUSH * | 0434-01-05 | 7,5W | 3000K | 200mA | 1000 lm | 920 lm | 92% |
| | | 0434-01-06 | 7,5W | 4000K | 200mA | 1030 lm | 948 lm | 92% |


220 V~ | CRI>80 | L90B10 >55.000h

* OTHER DIM OPTIONS PLEASE CONSULT



BASIC Fix 12V MAX 50W

0037-01-01- | W | NS |




BASIC Tilt 12V MAX 50W

0038-01-01- | W | NS |




BASIC Tilt Extra 12V MAX 50W

00321-01-01- | W | NS |




BASIC Fix 230V MAX 50W

0337-01-01- | W | NS |




BASIC Tilt 230V MAX 50W

0338-01-01- | W | NS |




BASIC Tilt Extra 230V MAX 50W


0325-01-01- | W | NS |




BASIC FIX



BASIC TILT



BASIC TILT EXTRA



COLOUR | W □ | NS ■ |

MATERIAL | AL |


RAL » 312

» PLEASE CONSULT




TRIMLESS TOOL

MORE INFO >>




TRIMLESS TOOL D16 X D34mm A478-00-00




Suitable for:
Magnetic Connector | A435-01-00:
· Coco | A499-00-XX
· Fit 20 | A431-01-XX
· Fit 27 | A432-01-XX
· Flip | A492-00-XX
· iO Micro | A434-01-XX
· Plus Micro | A433-01-XX
· Six XS | A429-01-XX
· Top Micro | A430-01-XX

TRIMLESS TOOL D20 X D52mm A478-00-01




Suitable for:
Alaska Big | A455-X1-XX
Dune | A48X-XX-XX
Wire Trimless Accessory | A023-XX-XX

TRIMLESS TOOL D43 X D70mm A478-00-02




Suitable for:
Alaska Trimless Accessory | A401-10-XX
Lens Light Trimless Accessory | A470-00-00
Shot Light Trimless Accessory | A269-00-0X

TRIMLESS TOOL D59 X D100mm A478-00-03




Suitable for:
Alaska Big Trimless Accessory | A426-10-00
Shot Light S Trimless Accessory | A463-00-00

TRIMLESS TOOL D79 X D86mm A478-00-04




Suitable for:
Shot Light S Flex | A477-00-00

TRIMLESS TOOL D79 X D120mm A478-00-05



Suitable for:
Shot Light M Trimless Accessory | A298-X0-00
Buddy Trimless Accessory | A50X-10-90

TRIMLESS MOUNTING






Installation guide

WIRE TRIMLESS


MORE INFO >>



- (A) Mains Trimless
- (B) Mains Thick Trimless
- (C) Coaxial Trimless
- (D) Unipolar Trimless
- (E) Steel Cable Trimless
- (F) Steel Cable Regulator Trimless



Mains Trimless A023-00-01- | W | N |




Suitable for:
 Black Foster Custom System (no dim) | A452-0X-00
 Black Foster Micro Custom (no dim) | A450-0X-00
 Black Foster Suspension (no dim) | A321-X1-XX
 Fifty+ Suspension (no dim) | A44X-XX-1X
 Salt (no dim) | A220-0X-1X
 Salt mini | A280-00-1X
 Scope | A261-XX-XX
 Track 48V Suspension (no dim) | A338-XX-00
 Vola Suspension | A442-00-XX

Mains Thick Trimless A023-00-02- | W | N |




Suitable for:
 Black Foster Custom System (dim) | A452-0X-00
 Black Foster Micro Custom (dim) | A450-0X-00
 Black Foster Suspension (dim) | A321-XX-XX
 Drum Suspension | A358-XX-XX
 Fifty+ Suspension (dim) | A44X-XX-XX
 Salt (dim) | A220-0X-XX
 Track 48V Suspension (dim) | A338-XX-00
 Vola Suspension | A442-00-XX

Coaxial Trimless A023-00-03- | W | N |




Suitable for:
 Alaska | A425-XX-XX
 Holly | A281-XX-XX
 Line Suspension | A43X-XX-XX
 Minimal Track
 Pipe | A48X-XX-XX
 Slimgot | A203-XX-XX
 Spin | A222-XX-XX
 Stick | A40X-XX-XX

Unipolar Trimless A023-00-04- | W | N |



Suitable for:
 Art | A34X-XX-XX

Steel Cable Trimless A023-00-05- | W | N |



Suitable for:
 Line Suspension | A43X-XX-XX
 Black Foster Custom System | A452-0X-00
 Black Foster Micro Custom | A450-0X-00
 Black Foster Suspension | A321-XX-XX
 Drum Suspension | A358-XX-XX
 Fifty+ Suspension | A44X-XX-XX
 Salt | A220-0X-XX
 Salt Mini | A280-00-1X
 Track 48V Suspension | A338-XX-00
 Vola Suspension | A442-00-XX

Steel Cable Regulator Trimless A023-00-06- | W | N |



Suitable for:
 Scope | A261-XX-XX

Accessories

LIGHT DISTRIBUTION



ELLIPTICAL REFRACTOR

Lente que reformula el haz de luz para conseguir una forma elíptica a través de la refracción de la luz en su disco de plástico (PMMA) + Film de PET.

Lens that modifies the light beam to achieve an elliptical shape through the refraction of light in its plastic disc (PMMA) + PET film.

Lentille qui reformule le faisceau lumineux pour obtenir une forme elliptique par le biais de la réfraction de la lumière dans son disque en plastique (PMMA) + Film de PET.

Lente che riformula il fascio di luce per ottenere una forma ellittica a causa della rifrazione della luce sul suo vetro ottico (PMMA) + Film in PET.

Linse, die den Lichtstrahl umformt, um durch die Lichtbrechung in ihrer Kunststoffscheibe (PMMA) + PET-Folie eine elliptische Form zu erreichen.



BEAM MIXER DIFFUSER

El difusor homogeneizador del haz de luz suaviza las distorsiones en la emisión de la luz provocadas por las lentes parabólicas, Fresnel o colimadores TIR, sin generar un alargamiento significativo del haz. Su diseño exclusivo consigue una homogeneización de la luz excelente en planos lejanos y una mezcla cromática con una extraordinaria luminosidad axial. Comparado con los difusores tradicionales, mantiene una mayor intensidad de candelas en el centro del haz (CBPC) y disminuye el antiestético efecto de “campos de luz” en ángulos amplios.

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening. The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBPC), and produce less undesirable “field light” at higher angles.

Le Diffuseur homogénéisateur de faisceau lumineux s'utilise pour atténuer les distorsions de l'émission de lumières provoquées par les lentilles paraboliques, Fresnel ou collimateurs TIR, sans allonger de manière significative le faisceau. Son design exclusif permet une excellente homogénéisation en champs lointains et un mélange chromatique d'une luminosité axiale remarquable. Comparé avec un diffuseur traditionnel, ce diffuseur maintient une plus haute intensité lumineuse au centre du faisceau (CBPC) et diminue

l'indésirable effet “champs de lumière” dans les angles plus amples.

Il Diffusore di fascio luminoso misto serve ad uniformare gli effetti distorsivi del fascio luminoso dovuti ai collimatori con lente parabolica, di Fresnel o TIR senza un allargamento significativo. L'eccezionale design “misto” assicura una migliore uniformità del campo lontano e una miscelazione cromatica con una straordinaria luminosità assiale. Rispetto ai diffusori tradizionali, mantiene una maggiore intensità luminosa in candele al centro del fascio (CBPC) e diminuisce la sgradevole “luce a lunga gittata” negli angoli più ampi.

Der Strahlenmischdiffusor wird verwendet, um durch parabolische, Fresnel- oder TIR-Linsen-Kollimatoren verursachte Strahlenartefakte ohne wesentliche Ausdehnung zu glätten. Das einzigartige Mischungskonzeption sorgt für hochwertige Fernfeldglättung und Farbmischung bei hoher on-axis-Helligkeit. Im Vergleich zu herkömmlichen Diffusoren bewahrt er eine höhere Lichtstärkenspitze (CBPC) und ruft bei größeren Winkeln weniger unerwünschte “Lichtfelder” hervor.



ANTI-GLARE HONEYCOMB LOUVER

Accesorio formado por una parrilla en forma de panel de abeja para reducir el deslumbramiento y la incidencia directa de los rayos en la visión.

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays on vision.

Accessoire composé d'une grille en nid d'abeille pour réduire l'éblouissement et l'incidence directe des rayons dans la vision.

Accesorio formado da una griglia a forma di pannello d'ape per ridurre l'abbagliamento e l'incidenza diretta dei raggi durante la visione.

Zubehör in Form eines Wabengitters, um die Blendung und den direkten Einfall der Strahlen in die Augen zu reduzieren.



LINEAR FILTER

Transforma el haz de luz circular en una forma lineal. Este filtro es ideal para aplicaciones donde se necesita una distribución precisa y lineal de la luz, para focalizar sobre superficies concretas o evitar el efecto de “manchas de luz” en espacios amplios.

Transforms the circular light beam into a linear form. This filter is ideal for applications where a precise and linear distribution of

light is needed, either for focusing on specific surfaces or to avoid the “light pooling” effect in large spaces.

Transforme le faisceau lumineux circulaire en une forme linéaire. Ce filtre est idéal pour les applications où une distribution précise et linéaire de la lumière est nécessaire, que ce soit pour se concentrer sur des surfaces spécifiques ou pour éviter l'effet de “taches lumineuses” dans de grands espaces.

Trasforma il fascio di luce circolare in una forma lineare. Questo filtro è ideale per applicazioni in cui è necessaria una distribuzione precisa e lineare della luce, sia per mettere a fuoco superfici specifiche che per evitare le proiezioni di luce puntuale nello spazio.

Verwandelt den kreisförmigen Lichtstrahl in eine lineare Form. Dieser Filter ist ideal für Anwendungen, bei denen eine präzise und lineare Lichtverteilung erforderlich ist, entweder um sich auf bestimmte Oberflächen zu konzentrieren oder um den Effekt von “Lichtflecken” in großen Räumen zu vermeiden.



ANTI-GLARE SCREEN & ANTI-GLARE ASYMMETRICAL SCREEN

Pantalla accesoría diseñada para reducir el deslumbramiento y la incidencia directa de los rayos en la visión. Además, en el caso de la pantalla asimétrica, se consigue una distribución luminica de incidencia lateral (adecuada para aplicaciones de bañador de pared, entre otras).

Accessory screen designed to reduce glare and direct ray incidence in vision. Additionally, in the case of the asymmetric screen, it achieves a lateral light distribution (suitable for wall washer applications, among others).

Écran accessoire conçu pour réduire l'éblouissement et l'incidence directe des rayons dans la vision. De plus, dans le cas de l'écran asymétrique, il permet d'obtenir une distribution lumineuse latérale (appropriée pour les applications de lèche-murs, entre autres).

Schermo accessorio progettato per ridurre l'abbagliamento e l'incidenza diretta dei raggi nella visione. Inoltre, nel caso dello schermo asimmetrico, si ottiene una distribuzione luminosa laterale (adatta per applicazioni di wall washer, tra le altre).

Zusatzbildschirm, der entwickelt wurde, um Blendung und direkten Lichteinfall in die Sicht zu reduzieren. Darüber hinaus ermöglicht er im Fall des asymmetrischen Bildschirms eine seitliche Lichtverteilung (zum Beispiel für Wandbestrahlung).

Special LED

FOR COMMERCIAL PRODUCT SHOWCASING

VIVID MODEL

| Colour Temperature | 2700K | 3000K | 3500K | 4000K | Light Pink |
|---------------------|-------|-------|-------|-------|------------|
| Reading | | | ● | ● | |
| Fruits & Vegetables | | ● | ● | | |
| Bakery | ● | | | | |
| Retail | | ● | ● | | |
| Cosmetics | | | ● | ● | |
| Meat | | | | | ● |
| Fish | | | | ● | |
| Seafood | | | | ● | ● |

AVAILABLE FOR | ALASKA · BUDDY · DARK M · DUNE 35 & 55 · DUOMO · FIT 65 & 80 · HIDDEN · HUBBLE · IO · LEX · LEX MINI · PLUS · PLUS MINI 1L & 3L · PUCK RECESSED S & L · SHOT LIGHT M & BIG · SIX XS, M & L · THOR · TOP · TOP MINI · TWIST · WELLIT S, M & L · WIZ · ZEN TUBE

Arkoslight ofrece en algunos de sus productos la posibilidad de dotarlos de un LED especial para iluminación orientada a la promoción visual de bienes y productos con finalidad comercial. Se trata de un LED de alta cromaticidad que persigue destacar los tonos que favorecen la percepción psicológica positiva del objeto iluminado.

Esta fuente de luz LED especial ofrece una paleta de colores más atractiva e intensa, por encima de lo que lo hace un LED convencional. Esto se consigue gracias a la configuración del LED bajo un “parámetro especial de saturación” que consigue que los colores y la textura de los objetos se muestren más atractivos dentro del espectro de luz visible. Para ello se selecciona, en cada caso, el COB pertinente, con su recubrimiento específico de fósforo.

For some of its products, Arkoslight offers the possibility to provide them with a special LED, designed to create an illumination focused on visually promoting goods or products for commercial purposes. It is a high chromaticity LED, capable of identifying the colour shades that produce a positive psychological perception of the illuminated object. This special LED lighting source offers a much more attractive and intense colour range than a conventional LED, besides being much wider. Technically, this is possible thanks to a special LED setting that includes a « special saturation parameter », capable of highlighting the objects colours and materials in such a way that they seem more attractive within the visible light spectrum. To achieve this performance, in each case, the appropriate COB and specific phosphor coating are carefully selected.

Arkoslight vous offre sur certains de ses produits la possibilité de les équiper d'une LED spéciale, qui a été conçue pour une illumination orientée à la promotion visuelle de biens ou produits à des fins commerciales. Il s'agit d'une LED de haute chromaticité permettant de mettre en évidence les tons qui favorisent une perception psychologique positive de l'objet illuminé.

Cette source de lumière LED spéciale vous offre une palette de couleurs plus attractive et intense, et plus vaste que celle d'une LED conventionnelle. Ceci est possible grâce à la configuration du LED qui inclue un “paramètre spécial de saturation”, lequel réussit à ce que les couleurs et la texture des objets apparaissent de manière plus attractive dans le spectre de lumière visible. Pour ce faire, le COB correspondant est sélectionné en fonction de chaque cas, et il en est de même pour son revêtement spécifique en phosphore.

Arkoslight offre su alcuni dei suoi prodotti la possibilità di dotarli di un LED speciale per illuminazione orientata alla promozione visiva di beni e prodotti a scopo commerciale. Si tratta di un LED ad alta cromaticità che mette in rilievo le tonalità che favoriscono la percezione psicologica positiva dell'oggetto illuminato. Questa sorgente di luce LED speciale offre una gamma di colori più attraenti e intensi, superiore a quella che può offrire un LED convenzionale. Ciò si ottiene grazie alla configurazione del LED secondo un “parametro speciale di saturazione” che fa in modo che i colori e la texture degli oggetti appaiano più attraenti all'interno dello spettro di luce visibile. A tale scopo si seleziona, in ciascun caso, l'apposito COB e il suo fosforo di rivestimento specifico.

Einige der Produkte von Arkoslight können mit einer Spezial-LED für die visuelle Bewerbung von Waren und Produkten zur Verkaufsförderung ausgerüstet werden. Dabei handelt es sich um eine hochchromatische LED, um Farbtöne hervorzuheben, die die positive psychologische Wahrnehmung des beleuchteten Objekts begünstigen. Diese spezielle LED-Lichtquelle bietet eine ansprechendere und intensivere Farbpalette als eine herkömmliche LED. Dies wird durch die Konfiguration der LED nach einem “speziellen Sättigungsparameter” erreicht, der Farben und Textur der Objekte innerhalb des sichtbaren Spektralbereichs attraktiver erscheinen lässt. Dafür wird die jeweils zweckdienliche COB und spezifische Phosphorbeschichtung gewählt.

Drivers

CONSTANT CURRENT LED DRIVER

| ON-OFF | | P (MAX) | I | D | |
|------------|--|--|--|-----------------------------------|-------------------|
| | 0486-04-35 | 3,5W | 350mA | 65 x 29 x 18mm | |
| | 0486-08-35 0434-01-30 | 8W 9W | 350mA 250mA | 59 x 41,6 x 22mm | |
| | 0486-12-70 | 12W | 700mA | 115 x 34 x 19mm | |
| | 0434-00-36 0434-00-37 0434-00-38 | 5,8W 8,3W 12,4W | 140mA 200mA 300mA | 115 x 34 x 19mm | |
| | 0434-01-85 0434-01-86 0434-01-87 | 5,5W 8,5W 22W | 125mA 200mA 300mA | 146,5 x 43,5 x 22mm | |
| | 0434-00-39 0434-01-53 0434-00-42 0434-00-40 0434-00-41 | 15W 18W 22W 31W 42W | 350mA 400mA 500mA 700mA 1050mA | 129 x 42 x 30mm | |
| | 0434-01-41 0434-01-42 0434-01-43 0434-01-44 | 25W 35W 50W 50W | 350mA 500mA 700mA 1050mA | 124 x 79 x 22mm | |
| DIM | | | | | |
| | PHASE CUT | 0434-01-92 | 8W | 200mA | 95 x 50 x 22mm |
| | PHASE CUT | 0434-01-95 | 9W | 350mA | 85 x 40,4 x 22mm |
| | DALI PUSH | 0434-01-89 0434-01-29 0434-01-94 0434-01-88 | 10W 10W 10W 10W | 200mA 250mA 350mA 500mA | 166 x 30 x 22mm |
| | DALI PUSH | 0433-01-07 | 11W | 300mA | 119 x 53 x 31mm |
| | 1-10V Push | 0434-00-78 0434-00-43 0434-00-45 | 18W 25W 32W | 350mA 500mA 700mA | 103 x 67 x 21mm |
| | DALI DT8 | 0434-01-90 | 18W | 400mA | 203 x 44,5 x 34mm |
| | DALI | 0434-00-79 0434-01-54 0434-00-44 0434-00-46 | 17W 19W 24W 32W | 350mA 400mA 500mA 700mA | 103 x 67 x 21mm |
| | DALI / PUSH / 1-10V | 0434-01-23 0434-01-24 0434-01-25 0434-01-26 | 25W 35W 50W 60W | 350mA 500mA 700mA 1050mA | 124 x 79 x 22mm |
| | CASAMBI | 0434-01-91 | 10W | 200mA | 150 x 42,5 x 22mm |
| | CASAMBI | 0434-01-45 0434-01-46 0434-01-47 0434-01-48 | 25W 35W 50W 60W | 350mA 500mA 700mA 1050mA | 124 x 79 x 22mm |

CONSTANT VOLTAGE LED DRIVER

| ON-OFF | | P (MAX) | V | D | |
|------------|--------------------------|--------------|------------|------------------------------------|-----------------|
| | 0434-01-37 | 60W | 24V | 180 x 52 x 30mm | |
| | 0433-10-22 | 100W | 24V | 295 x 43 x 30mm | |
| | 0434-01-61- W N | 100W | 48V | 298 x 16 x 19mm | |
| | 0434-01-62 0434-01-80 | 150W 250W | 48V 48V | 350 x 30 x 18mm 400 x 40 x 22mm | |
| DIM | | | | | |
| | DALI PUSH | 0433-10-23 | 80W | 24V | 346 x 32 x 22mm |
| | DALI PUSH | 0433-10-24 | 160W | 24V | 300 x 50 x 35mm |

MULTIFUNCTION EQUIPMENTS

| ON-OFF | | P / I | P / I or V | D | |
|----------------|---------------------|---|--|--|----------------------|
| | 0434-01-18 | 25W / 350mA 35W / 500mA 50W / 700mA | 50W / 900mA 50W / 1050mA 50W / 48V | 124 x 79 x 22mm | |
| DIM | | | | | |
| | 1-10V Push | 0486-00-00 | 16W / 300mA 18W / 350mA 25W / 500mA 30W / 600mA | 32W / 700mA 20W / 900mA 11W / 12V 20W / 24V | 103 x 67 x 21mm |
| | DALI | 0434-00-73 | 14W / 300mA 17W / 350mA 24W / 500mA 28W / 600mA | 32W / 700mA 10W / 12V 20W / 24V | 103 x 67 x 21mm |
| | DALI / PUSH / 1-10V | 0433-00-23 | 25W / 350mA 35W / 500mA 50W / 700mA | 60W / 900mA 60W / 1050mA 50W / 48V | 124 x 79 x 22mm |
| | CASAMBI | 0434-01-08 | 25W / 350mA 35W / 500mA 50W / 700mA | 60W / 900mA 60W / 1050mA 50W / 48V | 124 x 79 x 22mm |
| DIM 48V | | | | | |
| | DALI | 0434-01-93 | 8W / 200mA 12W / 300mA 16W / 400mA 20W / 500mA | 24W / 600mA 28W / 700mA 32W / 800mA 36W / 900mA | 97,5 x 17,6 x 11,8mm |

Driver options

FOR PRODUCTS WITH DRIVER EXCLUDED
220-240 VAC INPUT


| DIM | DRIVER | I | LUMINAIRES | | | | | | | | | | | | | | |
|---------|-----------|--------|-----------------|---------------------|------------------------------|--------------------------------|--------------------------------|-------------------------------|-------------------------------|--------------------------------|--------------------------------|-------|------------------|---------------------|--|---|--|
| | | | ALASKA TRIMLESS | BLACK FOSTER CUSTOM | BLACK FOSTER MICRO SURFACE 5 | BLACK FOSTER MICRO SURFACE 2X2 | BLACK FOSTER MICRO SURFACE 3X3 | BLACK FOSTER SURFACE REMOTE 3 | BLACK FOSTER SURFACE REMOTE 5 | BLACK FOSTER SURFACE REMOTE 10 | BLACK FOSTER SURFACE REMOTE 15 | BUDDY | BUDDY SUPER SPOT | BUDDY TUNABLE WHITE | | | |
| ON/OFF | D1 | 140mA | | | | | | | | | | | | | | | |
| | D2 | 200mA | | | | | | | | | | | | | | | |
| | D3 | 300mA | | | | | | | | | | | | | | | |
| | D4 | 350mA | | | | | | | | | | | | | | | |
| | D5 | 400mA | | | | | 1 | | | | | | | | | | |
| | D6 | 500mA | 1...4 | | 1...2 | 1...3 | | | | | | | | | | | |
| | D7 | 700mA | | | | | | 1...4 | 1...2 | 1 | | | | | | | |
| | D8 | 1050mA | | | | | | | | | | | | | | | |
| | D11 | 700mA | | 1...20* | | | | 1...6 | 1...3 | 1 | 1 | | | | | | |
| | D13 | 350mA | | | | | | | | | | | | | | | |
| | D14 | 350mA | | | | | | | | | | | | | | | |
| | D15 | 250mA | | | | | | | | | | | | | | | |
| | D16 | 125mA | | | | | | | | | 1 | | | | | | |
| | D17 | 200mA | | | | | | | | | 1 | | | | | | |
| | D18 | 500mA | | | | | | | | | | 1 | | | | | |
| | PHASE CUT | D19 | 200mA | | | | | | | | 1 | | | | | | |
| | | D20 | 350mA | | | | | | | | | | | | | | |
| | PUSH | D21 | 200mA | | | | | | | | 1 | | | | | | |
| D22 | | 250mA | | | | | | | | | | | | | | | |
| D23 | | 350mA | | | | | | | | | | | | | | | |
| D24 | | 500mA | | | | | | | | | | 1 | | | | | |
| D25 | | 300mA | | | | | | | | | | | | | | | |
| D26 | | 350mA | | | | | | | | | | | | | | | |
| D27 | | 500mA | 1...4 | | | | | | | | | | | | | | |
| D28 | | 700mA | | | | | | | | | | | | | | | |
| D34 | | 350mA | | | | | | | | | | | | | | | |
| D35 | | 500mA | 1...6 | | | | | | | | | | | | | | |
| D36 | 700mA | | 1...20* | | | | 1...6 | 1...3 | 1 | 1 | | | | | | | |
| D37 | 1050mA | | | | | | | | | | | | | | | | |
| DALI | D21 | 200mA | | | | | | | | 1 | | | | | | | |
| | D22 | 250mA | | | | | | | | | | | | | | | |
| | D23 | 350mA | | | | | | | | | | | | | | | |
| | D24 | 500mA | | | | | | | | | | 1 | | | | | |
| | D25 | 300mA | | | | | | | | | | | | | | | |
| | D29 | 350mA | | | | | | | | | | | | | | | |
| | D30 | 400mA | | | | | 1 | | | | | | | | | | |
| | D31 | 500mA | 1...4 | | 1...3 | 1...3 | | | | | | | | | | | |
| | D32 | 700mA | | | | | | 1...4 | 1...2 | 1 | | | | | | | |
| | D33 | 400mA | | | | | | | | | | | | | | 1 | |
| | D34 | 350mA | | | | | | | | | | | | | | | |
| D35 | 500mA | 1...6 | | | | | | | | | | | | | | | |
| D36 | 700mA | | 1...20* | | | | 1...6 | 1...3 | 1 | 1 | | | | | | | |
| D37 | 1050mA | | | | | | | | | | | | | | | | |
| CASAMBI | D38 | 350mA | | | | | | | | | | | | | | | |
| | D39 | 500mA | 1...6 | | | | | | | | | | | | | | |
| | D40 | 700mA | | 1...20* | | | | 1...6 | 1...3 | 1 | 1 | | | | | | |
| | D41 | 1050mA | | | | | | | | | | | | | | | |
| | D42 | 200mA | | | | | | | | | 1 | | | | | | |

| DIM | DRIVER | I | LUMINAIRES | | | | | | | | | | | | | | | |
|---------|-----------|--------|-------------------|---------|--------------|--------------|-----------|------------|----------------------|----------------------|-------------------------|----------|-------|--------|--------|-------|-------|--|
| | | | BUDDY DIM TO WARM | DARK M | DARK - RHINO | FLIP SURFACE | REC MICRO | SHOT LIGHT | SHOT LIGHT S SURFACE | SHOT LIGHT M SURFACE | STEP - STEP S - STEP XS | TOP MINI | WALLY | | | | | |
| ON/OFF | D1 | 140mA | | 1 | | | | | | | | | | | 1 | | | |
| | D2 | 200mA | | 1 | | | | | | | | | | | 1 | | | |
| | D3 | 300mA | | 1 | | | | | | | | | | | | | | |
| | D4 | 350mA | | | 1...12 | | | | | | | 1...3 | 1 | 1...12 | | | 1...4 | |
| | D5 | 400mA | | | | | | | | | | | | | | | | |
| | D6 | 500mA | | | | 1...3 | | | | | | 1...3 | | | | | 1...4 | |
| | D7 | 700mA | | | 1...12 | | | 1...2 | 1...12 | 1...3 | | | | | | | 1...4 | |
| | D8 | 1050mA | | | 1...11 | | | | | | | | | | | | | |
| | D11 | 700mA | | | 1...20 | | | 1...3 | 1...20 | | | | | | | | | |
| | D13 | 350mA | | | 1...3 | | | | | | | | | 1...3 | | | 1 | |
| | D14 | 350mA | | | 1...7 | | | | | | | | | 1...7 | | | | |
| | D15 | 250mA | | | | | | | | | | | | | | | 1...3 | |
| | D16 | 125mA | | | | | | | | | | | | | | | | |
| | D17 | 200mA | | | | | | | | | | | | | | | | |
| | D18 | 500mA | | | | | | | | | | | | | | | | |
| | PHASE CUT | D19 | 200mA | | | | | | | | | | | | | | | |
| | | D20 | 350mA | 1 | | | | | | | | | | | | | | |
| | PUSH | D21 | 200mA | | 1 | | | | | | | | | | | | | |
| D22 | | 250mA | | | | | | | | | | | | | | | 1...3 | |
| D23 | | 350mA | 1 | | | | | | | | | | | | | | | |
| D24 | | 500mA | | | | | | | | | | | | | | | | |
| D25 | | 300mA | | 1 | | | | | | | | | | | | | | |
| D26 | | 350mA | | | 4...14 | | | | | | | | 1 | 4...14 | | | 2...4 | |
| D27 | | 500mA | | | | | | | | | | | | | | 1...4 | | |
| D28 | | 700mA | | | 1...13 | | | | 1...13 | | | | | | | 1...4 | | |
| D34 | | 350mA | | | 1...20 | | | | | | | | | 1...20 | | | 1...6 | |
| D35 | | 500mA | | | | 1...5 | | | | | | | | | | 1...6 | | |
| D36 | 700mA | | | 1...20 | | | 1...3 | 1...20 | 1...5 | | | | | | 1...6 | | | |
| D37 | 1050mA | | | 1...16 | | | | | | | | | | | | | | |
| DALI | D21 | 200mA | | 1 | | | | | | | | | | | | | | |
| | D22 | 250mA | | | | | | | | | | | | | | | 1...3 | |
| | D23 | 350mA | 1 | | | | | | | | | | | | | | | |
| | D24 | 500mA | | | | | | | | | | | | | | | | |
| | D25 | 300mA | | 1 | | | | | | | | | | | | | | |
| | D29 | 350mA | | | 2...13 | | | | | | | | 1 | 2...13 | | | 1...4 | |
| | D30 | 400mA | | | | | | | | | | | | | | | | |
| | D31 | 500mA | | | | | | | | | 1...3 | | | | | 1...4 | | |
| | D32 | 700mA | | | 1...13 | | | 1...2 | 1...13 | 1...3 | | | | | | 1...4 | | |
| | D33 | 400mA | | | | | | | | | | | | | | | | |
| | D34 | 350mA | | | 1...20 | | | | | | | | | 1...20 | | | 1...6 | |
| D35 | 500mA | | | | 1...5 | | | | | | | | | | 1...6 | | | |
| D36 | 700mA | | | 1...20 | | | 1...3 | 1...20 | 1...5 | | | | | | 1...6 | | | |
| D37 | 1050mA | | | 1...16 | | | | | | | | | | | | | | |
| CASAMBI | D38 | 350mA | | | 1...20 | | | | | | | | | 1 | 1...20 | | 1...6 | |
| | D39 | 500mA | 1...6 | | | | | | | | | | | | | 1...6 | | |
| | D40 | 700mA | | 1...20* | | | | 1...6 | 1...3 | 1 | 1 | | | | | 1...6 | | |
| | D41 | 1050mA | | | | | | | | | | | | | | | | |
| | D42 | 200mA | | | | | | | | | 1 | | | | | | | |

CONSTANT CURRENT LED DRIVERS


| DRIVER | TYPOLGY | DIM | REFERENCE | DESCRIPTION | I |
|--------|---------|---------------------|--|--|--------|
| D1 | A | ON/OFF | 04340036 | DRIVER MP15 CONFIG.140mA | 140mA |
| D2 | A | | 04340037 | DRIVER MP15 CONFIG.200mA | 200mA |
| D3 | A | | 04340038 | DRIVER MP15 CONFIG.300mA | 300mA |
| D4 | A | | 04340039 | DRIVER PROFESSIONALE CONFIG.350mA | 350mA |
| D5 | A | | 04340153 | DRIVER PROFESSIONALE CONFIG.400mA | 400mA |
| D6 | A | | 04340042 | DRIVER PROFESSIONALE CONFIG.500mA | 500mA |
| D7 | B | | 04340040 | DRIVER PROFESSIONALE CONFIG.700mA | 700mA |
| D8 | C | | 04340041 | DRIVER PROFESSIONALE CONFIG.1050mA | 1050mA |
| D9 | A | | 04340141 | DRIVER MP50 K3 CONFIG.350mA | 350mA |
| D10 | A | | 04340142 | DRIVER MP50 K3 CONFIG.500mA | 500mA |
| D11 | B | | 04340143 | DRIVER MP50 K3 CONFIG.700mA | 700mA |
| D12 | C | | 04340144 | DRIVER MP50 K3 CONFIG.1050mA | 1050mA |
| D13 | G | | 04860435 | DRIVER LED 4W 350mA | 350mA |
| D14 | A | | 04860835 | DRIVER LED 8W BULL 350mA | 350mA |
| D15 | A | | 04340130 | DRIVER LED 9W BULL 250mA | 250mA |
| D16 | A | | 04340185 | DRIVER PRO FLAT CONFIG 125mA | 125mA |
| D17 | A | | 04340186 | DRIVER PRO FLAT CONFIG 200mA | 200mA |
| D18 | A | | 04340187 | DRIVER PRO FLAT CONFIG 500mA | 500mA |
| D19 | G | PHASE CUT | 04340192 | DRIVER LED DIM PH.CUT CONFIG.200mA | 200mA |
| D20 | G | | 04340195 | DRIVER 10W 350mA PHASE CUT DTW | 350mA |
| D21 | G | DALI + PUSH | 04340189 | DRIVER OTI DALI 10/220 PROGRAMADO 200mA | 200mA |
| D22 | G | | 04340129 | DRIVER OTI DALI 10/220 PROGRAMADO 250mA | 250mA |
| D23 | G | | 04340194 | DRIVER OTI DALI 10/220 PROGRAMADO 350mA | 350mA |
| D24 | G | | 04340188 | DRIVER OTI DALI 10/220 PROGRAMADO 500mA | 500mA |
| D25 | G | | 04330107 | KIT OTI LARK 11W 300mA DALI/PUSH | 300mA |
| D26 | D | PUSH + 1-10V | 04340078 | DRIVER JOLLY DIM 1/10V / PUSH CONFIG.350mA | 350mA |
| D27 | D | | 04340043 | DRIVER JOLLY DIM 1/10V / PUSH CONFIG.500mA | 500mA |
| D28 | E | | 04340045 | DRIVER JOLLY DIM 1/10V / PUSH CONFIG.700mA | 700mA |
| D29 | D | DALI | 04340079 | DRIVER JOLLY DIM DALI CONFIG 350mA | 350mA |
| D30 | D | | 04340154 | DRIVER JOLLY DIM DALI CONFIG 400mA | 400mA |
| D31 | D | | 04340044 | DRIVER JOLLY DIM DALI CONFIG 500mA | 500mA |
| D32 | E | | 04340046 | DRIVER JOLLY DIM DALI CONFIG 700mA | 700mA |
| D33 | G | DALI + PUSH + 1-10V | 04340190 | DRIVER OTI DALI 25 TW DT8 PROGRAMADO 400mA | 400mA |
| D34 | D | | 04340123 | DRIVER MAXI JOLLY CONFIG 350mA | 350mA |
| D35 | D | | 04340124 | DRIVER MAXI JOLLY CONFIG 500mA | 500mA |
| D36 | E | | 04340125 | DRIVER MAXI JOLLY CONFIG 700mA | 700mA |
| D37 | F | CASAMBI | 04340126 | DRIVER MAXI JOLLY CONFIG 1050mA | 1050mA |
| D38 | D | | 04340145 | DRIVER CASAMBI READY CONFIG.350mA | 350mA |
| D39 | D | | 04340146 | DRIVER CASAMBI READY CONFIG.500mA | 500mA |
| D40 | E | | 04340147 | DRIVER CASAMBI READY CONFIG.700mA | 700mA |
| D41 | F | | 04340148 | DRIVER CASAMBI READY CONFIG.1050mA | 1050mA |
| D42 | G | 04340191 | DRIVER OT WI 15/220 CASAMBI PROG.200mA | 200mA | |

Installation Schemes



Connection Tips

SEVERAL FIXTURES CONNECTION TO A SINGLE CONSTANT CURRENT DRIVER



Magnetic 24V

DROP VOLTAGE TABLE


DRIVER MAXIMUM DISTANCE RANGE

| DRIVER TYPOLGY | A | | | | B | | | | C | | | |
|----------------------|--------------------|------------------|--------------------|--------------------|--------------------|------------------|--------------------|--------------------|--------------------|------------------|--------------------|--------------------|
| | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² |
| WIRE CROSS - SECTION | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² |
| DISTANCE TO LED | 20m | 50m | 50m | 50m | 10m | 20m | 20m | 50m | 10m | 20m | 20m | 30m |

| D | | | | E | | | | F | | | | G | | | |
|--------------------|------------------|--------------------|--------------------|--------------------|------------------|--------------------|--------------------|--------------------|------------------|--------------------|--------------------|--------------------|------------------|--------------------|--------------------|
| 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² | 0,5mm ² | 1mm ² | 1,5mm ² | 2,5mm ² |
| 15m | 15m | 15m | 15m | 10m | 15m | 15m | 15m | 10m | 10m | 15m | 15m | 2m | 2m | 2m | 2m |

| POWER (W) | CABLE SECTION (mm ²) | CABLE LENGTH* (m) | CABLE LENGTH** (m) |
|-----------|----------------------------------|-------------------|--------------------|
| 60 | 0,75 | 10 | 30 |
| | 1,5 | 20 | 30 |
| 100 | 0,75 | 5 | 20 |
| | 1,5 | 10 | 30 |

*FOR MAGNETIC 24V COCO | ** FOR MAGNETIC 24V FLIP, FIT 20 & 27, iO MICRO, PLUS MICRO, TOP MICRO, SIX XS



ARK Control

BLUETOOTH

Los accesorios Ark Control Bluetooth permiten controlar de forma inalámbrica cualquier luminaria del catálogo utilizando la APP de Casambi disponible en Apple y Play Store. La tecnología de control de iluminación de Casambi ofrece la posibilidad de implementar y desarrollar un sistema de control de iluminación a medida tanto para la iluminación profesional como el sector residencial.


Ark Control Bluetooth accessories enables the wireless control of any luminaire in the catalogue using the Casambi APP available on Apple and Play Store. Casambi's lighting control technology provides the option to implement and design a tailor-made lighting control system for both professional lighting and the residential sector.

Les accessoires Ark Control Bluetooth permettent un contrôle sans fil des luminaires du catalogue compatibles avec l'application Casambi, disponible sur Apple et Play Store. La technologie de contrôle d'éclairage de Casambi offre la possibilité de mettre

en place et développer un système de contrôle d'éclairage sur mesure, que ce soit dans l'éclairage professionnel ou le secteur résidentiel.

Gli accessori Ark Control Bluetooth consentono di controllare in modalità wireless qualsiasi apparecchio di illuminazione del catalogo mediante la APP di Casambi, disponibile in Apple e Play Store. La tecnologia di controllo dell'illuminazione di Casambi offre la possibilità di implementare e sviluppare un sistema di controllo su misura, sia per l'illuminazione professionale che per il settore residenziale.

Mit dem Zubehör Ark Control Bluetooth können Sie jede Leuchte aus dem Katalog drahtlos über die Casambi APP steuern, die im Apple und Play Store erhältlich ist. Die Lichtsteuerungstechnologie von Casambi bietet die Möglichkeit, ein maßgeschneidertes Lichtsteuerungssystem sowohl für die professionelle Beleuchtung als auch für den Wohnbereich zu implementieren und zu entwickeln.



0434-00-31

ARK-Control 1-10V / DALI

Bluetooth control unit for LED power supplies with 0-10V, 1-10V or DALI dimming interface. One independent push button input. Up to five DALI power supplies



0434-00-34

ARK-Control Dimmer


Bluetooth control for phase cut adjustable LED power supplies.



0433-10-25

ARK-Control Passive


Bluetooth controller for DALI networks. It is supplied directly from a DALI bus. Four independent push button inputs.



0434-01-07

ARK-Control Sensor

Bluetooth control sensor depending on the ambient light and presence detection.




0434-00-35 | W | N |

ARK-Control User Interface W | N

Bluetooth control user interface that can be configured using the Casambi application.

The four destination buttons can control a scene, an animation, a luminaire or a group of them -according to the configuration desired by the user-




0434-01-45 350 mA

0434-01-46 500 mA

0434-01-47 700 mA

0434-01-48 1050 mA




0434-01-91 200 mA

0434-01-31 | W | N |

Adapter for Wireless Control

Compatible with Casambi technology. 64 luminaires can be programmed and assigned up to 8 groups.



0433-01-33

ARK-Control Constant Voltage dimmer

Constant voltage bluetooth dimmer.

MATTER

Matter es un lenguaje de código abierto para conectar dispositivos inteligentes. Está diseñado para que cualquier empresa pueda utilizarlo para desarrollar sus propios dispositivos inteligentes, aplicaciones móviles y servicios en la nube, de forma que se comuniquen y funcionen juntos a la perfección.

Matter permite la interoperabilidad entre ecosistemas y fabricantes de distintos dispositivos inteligentes. Este nuevo estándar es una iniciativa de Apple, Google, Amazon y Samsung, por lo tanto, la mayoría de sus ecosistemas Smart Home/ Building serán compatibles con Matter desde el principio.

Matter is an open-source language for connecting smart devices. It is designed for any company to use in developing their own smart devices, mobile applications, and cloud services so that they can communicate and work seamlessly together.

Matter enables interoperability between ecosystems and manufacturers of various smart devices. This new standard is an initiative of Apple, Google, Amazon, and Samsung, so the majority of their Smart Home/Building ecosystems will be compatible with Matter from the start.

Matter est un langage open source permettant de connecter des appareils intelligents. Il est conçu pour que n'importe quelle entreprise puisse l'utiliser afin de développer ses propres appareils intelligents, applications mobiles et services cloud, de manière à ce qu'ils puissent communiquer et fonctionner ensemble de manière transparente.

Matter permet l'interopérabilité entre les écosystèmes et les fabricants de différents appareils intelligents.

Cette nouvelle norme est une initiative d'Apple, de Google, d'Amazon et Samsung, ce qui signifie que la majorité de leurs écosystèmes domotiques et de bâtiments seront compatibles avec Matter dès le début.


Matter è un linguaggio open source per collegare dispositivi intelligenti. È progettato affinché qualsiasi azienda possa utilizzarlo per sviluppare i propri dispositivi intelligenti, applicazioni mobili e servizi cloud in modo che possano comunicare e funzionare insieme in modo perfetto.

Matter consente l'interoperabilità tra ecosistemi e produttori di diversi dispositivi intelligenti. Questo nuovo standard è un'iniziativa di Apple, Google, Amazon e Samsung, quindi la maggior parte dei loro ecosistemi per la casa e gli edifici intelligenti sarà compatibile con Matter fin dall'inizio.

Matter ist eine Open-Source-Sprache zur Verbindung von intelligenten Geräten. Sie wurde entwickelt, damit jedes Unternehmen sie verwenden kann, um seine eigenen intelligenten Geräte, mobilen Anwendungen und Cloud-Dienste zu entwickeln, damit sie nahtlos miteinander kommunizieren und zusammenarbeiten können.

Matter ermöglicht die Interoperabilität zwischen Ökosystemen und Herstellern verschiedener intelligenter Geräte.


Dieser neue Standard ist eine Initiative von Apple, Google, Amazon und Samsung, daher werden die meisten ihrer Smart-Home- und Gebäude-Ecosystems von Anfang an mit Matter kompatibel sein.



0434-01-70

ARK-Control Matter interface


Matter controller for up to 5 DALI fixtures.



0434-01-71

ARK-Control independent Matter interface


Matter controller for up to 25 DALI fixtures with strain relief set for independent applications.



0434-01-72

ARK-Control passive Matter interface

Matter controller for DALI networks. It is supplied directly from a DALI bus.



DALI

DALI es uno de los sistemas de regulación más comunes de iluminación direccionable digital. Permite el control remoto de las luminarias y su sencilla instalación facilita la creación de sistemas de iluminación flexibles en cualquier escala de proyecto.

DALI is one of the most common digital addressable lighting interface dimming systems. Enabling the remote control of luminaires and its simple installation facilitates the creation of flexible lighting systems on any project level.

DALI est l'un des systèmes de régulation d'éclairage adressable numériquement les plus communs. Il permet le contrôle à distance des luminaires,

et son installation simple facilite la création de systèmes d'éclairage flexibles, peu importe l'envergure du projet.

DALI è uno dei sistemi di regolazione più comuni per l'illuminazione orientabile digitale. Consente di controllare da remoto gli apparecchi di illuminazione e la sua facile installazione semplifica la creazione di sistemi di illuminazione flessibili per qualsiasi scala di progetto.

DALI ist eines der am weitesten verbreiteten Dimmsysteme für digital adressierbare Beleuchtung. Es ermöglicht die Fernsteuerung der Leuchten und seine einfache Installation erleichtert die Schaffung flexibler Beleuchtungssysteme für jede Projektgröße.

DALI BASIC


Sistema de control DALI para el control y configuración de 32 luminarias mediante dispositivos móviles.

DALI control system for the control and configuration of 32 luminaires via mobile devices.


Système de contrôle DALI permettant de contrôler et configurer 32 luminaires par le biais d'appareils mobiles.

Sistema di controllo DALI per il controllo e la configurazione di 32 apparecchi di illuminazione tramite dispositivi mobili.

DALI-Steuersystem für die Steuerung und Konfiguration von 32 Leuchten über mobile Geräte.




0434-01-14 DALI Power Supply
MAX 240mA | 300 m




0433-01-30 DALI Controller
The extremely compact application controller for DALI-2-based applications can be commissioned wirelessly via smartphone or tablet thanks to a Bluetooth interface and the sCS commissioning app. With 4 independent push button inputs.



0433-01-31 DALI-2 Sensor
DALI-2 ambient light and motion detection sensor.



0433-01-32 Constant Voltage DALI Dimmer
Intelligent digital dimmer (DALI-2) with constant output voltage.




0434-00-77 Interface DALI Bluetooth
DALI light controller for up to 32 DALI fixtures. Supports up to 4 groups and 4 input devices. Control the light via smartphone. One independent push button input.



0434-00-66 DALI Sensor
DALI light and presence sensor.



0434-01-27 DALI Push Button
Four independent DALI push button inputs.



WIFI


Sistema de regulación inalámbrico que permite controlar luminarias mediante asistentes de voz.

Wireless dimming system which enables luminaires to be controlled via voice assistance.

Système de régulation sans fil permettant de contrôler les luminaires par l'intermédiaire d'assistants vocaux.

Sistema di regolazione wireless, che consente di controllare gli apparecchi di illuminazione tramite assistenti vocali.


Drahtloses Dimmersystem, das die Steuerung von Leuchten mithilfe von Sprachassistenten ermöglicht.




0434-01-64

Constant voltage wifi dimmer

5A max



LED Emergency Kits



0434-00-64

1 Hour Emergency Kit

Batteries and green LED indicator included
Output 9-58 Vdc

0434-00-65

3 Hours Emergency Kit

Batteries and green LED indicator included
Output 9-58 Vdc

INFORMACIÓN TÉCNICA

TECHNICAL INFO/
RENSEIGNEMENTS
TECHNIQUES/
INFO TECNICHE/
TECHNISCHE
INFORMATION/

CCT - TEMPERATURA DE COLOR CORRELACIONADA (K)

Es una medida para describir el tono de una fuente luminica. Se define comparando su color dentro del espectro luminoso con el de la luz que emitiría un cuerpo negro calentado a una temperatura determinada y se mide en grados kelvin (K).

CCT - CORRELATED COLOR TEMPERATURE (K)

It is a measure to describe the colour appearance of a light source. It is defined by the comparison of its colour within the light spectrum with that of the light which would be emitted by a black body heated to a given temperature and is measured in degrees Kelvin (K).

CCT - TEMPÉRATURE DE COULEUR PROXIMALE (K)


Il s'agit d'une unité de mesure de la tonalité d'une source lumineuse. Elle est définie en comparant une couleur du spectre lumineux à celle de la lumière émise par un corps noir chauffé à une température précise, et mesurée en degrés Kelvin (K).

CCT - TEMPERATURA DI COLORE CORRELATA (K)

È una misura che descrive il tono di una sorgente luminosa. Si definisce comparando il suo colore nello spettro luminoso con quello che emetterebbe un corpo nero riscaldato a una determinata temperatura e si misura in gradi Kelvin (K).

CCT - KORRELIERTE FARBTEMPERATUR (K)

Ein Maß zur Beschreibung des Farbtons einer Lichtquelle. Sie wird durch den Vergleich ihrer Farbe innerhalb des Lichtspektrums mit der Farbe des Lichts definiert, das ein schwarzer, auf eine bestimmte Temperatur erhitzter Körper aussenden würde, und wird in Grad Kelvin (K) gemessen.



Colour Characterisation

TECHNICAL INFO

ESTABILIDAD CROMÁTICA (MacAdam)

En el diagrama cromático usado para describir todos los colores que puede percibir el ojo humano, se han definido regiones (llamadas elipses MacAdam) que agrupan los colores que son indistinguibles entre sí. Esta agrupación permite establecer una medida para determinar las diferencias entre coordenadas cromáticas: los pasos MacAdam o SDCM (Standard Deviation Color Matching).

Dentro de una tolerancia de desviación Step MacAdam 1, la diferencia percibida entre los colores es inexistente. Hasta 3 pasos MacAdam, la diferencia es prácticamente inapreciable y la temperatura de color de la fuente de luz se considerará homogénea.

Arkoslight selecciona cuidadosamente, las fuentes de luz LED adecuadas para conseguir una estabilidad cromática homogénea entre las diferentes unidades de una misma luminaria, sea cual sea el momento de su producción.

CHROMATIC STABILITY (MacAdam)

In the chromatic diagram used to describe all colours which can be perceived by the human eye, certain regions (called MacAdam ellipses) have been created to group colours which are indistinguishable, from the colour of the centre of the ellipse. This grouping facilitates establishing a measure in order to identify the differences between colour chromatic coordinates: the MacAdam steps or SDCM (Standard Deviation Color Matching).

Within a deviation tolerance of MacAdam Step 1 the perceived difference between the colours is non-existent. Up to 3 MacAdam steps, the difference is virtually negligible and the colour temperature of the light source is homogeneous. Arkoslight carefully selects the appropriate LED lighting sources in order to obtain homogeneous chromatic stability between the different units of a single luminaire, regardless of its date of manufacture.

STABILITÉ CHROMATIQUE (MacAdam)

Dans le diagramme chromatique où figurent toutes les couleurs perçues par l'œil humain, des zones regroupant les couleurs indiscernables entre elles (appelées ellipses MacAdam) ont été définies. Ce regroupement permet d'établir une unité de mesure afin de déterminer les différences entre les coordonnées chromatiques : les étapes MacAdam ou SDCM (Standard Deviation Color Matching).

Dans la fourchette de tolérance d'écart Step MacAdam 1, aucune différence n'est observée entre les couleurs. À la 3e étape MacAdam, les couleurs sont pratiquement indiscernables et la température chromatique de la source lumineuse est considérée comme étant homogène. Arkoslight choisit avec soin, les sources de lumière LED nécessaires à l'obtention d'une stabilité chromatique homogène entre les différentes pièces d'un même luminaire, peu importe le moment de production.

STABILITÀ CROMATICA (MacAdam)

È il diagramma cromatico usato per descrivere tutti i colori che l'occhio umano può percepire. Sono state definite delle regioni (chiamate ellissi MacAdam) che raggruppano i colori indistinguibili tra loro. Questo raggruppamento permette di stabilire una misura per determinare le differenze tra le coordinate cromatiche: gli step MacAdam o SDCM (Standard Deviation Color Matching).

All'interno di una tolleranza di deviazione Step MacAdam 1, la differenza percepita tra i colori è inesistente. Fino allo Step MacAdam 3, la differenza è praticamente impercettibile e la temperatura di colore della luce è considerata omogenea.


Arkoslight seleziona con cura, le sorgenti di luce LED adatte per ottenere una stabilità cromatica omogenea tra le varie unità di uno stesso apparecchio di illuminazione, qualsiasi sia il momento della loro fabbricazione.

FARBSTABILITÄT (MacAdam)

In der Farbtabelle, die zur Beschreibung aller vom menschlichen Auge wahrnehmbaren Farben verwendet wird, wurden Bereiche (so genannte MacAdam-Ellipsen) definiert, in denen Farben zusammengefasst sind, die nicht voneinander unterscheiden werden können. Diese Gruppierung ermöglicht die Festlegung eines Maßes zur Bestimmung der Unterschiede zwischen den Farbkoordinaten: die Schritte MacAdam oder SDCM (Standard Deviation Colour Matching).

Innerhalb einer Toleranz der Abweichung von MacAdam Step 1 ist der wahrgenommene Unterschied zwischen den Farben nicht existent. Bis zu 3 MacAdam-Schritten ist der Unterschied praktisch vernachlässigbar und die Farbtemperatur der Lichtquelle wird als homogen angesehen.


Arkoslight wählt sorgfältig die geeigneten LED-Lichtquellen aus, um eine homogene Farbstabilität zwischen den verschiedenen Einheiten ein und derselben Leuchte zu erreichen, unabhängig vom Zeitpunkt der Produktion.



El índice de reproducción cromática (CRI), es una escala cuantitativa que mide la capacidad de la luz, para reproducir fielmente la veracidad de los colores comparados con su reproducción bajo la luz ideal o natural. Para determinarlo, se compara la fuente luminosa con una fuente de referencia con el mismo CCT, utilizando hasta 15 patrones de color. El índice Ra se calcula como un promedio de los resultados para las 8 primeras muestras de color. Se obtiene un valor de hasta un máximo de 100, considerando el 100 el valor que más se acerca a la perfección en cuanto a la reproducción de los colores. En Arkoslight hay disponibles tres rangos de cromaticidad 80, 90 y 97, además de los LED para aplicaciones especiales.

The color rendering index (CRI) is a quantitative measure of the ability of a light source to reproduce true colours in comparison to their rendering under ideal or natural light. It is determined by comparing the light source to a reference source with the same CCT using up to 15 colour standards. The Ra index is calculated as an average of the results for the first 8 colour samples. A value of up to a maximum of 100 is obtained, with 100 being considered the value that comes closest to perfection in terms of colour rendering. At Arkoslight three chromaticity ranges 80, 90 and 97 are available in addition to the LED for special applications.

L'indice de rendu des couleurs (CRI en anglais) est une mesure quantitative de la capacité d'une source lumineuse de reproduire les couleurs des objets de manière réaliste par rapport à un idéal ou à la lumière naturelle. Il est déterminé en comparant la source de lumière avec une source de référence au même CCT, à l'aide de jusqu'à 15 patrons de couleur. L'indice Ra est égal à la moyenne des résultats des huit premiers échantillons de couleur. La valeur obtenue est inférieure ou égale à 100, 100 étant la valeur la plus proche de la perfection en matière de reproduction des couleurs. Pour les applications spéciales, Arkoslight propose trois niveaux de chromaticité (80, 90 et 97) en plus des LED.



L'indice rendering di colore (CRI) è una scala quantitativa che misura l'abilità di una sorgente luminosa di rivelare i colori fedelmente, rispetto a una sorgente luminosa ideale o naturale. Per determinarlo si raffronta la sorgente luminosa con una sorgente di riferimento che possiede lo stesso CCT, impiegando fino a 15 modelli di tinta. L'indice Ra si calcola come media dei risultati per gli 8 primi campioni di colore. Si ottiene un valore che raggiunge un massimo di 100, dove 100 è il valore che più si avvicina alla perfezione, relativamente alla riproduzione dei colori. Arkoslight utilizza tre intervalli di cromaticità, 80, 90 e 97, oltre ai LED per utilizzi speciali.

Der Farbwiedergabeindex (CRI) ist eine quantitative Skala, die die Fähigkeit des Lichts misst, Farben im Vergleich zu ihrer Wiedergabe bei idealem oder natürlichem Licht originalgetreu wiederzugeben. Um dies zu ermitteln, wird die Lichtquelle mit einer Referenzquelle mit dem gleichen CCT verglichen, wobei bis zu 15 Farbstandards verwendet werden. Der Ra-Index wird als Durchschnitt der Ergebnisse für die ersten 8 Farbmuster berechnet. Es wird ein Wert von bis zu 100 erreicht, wobei 100 als der Wert gilt, der der Perfektion der Farbwiedergabe am nächsten kommt. Drei Farbbereiche 80, 90 und 97 sind bei Arkoslight neben LED für spezielle Anwendungen erhältlich.




Método para la evaluación de la reproducción cromática de una fuente de luz publicado por la "Illuminating engineering society (IES)". Se fija en tres conceptos: Fidelity Index (Rf), una interpretación precisa del color, similar al CRI, pero basada en 99 muestras de color; Gamut Index (Rg), que provee información sobre el promedio de saturación de la fuente y Color Vector, una representación gráfica que muestra la desviación de saturación de los diferentes colores respecto a una fuente de referencia. Los colores estarán más o menos saturados según se encuentren en el exterior o interior del círculo de referencia.

Method for evaluating the colour rendering of a light source published by the Illuminating engineering society (IES). It is based on three concepts: Fidelity Index (Rf), a precise interpretation of colour, similar to the CRI, but based on 99 colour evaluation samples; Gamut Index (Rg), which provides information on the average saturation of a light source and Colour Vector, a geographical representation showing the saturation deviation of the different colour as regards a reference light source. The colours will be more or less saturated depending on whether these are on the exterior or interior of the reference circle.

Méthode d'évaluation de la reproduction chromatique d'une source de lumière, publiée par la «Illuminating engineering society» (IES). Elle se fonde sur trois concepts : L'Indice de fidélité (Rf), interprétation précise de la couleur comparable au CRI, basée cependant sur 99 échantillons de couleur, l'indice de Gamut (Rg), qui fournit de l'information sur la moyenne de saturation de la source et le Vecteur chromatique, représentation graphique présentant l'écart de saturation des différentes couleurs en fonction d'une source de référence. Les couleurs sont plus ou moins saturées selon qu'elles se trouvent à l'intérieur ou à l'extérieur du cercle de référence.

Metodo di valutazione della riproduzione cromatica di una sorgente luminosa, pubblicato dalla "Illuminating engineering society (IES)". Si basa su tre concetti: Fidelity Index (Rf), una precisa interpretazione del colore, simile al CRI, ma basata su 99 campioni di colore; Gamut Index (Rg), che fornisce informazioni sulla saturazione media della sorgente e Color Vector, una rappresentazione grafica che mostra la deviazione di saturazione dei vari colori, rispetto a una sorgente di riferimento. I colori saranno più o meno saturi, a seconda che si trovino all'esterno o all'interno del cerchio di riferimento.

Methode zur Bewertung der Farbwiedergabe einer Lichtquelle, veröffentlicht von der Illuminating Engineering Society (IES). Sie beruht auf drei Konzepten: Fidelity Index (Rf), eine genaue Interpretation der Farbe, ähnlich wie CRI, aber basierend auf 99 Farbproben; Gamut Index (Rg), der Informationen über die durchschnittliche Sättigung der Quelle liefert; und Colour Vector, eine grafische Darstellung, die die Sättigungsabweichung verschiedener Farben von einer Referenzquelle zeigt. Die Farben sind mehr oder weniger gesättigt, je nachdem, ob sie sich außerhalb oder innerhalb des Referenzkreises befinden.



DIM TO WARM

Regulación sincronizada de la temperatura de color y la intensidad luminosa. Se necesita un único canal de regulación.

Synchronised adjustment of colour temperature and luminous intensity. Only a single controller channel is required.

Régulation synchronisée de la température chromatique et de l'intensité lumineuse. Elle ne requiert qu'un seul canal de régulation.

Regolazione sincronizzata della temperatura di colore e dell'intensità luminosa. È necessario un unico canale di regolazione.

Synchronisierte Regelung von Farbtemperatur und Lichtstärke. Es wird nur ein Regelungskanal benötigt.

TUNNABLE WHITE

Regulación independiente de la temperatura de color y la intensidad luminosa. Permite optimizar la luz de acuerdo con el entorno o incluso la hora del día y equiparar lo máximo posible la luz artificial a la luz natural con el objetivo de mejorar la calidad de vida y el bienestar de las personas.

Independent adjustment of colour temperature and luminous intensity. Enables optimising the light according to the environment or even the time of day and to bring artificial light as close as possible to natural daylight in order to improve people's quality of life and well-being.

Régulation indépendante de la température chromatique et de l'intensité lumineuse. Pour une optimisation de la lumière en fonction du cadre ou même de l'heure de la journée, et une correspondance optimale entre lumière artificielle et lumière naturelle afin d'améliorer la qualité de vie et le bien-être des personnes.

Regolazione indipendente della temperatura di colore e dell'intensità luminosa. Consente di ottimizzare la luce in base all'ambiente o persino all'ora del giorno e di equiparare il più possibile la luce artificiale a quella naturale, al fine di migliorare la qualità di vita e il benessere delle persone.

Unabhängige Regulierung von Farbtemperatur und Lichtstärke. Sie ermöglicht es, das Licht je nach Umgebung oder sogar Tageszeit zu optimieren und das künstliche Licht dem Tageslicht so nahe wie möglich zu bringen, um die Lebensqualität und das Wohlbefinden der Menschen zu verbessern.

VIDA ÚTIL

Método de medida de mantenimiento de flujo luminoso a lo largo del tiempo. Se expresa mediante los parámetros L (porcentaje de flujo luminoso que mantiene la luminaria respecto del flujo original tras las horas de funcionamiento indicadas) y B (porcentaje de luminarias cuyo flujo será inferior al determinado por L).

Por ejemplo, una vida útil de 50000 horas L80B10, quiere decir que, tras 50000 horas de funcionamiento, el 90% de las luminarias mantiene un flujo luminoso igual o superior al 80% del flujo inicial.

LIFE TIME

Method of measuring the maintenance of luminous flux over time. It is expressed by the parameters L (percentage of luminous flux maintained by the luminaire in relation to the original flux after the specified operating hours) and B (percentage of luminaires whose flux will be lower than that determined by L).

For example, a life time of 50,000 hours L80B10 means that, after 50,000 hours of operation, 90% of the luminaires maintain a luminous flux equal to or greater than 80% of the initial flux.

DURÉE DE VIE

Unité de mesure du maintien du flux lumineux au cours du temps. Elle est exprimée par les paramètres L (pourcentage du flux lumineux conservé par le luminaire par rapport au flux original après les heures de fonctionnement indiquées) et B (pourcentage de luminaires au flux inférieur à celui déterminé par L). Par exemple, une durée de vie de 50 000 heures L80B10 signifie qu'après 50 000 heures de fonctionnement, 90 % des luminaires conservent un flux lumineux supérieur ou égal à 80 % du flux initiale.

VITA UTILE


Metodo di misurazione del mantenimento del flusso luminoso nel tempo. Si esprime tramite i parametri L (percentuale del flusso luminoso che mantiene l'illuminazione rispetto al flusso originale, una volta trascorse le ore di funzionamento indicate) e B (percentuale di illuminazioni il cui flusso sarà inferiore a quello determinato da L).

Ad esempio, una vita utile di 50000 ore L80B10 significa che, dopo 50000 ore di funzionamento, il 90% dell'illuminazione mantiene un flusso luminoso uguale o superiore all'80% del flusso iniziale.


HALTBARKEIT

Methode zur Messung der Aufrechterhaltung des Lichtstroms über die Zeit. Er wird durch die Parameter L (Prozentsatz des Lichtstroms, den die Leuchte nach den angegebenen Betriebsstunden im Vergleich zum ursprünglichen Lichtstrom beibehält) und B (Prozentsatz der Leuchten, deren Lichtstrom unter dem durch L bestimmten Lichtstrom liegt) ausgedrückt. Zum Beispiel bedeutet eine Lebensdauer von 50.000 Stunden L80B10, dass nach 50.000 Betriebsstunden 90 % der Leuchten einen Lichtstrom von mindestens 80 % des ursprünglichen Lichtstroms aufweisen.


DIM TO WARM



TUNNABLE WHITE



LIFE TIME



Sources With Chromatic Adjustment

TECHNICAL INFO

NOTA SOBRE LOS VALORES EXPRESADOS EN ESTE CATÁLOGO

Los valores de potencia (W) y flujo luminoso (lm) expresados en este catálogo, corresponden a la fuente de luz. Si desea conocer los valores de potencia del sistema (que incluye el consumo del driver), éstos están recogidos en la ficha técnica de cada referencia, disponible en www.arkoslight.com

CRITERIOS DE CALIDAD EN LA SELECCIÓN DEL LED

Arkoslight selecciona minuciosamente sus fuentes de luz LED teniendo en cuenta el método de categorización "binning". Durante la producción de LED, debido a las tolerancias de fabricación, existen variaciones en el flujo, la temperatura de color y el voltaje. Por este motivo se clasifica la producción de LED en "BIN", según estos parámetros. Al elegir las fuentes de luz de sus luminarias, Arkoslight selecciona los "BIN" o grupos a los que pertenecerán todos los LED que se emplearán en las luminarias de producción. Así, se logra reducir el rango de tolerancias de estas tres características y se garantiza mayor estabilidad en el flujo luminoso, el voltaje y la temperatura de color.

FLUJO LUMINOSO (lumen)

Cantidad total de luz que emite una fuente luminosa en todo el espacio que le rodea.

ILUMINANCIA (lux)

Cantidad de flujo luminoso recibido en una superficie. El lux también puede ser definido como nº de lúmenes/m²

EFICACIA LUMINOSA (lm/W)

Indica con qué eficiencia una fuente de luz convierte la energía eléctrica en luz.

EFICIENCIA DE LA LUMINARIA - LOR (%)

Relación entre el flujo luminoso de la luminaria y el flujo luminoso de las fuentes luminosas.

REGULACIÓN

DALI (Digital Addressable Lighting Interface)

Es un estándar de regulación para iluminación que permite integrar equipos de control de diferentes fabricantes en un mismo sistema. Un sistema DALI consiste en un controlador y uno o más dispositivos para la instalación luminica (drivers, sensores, interruptores, pulsadores...) que cuentan con una interface DALI.

PUSH DIM

Control a través de un botón pulsador. La regulación por pulsación no posee un standard y existen diferentes opciones de cableado e instalación para este tipo de regulación según cada fabricante de equipos. Usualmente serán necesarios uno o dos cables extra para su instalación, según cada fabricante.

DIM ON BOARD

La luminaria lleva su dimmer integrado, para control directo e individual.

PHASE CUT

El recorte de fase se realiza sin necesidad de una línea de control adicional, conectando un regulador en serie entre la línea de alimentación y el equipo. Dependiendo como se realiza el recorte de la tensión de red, se puede distinguir entre Leading-edge y Trailing-edge.

1-10V

Regulación continua a través de señal analógica de control. Los niveles de iluminación, pueden establecerse ente el 1% y el 100% de luz de salida.

UGR

Escala que unifica los diferentes métodos de evaluación del deslumbramiento. El UGR trata de describir una percepción subjetiva en términos medibles considerando el deslumbramiento potencial de todas las luminarias situadas dentro del campo visual de un observador. Los valores oscilan entre 10 y 30, donde 10 significa "no deslumbramiento" y 30 significa "deslumbramiento perturbador".

El UGR no es una característica propia de la luminaria, sino de la instalación, por lo que los UGR dados en este catálogo se han calculado usando una instalación estándar. Recomendamos el cálculo del UGR concreto de su instalación, para asegurar el valor deseado. En este catálogo todos los UGR se han calculado bajo los valores: 4H 2H Shr1

IK

El grado de protección IK es una clasificación numérica internacional para los grados de protección proporcionados por las envolventes de materiales eléctricos contra los impactos mecánicos externos, como se expresa en la Tabla 1.

CÓDIGO IP

Sistema de codificación para indicar los grados de protección proporcionados por una envoltura contra el acceso a partes peligrosas, la penetración de cuerpos sólidos extraños y la penetración de agua. El código IP está formado por dos cifras situadas inmediatamente después de las letras "IP", cuyo significado se expresa en la Tabla 2.

TABLA 1

| Código IK | IK00 | IK01 | IK02 | IK03 | IK04 | IK05 | IK06 | IK07 | IK08 | IK09 | IK10 |
|----------------------------|------|------|------|------|------|------|------|------|------|------|------|
| Energía de impacto (julio) | * | 0.15 | 0.20 | 0.35 | 0.50 | 0.70 | 1 | 2 | 5 | 10 | 20 |

TABLA 2

| IP | PRIMERA CIFRA | | SEGUNDA CIFRA |
|----|--|---|---|
| | Protección contra contactos eléctricos directos | Protección contra penetración de cuerpos sólidos extraños | Protección contra penetración de agua |
| 0 | Ninguna protección | Ninguna protección | Ninguna protección |
| 1 | Penetración mano | Cuerpos $\varnothing > 50$ mm | Goteo vertical |
| 2 | Penetración dedo $\varnothing > 12$ mm y 80 mm de longitud | Cuerpos $\varnothing > 12,5$ mm | Goteo desviado 15° de la vertical |
| 3 | Penetración herramienta | Cuerpos $\varnothing > 2,5$ mm | Lluvia. Goteo desviado 60° de la vertical |
| 4 | Penetración alambre | Cuerpos $\varnothing > 1$ mm | Proyecciones de agua en todas direcciones |
| 5 | Penetración alambre | Puede penetrar polvo en cantidad no perjudicial | Chorros de agua en todas direcciones |
| 6 | Penetración alambre | No hay penetración de polvo | Fuertes chorros de agua en todas direcciones |
| 7 | --- | --- | Inmersión temporal |
| 8 | --- | --- | Inmersión prolongada (Material sumergible) bajo las condiciones indicadas por el fabricante |

Glosario

INFORMACIÓN TÉCNICA

NOTE CONCERNING THE VALUES SPECIFIED IN THIS CATALOGUE

The power (W) and luminous flux (lm) values specified in this catalogue correspond to the lighting source. Should you wish to know the power values of the system (including the driver's consumption), these are specified in the Technical Data Sheet of each item, available at www.arkoslight.com

QUALITY CRITERIA FOR LED SELECTION

Arkoslight methodically selects its LED lighting sources, using the "binning" classification method. During the production process of the LED, and taking into account the manufacturing tolerances, certain variations of the flux, the colour temperature or the voltage usually occur. For this reason, the production of the LED is classified in "BIN", according to the formerly mentioned parameters. When choosing the lighting sources for its luminaires, Arkoslight always selects the "BIN" or the groups corresponding to all the LED to be used for the luminaires to be produced. In doing so, a significant reduction of the tolerance range of these 3 characteristics can be obtained and likewise ensures greater stability of the luminous flux, voltage and colour temperature.

LUMINOUS FLUX (lumen):

This is the measurement of the total luminous output emitted by a light source throughout the surrounding space.

ILLUMINANCE (lux)

This is the unit that measures the degree of luminous flux received on a surface. The lux can also be defined as the number of lumens/m²

LUMINOUS EFFICENCY (lm/W)

Specifies the efficiency of a light source converting electrical energy into light.

LUMINAIRE EFFICIENCY - LOR (%)

This is the ratio of light output emitted by the luminaire to the light output emitted by its lamps.

DIMMING

DALI (Digital Addressable Lighting Interface)

It is a dimming standard for lighting which enables equipment from different manufacturers to be integrated into a single network. A DALI network consists of a controller and one or more devices for the lighting installation (drivers, sensors, switches, push buttons...) which have DALI interfaces.

PUSH DIM

Dimming control via a push button switch. No standard exists for push button dimming, reason why various wiring and installation options exist for this type of dimming depending on each equipment manufacturer. Generally, one or two extra wires will be required for installation, depending on each manufacturer.

PHASE CUT

Phase cutting is carried out without the need for an additional control light, by connecting a dimmer in line between the power supply line and the equipment. Depending on how the mains voltage is cut, a distinction can be made between Leading-edge and Trailing-edge.

DIM ON BOARD

The luminaire has an integrated dimmer for direct and individual control.

1-10V

Continuous dimming via analogue control signal. Light levels can be set anywhere between 10% to 100% of light output.

UGR

This is a scale which unifies different glare evaluation methods. The UGR describes subjective perception in measurable terms considering the potential glare of all the luminaires located within the observer's field of vision. The values range between 10 and 30, where 10 means "no glare" and 30 means "discomfort glare". The UGR value is not a characteristic of the luminaire itself, but of the entire installation, which is why the calculated UGR values specified in our catalogue are based on a common standard installation. The UGR calculation for your particular installation is recommended to ensure the desired UGR value. All UGRs specified in this catalogue are calculated under the values: 4H 2H Shr1

IK

The IK protection level is an international numerical classification for the degrees of protection provided by casings of electrical materials against external mechanical impacts, as specified in Table 1.

IP CODE

Coding system which specifies the degrees of protection provided by an enclosure against access to hazardous parts, penetration of solid foreign bodies and water ingress. The IP code consists of two digits immediately following the letters "IP", the meaning of which is specified in Table 2.

TABLE 1

| IK Code | IK00 | IK01 | IK02 | IK03 | IK04 | IK05 | IK06 | IK07 | IK08 | IK09 | IK10 |
|------------------------|------|------|------|------|------|------|------|------|------|------|------|
| Impact energy (joules) | * | 0.15 | 0.20 | 0.35 | 0.50 | 0.70 | 1 | 2 | 5 | 10 | 20 |

TABLE 2

| IP | FIRST FIGURE | | SECOND FIGURE |
|----|---|--|---|
| | Protection against direct electrical contacts | Protection against penetration of solid foreign bodies | Protection against the penetration of moisture |
| 0 | No protection | No protection | No protection |
| 1 | Hand protection | Bodies of $\phi > 50$ mm | Vertical dripping water |
| 2 | Finger protection $\phi > 12$ mm and 80 mm long | Bodies of $\phi > 12.5$ mm | Dripping water tilted up to 15° |
| 3 | Tool protection | Bodies of > 2.5 mm | Dripping water tilted up to 60° |
| 4 | Metal wire protection | Bodies of > 1 mm | Splashing water in all directions |
| 5 | Metal wire protection | Dust can enter in a harmless quantity | Water jets in all directions |
| 6 | Metal wire protection | No entry of dust | Strong water jets in all directions |
| 7 | --- | --- | Temporary immersion |
| 8 | --- | --- | Constant immersion (submersible material) under manufacturer's conditions |

ELECTRICAL SAFETY



Class I Luminaires

Luminaires in which the protection against electric shocks does not depend solely on the main insulation, but on an additional safety device such as a connecting system between the accessible conductive parts and the protective earth conductor.



Class II Luminaires

Luminaires in which the protection against electric shocks does not depend solely on the main insulation, but comprises additional safety devices, such as double insulation, or reinforced insulation, and on which there is no protective earth system nor any dependence on the conditions of the installation.



Class III Luminaires

Luminaires on which the protection against electric shocks depends on the supply of very low safety voltage and on which the voltage generated is not higher than that supplied.

À PROPOS DES VALEURS INDIQUÉES DANS CE CATALOGUE

Les valeurs de puissance (W) et de flux lumineux (lm) indiquées dans ce catalogue correspondent à la source de lumière. Pour plus d'information à propos des valeurs de puissance du système (y compris la consommation du driver), veuillez consulter la fiche technique correspondant à ladite référence, disponible sur le site www.arkoslight.com

CRITÈRES DE QUALITÉ LORS DE LA SÉLECTION DE LA LED

Arkoslight sélectionne avec soin ses sources de lumières LED, conformément à la méthode de classement du «binning». Étant donné les tolérances de fabrication, il existe des variations de flux, température chromatique et voltage lors de la production des LED. C'est pourquoi, selon ces paramètres, la production de LED est classée dans les «BIN». Au moment de choisir les sources lumineuses de vos luminaires, Arkoslight sélectionne les «BIN» ou groupes auxquelles appartiennent toutes les LED employées pour les luminaires de production. C'est ainsi que nous parvenons à réduire la marge de tolérance de ces trois caractéristiques et à assurer une meilleure stabilité du flux lumineux, du voltage et de la température chromatique.

FLUX LUMINEUX (lumen)

Quantité totale de lumière émise par une source de lumière dans l'espace l'entourant.

ÉCLAIREMENT (lux)

Quantité de flux lumineux reçue par une surface. Le lux peut également être défini comme la quantité de lumens par m².

EFFICACITÉ LUMINEUSE (lm/W)

Elle indique l'efficacité par laquelle une source lumineuse convertit l'énergie en lumière.

EFFICACITÉ DU LUMINAIRE — LOR (%)

Rapport entre le flux lumineux du luminaire et le flux lumineux des sources de lumière.

RÉGLAGE

DALI (Digital Addressable Lighting Interface)

Il s'agit d'une norme de régulation pour luminaire permettant d'intégrer à un même système l'équipement de contrôle de différents fabricants. Un système DALI est composé d'un régulateur et d'un ou plusieurs dispositifs destinés à l'installation lumineuse (drivers, capteurs, interrupteurs, boutons poussoirs...) qui dépendent de l'interface DALI.

PUSH DIM

Se contrôle grâce à un bouton poussoir. Aucune norme n'existe en matière de réglage par pression, et il existe diverses options de câblage et d'installation pour ce type de réglage, selon le fabricant de matériel. En général, l'installation requiert un ou deux câbles supplémentaires, en fonction de chaque fabricant.

PHASE CUT

La réduction de phase ne requiert aucune ligne de contrôle supplémentaire, en connectant un régulateur série entre la ligne d'alimentation et le matériel. Selon la manière comment la réduction de tension du réseau est effectuée, nous pouvons distinguer le Leading-edge et le Trailing-edge.

DIM ON BOARD

Le luminaire dispose de son propre dimmer intégré, pour un contrôle direct et individuel.

1-10V

Régulation continue par signal analogique de contrôle. Les niveaux d'éclairage peuvent être fixés entre 1 % et 100 % de la lumière de sortie.

UGR

Échelle unifiant les différentes méthodes d'évaluation de l'éblouissement. L'UGR a pour fin la définition d'une perception subjective en termes mesurables, en prenant en compte l'éventuel éblouissement engendré par tous les luminaires situés dans le champ de vision d'un observateur. Les valeurs oscillent entre 10 et 30, où 10 correspond à «aucun éblouissement» et 30 à un «éblouissement perturbant». L'UGR n'est pas une caractéristique propre au luminaire, sinon du contexte d'installation. Par conséquent, les UGR présentés dans ce catalogue ont été calculés en fonction d'une installation standard. Nous vous conseillons de calculer l'UGR réel de votre installation afin d'assurer la valeur souhaitée. Dans ce catalogue, tous les UGR ont été calculés en se basant sur les valeurs suivantes : 4H 2H Shr1

IK

L'indice de protection IK est une classification numérique internationale définissant le degré de protection contre les impacts mécaniques externes fourni par une enveloppe de matériel électronique, comme indiqués au Tableau 1.

CODE IP

Système de codification indiquant le degré de protection fourni par une enveloppe contre l'accès aux parties dangereuses, la pénétration de corps solides étrangers et la pénétration d'eau. Le code IP est composé de deux chiffres situés juste après les lettres «IP», et dont le Tableau 2 récapitule leur signification.

TABLEAU 1

| Code IK | IK00 | IK01 | IK02 | IK03 | IK04 | IK05 | IK06 | IK07 | IK08 | IK09 | IK10 |
|---------------------------|------|------|------|------|------|------|------|------|------|------|------|
| Énergie d'impact (joules) | * | 0.15 | 0.20 | 0.35 | 0.50 | 0.70 | 1 | 2 | 5 | 10 | 20 |

TABLEAU 2

| IP | PREMIER CHIFFRE | | SECOND CHIFFRE |
|----|--|---|--|
| | Protection contre les contacts électriques directs | Protection contre la pénétration de corps solides étrangers | Protection contre la pénétration d'eau |
| 0 | Aucune protection | Aucune protection | Aucune protection |
| 1 | Protection main | Corps ø > 50 mm | Égouttement vertica |
| 2 | Protection doigt ø > 12 mm et 80 mm de longueur | Corps ø > 12,5 mm | Égouttement dévié de 15° de la verticale |
| 3 | Protection outil | Corps ø > 2,5 mm | Pluie. Égouttement dévié de 60° de la verticale |
| 4 | Protection fil métallique | Corps ø > 1 mm | Projection d'eau dans toutes les directions |
| 5 | Protection fil métallique | La poussière peut pénétrer en quantité non préjudiciable | Jets d'eau dans toutes les directions |
| 6 | Protection fil métallique | Aucune pénétration de poussière | Forts jets d'eau dans toutes les directions |
| 7 | --- | --- | Immersion temporaire |
| 8 | --- | --- | Immersion prolongée (matériel submersible) dans le respect des conditions indiquées par le fabricant |

SÉCURITÉ ÉLECTRIQUE



Luminaire de Classe I

Luminaire dont la protection contre les chocs électriques ne dépend pas exclusivement de l'isolation principale, mais également d'un moyen de sécurité supplémentaire sous forme de moyens de connexion entre les parties conductrices accessibles et un conducteur de production mis à la terre.



Luminaire de Classe II

Luminaire dont la protection contre les chocs électriques ne dépend pas exclusivement de l'isolation principale, mais également de moyens de sécurité supplémentaires, tels que la double isolation ou l'isolation renforcée, sans moyens de mise à la terre de protection ni dépendance des conditions d'installation.



Luminaire de Classe III

Luminaire dont la protection contre les chocs électriques dépend d'une alimentation de sûreté à très basse tension, ne générant aucune tension supérieure à celle-ci.

NOTA SUI VALORI INDICATI IN QUESTO CATALOGO

I valori di potenza (W) e di flusso luminoso (lm) espressi in questo catalogo corrispondono alla sorgente luminosa. Per conoscere i valori di potenza del sistema (che comprende il consumo del driver), si rimanda alla scheda tecnica di ciascun articolo, disponibile su www.arkoslight.com

CRITERI DI QUALITÀ NELLA SELEZIONE DEI LED

Arkoslight seleziona minuziosamente le sue sorgenti di luce LED tenendo conto del metodo di classificazione "binning". Durante la produzione dei LED, dovuto alle tolleranze di fabbricazione, esistono variazioni nel flusso, la temperatura di colore e la tensione. Per questo motivo la produzione di LED è classificata in "BIN", secondo questi parametri. Nella scelta delle sorgenti luminose dei suoi apparecchi di illuminazione, Arkoslight seleziona i "BIN" o gruppi a cui appartengono tutti i LED che saranno utilizzati negli apparecchi di illuminazione in produzione. In questo modo, si riescono a ridurre le tolleranze di queste tre caratteristiche e si garantisce una maggiore stabilità del flusso luminoso, della tensione e della temperatura di colore.

FLUSSO LUMINOSO (lumen)

Quantità totale di luce emessa da una sorgente luminosa in tutto lo spazio che la circonda.

ILLUMINAMENTO (lux)

Quantità di flusso luminoso distribuito su una superficie. Il lux può essere definito anche come n° di lumen/m²

EFFICACIA LUMINOSA (lm/W)

Indica l'efficienza di una sorgente luminosa nella conversione dell'energia elettrica in luce.

EFFICIENZA DELL'APPARECCHIO DI ILLUMINAZIONE - LOR (%)

Rapporto tra il flusso luminoso dell'apparecchio di illuminazione e il flusso luminoso delle sorgenti luminose.

REGOLAZIONE

DALI (Digital Addressable Lighting Interface)

È uno standard di regolazione per gli apparecchi di illuminazione, che consente di integrare dispositivi di controllo di vari fabbricanti in uno stesso sistema. Un sistema DALI si compone di un regolatore e uno o più dispositivi di luce (driver, sensori, interruttori, pulsanti, ecc.) che possiedono un'interfaccia DALI.

PUSH DIM

Controllo tramite un interruttore a pulsante. La regolazione tramite pulsante non possiede uno standard ed esistono varie opzioni di cablaggio e installazione per la stessa, a seconda del fabbricante dei dispositivi. In genere per l'installazione sono necessari uno o due cavi aggiuntivi, in base al fabbricante.

PHASE CUT

Il controllo di fase, chiamato anche diluizione di fase, si effettua senza dover installare una linea di controllo aggiuntiva, collegando in serie un regolatore tra la linea di alimentazione e il dispositivo. In base a come si effettui il controllo della tensione di rete, si distingue tra Leading-edge e Trailing-edge.

DIM ON BOARD

L'illuminazione è dotata di un dimmer integrato, per un controllo diretto e individuale.

1-10V

Smorzamento continuo tramite segnale di controllo analogico. I livelli di luce possono essere selezionati in qualsiasi punto di luce in uscita tra 1% e 100%.

UGR

Scala che unifica i vari metodi di valutazione dell'abbagliamento. L'UGR cerca di descrivere una percezione soggettiva in termini di misura, considerando l'abbagliamento potenziale di tutti i punti luce situati all'interno del campo visivo di un osservatore. I valori oscillano tra 10 e 30, dove 10 significa "non abbagliamento" e 30 significa "abbagliamento molesto". L'UGR è una caratteristica dell'impianto, non dell'apparecchio di illuminazione, pertanto gli UGR di questo catalogo sono stati calcolati in base a un impianto standard. Raccomandiamo di calcolare l'UGR particolare del proprio impianto, al fine di assicurare il valore desiderato. In questo catalogo tutti gli UGR sono stati calcolati in base ai valori: 4H 2H Shr1

IK

Il grado di protezione di IK è una classificazione numerica internazionale per i gradi di protezione forniti dai materiali elettrici di rivestimento contro gli impatti meccanici esterni, come indicato nella Tabella 1.

CODICE IP

Sistema di codifica che indica il grado di protezione fornito da un materiale di rivestimento rispetto all'accesso a parti pericolose, alla penetrazione di corpi estranei solidi e di acqua. Il codice IP è formato da due cifre situate immediatamente dopo le lettere "IP", il cui significato è espresso nella Tabella 2.

TABELLA 1

| Codice IK | IK00 | IK01 | IK02 | IK03 | IK04 | IK05 | IK06 | IK07 | IK08 | IK09 | IK10 |
|-----------------------------|------|------|------|------|------|------|------|------|------|------|------|
| Energia di impatto (luglio) | * | 0.15 | 0.20 | 0.35 | 0.50 | 0.70 | 1 | 2 | 5 | 10 | 20 |

TABELLA 2

| IP | PRIMA CIFRA | | SECONDA CIFRA |
|----|--|--|--|
| | Protezione contro il contatto elettrico diretto | Protezione contro la penetrazione di corpi estranei solidi | Protezione contro la penetrazione di acqua |
| 0 | Nessuna protezione | Nessuna protezione | Nessuna protezione |
| 1 | Protetto dal contatto con la mano | Corpi $\varnothing > 50$ mm | Gocciolamento verticale |
| 2 | Protetto dal contatto con le dita $\varnothing > 12$ mm e 80 mm di lunghezza | Corpi $\varnothing > 12,5$ mm | Gocciolamento deviato di 15° rispetto alla verticale |
| 3 | Protetto dall'inserimento di strumenti | Corpi $\varnothing > 2,5$ mm | Pioggia. Gocciolamento deviato di 60° rispetto alla verticale |
| 4 | Protetto dall'inserimento di filo di ferro | Corpi $\varnothing > 1$ mm | Getti d'acqua in tutte le direzioni |
| 5 | Protetto dall'inserimento di filo di ferro | Può penetrare polvere in quantità non dannose | Getti d'acqua in tutte le direzioni |
| 6 | Protetto dall'inserimento di filo di ferro | Nessun accesso di polvere | Forti getti d'acqua in tutte le direzioni |
| 7 | --- | --- | Immersione temporanea |
| 8 | --- | --- | Immersione prolungata (Materiale sommergibile) in condizioni indicate dal produttore |

Glossario

INFO TECNICHE

SICUREZZA ELETTRICA



Illuminazione di Classe I

Illuminazione in cui la protezione contro gli shock elettrici non è unicamente affidata all'isolamento principale, ma è dotata di una misura di sicurezza supplementare sotto forma di mezzo di connessione delle parti conduttrici, accessibili ad un conduttore di protezione e messa a terra.



Illuminazione di Classe II

Illuminazione in cui la protezione contro gli shock elettrici non è unicamente affidata all'isolamento principale, ma è dotata di misure di sicurezza supplementari come il doppio isolamento o l'isolamento rinforzato e di sistemi in cui non esistono mezzi di messa a terra di protezione o vincoli nelle condizioni di installazione.



Illuminazione di Classe III

Illuminazione in cui la protezione contro gli shock elettrici è affidata al sistema di alimentazione a bassissima tensione e in cui non si genera mai un carico di tensione superiore alla stessa.

HINWEIS ZU DEN IN DIESEM KATALOG ANGEgebenEN WERTEN

Die in diesem Katalog angegebenen Werte für Leistung (W) und Lichtstrom (lm) entsprechen der Lichtquelle. Wenn Sie die Leistungswerte des Systems (einschließlich des Treiberverbrauchs) wissen möchten, finden Sie diese in den auf www.arkoslight.com verfügbaren technischen Datenblättern der jeweiligen Referenzen.

QUALITÄTSKRITERIEN FÜR DIE LED-AUSWAHL

Arkoslight wählt seine LED-Lichtquellen sorgfältig unter Berücksichtigung der Kategorisierungsmethode „Binning“ aus. Bei der LED-Produktion kommt es aufgrund von Fertigungstoleranzen zu Schwankungen bei Lichtstrom, Farbtemperatur und Spannung. Aus diesem Grund wird die Produktion von LED nach diesen Parametern in „BIN“ unterteilt. Bei der Auswahl der Lichtquellen für seine Leuchten wählt Arkoslight die „BIN“ oder Gruppen aus, zu denen alle LED gehören, die in den Produktionsleuchten verwendet werden. Dadurch wird der Toleranzbereich dieser drei Merkmale verringert und eine größere Stabilität des Lichtstroms, der Spannung und der Farbtemperatur gewährleistet.

LICHTSTROM (lumen)

Die gesamte Lichtmenge, die von einer Lichtquelle in den sie umgebenden Raum abgegeben wird.

BELEUCHTUNGSSTÄRKE (lux)

Menge des auf einer Oberfläche empfangenen Lichtstroms. Lux kann auch als Anzahl der lumen/m² definiert werden.

LICHTWIRKSAMKEIT (lm/W)

Gibt an, wie effizient eine Lichtquelle elektrische Energie in Licht umwandelt.

WIRKUNGSGRAD DER LEUCHE - LOR (%)

Verhältnis zwischen dem Lichtstrom der Leuchte und dem Lichtstrom der Lichtquellen.

REGULIERUNG

DALI (Digital Addressable Lighting Interface)

Es handelt sich um einen Dimmstandard für die Beleuchtung, der die Integration von Betriebsgeräten verschiedener Hersteller in ein einziges System ermöglicht. Ein DALI-System besteht aus einem Controller und einem oder mehreren Geräten für die Beleuchtungsanlage (Treiber, Sensoren, Schalter, Taster usw.), die über eine DALI-Schnittstelle verfügen.

PUSH DIM

Für die Push Dimmung gibt es keine Norm, und je nach Gerätehersteller sind unterschiedliche Verdrahtungs- und Installationsoptionen für diese Art der Regelung verfügbar. In der Regel werden je nach Hersteller ein oder zwei zusätzliche Kabel für die Installation benötigt.

PHASE CUT

Die Phasenschnitt erfolgt ohne eine zusätzliche Steuerleitung, indem ein Dimmer zwischen Netzzuleitung und Gerät geschaltet wird.

Je nachdem, wie die Netzspannung geschaltet wird, kann zwischen Leading-Edge und Trailing-Edge unterschieden werden.

DIM ON BOARD

Die Leuchte verfügt über einen integrierten Dimmer zur direkten und individuellen Steuerung.

1-10 V

Stufenlose Regelung über analoges Steuersignal. Die Beleuchtungsstärke kann zwischen 1 % und 100 % Lichtleistung eingestellt werden.

UGR

Eine Skala, die die verschiedenen Methoden der Blendungsbewertung vereinheitlicht. Die UGR versucht, eine subjektive Wahrnehmung messbar zu machen, indem sie die potenzielle Blendung aller Leuchten im Sichtfeld des Betrachters berücksichtigt. Die Werte reichen von 10 bis 30, wobei 10 für „keine Blendung“ und 30 für „störende Blendung“ steht.

Die UGR ist keine Eigenschaft der Leuchte selbst, sondern der Installation. Daher wurde die in diesem Katalog angegebene UGR anhand einer Standardinstallation berechnet. Wir empfehlen, die spezifische UGR Ihrer Anlage zu berechnen, um den gewünschten Wert sicherzustellen. In diesem Katalog wurden alle UGRs nach folgenden Werten berechnet: 4H 2H Shr1

IK

Der IK-Schutzgrad ist eine internationale numerische Klassifizierung für den Schutzgrad von elektrischen Gehäusen gegen äußere mechanische Einwirkungen, wie in Tabelle 1 angegeben.

IP-CODE

Kodierungssystem zur Angabe der Schutzarten, die ein Gehäuse gegen den Zugang zu gefährlichen Teilen, das Eindringen von festen Fremdkörpern und das Eindringen von Wasser bietet. Der IP-Code besteht aus zwei Ziffern, die unmittelbar auf die Buchstaben „IP“ folgen und deren Bedeutung in der Tabelle 2 angegeben ist.

TABELLE 1

| IK-Code | IK00 | IK01 | IK02 | IK03 | IK04 | IK05 | IK06 | IK07 | IK08 | IK09 | IK10 |
|---------------------|------|------|------|------|------|------|------|------|------|------|------|
| Aufprallenergie (J) | * | 0.15 | 0.20 | 0.35 | 0.50 | 0.70 | 1 | 2 | 5 | 10 | 20 |

TABELLE 2



































| IP | ERSTE KENNZIFFER | | ZWEITE KENNZIFFER |
|----|--|---|---|
| | Schutz gegen direkte elektrische Berührung | Schutz gegen das Eindringen von festen Fremdkörpern | Schutz gegen das Eindringen von Wasser |
| 0 | Kein Schutz | Kein Schutz | Kein Schutz |
| 1 | Schutz gegen Zugang mit dem Handrücken | Fremdkörper $\varnothing > 50$ mm | Schutz gegen Tropfwasser |
| 2 | Schutz gegen Zugang mit einem Finger $\varnothing > 12$ mm und 80 mm Länge | Fremdkörper $\varnothing > 12,5$ mm | Schutz gegen fallendes Tropfwasser, Gehäuse um 15° geneigt |
| 3 | Schutz gegen Zugang mit Werkzeug | Fremdkörper $\varnothing > 2,5$ mm | Schutz gegen Regen. Fallendes Tropfwasser, Gehäuse um 60° geneigt |
| 4 | Schutz gegen Zugang mit einem Draht | Fremdkörper $\varnothing > 1$ mm | Schutz gegen allseitiges Spritzwasser |
| 5 | Schutz Zugang mit einem Draht | Eindringen von Staub in nicht schädlicher Menge möglich | Schutz gegenallseitiges Strahlwasser |
| 6 | Schutz gegen Zugang mit einem Draht | Kein Eindringen von Staub | Schutz gegen kräftiges allseitiges Strahlwasser |
| 7 | --- | --- | Schutz bei zeitweiligem Untertauchen |
| 8 | --- | --- | Schutz bei dauerndem Untertauchen (Unterwasserfähiges Material) gemäß den Herstellerangaben |

Glossar

TECHNISCHE INFORMATION

Colours

The lighting values indicated for each ref. code correspond to the results obtained from the tests carried out on the first mentioned colour of the list.

| | | | | | |
|---|---------------------|---|---------------------------|---|---|
|  | B White |  | TW Transparent-White |  | WTMG Textured white - Metallized gold |
|  | WT Textured White |  | TN Transparent-Black |  | WMG White - Metallized gold |
|  | W Matt White |  | R Red |  | NTMG Textured black - Metallized gold |
|  | WG White-Gold |  | G Gold |  | NMG Matt black - Metallized gold |
|  | WR White-Red |  | BC Brushed Copper |  | Z Aluminium |
|  | WN White-Black |  | BG Brushed Gold |  | NX Stainless Steel |
|  | NT Textured Black |  | MC Metallized Copper |  | NS Satin Nickel |
|  | N Matt Black |  | MG Metallized Gold |  | PR Primer Coating Finishing |
|  | NW Black-White |  | SP Textured Salmon Pink |  | CR Chrome |
|  | NG Black-Gold |  | LG Textured Light Green |  | BE Textured Beige |
|  | NR Black-Red |  | OG Textured Olive Grey |  | PG Textured Pebble Grey |
| | |  | OX Textured Oxidon |  | GT Textured Black Grey |

ALASKA
 BG = RAL not available. Electrolytic bath
 N = Colour in the mass looks alike RAL 9005
 NT = Anodised, bath colour, looks alike RAL 9005
 N = RAL 9005

ART
 BC = RAL not available. Electrolytic bath.
 BG = RAL not available. Electrolytic bath.
 NT = RAL 9005
 WT = RAL 9016

AURAE
 NT = RAL 9005
 WT = RAL 9016

BASIC
 NS = RAL not available. Electrolytic bath
 W = RAL 9016

BLACK FOSTER
 N = RAL 9005
 NT = RAL 9005
 NTMG = RAL not available. Metallic finish
 NMG = RAL not available. Metallic finish
 W = Colour in the mass looks alike RAL 9010
 WN = Colour in the mass looks alike RAL 9016 & RAL 9005
 WT = RAL 9016
 WTMG = RAL 9005 not available. Metallic finish
 WTW = RAL 9016

BRIGHT LINE
 W = RAL 9016

BUDDY
 N = RAL 9005
 NG = RAL 9005 & RAL 1036
 W = Colour in the mass looks alike RAL 9010

WG = Colour in the mass looks alike RAL 9010 & RAL 1036
 WN = Colour in the mass looks alike RAL 9010 & RAL 9005

COCO 48V
 NT = RAL 9005
 WT = RAL 9016

DARK
 N = RAL 9005
 NX = RAL not available. Stainless steel

DEEP
 WT = RAL 9016

DREAM
 N = Colour in the mass looks alike RAL 7022
 R = Colour in the mass looks alike RAL 3018
 W = Colour in the mass looks alike RAL 9001

DROP
 NT = RAL 9005
 WT = RAL 9016

DRUM
 NT = RAL 9005
 WT = RAL 9016

DUNE
 BE = RAL 1001
 NT = RAL 9005
 OG = RAL 7002
 PG = RAL7032
 WT = RAL 9016

DUOMO
 W = Colour in the mass looks alike RAL 9016

ESSENTIALS
 W = RAL 9016

FANCY SHAPE
 NT = RAL 9005
 WT = RAL 9016

FIFTY+
 NT = RAL 9005
 WT = RAL 9016

FIT
 G = RAL not available. Paint of metallic nanoparticles
 NT = RAL 9005
 WT = RAL 9016

FLIP
 NT = RAL 9005
 NTMG = RAL not available. Metallic finish
 WT = RAL 9016
 WTW = RAL 9016

FOX
 W = Colour in the mass looks alike RAL 9016

HIDDEN
 NT = RAL 9005
 WT = RAL 9016

HOLLY
 MC = RAL not available. Electrolytic bath.
 MG = RAL not available. Electrolytic bath.
 NT = RAL 9005
 WT = RAL 9016

HUBBLE
 NT = RAL 9005
 WT = RAL 9016

IO
 NT = RAL 9005
 WT = RAL 9016

LARK - 111
 N = RAL 9005
 W = RAL 9016

LENS LIGHT
 N = Colour in the mass looks alike RAL 9005
 W = Colour in the mass looks alike RAL 9016

LEX
 G = RAL 1036
 N = RAL 9005
 R = RAL 2004
 W = RAL 9016
 WN = RAL 9016 & RAL 9005
 Z = RAL 9006

LINE
 N = Anodised, bath colour, looks alike RAL 9005
 NT = RAL 9005
 WT = RAL 9016

LIP
 NT = RAL 9005
 WT = RAL 9016

LOOP
 BG = RAL not available. Electrolytic bath
 N = RAL 9005

MADISON
 W = RAL 9010

MINIMAL TRACK
 N = RAL 9005
 WT = RAL 9016

MIX
 W = RAL 9010

OLYMPIA
 W = Colour in the mass looks alike RAL 9016

ORBITAL
 N = RAL 9005
 W = RAL 9016

PIPE
 NT = RAL 9005
 NTMG = RAL not available. Metallic finish
 WT = RAL 9016
 WTW = RAL 9016

PLUS
 NT = RAL 9005
 WT = RAL 9016

POINTER
 N = RAL 9005
 W = Colour in the mass looks alike RAL 9010

POP UP
 NT = RAL 9005
 WT = RAL 9016

PUCK
 MC = RAL not available. Electrolytic bath.
 MG = RAL not available. Electrolytic bath.
 NT = RAL 9005
 WT = RAL 9016

QUAD
 W = RAL 9010
 Z = RAL 9006

REC
 NT = RAL 9005
 PR = Primer coating finish
 WT = RAL 9016

RHINO
 NT = RAL 9005
 WT = RAL 9016

SALT
 NG = RAL 9005 & RAL 1036
 NR = RAL 9005 & RAL 2004
 NW = RAL 9005 & RAL 9016
 TN = Transparent & RAL 9005
 TW = Transparent & RAL 9016
 WG = RAL 9016 & RAL 1036
 WR = RAL 9016 & RAL 2004
 WW = RAL 9016 & RAL 9016

SCOPE
 NG = RAL 9005 & RAL 1036
 NN = RAL 9005 & RAL 9005
 WG = RAL 9016 & RAL 1036
 WR = RAL 9016 & RAL 2004
 WW = RAL 9016 & RAL 9016

SHOT LIGHT
 BG = RAL not available. Electrolytic bath
 CR = RAL not available. Electrolytic bath
 MC = RAL not available. Metallic finish
 MG = RAL not available. Metallic finish
 N = Colour in the mass looks alike RAL 9005
 NMG = RAL not available. Metallic finish
 NT = Colour in the mass looks alike RAL 9005
 NTMG = RAL not available. Metallic finish
 W = Colour in the mass looks alike RAL 9016
 WMG = RAL not available. Metallic finish
 WT = Colour in the mass looks alike RAL 9016
 WTW = Colour in the mass looks alike RAL 9016

SIX
 NT = RAL 9005
 WT = RAL 9016

SKIP
 GT = RAL 7021
 OX = RAL not available

SKY
 WT = RAL 9016

SLIMGOT
 NT = RAL 9005
 WT = RAL 9016

SPIN
 MC = RAL not available. Electrolytic bath.
 MG = RAL not available. Electrolytic bath.
 NT = RAL 9005
 WT = RAL 9016

STANDUP
 NT = RAL 9005
 WT = RAL 9016

STEP
 N = RAL 9005
 NX = RAL not available. Stainless steel
 W = RAL 9016

STICK
 MG = RAL not available. Electrolytic bath.
 NT = RAL 9005
 WT = RAL 9016

STRAM
 NT = RAL 9005
 WT = RAL 9016

SWAP
 G = RAL 1036
 N = RAL 9005
 R = RAL 2004
 W = Colour in the mass looks alike RAL 9010
 W65 = Colour in the mass looks alike RAL 9010
 WN = Colour in the mass looks alike RAL 9010 & RAL 9005
 Z = RAL 9006

THOR
 NT = RAL 9005
 WT = RAL 9016

TOP
 NT = RAL 9005
 WT = RAL 9016

TRACK 1L / 3L
 B = RAL 9016
 N = RAL 9005

TRACK 48V
 N = RAL 9005
 NT = RAL 9005
 WT = RAL 9016

TWIST
 NT = RAL 9005
 WT = RAL 9016

UP
 NT = RAL 9005
 WT = RAL 9016

VOLA
 NT = RAL 9005
 WT = RAL 9016

WALLY
 N = Colour in the mass looks alike RAL 9005
 W = Colour in the mass looks alike RAL 9016

WELLIT
 NT = RAL 9005
 WT = RAL 9016

WIZ
 NT = RAL 9005
 WT = RAL 9016

YORU
 LG = RAL 6027
 NT = RAL 9005
 OX = RAL not available
 PG = RAL 7032
 SP = RAL 3022
 WT = RAL 9016

ZEN TUBE
 NT = RAL 9005
 WT = RAL 9016

Symbols

GLOSSARY

| | | | | | |
|---|---|--|---|---|--|
| L | Longitud (en mm). | Length (in mm). | Longueur (en mm). | Lunghezza (in mm). | Länge (in mm). |
| AL | Aluminio | Aluminium | Aluminium | Alluminio | Aluminium |
| PC | Policarbonato | Polycarbonate | Polycarbonate | Policarbonato | Polycarbonat |
| PE | Poliétileno | Polyethylene | Polyéthylène | Poietilene | Polyäthlen |
| GL | Cristal | Glass | Verre | Vetro | Glas |
| PMMA | Polimetilmetacrilato | Polymethyl methacrylate | Polyméthacrylate de méthyle | Polimetilmetacrilato | Polymethylmetacrylat |
| INOX | Acero inoxidable | Stainless steel | Acier inoxydable | Acciaio inossidabile | Edelstahl |
| MATT | Mate | Matt | Opaque | Opaco | Matt |
| TRANS | Transparente | Transparent | Transparent | Trasparente | Transparent |
| ABS | Acilonitrilo Butadieno Estireno | Acrylonitrile Butadiene Styrene | Acrylonitrile Butadiène Styrene | Acilonitrile Butadiene Stirene | Acrylnitril-Butadien-Styrol |
| LOR | <i>Lumen Output Ratio.</i> | Lumen Output Ratio. | <i>Lumen Output Ratio.</i> | <i>Lumen Output Ratio.</i> | <i>Lumen Output Ratio.</i> |
| IPXX | Índice de estanqueidad | Sealing rating | Indice d'étanchéité | Indice di sigillatura | Schutzgrad gegen Eindringen von Staub und Feuchtigkeit |
| IKXX | Índice de protección contra impactos | Impact resistance | Indice de protection contre des impacts | Indicizzi di protezione contro impatti | Stoßfestigkeitsgrad |
| MAX XX W | Potencia máxima | Maximum power | Puissance Maximum | Potenza massima | Maximale Leistung |
| CCT | Temperatura de color | Colour Temperature | Température de couleur | Temperatura di colore | Farbtemperatur |
|  | Cuerpo | Boddy | Corps | Corpo | Körper |
|  | Reflector | Screen | Réflecteur | Riflettore | Reflektor |
|  | Cristal óptico | Optical glass | Verre optique | Verro ottico | Optischem glas |
|  | Difusor | Diffuser | Diffuseur | Diffusore | Diffusor |
|  | Filtro lineal | Linear filter | Filtre linéaire | Filtro lineare | Lineares Filter |
|  | Lente refractora elíptica | Elliptical refractor | Réfracteur elliptique | Rifrattore ellittico | Linse (f. elliptischen Lichtkegel) |
|  | Filtro panel de abeja | Honeycomb filter | Filtre nid d'abeilles | Filtri favo | Waben-Raster |
|  | Pantalla asimétrica | Asymmetric screen | Accessoire asymétrique | Visiera asimetrica | Assymetrischer Schirm/Blende |
|  | Difusor homogeneizador del haz de luz | Beam Mixer Diffuser | Diffuseur homogénéisateur de faisceau lumineux | Diffusore di fascio luminoso misto | Strahlenmischdiffusor |
|  | Bisel extra | Add-on bezel | Collerette extra | Cornice extra | Zusatz-Zierring |
|  | Certificado ENEC | ENEC certified | Certifié ENEC | Certificato ENEC | ENEC-Zertifizierung |
|  | Certificado IEC | IEC certified | Certifié IEC | Certificato IEC | IEC-Zertifizierung |
|  | Compatible con la normativa francesa RT2012 & BBC | Compatible with the French Standard RT2012 & BBC | Compatible avec la Norme française RT2012 & BBC | Compatible con la normativa francese RT2012 & BBC | Kompatibel mit der französischen Norm RT2012 & BBC |



| | | | | | |
|---|--|--|---|--|--|
|  | Clase I | Class I | Classe I | Classe I | Klasse I |
|  | Clase II | Class II | Classe II | Classe II | Klasse II |
|  | Clase III | Class III | Classe III | Classe III | Klasse III |
| 12 V | Tensión de alimentación 12V | Input supply voltage 12V | Tension d'alimentation de l'ampoule 12V | Tensione di alimentazione della lampada 12V | Anschlussspannung 12V |
| 24 V | Tensión de alimentación 24vdc | Power supply voltaje 24vdc | Tension d'alimentation de l'ampoule 24vdc | Tensione di alimentazione della lampada 24vdc | Netzspannung 24vdc |
| 48 V | Tensión de alimentación 48vdc | Power supply voltaje 48vdc | Tension d'alimentation de l'ampoule 48vdc | Tensione di alimentazione della lampada 48vdc | Netzspannung 48vdc |
| 220 V ~ 240 | Tensión de alimentación 220-240V | Power supply voltaje 220-240V | Tension d'alimentation de l'ampoule 220-240V | Tensione di alimentazione della lampada 220-240V | Netzspannung 220-240V |
|  | Equipo no incluido | Control gear not included | Équipement non inclus | Alimentatore non compreso | Vorschaltgerät exklusive |
|  | Equipo electrónico incluido | Electronic control gear included | Équipement électronique inclus | Alimentatore elettronico compreso | Vorschaltgerät elektronische inklusive |
|  | Accesorio trimless | Trimless accessory | Accessoire trimless | Accessorio trimless | Trimless Zubehör |
|  | Alojamiento en mm para empotrables | Fitting hole for recessed luminaires in mm | Espace d'emplacement en mm pour encastrables | Foro in mm ad incasso | Einbauloch in mm |
|  | Empotrable cuadrado para agujero redondo | Squared fixture for round fitting holes | Encastrable carré pour trou rond | Quadrato da incasso per foro rotondo | Quadratische Leuchte mit rundem Einbauloch |
|  | Ángulo de basculación | Tilting angle | Angle de basculation | Angolo di inclinazione | Drehwinkel - Kippwinkel |
|  | Doble basculación | Double tilting acción | Double basculation | Doppia inclinazione | Doppelte Schwenkbarkeit |
|  | Ángulo de giro | Rotation angle | Angle de rotation | Angolo di rotazione | Drehwinkel |
|  | Conexión rápida | Fast connection | Conexion rapide | Collegamento rapido | Schnellsteckeranschluss |
|  | Bloque de conexión no incluido | Terminal strip not included | Bande terminale connector exclus | Morsetto non compreso | Ohne Klemmenleiste |
|  | Conector USB-C | USB-C connector | Port USB-C | USB-C connect | USB-C Verbindungskabel |
|  | Cargador universal | Universal charger | Chargeur universel | Caricatore universale | Universal-Ladegerät |
|  | Conexión con enchufe | Plug-in | Connexion avec prise | Collegamento con spina | Anschluss mit Stecker |
|  | Tipo de carril | Rail Type | Type de rail | Tipo de binario | Schiemodelle |
|  | Regulable | Dimmable | Gradable | Dimmerabile | Dimmbar |
|  | Longitud del cable | Cable length | Longueur de câble | Lunghezza di cavo | Hängekabel Schnelljustierungsvorrichtung |
|  | Regulación rápida del cable de suspensión | Quick adjustment for cable suspension | Régulation rapide du câble de suspension | Regolazione rapida del cavo di sospensione | Schnelle Regulation del Hängekabels |
|  | Control inalámbrico | Wireless control | Contrôle sans fil | Wireless control | Wireless control |
|  | Dispositivo para alumbrado de emergencias | Emergency lighting device | Dispositif pour éclairage de secours | Dispositivo por illuminazione di emergenza | Notbeleuchtung |
|  | Batería LI-ION | LI-ION battery | Batterie au lithium-ion | Batteria agli ioni di litio | Lithium-Ionen-Akku |
|  | Tipo de instalación y dirección del haz de luz | Installation type and light beam direction | Type d'installation et direction du faisceau lumineux | Tipo d'impianto e direzione del fascio | Art und Ausrichtung des Lichtkegels |
|  | Confort visual. UGR (Unified Glare Rating) | UGR (Unified Glare Rating) Visual comfort | Confort visuel. UGR (Unified Glare Rating) | Comfort visivo. UGR (Unified Glare Rating) | Sehkomfort. UGR (Unified Glare Rating) |
|  | Estabilidad cromática: Pasos MacAdam | Chromatic stability: MacAdam Steps | Stabilité chromatique: Pas MacAdam | Stabilità cromatica: Step MacAdam | Farbstabilität: MacAdam Stufen |
|  | Carga máxima soportada | Maximum supported load | Charge maximale supportée | Carico massimo supportato | Maximale Traglast |
|  | Temperatura máxima en superficie | Maximum surface temperature | Température Maximale sur une surface | Temperatura massima in superficie | Maximale Temperatur an der Oberfläche |
|  | Válido para exterior | Suitable for outdoor use | Agréé pour l'extérieur | Adatto per uso esterno | Geeignet für Ausseninstallation |



Reference

INDEX


| | | | | | | | | | | | | | | | |
|------------|--|------------|---|------------|---|------------|-------------------------|------------|----------|------------|------------------------------|------------|------------------------------|------------|--|
| 0000-55-XX | 222 | 0434-00-79 | 111, 171, 282 | 0434-01-90 | 36, 37, 38, 39, 282 | A071-01-XX | 54 | A235-XX-XX | 64 | A318-XX-XX | 16, 17 | A380-XX-XX | 86 | A456-00-00 | 164 |
| 0037-01-01 | 275 | 0434-00-96 | 81, 275 | 0434-01-91 | 36, 37, 38, 39, 282, 289 | A071-02-XX | 55 | A236-XX-XX | 67 | A319-XX-XX | 12, 13 | A381-XX-XX | 87 | A457-00-XX | 168 |
| 0038-01-01 | 275 | 0434-01-02 | 81, 275 | 0434-01-92 | 36, 37, 38, 39, 282 | A155-XX-XX | 73 | A237-XX-XX | 66 | A320-XX-XX | 106, 107 | A382-XX-XX | 88 | A458-00-01 | 252, 253 |
| 0223-00-00 | 130, 131, 142, 146, 147, 185, 214, 236, 237, 238, 239, 240, 241, 143, 144, 148, 213, 215 | 0434-01-03 | 81, 275 | 0434-01-93 | 283 | A171-0X-XX | 74 | A239-X0-XX | 121 | A321-XX-XX | 133 | A383-00-XX | 181 | A459-XX-XX | 105 |
| 0224-00-00 | 236, 237, 238, 239, 240, 241 | 0434-01-04 | 81, 275 | 0434-01-94 | 36, 37, 38, 39, 282 | A173-0X-XX | 75 | A246-0X-1X | 117 | A323-00-XX | 201 | A384-00-XX | 176 | A461-00-0X | 168 |
| 032X-01-01 | 275 | 0434-01-05 | 81, 275 | 0434-01-95 | 36, 37, 38, 39, 282 | A181-01-01 | 75 | A246-03-XX | 117 | A324-00-0X | 229 | A384-02-00 | 176, 179 | A462-XX-XX | 26 |
| 033X-01-01 | 275 | 0434-01-06 | 81, 275 | 0458-00-00 | 275 | A182-01-01 | 75 | A248-XX-XX | 63 | A325-00-XX | 101 | A385-00-0X | 181 | A463-0X-XX | 27 |
| 0350-00-00 | 73 | 0434-01-07 | 289 | 0486-00-00 | 283 | A187-XX-XX | 69 | A249-XX-XX | 63 | A326-00-XX | 201, 221 | A386-00-XX | 184 | A465-0X-XX | 212 |
| 0354-00-00 | 74 | 0434-01-08 | 283 | 0486-04-35 | 171 | A188-XX-XX | 69 | A250-XX-XX | 63 | A328-00-XX | 101 | A387-00-XX | 93, 183 | A466-0X-XX | 192 |
| 0355-00-00 | 74 | 0434-01-14 | 292 | 0486-XX-XX | 282 | A189-0X-XX | 71 | A251-X0-0X | 116 | A329-0X-XX | 194 | A388-00-0X | 182 | A467-XX-XX | 177 |
| 0419-00-00 | 275 | 0434-01-18 | 247, 283 | 0700-08-00 | 77, 127, 203, 230 | A190-0X-XX | 70 | A254-3X-XX | 46 | A330-0X-XX | 195 | A389-00-XX | 182 | A468-20-XX | 180 |
| 0433-00-23 | 247, 283 | 0434-01-23 | 170, 282 | 0486-04-35 | 171 | A193-XX-XX | 64 | A255-3X-XX | 47 | A331-XX-XX | 227 | A391-XX-XX | 145 | A469-0X-XX | 34 |
| 0433-01-07 | 282 | 0434-01-24 | 123, 282 | 0486-04-35 | 282 | A194-XX-XX | 65 | A256-00-XX | 166 | A332-XX-XX | 98 | A392-00-XX | 269 | A470-0X-XX | 35 |
| 0433-01-30 | 292 | 0434-01-25 | 108, 110, 168, 170, 282 | 0700-02-00 | 77, 127, 203, 230 | A195-0X-XX | 120 | A257-00-XX | 62 | A333-0X-XX | 195 | A393-00-XX | 269 | A471-0X-XX | 125 |
| 0433-01-31 | 292 | 0434-01-26 | 170, 282 | 0802-00-00 | 231 | A196-XX-00 | 80 | A258-00-XX | 62 | A334-0X-XX | 99 | A395-XX-XX | 183 | A472-0X-XX | 125 |
| 0433-01-32 | 90, 91, 92, 93, 94, 95, 176, 177, 179, 267, 292 | 0434-01-27 | 293 | 0802-0X-00 | 89, 231 | A197-XX-XX | 67 | A260-X0-XX | 113 | A335-XX-X | 196 | A396-00-XX | 111 | A473-XX-XX | 132 |
| 0433-01-33 | 90, 91, 92, 93, 94, 95, 176, 177, 179, 267, 289 | 0434-01-29 | 171, 282 | 0805-01-00 | 76, 114, 115, 126, 202, 210, 211, 220, 236 | A198-XX-XX | 66 | A261-X0-0X | 149 | A336-0X-XX | 99 | A399-XX-XX | 184 | A475-X-XX | 267 |
| 0433-10-22 | 90, 91, 92, 93, 94, 95, 176, 177, 179, 260, 267, 283 | 0434-01-30 | 171, 282 | 0805-01-00 | 76, 114, 115, 126, 202, 210, 211, 220, 236 | A200-XX-XX | 77 | A262-00-XX | 220 | A338-00-01 | 190, 191, 193, 251, 253, 257 | A400-0X-XX | 179 | A477-0X-XX | 29 |
| 0433-10-23 | 260, 283 | 0434-01-31 | 193, 190, 289 | 0805-01-00 | 76, 114, 115, 126, 202, 210, 211, 220, 236 | A203-XX-XX | 157 | A263-00-XX | 126 | A338-0X-00 | 188 | A401-0X-XX | 60 | A478-00-00 | 90, 91, 92, 93, 94, 95, 277 |
| 0433-10-24 | 260, 283 | 0434-01-37 | 90, 91, 92, 93, 94, 95, 176, 177, 179, 267, 283 | 0805-01-00 | 76, 114, 115, 126, 202, 210, 211, 220, 236 | A204-XX-XX | 78 | A264-XX-XX | 218, 219 | A338-1X-00 | 188 | A402-00-0X | 163 | A478-00-01 | 130, 131, 133, 135, 136, 142, 143, 144, 146, 147, 148, 149, 150, 151, 152, 153, 155, 156, 157, 158, 159, 178, 191, 193, 251, 257, 263, 277 |
| 0433-10-25 | 289 | 0434-01-41 | 282 | 0805-02-00 | 77, 127, 203, 230 | A212-00-00 | 41, 42, 43 | A268-0X-XX | 22, 23 | A338-2X-00 | 188 | A410-01-XX | 185 | A478-00-02 | 25, 35, 60, 277 |
| 0434-00-0X | 81, 275 | 0434-01-42 | 282 | 0805-03-00 | 89, 231 | A212-1X-XX | 40 | A269-0X-XX | 24, 25 | A339-0X-XX | 210 | A412-XX-XX | 50 | A478-00-03 | 27, 61, 277 |
| 0434-00-1X | 81, 275 | 0434-01-43 | 108, 168, 282 | 0806-00-00 | 76, 126, 202, 220 | A212-2X-XX | 41 | A271-XX-XX | 51 | A340-0X-XX | 211 | A414-XX-XX | 10, 11 | A478-00-04 | 29, 277 |
| 0434-00-31 | 289 | 0434-01-44 | 282 | 0806-00-00 | 76, 126, 202, 220 | A212-3X-XX | 42 | A274-00-XX | 270 | A341-XX-XX | 203 | A415-20-XX | 180 | A478-00-05 | 31, 32, 37, 39, 277 |
| 0434-00-34 | 289 | 0434-01-45 | 282 | 0807-00-00 | 236, 114, 115, 210, 211 | A212-4X-XX | 43 | A275-00-0X | 268 | A342-00-XX | 134 | A416-XX-XX | 208 | A479-4X-XX | 15 |
| 0434-00-35 | 289 | 0434-01-45 | 289 | A01X-1X-XX | 118 | A215-X2-XX | 79 | A276-XX-XX | 89 | A342-10-XX | 138 | A417-0X-11 | 236, 237, 238, 239, 240, 241 | A479-4X-XX | 15 |
| 0434-00-36 | 111, 271, 282 | 0434-01-46 | 282, 289 | A01X-2X-XX | 118 | A216-2X-XX | 44 | A277-XX-XX | 89 | A343-00-XX | 134 | A418-XX-XX | 239 | A480-XX-XX | 108, 109 |
| 0434-00-37 | 111, 271, 282 | 0434-01-47 | 282, 289 | A01X-3X-XX | 119 | A216-3X-XX | 45 | A278-XX-XX | 76 | A343-10-XX | 138 | A419-XX-XX | 238 | A481-4X-XX | 207 |
| 0434-00-38 | 271, 282 | 0434-01-48 | 282, 289 | A01X-4X-XX | 119 | A217-0X-XX | 68 | A279-00-XX | 169 | A344-XX-XX | 200 | A420-XX-XX | 240 | A482-XX-XX | 146 |
| 0434-00-39 | 110, 111, 170, 268, 269, 270, 282, 171 | 0434-01-53 | 105, 282 | A010-1X-0X | 82, 84 | A218-0X-XX | 68 | A280-00-1X | 150 | A345-00-00 | 100, 124, 198, 199, 246 | A421-XX-XX | 241 | A483-XX-XX | 147 |
| 0434-00-40 | 108, 110, 168, 170, 270, 282, 115 | 0434-01-54 | 105, 282 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-20-0X | 223, 225 | A281-X0-XX | 143 | A345-1X-XX | 199 | A425-XX-XX | 130 | A484-XX-XX | 20 |
| 0434-00-41 | 170, 270, 282 | 0434-01-55 | 105, 282 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-01 | 224 | A282-01-XX | 222, 223 | A345-2X-XX | 100 | A426-00-XX | 61 | A485-XX-XX | 21 |
| 0434-00-42 | 60, 105, 110, 123, 282, 115 | 0434-01-56 | 250, 252, 256, 188, 192, 283 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-02 | 224 | A284-1X-XX | 127 | A345-35-XX | 124 | A426-10-00 | 61 | A486-00-XX | 110 |
| 0434-00-43 | 282, 115 | 0434-01-61 | 188, 192, 250, 252, 256, 266, 283 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-03 | 224 | A284-2X-XX | 230 | A429-0X-XX | 124 | A427-XX-XX | 236 | A487-XX-XX | 148 |
| 0434-00-44 | 60, 105, 123, 282, 115 | 0434-01-62 | 188, 192, 250, 252, 256, 266, 283 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-04 | 225 | A285-XX-XX | 58 | A346-0X-XX | 100, 197 | A430-01-XX | 94 | A488-XX-XX | 148 |
| 0434-00-45 | 282, 115 | 0434-01-64 | 90, 91, 92, 93, 94, 95, 176, 177, 179, 267, 294 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-05 | 225 | A286-XX-XX | 226 | A346-2X-XX | 100 | A431-01-XX | 92 | A489-0X-XX | 206 |
| 0434-00-46 | 108, 110, 168, 282, 115 | 0434-01-65 | 164 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-06 | 247, 253, 260, 223, 225 | A287-XX-XX | 97 | A348-0X-XX | 202 | A432-01-XX | 92 | A490-00-XX | 123 |
| 0434-00-64 | 294 | 0434-01-66 | 268, 270, 271 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-07 | 225 | A288-00-XX | 165 | A349-XX-XX | 215 | A433-01-0X | 94 | A491-0X-XX | 96 |
| 0434-00-65 | 294 | 0434-01-67 | 267 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-08 | 225 | A295-00-XX | 114 | A350-XX-XX | 213 | A434-01-XX | 93 | A492-00-XX | 91 |
| 0434-00-66 | 293 | 0434-01-68 | 267 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-09 | 225 | A296-00-XX | 115 | A351-XX-XX | 170, 171 | A435-01-00 | 90, 91, 92, 93, 94, 95 | A493-0X-XX | 112 |
| 0434-00-73 | 283 | 0434-01-7X | 291 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-10 | 247, 253, 260, 223, 225 | A297-0X-XX | 30 | A354-32-XX | 46 | A436-XX-XX | 154 | A494-00-XX | 162 |
| 0434-00-77 | 293 | 0434-01-80 | 188, 192, 250, 252, 256, 283 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-11 | 223, 225 | A297-1X-XX | 32 | A355-32-XX | 47 | A437-XX-XX | 154 | A495-0X-XX | 28 |
| 0434-00-78 | 282 | 0434-01-81 | 266 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-12 | 225 | A297-2X-XX | 30 | A356-0X-XX | 228 | A438-XX-XX | 156 | A497-XX-XX | 266 |
| | | 0434-01-82 | 266 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-13 | 225 | A298-0X-XX | 31 | A356-00-00 | 125, 221, 228 | A439-0X-XX | 165 | A498-XX-XX | 90, 204 |
| | | 0434-01-83 | 266 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-14 | 225 | A298-1X-XX | 32 | A356-01-XX | 228 | A440-00-XX | 271 | A499-00-XX | 90 |
| | | 0434-01-84 | 266 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-15 | 225 | A301-00-XX | 271 | A357-00-00 | 125, 228 | A441-00-XX | 120 | A507-XX-XX | 36, 37 |
| | | 0434-01-85 | 36, 37, 38, 39, 282 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-16 | 223, 225, 247, 253, 260 | A303-00-XX | 258, 259 | A357-0X-XX | 228 | A442-00-XX | 152 | A508-XX-XX | 38, 39 |
| | | 0434-01-86 | 36, 37, 38, 39, 282 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-17 | 223, 225, 247, 253, 260 | A303-10-0X | 260 | A358-XX-XX | 153 | A443-XX-XX | 261 | A513-00-XX | 270 |
| | | 0434-01-87 | 36, 37, 38, 39, 282 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-18 | 223, 225, 247, 253, 260 | A304-00-XX | 258, 259 | A358-0X-XX | 153 | A444-XX-XX | 261 | A514-00-XX | 271 |
| | | 0434-01-88 | 36, 37, 38, 39, 282 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-19 | 223, 225, 247, 253, 260 | A308-00-XX | 166 | A359-00-00 | 125, 228 | A444-XX-XX | 261 | | |
| | | 0434-01-89 | 36, 37, 38, 39, 282 | A023-00-01 | 133, 149, 150, 151, 152, 158, 159, 191, 193, 251, 257, 263, 279 | A219-21-20 | | | | | | | | | |

Product

INDEX

| | | | | | | | |
|------------------------------------|-----|------------------------------|-----|------------------------------|-----|------------------------|-----|
| ALASKA | 130 | DREAM | 169 | LIP | 165 | SIX M 48V | 195 |
| ALASKA 24V | 181 | DROP | 64 | LOOP | 132 | SIX M Recessed | 98 |
| ALASKA Big | 131 | DROP Maxi | 64 | LOOP Indirect | 132 | SIX S 48V | 195 |
| ALASKA Big Fancy Shape | 238 | DROP Micro | 65 | MADISON | 70 | SIX S Recessed | 99 |
| ALASKA Big Trimless | 61 | DROP Micro Trans | 65 | MAGNETIC 24V COCO | 90 | SIX XS 24V | 182 |
| ALASKA Fancy Shape | 239 | DROP Mini | 65 | MAGNETIC 24V FIT | 92 | SIX XS 48V | 196 |
| ALASKA Trimless | 60 | DRUM 70 | 121 | MAGNETIC 24V Flip | 91 | SIX XS Recessed | 99 |
| ART | 134 | DRUM 70 Suspension | 153 | MAGNETIC 24V iO Micro | 93 | SKIP | 266 |
| ART Base | 138 | DRUM 90 | 121 | MAGNETIC 24V PLUS Micro | 94 | SKY | 120 |
| ART Base Direct & Indirect | 139 | DRUM 90 Suspension | 153 | MAGNETIC 24V SIX XS | 95 | SLIMGOT | 157 |
| ART Direct & Indirect | 135 | DUNE 35 | 146 | MAGNETIC 24V TOP Micro | 94 | SPIN | 144 |
| ART Modular | 136 | DUNE 55 | 147 | MINIMAL TRACK 24V | 179 | SPIN 48V | 213 |
| ART Modular Base | 140 | DUOMO | 58 | MINIMAL TRACK 24V Suspension | 179 | SPIN Fancy Shape | 240 |
| AURAE | 165 | FIFTY + HO Surface | 122 | MINIMAL TRACK 24V Trimless | 177 | STANDUP | 162 |
| BASIC | 275 | FIFTY + HO Surface Custom | 261 | MIX | 69 | STEP | 268 |
| BATH | 73 | FIFTY + HO Suspension | 158 | MIX Mini | 69 | STEP S | 269 |
| BLACK FOSTER | 247 | FIFTY + HO Suspension Custom | 262 | OLYMPIA | 62 | STEP XS | 269 |
| BLACK FOSTER 48V Tilt 5 | 207 | FIFTY + Surface | 122 | OLYMPIA Mini | 62 | STICK | 142 |
| BLACK FOSTER Asymmetric Custom | 245 | FIFTY + Surface Custom | 261 | ORBITAL | 82 | STICK 22 24V | 185 |
| BLACK FOSTER Asymmetric Recessed | 18 | FIFTY + Suspension | 158 | ORBITAL Mini | 80 | STICK 48V | 214 |
| BLACK FOSTER Asymmetric Trimless | 19 | FIFTY + Suspension Custom | 262 | ORBITAL Surface | 118 | STICK Fancy Shape | 237 |
| BLACK FOSTER Custom | 244 | FIFTY + UGR HO Surface | 122 | ORBITAL Trimless | 84 | STRAM | 67 |
| BLACK FOSTER Custom Module | 249 | FIFTY + UGR HO Suspension | 159 | PIPE | 148 | STRAM Mini | 67 |
| BLACK FOSTER Custom Surface | 251 | FIFTY + UGR Surface | 122 | PLUS | 229 | STRAM Mini Prismatic | 66 |
| BLACK FOSTER Custom Trimless | 252 | FIFTY + UGR Suspension | 159 | PLUS 48V | 201 | STRAM Prismatic | 66 |
| BLACK FOSTER FIT 35 | 246 | FIT 20 24V | 184 | PLUS Micro 24V | 182 | STRAM Surface | 117 |
| BLACK FOSTER FIT 35 Recessed | 251 | FIT 20 48V | 200 | PLUS Mini | 229 | STRAM Surface Mini | 117 |
| BLACK FOSTER FIT 35 Surface | 124 | FIT 27 24V | 184 | PLUS Mini 1L | 221 | SWAP L | 42 |
| BLACK FOSTER FIT 50 Recessed | 100 | FIT 35 48V | 199 | PLUS Mini 48V | 201 | SWAP L Asymmetric | 45 |
| BLACK FOSTER FIT 50 Surface | 197 | FIT 35 Recessed | 100 | PLUS Mini Recessed | 101 | SWAP M | 41 |
| BLACK FOSTER FIT 65 | 228 | FIT 50 48V | 197 | PLUS Recessed | 101 | SWAP M Asymmetric | 44 |
| BLACK FOSTER FIT 65 1L | 221 | FIT 50 Recessed | 100 | POINTER | 51 | SWAP M RT 2012 | 50 |
| BLACK FOSTER FIT 65 Surface | 125 | FIT 65 | 228 | POP UP | 76 | SWAP S | 40 |
| BLACK FOSTER FIT 80 | 228 | FIT 65 1L | 221 | PUCK | 116 | SWAP Square | 46 |
| BLACK FOSTER FIT 80 Surface | 125 | FIT 65 Surface | 125 | PUCK Recessed | 59 | SWAP Square Asymmetric | 47 |
| BLACK FOSTER FLIP 48V | 206 | FIT 80 | 228 | QUAD | 71 | SWAP S RT 2012 | 50 |
| BLACK FOSTER FLIP Recessed | 96 | FIT 80 Surface | 125 | REC | 166 | SWAP XL | 43 |
| BLACK FOSTER FLIP Surface | 123 | FLIP 48V | 206 | REC Double | 167 | THOR | 231 |
| BLACK FOSTER FOX | 68 | FLIP Recessed | 96 | REC Double Engine | 167 | TOP | 114 |
| BLACK FOSTER FOX Mini | 68 | FLIP Surface | 123 | REC Double Mini | 167 | TOP 48V | 210 |
| BLACK FOSTER GAP | 74 | FOX | 68 | REC Micro | 168 | TOP Fancy Shape | 236 |
| BLACK FOSTER HIDDEN | 77 | FOX Mini | 68 | REC Mini | 166 | TOP Micro 24V | 181 |
| BLACK FOSTER HOLLY | 143 | GAP | 74 | REC Slim | 168 | TOP Mini | 115 |
| BLACK FOSTER HOLLY 48V | 215 | HIDDEN | 77 | RHINO | 170 | TOP Mini 48V | 211 |
| BLACK FOSTER HOLLY Fancy Shape | 241 | HOLLY | 143 | SALT | 151 | TRACK 1L | 218 |
| BLACK FOSTER HUBBLE | 89 | HOLLY 48V | 215 | SALT Mini | 150 | TRACK 3L | 222 |
| BLACK FOSTER iO | 220 | HOLLY Fancy Shape | 241 | SCOPE | 149 | TRACK 48V + IND. LIGHT | 192 |
| BLACK FOSTER iO 48V | 202 | HUBBLE | 89 | SCOPE Surface | 113 | TRACK 48V SURFACE | 188 |
| BLACK FOSTER iO Micro 24V | 183 | iO | 220 | SHOT LIGHT | 22 | TRACK 48V SHORT | 188 |
| BLACK FOSTER iO Surface | 126 | iO 48V | 202 | SHOT LIGHT Big | 33 | TRACK 48V TRIMLESS | 188 |
| BLACK FOSTER Lark | 275 | iO Micro 24V | 183 | SHOT LIGHT M | 30 | TRIMLESS TOOL | 277 |
| BLACK FOSTER Lark-T11 | 274 | iO Surface | 126 | SHOT LIGHT M Asymmetric | 32 | TWIST | 78 |
| BLACK FOSTER LENS LIGHT | 34 | Lark | 275 | SHOT LIGHT M | 32 | TWIST Round | 79 |
| BLACK FOSTER LENS LIGHT Trimless | 35 | Lark-T11 | 274 | SHOT LIGHT M Asymmetric | 32 | UP | 163 |
| BLACK FOSTER LEX | 52 | LENS LIGHT | 34 | SHOT LIGHT M | 32 | VOLA | 120 |
| BLACK FOSTER LEX Asymmetric | 54 | LENS LIGHT Trimless | 35 | SHOT LIGHT M Asymmetric | 32 | VOLA Suspension | 152 |
| BLACK FOSTER LEX Blue | 53 | LEX | 52 | SHOT LIGHT M Asymmetric | 32 | WALLY | 171 |
| BLACK FOSTER LEX Mini | 56 | LEX Asymmetric | 54 | SHOT LIGHT M Asymmetric | 32 | WELLIT L | 88 |
| BLACK FOSTER LEX Mini Asymmetric | 57 | LEX Blue | 53 | SHOT LIGHT M Asymmetric | 32 | WELLIT M | 87 |
| BLACK FOSTER LEX Mini Blue | 56 | LEX Mini | 56 | SHOT LIGHT M Asymmetric | 32 | WELLIT S | 86 |
| BLACK FOSTER LINE 48V | 209 | LEX Mini Asymmetric | 57 | SHOT LIGHT M Asymmetric | 32 | WIRE TRIMLESS | 279 |
| BLACK FOSTER Line Micro 24V | 183 | LEX Blue | 53 | SHOT LIGHT M Asymmetric | 32 | WIZ 48V | 212 |
| BLACK FOSTER Line Micro Suspension | 156 | LEX Mini | 56 | SHOT LIGHT M Asymmetric | 32 | YORU | 164 |
| BLACK FOSTER Line Suspension | 154 | LEX Mini Blue | 56 | SHOT LIGHT M Asymmetric | 32 | YORU Spike 24V | 267 |
| BLACK FOSTER Direct & Indirect | 155 | LINE 48V | 209 | SHOT LIGHT M Asymmetric | 32 | ZEN TUBE | 230 |
| | | Line Micro 24V | 183 | SHOT LIGHT M Asymmetric | 32 | ZEN TUBE 48V | 203 |
| | | Line Micro Suspension | 156 | SHOT LIGHT M Asymmetric | 32 | ZEN TUBE Surface | 127 |
| | | Line Suspension | 154 | SIX L | 226 | | |
| | | Direct & Indirect | 155 | SIX L 48V | 194 | | |
| | | | | SIX L Recessed | 97 | | |
| | | | | SIX M | 227 | | |

Lighting Design



En el desarrollo de proyectos luminotécnicos, Arkoslight utiliza la última tecnología BIM (*Building Information Modeling*) y plataformas pioneras como Dialux que nos permiten incrementar la eficiencia del proceso y la exactitud de los cálculos lumínicos. También, ponemos a disposición de arquitectos, interioristas y *lighting designers* archivos 3D de nuestras luminarias en diversos formatos para potenciar su creatividad.

In developing lighting technology projects, Arkoslight uses the latest BIM (*Building Information Modeling*) technology and pioneering platforms such as Dialux which enables us to increase the efficiency of the process and the accuracy of lighting calculations. Likewise, making available to architects, interior and *lighting designers* 3D files of our luminaires in various formats to foster their creativity.

Lors du développement de projets luminotechniques, Arkoslight fait appel à la dernière technologie BIM (*Building Information Modeling*) et à des plateformes pionnières telles que Dialux, qui nous permettent d'augmenter l'efficacité du processus et l'exactitude des calculs de luminosité.

Nous mettons également à la disposition des architectes, décorateurs d'intérieur et *lighting designers* les archives 3D de nos luminaires dans divers formats afin d'encourager leur créativité.

Per lo sviluppo di progetti illuminotecnici Arkoslight impiega l'ultima tecnologia BIM (*Building Information Modeling*) e piattaforme pionieristiche come Dialux, che ci consentono di incrementare l'efficienza del processo e l'esattezza dei calcoli di luminosità. Inoltre, mettiamo a disposizione di architetti, progettisti d'interni e *lighting designers* file 3D in diversi formati dei nostri apparecchi di illuminazione per potenziare la loro creatività.

Bei der Entwicklung von Projekten der Beleuchtungstechnik verwendet Arkoslight die neueste BIM (*Building Information Modeling*)-Technologie und wegweisende Plattformen wie Dialux, mit denen wir die Prozesseffizienz und die Exaktheit der Lichtberechnungen erhöhen können. Wir stellen Architekten, Innendesignern und *Lighting Designer* 3D-Dateien unserer Leuchten in verschiedenen Formaten zur Verfügung, um deren Kreativität zu unterstützen.

Our goal is to work hand-in-hand with architects, interior designers, and lighting designers to create truly unique projects that are both innovative and functional. We pride ourselves on being your trusted partner throughout the entire process, from designing the perfect lighting to selecting the right products. We are here for you every step of the way. Let's start a conversation today.

info@arkoslight.com

CREDITS

ART DIRECTION
Arkoslight Team

GRAPHIC DESIGN
Estudio David Cercós

PHOTO PRODUCT
Angular - Fotografía Industrial y Publicitaria
Cualiti Photo Studio
Héctor Rubio - Images Positive
Javier Márquez Photo
Ángel Márquez
Salvador Martín

EDITION
January 2024
Copyright © Arkoslight 2024
All rights reserved

PRINTED BY
Rafa Sanz S.L.
Valencia · Spain

ARKOSLIGHT

Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia
Valencia · Spain
Fax +34 961 667 054
info@arkoslight.com
www.arkoslight.com

 Tel. +34 961 667 207
 Tel. +44 2039 66 45 92
 Tel. +33 182 885 200
 Tel. +39 02 9475 0007
 Tel. +49 221 7159 4740

JOKERLIGHT

Arkoslight trades its products with UL certification through Jokerlight
2750 NW 84th Ave
Doral · FL 33122 (USA)
info@jokerlight.com
www.jokerlight.com

